



CRUZ Performance Header Installation

Thank you for purchasing CRUZ Performance USA made Headers.

CRUZ Performance test fit these headers prior to shipment to confirm ease of installation.

CRUZ Performance recommends to use Permatex Ultra Copper sealant on header surface.

Apply to smooth clean surface. (No gaskets required)

Hardware supplied, install as follows

1. 2 long studs (spacers welded to header flange) install on driver side on top hole of front two cylinders.
2. 1 short stud install on passenger side head on top of middle cylinder
3. Install all of the rest of the supplied bolts very loosely to allow header to align on the head.
****DO NOT TIGHTEN A SINGLE NUT OR BOLT UNTIL ALL BOLTS HAVE STARTED TO THREAD INTO THE HEAD****
4. Installing crossover will take patience & finesse to align v-bands on to headers
(Install crossover with pipes already connected in to the double slip fit)

****ALL CRUZ PERFORMANCE HEADERS ARE TEST FITTED PRIOR TO SHIPMENT. MAKE SURE TO ALIGN MARKS ON THE CROSSOVER FOR EASY INSTALLATION****

Any questions please contact us

Don@cruzperformance.com

813-399-0409

Thank you again for purchasing USA made Headers



CRUZ Performance
505 N Falkenburg Rd Suite B
Tampa, FL 33619
813-399-0409
don@cruzperformance.com