Safety Data Sheet

Section 1 - Identification

Product Name: Super Cretex-w (25180)

North American PW Outlet 3427 Springdale Forrest Circle Gainesville, GA 30506 678-943-1488

Emergency Phone: 800-535-5053

Product Use: Concrete Dissolver

Section 2 - Hazards Identification

GHS Ratings:

Skin corrosive 1A Destruction of dermal tissue: Exposure < 3 min. Observation

< 1 hour, visible necrosis in at least one animal

Eye corrosive 1 Serious eye damage: Irreversible damage 21 days after

exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

GHS Hazards

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

GHS Precautions

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P264 Wash hands thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P310 Immediately call a POISON CENTER or doctor/physician if you feel unwell after

exposure of this product

P321 Specific treatment (see First Aid below or label)
P363 Wash contaminated clothing before reuse

P301+P330+P331 IF SWALLOWED: Call a POISON CENTER or doctor/physician. Rinse mouth. Do

NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P405 Store locked up

P501 Dispose of contents/container in conformance with State, Local, and Federal

regulations.

Signal Word: Danger



SDS for: Super Cretex-w (25180)

Page 1 of 5

Section 3 - Composition, Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Hydrochloric Acid	7647-01-0	20.00% - 30.00%
Carbamidic Acid	57-13-6	10.00% - 20.00%
Phosphoric Acid	7664-38-2	1.00% - 5.00%
Nonylphenol, ethoxylated	127087-87-0-9	1.00% - 5.00%

Section 4 - First Aid Measures

After inhalation:

Take affected persons into fresh air and keep quiet. Supply fresh air. Call a doctor immediately

After eye contact: Rinse opened eye for several minutes under running water. Call a doctor immediately. After skin contact: Immediately wash with water and soap and rinse thoroughly. Call a doctor immediately. After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help

immediately. NOTE: Never give an unconscious person anything to drink.

Information for doctor:

Most important symptoms and effects, both acute and delayed: Causes severe skin burns and eye damage. Gastric or intestinal disorders · Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

Section 5 - Fire Fighting Measures

Flash Point: 238 C (460 F)

LEL: UEL:

The product is not flammable

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

Hazardous Decomposition:

Chlorine, Hydrogen Chloride, Hydrogen gas

Advice for firefighters Protective equipment: Wear self-contained respiratory protective device.

Wear fully protective suit. Additional information Cool endangered receptacles with water spray.

Use fire extinguishing methods suitable to surrounding conditions.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Mount respiratory protective device.

Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

Use neutralizing agent. Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation.

Section 7 - Handling & Storage

Precautions for safe handling: Keep receptacles tightly sealed. Ensure good ventilation/exhaustion at the workplace. When diluting always pour product into water and not vice versa.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities: Store only in the original receptacle. Use polyolefine receptacles. Provide acid-resistant floor.

Suitable material for receptacles and pipes: Stainless steel.

SDS for: Super Cretex-w (25180) Page 2 of 5 Printed: 8/25/2020 at 10:59:54AM

Information about storage in one common storage facility: Store away from reducing agents. Store away from metals. Do not store together with alkalis (caustic solutions). Do not store together with organic materials. Further information about storage conditions: Keep container tightly sealed.

Section 8 - Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Hydrochloric Acid 7647-01-0	PEL: 5 ppm (7 mg/m3) Ceiling Limit	TLV: 5 ppm (7 mg/m3) Ceiling	Not Established
Carbamidic Acid 57-13-6	PEL: 5 mg/m3 TWA: 5 mg/m3 (nuisance dust)	TWA 10mg/m3 (nuisance dust)	Not Established
Phosphoric Acid 7664-38-2	TWA-8hrs: 1 mg/m3 STEL-15min.:2mg/m3	Not Established	Not Established
Nonylphenol, ethoxylated 127087-87-0-9	Not Established	Not Established	Not Established

General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Do not eat or drink while working. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Limitation and supervision of exposure into the environment: Avoid discharging of Hydrochloric / Phosphoric acid solutions into municipal wastewater, surface water or soils, when such discharges are expected to cause significant pH changes.

Risk management measures: Regular control of the pH value previous to or during discharges into open waters is required. Discharges should be carried out as to minimize pH changes in receiving surface waters. In general most aquatic organisms can tolerate pH values in the range of 6-9.

Eye protection: Tightly sealed goggles

Body protection: Acid resistant protective clothing, Boots

Protection of hands: Protective gloves. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Material of gloves Butyl rubber, BR Fluorocarbon rubber (Viton) Nitrile rubber, NBR Natural rubber, NR Chloroprene rubber, CR Neoprene gloves

Penetration time of glove material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials: Leather gloves

Section 9 - Physical & Chemical Properties

Boiling Range 84 to 150 °C	Appearance Clear to SI.
	Hazy liquid
^{Color} Straw	pH <=1
Specific Gravity 1.16-1.18	Odor Acerbic

Section 10 - Stability & Reactivity

STABLE

INCOMPATABILITIES:

None Known

SDS for: Super Cretex-w (25180) Page 3 of 5 Printed: 8/25/2020 at 10:59:54AM Materials To Avoid

Alkalines, metal oxides, metals, metal alloys, and organic matters, fluorine, strong reducing agents, bases, sulphur trioxide, phosphorus pentoxide.

Oxidizing agents, acids, nitrogen containing organic, metals, iron, copper, nickel, cobalt, organic materials, and ammonia. Corrosive to most metals with evolution of hydrogen gas, which may form explosive mixtures with air. May form explosive mixture if in contact with strong acid such as nitric or perchloric acids. Avoid contact with: strong oxidizers; strong acids or bases; nitrates; hypochlorites. Reacts with sodium or calcium hypochlorite to form explosive nitrogen trichloride.

DECOMPOSITION:

None Known

Oxides of Sodium, Oxides of Phosphorus

Instability Temperature: 85°C. Rate of decomposition increases with heat.

Conditions of Instability: High heat, ultraviolet light.

Special Remarks on Reactivity: Rate of decomposition increases with heat.

Under conditions of fire this material may produce: Nitrogen oxides; Ammonia; Biuret; Carbon oxides

Hazardous polymerization will not occur.

Section 11 - Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 2.785mg/kg

Component Toxicity

7647-01-0 Hydrochloric Acid

Oral LD50: 700 mg/kg (Rat) Inhalation LC50: 1,562 ppm (Rat)

7664-38-2 Phosphoric Acid

Oral LD50: 2,040 mg/kg (RAT) Dermal LD50: 3,653 mg/kg (Rabbit)

127087-87-0-9 Nonylphenol, ethoxylated

Oral LD50: 3,314 mg/kg (Rat) Dermal LD50: 3,050 mg/kg (Rabbit)

CAS Number Description Carcinogen Rating % Weight None N/A

Section 12 - Ecological Information

Do not discharge into waterways. The strong lowering of pH can destroy organisms.

Component Ecotoxicity

Hydrochloric Acid This product is toxic to fish and aquatic organisms. Do not contaminate

> water containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

Phosphoric Acid Acute Fish Toxicity

Harmful to aquatic life in very low concentrations. May be dangerous if it enters

Section 13 - Disposal Considerations

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

Uncleaned packaging Recommendation:

SDS for: Super Cretex-w (25180) Page 4 of 5 Printed: 8/25/2020 at 10:59:54AM

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. Packagings that may not be cleansed are to be disposed of in the same manner as the product. Disposal must be made in accordance with Local Authority requirements.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

Section 14 - Transportation Information

Agency Proper Shipping Name

OT Corrosive liquid, acidic, ino

<u>UN Number</u> UN3264 PGII

Hazard Class

Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric Acid, Phosphoric Acid),

Section 15 - Regulatory Information

<u>Country</u> <u>Regulation</u>

All Components Listed

Section 16 - Other Information

Hazardous Material Information System (HMIS)

FLAMMABILITY 0 PHYSICAL HAZARD 0 PERSONAL PROTECTION C

HMIS & NFPA Hazard Rating Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



The information and recommendations contained herein is believed to be reliable. However, the manufacturer does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. The manufacturer assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

Reviewer Revision

Date Prepared: 8/25/2020