SAFETY DATA SHEET

Luminary **Empower**

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards | SDS Revision: 4.10

SDS Revision Date: 5/23/2016

	1. PRODUCT INDENTIFICATION				
1.1	Product Name:				
	LuminaryEmpower				
1.2	Chemical Name:				
	POLYURETHANE (METH)ACRYLATE PREPOLYMER RESIN BLEND				
1.3	Synonyms:				
	NA				
1.4	Trade Names:				
	NA				
1.5	Product Use:				
	PROFESSIONAL USE ONLY, EXPERNAL USE ONLY, KEEP OUT OF THE REACH OF CHILDREN				
1.6	Manufacturer's Name:				
	VanDahl Inc.				
1.7	Manufacturer's Adress:				
	8784 S. Maryland Pkwy STE 125 Las Vegas, NV 89123				
1.8	Emergency Phone:				
	CHEMTREC: +1 703 527 3887 / +1 800 424 9300 (CCN 866131)				
1.9	Business Phone / Fax:				
	725 204 1029				

2. HAZARD INDENTIFICATION

2.1 Hazard Identification:

> WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H): H226 - Flammable liquid and vapor. H317 - May cause an allergic skin reaction. H320 -Causes eye irritation. Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P223 - Keep container tightly closed. P243 - Take precaustionary measures against static discharge. P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaiminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - Iff eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



Routes of Entry: Absorption: YES Inhalation: YES Ingestion: YES

2.3 Effects of Exposure:

> If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression. INGESTION:

EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye

inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin reactions

la a rachae walte darmatitie) unon prolongad or rapaatad avneoura

INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms

of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give some warning of

exposure but odor fatigue may occur.

2.4 Symptoms of Overexposure:

Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure.

Acute Health Effects:

Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.

2.6 Chronic Health Effects:

The material may cause an allergic reaction for some sensitive individuals.

Target Organs:

Eyes, skin

		3. COM	POSITION	& INGRE	DIENT	INF	ORM	ATIO	N				
			EXPOSURE LIMITS IN AIR (mg/m3)										
					AC	GIH		NOHSC	;		OSHA		
					pr	m		ppm			ppm	•	
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
Bis-HEMA Poly	NA	NA	NA	40-45	#####	#####	#####	#####	#####	#####	#####	#####	
(Neopentyl Glycol Adipate) / IPDI Copolymer Dilution													
Isobornyl Methacryalte	7534-94-3	NA	231-403-1	20-50	NA	NA	NA	NA	NF	NA	NA	NA	
Trimethylolpropane	3290-92-4	NA	NA	5-20	NA	NA	NA	NA	NF	NA	NA	NA	
Trimethacrylate													
Nitrocellulose	9004-70-0	NA	NA	5-10	NA	NA	NA	NA	NF	NA	NA	NA	
1-hydroxycyclohexyl	947-19-3	NA	278-355-8	1-3	NA	NA	NF	NF	NF	NA	NA	NA	
phenylketone													
Acrylates Copolymers	25035-69-2	NA	NA	0-1	NA	NA	NA	NA	NF	NA	NA	NA	•

4. FIRST AID MEASURES

4.1 First Aid:

INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient

is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the

amount of the substance that was swallowed.

SKIN & EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s)

to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soak and waster. Remove all contaminated clothing including footwear and wash thoroughly

before reuse. If irritation, redness or swelling persists, consult a physician immediately.

INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.

4.2 Medical Conditions Aggravated by Exposure:

Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin)

	HEALTH	1
)	FLAMMABILITY	0
-	PHYSICAL HAZARDS	0
	PROTECTIVE EQUIPMENT	В
	EYES SKIN	

5.1 Flashpoint & Method: >100 °C (> 212 °F) 5.2 Autoignition Temperature: NA 5.3 Flammability Limits: Lower Explosive Limit (LEL): NA Upper Explosive Limit (UEL): NA

5.4 Fire & Explosion Hazards:

This product is slightly flammable. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)

5.5 Extinguishing Methods:

Water, Foam, CO2, Dry Chemical

5.6 Fire Fighting Procedures:

First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water before returnign to service.

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of

7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 °C (122 °F).

	8. E	EXPOSURE CONTROLS & PERSONAL PROTECTION			
8.1	8.1 Ventilation & Engineering Controls: Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontaimination equipment is available (e.g., sink, safety shower, eye wash station).				
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.			
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.			
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves.			
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.			

	9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Density:	1.1				
9.2	Boiling Point:	NA				
9.3	Melting Point:	ND				
9.4	Evaporation Rate:	NA				
9.5	Vapor Pressure:	NA				
9.6	Appearance & Color:	Clear or pigmented liquid				
9.7	Odor Threashold:	NE				
9.8	Solubility:	Not soluble				
9.9	pH:	NA				
9.1	Viscosity:	approximately 4,000 cps				
9.1	Flash Point:	NA				
9.1	Other Information:	NA				

There is no specific data availble for this product on aquatic life.

13. DISPOSAL CONSIDERATIONS

13 Waste Disposal:

Dispose inaccordance with local, state and Federal waste laws.

13 Special Considerations:

This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations.

	internally. Keen away from heat and onen flame. KFFP OUT OF THE REACH OF CHILDREN. Terms & Definitions:
-	Please see last page of this SDS.
	Disclaimer: This Safety Data Sheet (SDS) is offered persuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other governement regulations must be reviewed for applicability to this product. To the best of McConnell Labs' knowledge, the information contained herein is reliable and accurate as of the date it was prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to sonsult the latest edition.
	Prepared for: VanDahl Inc. Luminary Nail Systems 8784 S. Maryland Pkwy STE 125 Las Vegas, NV 89123 NAIL SYSTEMS

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective

기 of 8

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	ACGIH American Conference on Governmental Industrial Hygienists			
TLV	TLV Threshold Limit Value			
OSHA	OSHA U.S. Occupational Safety and Health Administration			
PEL	PEL Permissible Exposure Limit			
IDLH Immediately Dangerous to Life and Health				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard		
1	1 Slight Hazard		
2	2 Moderate Hazard		
3	3 Severe Hazard		
4	4 Extreme Hazard		



PERSONAL PROTECTION RATINGS:

TERCONAL TROTEOTION TO TIMOS.					
Α					
В					
С					
D					
E					
F					





Full Face Respirator











Respirator







a Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available	
NR	NR No Results	
NE	Not Established	
ND	Not Determined	
ML	Maximum Limit	
SCBA	Self-Contained Breathing Apparatus	

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Minimum temperature required to initiate combustion in air with no oth Temperature source of ignition						
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

	Minimal Hazard		
0			
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4 Extreme Hazard			
ACD Acidic			
ALK Alkaline			
COR Corrosive			
w	Use No Water		
OX Oxidizer			
TREFOIL Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD_lo	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TCo, LCio, & LCo	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	EPA U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	SCA U.S. Toxic Substance Control Act				
EU	EU European Union (European Union Directive 67/548/EEC)				
WGK	WGK Wassergefährdungsklassen (German Water Hazard Class)				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(2)	@	(T)	®		(R)
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

	C E F		*			×	×
С			N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

				A LANGE OF THE PARTY OF THE PAR		(!)		(
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment