luminary NAIL SYSTEMS

# **SAFETY DATA SHEET**

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards SDS Revision: 4.11 SDS

SDS Revision Date: 04/15/2021

	1. PRODUCT INDENTIFICATION
1.1	Product Name: Luminary Multi-Flex Clarity
1.2	Chemical Name: POLYURETHANE (METH)ACRYLATE PREPOLYMER RESIN BLEND
1.3	Synonyms: NA
1.4	Trade Names: NA
1.5	Product Use: PROFESSIONAL USE ONLY, EXPERNAL USE ONLY, KEEP OUT OF THE REACH OF CHILDREN
1.6	Manufacturer's Name: VanDahl Inc.
1.7	Manufacturer's Adress:
	8784 S. Maryland Pkwy STE 125 Las Vegas, NV 89123
1.8	Emergency Phone: CHEMTREC: +1 703 527 3887 / +1 800 424 9300 (CCN 866131)
1.9	Business Phone / Fax:
	725-204-1928
	2. HAZARD INDENTIFICATION
2.1	Hazard Identification: WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H): H226 - Flammable liquid and vapor. H317 - May cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P223 - Keep container tightly closed. P243 - Take precaustionary measures against static discharge. P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaiminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - ilf eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).
2.2	Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES
2.3	Effects of Exposure:         INGESTION:       If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression.         EYES & SKIN:       The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin reactions (a g raches walts dermatitic) upon prolonged or repeated evacuure         INHALATION:       Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give some warning of exposure but odor fatigue may occur.
2.4	Symptoms of Overexposure: Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure.
2.5	Acute Health Effects: Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.
2.6	Chronic Health Effects: The material may cause an allergic reaction for some sensitive individuals.
2.7	Target Organs: Eyes, skin
R	

1 of 8

		5. COIVII	POSITION		-									2
							.imits		(mg/m3	3)	0011	<u>,                                     </u>		
						GIH		NOHS			OSH/			
					p	om I	ES-	ES-	ES-		ppm			
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL		PEL	STEL	IDLH	OTHER	
Bis-Hydroxyethyl	NA	NA	NA	40-45	NA	NA	NA	NA	NF	NA	NA	NA		
Methacrylate Poly (Neopentyl Glycol Adipate) / IPDI Copolymer Dilution														
lsobornyl Methacryalte	7534-94-3	NA	231-403-1	20-50	NA	NA	NA	NA	NF	NA	NA	NA		
Trimethylolpropane Trimethacrylate	3290-92-4	NA	NA	5-13	NA	NA	NA	NA	NF	NA	NA	NA		
Bis(methacryloyloxy-	32435-46-4	NA	NA	1-5	NA	NA	NA	NA	NF	NA	NA	NA		-
ethyl) Phosphate		-	-	-	-	-	-	-	-	-	-			
1-hydroxycyclohexyl	947-19-3	NA	278-355-8	1-3	NA	NA	NF	NF	NF	NA	NA	NA		
phenylketone														
Acrylates Copolymers	25035-69-2	NA	NA	0-1	NA	NA	NA	NA	NF	NA	NA	NA		_
MAY ALSO CONTAIN:	<u>I</u>													-
CI 77891 (Titanium	13463-67-7	XR2275000	236-675-5	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
Dioxide)														
CI 15850 (Red 6)	17852-98-1	NA	241-806-4	⊴0.1	NA	NA	NF	NF	NF	NA	NA	NA		_
CI 77002 (Yellow 10)	21645-51-2	GL8510000	215-573-4	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		_
CI 77007 (Ultramarine Blue)	57455-37-5	BQ4725000	215-111-1	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		_
CI 45410 (Red 28)	18472-87-2	NA	241-409-6	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77499 (Black Iron Oxide)	52357-70-7	NA	257-870-1	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
MICA	12001-26-2	ZF6680000	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 16035 (Red 40)	25956-17-6	VV8760000	247-368-0	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 19140 (Yellow 5)	12225-21-7	NA	235-428-9	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 45410 (Red 48)	18472-87-2	NA	242-355-6	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77499 (Iron Oxide)	12227-89-3	NA	235-442-5	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
Cl 77491 (Iron Oxide)	1309-37-1	NA	215-168-2	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		_
Polybutylene Terephthalate	26062-94-2 Eye Irritant 2; H3	NA 319	NA	⊴0.1	NA	NA	NF	NF	NF	NA	NA	NA		_
Polyethylene	25038-59-9	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
Terephthalate														
CI15880 (Red 63)	6417-83-0	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 19140 (Yellow 23 Al	12225-21-7	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
Lake) CI 15850 (Red 57)	5281-04-9	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77510 (Prussion	25869-00-5	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
Blue)		NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		

CI 15850 (Red 7)	6417-83-0	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	3
CI 42090 (Blue 1)	15792-67-3	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
		-	1			1	1	1	-	1	-	-	1
CI 77510 (Blue 27)	25869-00-5	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	<u> </u>
CI 77266 (Carbon	1333-86-4	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
Black)													
Acrylates Copolymer	25035-69-2	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
Bis(glycidoxyphenyl)p	146277-66-9	NA	500-326-8	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
opane/Bisaminometh	21645-51-2		244-492-7										
ylnorbornane	18472-87-2		242-355-6										
Copolymer /	17372-87-1		241-409-6										
Aluminum hydroxide /	8004-92-0		NA										
CI 45410 / CI 45380 /													
Bis(glycidoxyphenyl)p	146277-66-9	NA	500-326-8	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
opane/Bisaminometh	21645-51-2		244-492-7										
ylnorbornane	18472-87-2		242-355-6										
Copolymer /	17372-87-1		241-409-6										
Aluminum hydroxide /													
CI 45410 / CI 45380													
Aluminum	1333-86-4	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
Polyurethane-33	125826-44-0	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	1
, u. cu. u. c	00 0												•
Aluminum	7429-90-5	NA	NA	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	
CI 60725 (Violet #2)	81-48-1	NA	201-353-5	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	

	4. FI	<b>RST AID</b>	MEASURES
--	-------	----------------	----------

4.1	First Aid:			
	INGESTION:	If ingested, do not induce vomiting! If product has been swallowed, drink p is vomiting, continue to offer water or milk. Never give water or milk to an Control Center or local emergency number. Provide an estimate of the tim amount of the substance that was swallowed.	unconscious person. Contact the	e nearest Poison
	SKIN & EYES:	If product gets in the eyes, flush with copious amounts of lukewarm water to ensure thorough irrigation. Seek immediate medical attention. If proble irritation occurs & product is on the skin, rinse thoroughly with lukewarm w affected area with plenty of soak and waster. Remove all contaminated clo before reuse. If irritation, redness or swelling persists, consult a physician	m persists, seek immediate med vater followed by a thorough was thing including footwear and wa immediately.	ical attention. If shing of the sh thoroughly
	INHALAHON.	Remove victim to fresh air at once. If breathing stops, perform artificial res	piration. Seek immediate medica	a allention.
4.2	Medical Conditi	ons Aggravated by Exposure:	HEALTH	1
	Pre-existing de	rmatitis, other skin conditions and disorders of the target organs (eyes, skin)	FLAMMABILITY	0
			PHYSICAL HAZARDS	0
			PROTECTIVE EQUIPMENT	В
			EYES SKIN	

5. FIREFIGHTING MEASU
-----------------------

5.1 Flashpoint & Method:
--------------------------

> 100 °C (> 212 °F)
5.2 Autoignition Temperature:

NA

5.3 Flammability Limits:5.4 Fire & Explosion Hazards:

Upper Explosive Limit (UEL): NA

 This product is slightly flammable. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)

 5.5
 Extinguishing Methods:

Lower Explosive Limit (LEL): NA

Water, Foam, CO2, Dry Chemical

5.6 Fire Fighting Procedures:

First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water before returnign to service.

# 6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material to UV light source for 2-5 minutes. Lift cured material and place into appropriate closed container solution (e.g., Sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container(s). Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of

# 7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers shoiuld be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 °C (122 °F).

# 8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls:	Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate de equipment is available (e.g., sink, safety shower, eve wash station).	econtaimination
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.	
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.	
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves.	

4 of 8

8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities		
		(e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon	5 c	of 8
		completion of work activities involving large quantities of this product, wash any		
		exposed areas thoroughly with soap and water.		

## 9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	1.1
9.2	Boiling Point:	NA
9.3	Melting Point:	ND
9.4	Evaporation Rate:	NA
9.5	Vapor Pressure:	NA
9.6	Appearance & Color:	Clear or pigmented liquid
9.7	Odor Threashold:	NE
9.8	Solubility:	Not soluble
9.9	pH:	NA
9.1	Viscosity:	approximately 4,000 cps
9.1	Flash Point:	NA
9.1	Other Information:	NA

# **10. STABILITY & REACTIVITY**

# Stability: Relatively stable under ambient conditions when stored properly. Hazardous Decomposition Products:

If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon and nitrogen).

### 10 Hazardous Polymerization:

Will not occur.

# 10 Conditions to Avoid:

Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.

11 Incompatable Substances:

## Strong oxidizers, peroxides, strong acids or alkalis.

## **11. TOXICOLOGICAL INFORMATION**

## 11 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the produt which are found in scientific literature. These data have not been presented in this document. 11 Acute Toxicity: See Section 2.5 11 Chronic Toxicity: See Section 2.6 11 Suspected Carcinogen: The ingredients of this product are not listed as carcinogens by the National Toxicology Program and have not been evaluated by the Internail Agency for Research on Cancer or the American Conference of Government Industrial Hygenists. 12 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embrvotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This products is not reported to cause teratogenic effects in humans. 12 Irritancy of Product: See Section 2.3 12 Biological Exposure Indicies: NE 12 Physician Recommendations: Treat syptomatically

## **12. ECOLOGICAL INFORMATION**

12 Environmental Stability:

This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Butyl Acetate: K<sub>oc</sub> = 1.82. Water Solubility: 120 parts H<sub>2</sub>O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization and biodegredation. This compound's half life is 6.1 hours.

12	Effects on Plants & Animals: There is no specific data availble for this product on plant life.	6
12	Effects on Aquatic Life:	
	There is no specific data availble for this product on aquatic life.	
	13. DISPOSAL CONSIDERATIONS	
13	Waste Disposal:	
13	Dispose inaccordance with local, state and Federal waste laws. Special Considerations:	
	This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastic environment and is more easily handled for disposal according to local, state and Federal regulations.	s is safer for the
	14. TRANSPORTATION INFORMATION	
The b	pasic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transpo	ortation. Additional
	riptive information may be required by 49 CFR. IATA/ICAO. IMDG. SCT. ADR and the CTDGR.	
14	49 CFR (GRD): NOT REGULATED	
14	IATA (AIR): NOT REGULATED	
	NOT REGULATED	
14	IMDG (OCN):	
14	NOT REGULATED TDGR (Canadian GND):	
14	NOT REGULATED	
15	ADR/RID (EU): NOT REGULATED	
15	MEXICO (SCT):	
	NOT REGULATED	
15	ADGR (AUS): NOT REGULATED	
	15. REGULATORY INFORMATION	
15	SARA Reporting: NA	
15	SARA Threshold Planning Quantity:	
15	TSCA Inventory Status:	
45	All components of this product are listed in the TSCA Inventory or are exempt	
15	CERCLA Reportable Quantity (RQ): NA	
16	Other Federal Requirements:	
16	This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetic: Other Canadian Regulations:	s).
10	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information	Æ
	required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this	Ċ
16	product are on the Priorities Substances List. State Regulatory Information:	
10	Ingredients in this mixture are found on the following state criteria lists: <u>Titanium Dioxide</u> is listed on the following state criteria	eria list(s):
	Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right-to-Know Lis	
	Permissible Exposure List (WA).	
16	67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements:	
	The primary concents of this product are not listed in Annex 1 of EU Directive 67/548/EEC. Irritant (Xi). Risk Phrases (R):	
	36/37/38 - Irritating to eyes, respiratory system and skin. Safety Phrases (S): 2-23-29 - Keep out of reach of Children. Do	
	not breath gas, fumes, vapor or spray. Do not empty into drains.	
1		

5 of 8

	16. OTHER INFORMATION	Z of 8
16	Other Information: WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - get medical advice/attention. Do not take internally. Keep away from heat and open flame. KEEP OUT OF THE REACH OF CHILDREN.	
16	Terms & Definitions: Please see last page of this SDS.	
16	Disclaimer: This Safety Data Sheet (SDS) is offered persuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other governement regulations must be reviewed for applicability to this product. To the best of McConnell Labs' knowledge, the information contained herein is reliable and accurate as of the date it was prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to sonsult the latest edition.	
16	Prepared for: VanDahl Inc. Luminary Nail Systems 8784 S. Maryland Pkwy STE 125 Las Vegas, NV 89123 NAIL SYSTEMS	
17	Prepared by: McConnell Labs, Inc. 406 SW Umatilla Ave Redmond, OR 97756 USA Tel: +1 541 526 1417 Fax: +1 541 526 1418	

٦

ſ

## **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following: GENERAL INFORMATION:

#### CAS No. Chemical Abstract Service Number

#### EXPOSURE LIMITS IN AIR:

ACGIH	CGIH American Conference on Governmental Industrial Hygienists					
TLV	Threshold Limit Value					
OSHA U.S. Occupational Safety and Health Administration						
PEL Permissible Exposure Limit						
IDLH	Immediately Dangerous to Life and Health					

#### FIRST AID MEASURES:


CPR Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.

## HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

#### HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTIO
4	Extreme Hazard	

#### PERSONAL PROTECTION RATINGS:



#### OTHER STANDARD ABBREVIATIONS:

NA	NA Not Available						
NR	No Results						
NE	NE Not Established						
ND Not Determined							
ML	Maximum Limit						
SCBA	Self-Contained Breathing Apparatus						

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	LEL Lower Explosive Limit - lowest percent of vapor in air, by volume, that w explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

#### HAZARD RATINGS:

0	Minimal Hazard					
1 Slight Hazard						
2 Moderate Hazard						
3	Severe Hazard					
4	Extreme Hazard					
ACD	Acidic					
ALK	Alkaline					
COR	Corrosive					
w	Use No Water					
ох	Oxidizer					
TREFOIL	Radioactive					



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>to</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>lo</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	SL Canadian Non-Domestic Substance List					
PSL	PSL Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	EU European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

$\bigcirc$	۲	٨		1			(ř)
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### EC (67/548/EEC) INFORMATION:

		*	¥		<b>₽</b> X	×	×
С	E	F	N	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

#### CLP/GHS (1272/2008/EC) PICTOGRAMS:

			$\Diamond$					
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment