

Cabled Mittens

By Isaac Mizrahi CRAFT Design Team
Level: Intermediate



SIZES

Adult Medium

FINISHED MEASUREMENTS

Hand Circumference: 8"

MATERIALS

Isaac Mizrahi® CRAFT™ Skyscraper by Premier® Yarns (64% acrylic, 12% wool, 12% bamboo, 12% alpaca; 100 g/166 yds)

- IM2014-06 Hearst – 1 ball

Needles: US Size 10 (6 mm) knitting needles *or size needed to obtain gauge*

Notions: Tapestry needle, stitch markers, stitch holder

GAUGE

14 sts x 22 rows = 4" in St st

Save time, check your gauge.

STITCH PATTERNS

2x2 Ribbing (*multiple of 4 sts + 2*)

Row 1 (WS): P2, * k2, p2; repeat from * to end.

Row 2 (RS): K2, * p2, k2; repeat from * to end.

Repeat Rows 1 and 2 for pattern.

Cable Panel (*worked over 14 sts*)

Row 1 (RS): P2, 2/2 RC, p2, 2/2 LC, p2.

Row 2 (WS): K2, p4, k2, p4, k2.

Row 3: P2, k4, p2, k4, p2.

Row 4: Repeat Row 2.

Repeat Rows 1-4 for pattern.

Stockinette Stitch (*any number of stitches*)

Knit the RS rows.

Purl the WS rows.

Right Mitten

Cast on 26 sts.

Cuff:

Work in 2x2 Ribbing for 7 rows, ending with a WS row.

Next row (RS): K2, pm, p2, [k1, m1] twice, p2, [k1, m1] twice, p2, pm, k2, * p2, k2; rep from * to end. - 30 sts

Next row (WS): P2, [k2, p2] to m, k2, p4, k2, p4, k2, p2.

Begin Cable Panel:

Next row (RS): K2, work Row 1 of Cable Panel between markers, knit to end.

Next row (WS): Purl to m, work Row 2 of Cable Panel between markers, purl to end.

Continue in patt as established, with Cable Panel between markers and Stockinette st on rem sts.

Shape Thumb Gusset:

Row 1 (RS): K2, work Cable Panel to m, k2, pm, m1, pm, knit to end.

Row 2 (WS): Work in established patt.

Row 3 - Increase Row: Work in patt to third m, sm, m1, knit to fourth marker, m1, sm, work in patt to end. - 3 sts in thumb gusset.

Continue in patt, rep Increase Row every RS row 2 more times, then every 4th row twice. -11 sts in thumb gusset; 41 sts total

Next RS row: Work in patt to third m, remove m, slip 11 gusset sts to stitch holder, remove m, work in patt to end. - 30 sts rem

Continue in established patt until piece measures 3" past the row where thumb gusset was put on holder, ending with a WS row.

Shape Top:

Note: The shaping will encroach on the Cable Panel. Remove the stitch markers on either side of the Cable Panel.

Row 1 (RS): K1, ssk, p1, k4, p2, k4, p1, k2tog, ssk, knit to last 3 sts, k2tog, k1. - 26 sts.

Row 2 (WS): P12, k1, p4, k2, p4, k1, p2.

Row 3: K1, ssk twice, k2, p2, k2, k2tog twice, ssk, knit to last 3 sts, k2tog, k1. - 20 sts.

Row 4: P13, k2, p5.

Row 5: K1, ssk twice, p2, k2tog twice, ssk, knit to last 3 sts, k2tog, k1. - 14 sts.

Row 6: P9, k2, p3.

Row 7: K1, ssk, p2, k2tog, ssk, k2, k2tog, k1. - 10 sts.

Row 8: P6, k2, p2.

Row 9: K1, ssk, k2tog, ssk, k2tog, k1. - 6 sts.

Break yarn, leaving a tail 18" long. Use tapestry needle to draw tail through remaining sts and pull tight. Leave tail attached.

Thumb:

Return 11 thumb sts to needles. Join yarn ready to work a RS row.

Work in 10 rows in Stockinette St, ending with a WS row.

Next row (RS): [K1, k2tog] 3 times, k2. - 8 sts.

Next row (WS): Purl.

Next row: K1, k2tog 3 times, k1. - 5 sts.

Break yarn, leaving 12" tail. Use tapestry needle to draw tail through rem sts and pull tight. Continuing with tail, sew side seam of thumb, closing up any gaps at base of thumb.

Use tail from top of mitten to sew side seam from top to cuff.

Left Mitten

Cast on 26 sts.

Cuff:

Work in 2x2 Ribbing for 7 rows, ending with a WS row.

Next row (RS): K2, [p2, k2] 3 times, pm, p2, [k1, m1] twice, p2, [k1, m1] twice, pm, k2. - 30 sts.

Next row (WS): P2, k2, p4, k2, p4, k2, p2, * k2, p2; rep from * to end.

Begin Cable Panel:

Next row (RS): Knit to marker, work Row 1 of Cable Panel between markers, knit to end.

Next row (WS): Purl to marker, work Row 2 of Cable Panel between markers, purl to end.

Continue in patt as established, with Cable Panel between markers and Stockinette St on remaining sts.

Shape Thumb Gusset:

Row 1 (RS): K12, pm, m1, pm, k2, work Cable Panel to marker, knit to end.

Row 2 (WS): Work in established patt.

Row 3 - Increase Row: Work in patt to first m, sm, m1, knit to second marker, m1, sm, work in patt to end. - 3 sts in thumb gusset.

Continue in patt, rep Increase Row every RS row 2 more times, then every 4th row twice. - 11 sts in thumb gusset; 41 sts total

Next RS row: Work in patt to first m, remove m, slip 11 gusset sts to stitch holder, remove second marker, work in patt to end. - 30 sts remain.

Continue in established patt until piece measures 3" past the row where thumb gusset was put on holder, ending with a WS row.

Shape Top:

Note: The shaping will encroach on the Cable Panel. Remove the stitch markers on either side of the Cable Panel.

Row 1 (RS): K1, ssk, k8, k2tog, ssk, p1, k4, p2, k4, p1, k2tog, k1. - 26 sts.

Row 2 (WS): P2, k1, p4, k2, p4, k1, purl to end.

Row 3: K1, ssk, k6, k2tog, ssk twice, k2, p2, k2, k2tog twice, k1. - 20 sts.

Row 4: P5, k2, purl to end.

Row 5: K1, ssk, k4, k2tog, ssk twice, p2, k2tog twice, k1. - 14 sts.

Row 6: P3 k2, purl to end.

Row 7: K1, ssk, k2, k2tog, ssk, p2, k2tog, k1. - 10 sts.

Row 8: P2, k2, p6.

Row 9: K1, ssk, k2tog, ssk, k2tog, k1. - 6 sts.

Break yarn, leaving a tail 18" long. Use tapestry needle to draw tail through rem sts and pull tight. Leave tail attached.

Work Thumb and sew seams same as for Right Mitten.

FINISHING

Weave in ends and lightly block.

Abbreviations

k: knit

k2tog: knit 2 stitches together

m: marker(s)

m1: insert left hand needle from back to front under the strand running between last st worked and next st, knit into the front of this loop. 1 st increased.

p: purl

patt: pattern

pm: place marker on needle

RS: Right Side

rem: remain(ing)

rep: repeat(ing)

sm: slip marker

ssk: slip 2 sts individually as if to knit, then knit these 2 sts together through back loops

st(s): stitch(es)

WS: Wrong Side