PREMIER®



Cross Cable Pullover

SIZES

XS (S, M, L, 1X) (2X, 3X, 4X, 5X) Shown in S Size.

FINISHED MEASUREMENTS

Bust: 38 (42, 46, 50, 54) (58, 62, 66, 70)", intended to fit with 6-8" of positive ease **Length:** 18½ (19, 20, 20½, 21) (22, 22½, 23, 24)"

MATERIALS

Premier® Yarns Snow Cone™ Light Chenille (100% Polyester; 7oz/200g, 188yds/172m)

2013-11 Passion Fruit – 3 (3, 3, 4, 4) (5, 5, 6, 6) balls

Needle: US Size 11 (8 mm) straight or 24" circular needle (or longer) or size needed to obtain gauge

US Size 10 (6 mm) straight or 24" circular needle (or longer) and 16" circular needle (for Cowl Neck)

Notions: Tapestry needle, stitch markers, removable stitch markers, cable needle, stitch holders

GAUGE

10 sts x 12 rows = 4" in St st with larger needle **Save time, check your gauge.**

Skills/techniques used in pattern:

- Knit and purl stitches.
- Decreasing.
- Sewing seams using mattress stitch.
- Picking up and knitting stitches.
- Working flat and in the round.
- Cable cross stitch.

STITCH GUIDE

3x3 Right Cross (3x3 RC): SI next 3 sts to cn and hold in back, k3 from left needle, k3 from cn.

K1, P1 Ribbing (even number of sts) **Row 1:** * K1, p1; rep from * to end.
Rep Row 1 for patt.

Cable (panel of 8 sts)

Row 1 (RS): P1, k6, p1.

Row 2 (WS): K1, p6, k1.

Rows 3-4: Rep Rows 1-2.

Row 5: P1, 3x3 RC, p1.

Row 6: K1, p6, k1.

Rep Rows 1-6 for patt.

PATTERN NOTES

This cozy pullover is worked both flat and in the round. Front and Back are worked from the bottom up and sewn together at the shoulders. Then, stitches for the sleeves are picked up from the sides of the Front and Back. After seaming the sleeves and side, stitches are picked up for the Cowl Neck and worked in the round.

SWEATER

Back

Back Hem

With smaller needle, cast on 48 (52, 56, 64, 68) (72, 76, 84, 88) sts. Work in **K1, P1 Ribbing** for 2".

Main Back

Switch to larger needle.

Set-up row (WS): *P6 (7, 8, 10, 11) (12, 13, 15, 16), pm, k1, p6, k1, pm; rep from * 2 more times, p6 (7, 8, 10, 11) (12, 13, 15, 16).

Cross Cable Pullover

project continued

Row 1 (RS): * Knit to m, sl m, work Row 1 of Cable to m, sl m; rep from * 2 more times, knit to end.

Row 2 (WS): * Purl to m, sl m, work Row 2 of Cable to m, sl m; rep from * 2 more times, purl to end.

Continue as established through Row 6 of **Cable**, then rep Rows 1-6 until Back meas 12 (12, 12½, 12½, 12½) (13, 13, 13, 13½)" from cast-on edge, ending with any WS row.

Place removable markers each side to indicate armhole opening. Continue in patt as est'd until piece meas 6½ (7, 7½, 8, 8½) (9, 9½, 10, 10½)" from armhole markers, ending with WS row.

Next row: Bind off 15 (17, 19, 22, 24) (26, 27, 31, 33) Shoulder sts, place 18 (18, 18, 20, 20) (20, 22, 22, 22) Neck sts on holder, Bind off 15 (17, 19, 22, 24) (26, 27, 31, 33) Shoulder sts.

Front

Work as for Back until Front meas 4% (5, 5%, 6, 6%) (7, 7%, 8, 8%)" from armhole markers, ending with WS row.

Shape Front Neck

Place markers on either side of center 10 (10, 10, 10, 12) (12, 12, 12, 12) sts.

Row 1 (RS): Work over Left Front sts in patt as est'd to marked Neck st, place center 10 (10, 10, 10, 12) (12, 12, 12, 12) sts on holder, with new ball of yarn, work over Right Front sts in patt as est'd to end - 17 (19, 21, 23, 24) (26, 28, 30, 32) sts rem each for Left and Right Front. Place Left Front sts on holder.

Row 2 (WS): Work in patt to last 3 sts, p2tog, p1 - 1 st dec'd.

Row 3: K1, k2tog, work in patt to end – 1 st dec'd.

Row 4: Rep Row 2-1 st dec'd, 14 (16, 18, 20, 21) (23, 25, 27, 29) sts rem. Work even for 2 more rows or until piece meas $6\frac{1}{2}$ (7, $7\frac{1}{2}$, 8, $8\frac{1}{2}$) (9, $9\frac{1}{2}$, 10, $10\frac{1}{2}$)" from armhole markers, ending with WS row. Bind off all sts.

Return Right Front sts to needle.

Row 2 (WS): P1, p2tog, work in patt to end -1 st dec'd.

Row 3 (RS): Work in patt to last 3 sts, ssk, k1 - 1 st dec'd.

Row 4: Rep Row 2-1 st dec'd, 14 (16, 18, 20, 21) (23, 25, 27, 29) sts rem. Work even for 2 more rows or until piece meas $6\frac{1}{2}$ (7, $7\frac{1}{2}$, 8, $8\frac{1}{2}$) (9, $9\frac{1}{2}$, 10, $10\frac{1}{2}$)" from armhole markers, ending with WS row. Bind off all sts.

Sew Shoulder Seams using mattress stitch.

Sleeves

With larger needle and RS facing, pick up and knit 34 (36, 38, 40, 44) (46, 48, 50, 54) sts evenly between Armhole markers. Work even in St st until piece meas 3" from picked-up edge, ending with WS row.

Dec Row (RS): K1, k2tog, knit to last 3 sts, ssk, k1-2 sts dec'd.

Rep Dec Row every 6 (6, 6, 4, 4) (4, 4, 4, 4) rows, 1 (1, 1, 7, 7) (6, 7, 6, 4) more time(s), then rep Dec Row every 4 (4, 4, 2, 2) (2, 2, 2, 2) rows, 5 (6, 6, 1, 2) (4, 3, 5, 9) time(s) - 20 (20, 22, 22, 24) (24, 26, 26, 26) sts rem. Work even in St st until piece meas 14 (14, 14½, 14½, 15) (15, 15½, 15½, 16)" from picked-up edge, ending with WS row. Switch to smaller needle. Work in **K1, P1 Ribbing** for 2". Bind off all sts in patt.

FINISHING

Sew Sleeve and Side seams using mattress stitch.

Cowl Neck

With smaller 16" circular needle and RS facing, knit across 18 (18, 18, 20, 20) (20, 22, 22, 22) sts along Back Neck, pick up and knit 6 sts along Left Front Neck, knit across 12 (12, 12, 14, 14) (14, 16, 16, 16) sts along Front Neck bind-off edge, pick up and knit 6 sts along Right Front Neck – 42 (42, 42, 46, 46) (46, 50, 50, 50) sts. Pm and join to work in the rnd, being careful not to twist.

Rnd 1: * K1, p1; rep from * to end.

Rep Rnd 1 until Cowl Neck meas 7". Bind off all sts in patt.

Note: Cowl Neck is intended to be worn folded down in half. For a shorter neck, work fewer rounds.

Weave in ends and block.

Abbreviations

cn cable needledec('d) decreasedest'd established

k knit

k2tog knit 2 sts together (1 st dec'd)

m markermeas measuresp purl

p2tog purl 2 sts together (1 st dec'd)

patt pattern
pm place marker
rem remain(ing)
rep repeat(ing)



project continued

