## ROLL STRIES

Address: 15401 Cobalt St. Sylmar, Website: www.roncofurniture.com Toll Free: 1800 - 468 - 8738 Local: 818 - 362 - 1578 Fax: 818 - 362 - 1484 Email: info@roncofurniture.com

## Product General and Technical Information

Date: 12/19/2001

General Information
Dryfast foam is a greatquality foam with a firm feel.
Dryfast's wide, open cells
allow it to drain liquid easily,
so it doesn't absorb moisture
like conventional foams.
Common applications
include outdoor uses like
patio cushions, boat
cushions and boat
mattresses. Typical life is 5
to 8 years.

## DRY FAST WATER PROOF FOAM PADDING

Property	Test Method	Values
Density (LB/Cubic Ft.) 25% IFD (LB) 65% IFD (LB) Ceil Count (Pores PSI) Air Flow (CFM) Tensile (PSI) Min. Elongation (%) Min. Tear (PSI) Min. Sag Factor (Nominal) Compression Set (@ 50% Deflection) % Max. 25% CLD Autoclave Loss (% Max.) Compression Set (@ 50% Deflection Autoclave Loss) % Max. Tensile Strength Dry Heat Loss (% Max.) Fire Retardant Classification	ASTM 3574-91 (ali)	1.8 60 105 25 20 20 150 5.0 1.8 20 25 10

All values reported are typical values. We cannot guarantee the applicability or the accuracy of this information or the sultability of the product for any particular purpose. This product is sold without warranty, expressed or implied. (Unless stated otherwise.) Buyer assumes all responsibility for loss or damage arising from the handling and use of this product, whether done in accordance with directions or not. Statements concerning the possible use of this product are not intended as recommendation to use this product in the infringement of any patent.