

1100	100	S.R.P.	22,350.00
		82 mm (3-1/4") 750 W Power Planer	
		Continuous rating Input 750W Planing Width 82 mm (3-1/4") Planing Depth 3 mm (1/8") No Load Speed (RPM) 18,000 Net weight 5.1 kg (11.2 lbs.) Shipping 20mm (3/4")	

1600	100	S.R.P.	24,000.00
		80 mm (3-1/8") 750 W Power Planer	
		Continuous rating Input 750W Planing Width 80 mm (3-1/8") Planing Depth 3 mm (1/8") No Load Speed (RPM) 16,000 Net weight 5.3 kg (11.8 lbs.) Shipping No	

1804N	153	S.R.P.	28,900.00
		136 mm (5-3/8") 960 W Power Planer	
		Continuous rating Input 960W Planing Width 136 mm (5-3/8") Planing Depth 3 mm (1/8") No Load Speed (RPM) 16,000 Net weight 7.9 kg (17.4 lbs.) Shipping No	

1805N	153	S.R.P.	29,600.00
		155 mm (6-1/8") 1,140 W Power Planer	
		Continuous rating Input 1,140W Planing Width 155 mm (6-1/8") Planing Depth 2 mm (1/16") No Load Speed (RPM) 15,000 Net weight 7.9 kg (17.3 lbs.) Shipping No	

1806B	153	S.R.P.	30,450.00
		170 mm (6-3/4") 1,200W Power Planer	
		Continuous rating input 1,200W Planing Width 170 mm (6-3/4") Planing Depth 2 mm (1/16") No Load Speed (RPM) 15,000 Net weight 8.8 kg (19.3 lbs.) Shipping No	

1911B	106	S.R.P.	16,600.00
		110 mm (4-3/8") 840 W Power Planer Power	
		Continuous rating Input 840W Planing Width 110 mm (4-3/8") Planing Depth 2 mm (1/16") No Load Speed (RPM) 16,000 Net weight 4.1 kg (9.1 lbs.) Shipping No	

2012NB	153	S.R.P.	46,950.00
		304 mm (12") 1,650 W Planer	
		Continuous rating Input 1,650W Planing Width 304 mm (12") Cutting Width 304 mm (12") Cutting Depth Cutting width 0-150 mm: 3 mm (1/8") Cutting width 150-240 mm: 1.5 mm (1/16") Feed rate/min. 8.5 m (27.9 ft) No Load Speed (RPM) 8,500 Net weight 27.1 - 27.6 kg (59.7 - 60.9 lbs.)	

2107FK	303	S.R.P.	25,950.00
		120 x 120 mm (4-3/4" x 4-3/4") 710 W Variable Speed Portable Band Saw with Light	
		Continuous rating Input 710W Capacity Round: 120 mm (4-3/4") Rectangular: 120 x 120 mm (4-3/4 x 4-3/4") Blade speed 1.0 - 1.7 m/s Blade Size Length: 1,140 mm Width: 13 mm Thickness: 0.5 mm Net weight 6.3 kg (13.9 lbs.)	

2414	153	S.R.P.	27,900.00
		355 mm (14") 1,430 W Portable Cut-Off	
		Continuous rating Input 1,430W Wheel diameter 355mm (14") Hole dia. 25.4mm (1") No load speed (rpm) 3,800 Net weight 16.2 kg (35.7 lbs)	



2414NB	203	S.R.P.	14,000.00
		355 mm (14") 1,430 W Portable Cut-Off	
		Continuous rating Input 2,000W Wheel diameter 355mm (14") Hole dia. 25.4mm (1") No load speed (rpm) Net weight 3,800 18.4kg (40.6lbs)	

2416S	153	S.R.P.	39,550.00
		405 mm (16") 1,430 W Portable Cut-Off	
		Continuous rating Input 1,430W Wheel Diameter 405 mm (16") Hole Diameter 25.4 mm (1") No Load Speed (RPM) 2,300 Net weight 19.2 kg (42.3 lbs.)	

2703	153	S.R.P.	50,000.00
		255 mm (10") 1,650 W Table Saw	
		Continuous rating Input 1,650W Max Cutting Capacity 0°: 91 mm (3-9/16") 45°: 63 mm (2-1/2") Wheel Diameter 255 mm (10") No Load Speed (RPM) 4,600 Net weight 17.8 - 18.9 kg (39.2 - 41.7 lbs.)	

3501N	153	S.R.P.	30,950.00
		120 mm (4-3/4") 1,160 W Groove Cutter	
		Continuous rating Input 1,160W Max cutter blade size Diameter x Width: 120 x 36 mm (4-3/4 x 1-3/8") Max cutting depth Cutter / Cutter: 30 mm (1-1/8") / 65 mm (2-1/2") No Load Speed (RPM) 6,500 Net weight 7.2 kg (15.8 lbs.)	


3600H	153	S.R.P.	19,600.00
		1/4 / 3/8 / 1/2" 1,500 W D-Handle Router	
		Continuous rating Input 1,500W Collet size 1/4 / 3/8 / 1/2" Base dia. 160 mm (6-1/4") Base inner 40 mm (1-9/16") No Load Speed (RPM) 24,000 Net weight 4.4 kg (9.8 lbs.)	



3601B **153** **W** S.R.P. 18,650.00

1/4" / 3/8" / 1/2" 930 W D-Handle Router

Continuous rating Input 930W
 Collet size 1/4" / 3/8" / 1/2"
 Base inner 40 mm (1-9/16")
 No Load Speed (RPM) 23,000
 Net weight 3.6 kg (7.9 lbs.)



3710 **411** **W** S.R.P. 6,000.00

1/4" 530 W Tilt Base Trimmer


Continuous rating Input 530W
 Collet size 1/4"
 Base inner 28 mm (1-1/8")
 No Load Speed (RPM) 30,000
 Net weight 1.5 kg (3.3 lbs.)



4100KB **303** **W** S.R.P. 6,400.00

125 mm (5") 1,400 W Dustless Cutter, Dry Type


Continuous rating Input 1,400W
 Wheel Diameter 125 mm (5")
 Hole Diameter 20 mm (13/16")
 Max Cutting Capacity 40.0 mm (1-9/16")
 No Load Speed (RPM) 12,200
 Net weight 3 kg (6.6 lbs.)



4100NH2 **303** **W** S.R.P. 6,200.00

110 mm (4-3/8"), 125 mm (5") 1,400 W Cutter


Continuous rating Input 1,400W
 Wheel Diameter 110 - 125 mm (4-3/8" - 5")
 Max cutting capacity w/ 110mm (4-3/8") wheel 0°: 32.5 mm (1-1/4")
 45°: 21.5 mm (7/8")
 Max cutting capacity w/ 125mm (5") wheel 0°: 40.0 mm (1-9/16")
 45°: 27.0 mm (1-1/16")
 No Load Speed (RPM) 12,200
 Net weight 3 kg (6.6 lbs.)



4131 **303** **W** S.R.P. 22,800.00

185 mm (7-1/4") 1,100 W Metal Cutter


Continuous rating Input 1,100W
 Wheel Diameter 185 mm (7-1/4")
 Hole Diameter 15.88 / 20 / 30 mm (5/8" / 13/16" / 1-3/16")
 Capacity Max cutting: 63 mm (2-1/2")
 No Load Speed (RPM) 3,500
 Net weight 4.8 kg (11.3 lbs.)



4327M **64** **W** S.R.P. 4,800.00

450 W Top Handle Jig Saw


Continuous rating input 450W
 Capacity Wood: 65 mm (2-9/16")
 Steel: 6 mm (1/4")
 Length of Stroke 18 mm (11/16")
 Strokes Per Minute (SPM) 500 - 3,100
 Net weight 1.9 kg (4.2 lbs.)
 Power supply cord 2.0 m (6.6 ft)



4403 **411** **W** S.R.P. 58,800.00

1/4" 530 W Sash Router


Continuous rating Input 530W
 Collet size 1/4"
 Max width of work 123 mm (4-7/8")
 Max width of work (45°) 77 mm (3")
 Max height of work 185 mm (7-1/4")
 Transverse travel of table 113 mm (4-1/2")
 Longitudinal travel of table 73 mm (2-7/8")
 No Load Speed (RPM) 30,000
 Net weight 16 kg (35.3 lbs.)



3706 **64** **W** S.R.P. 9,300.00

6.35 mm (1/4") 550 W Cut-Out Tool


Continuous rating Input 550W
 Collet capacity 3.18, 6.35 mm or 1/8, 1/4"
 No Load Speed (RPM) 32,000
 Net weight 1.1 kg (2.4 lbs.)



3712 **411** **W** S.R.P. 7,000.00

1/4" Anti-Restart, Soft Start 530 W Tilt Base Trimmer


Continuous rating Input 530W
 Collet size 1/4"
 Base inner 28 mm (1-1/8")
 No Load Speed (RPM) 32,000
 Plunge capacity 0 - 42 mm (0 - 1-5/8")
 Net weight 1.7 kg (3.7 lbs.)



4100NH **303** **W** S.R.P. 5,800.00

110mm (4-3/8") 1,300 W Cutter


Continuous rating Input 1,300W
 Capacity Max. cutting : 34mm (1-5/16")
 Blade diameter 110mm (4-3/8")
 No load speed (rpm) 13,000
 Net weight 2.9kg (6.5lbs)



4107R **153** **W** S.R.P. 25,500.00

180 mm (7-1/8") 1,400 W Cutter


Continuous rating Input 1,400W
 Capacity Max cutting: 60 mm (2-3/8")
 Wheel Diameter 180 mm (7-1/8")
 No Load Speed (RPM) 5,000
 Net weight 6.3 kg (14.5 lbs.)



4300BV **51** **W** S.R.P. 13,500.00

390 W Variable Speed Jig Saw


Continuous rating Input 390W
 Capacity Wood: 55 mm (2-1/8")
 Steel: 6 mm (1/4")
 Length of Stroke 26 mm (1")
 Strokes Per Minute (SPM) 0 - 3,100
 Bevel range 0 - 45°
 Net weight 2.5 kg (5.5 lbs.)



4350CT **419** **W** S.R.P. 13,450.00

720 W Top Handle Jig Saw, 3 Orbital Settings





Continuous rating Input 720W
 Capacity Wood: 135 mm (5-5/16")
 Steel: 10 mm (3/8")
 Length of Stroke 26 mm (1")
 Strokes Per Minute (SPM) 800 - 2,800
 Bevel range 0 - 45°
 Net weight 2.7 kg (5.8 lbs.)



5008MG **153** **W** S.R.P. 13,650.00


210 mm (8-1/4") 1,800 W Magnesium Circular Saw

Continuous rating Input 1,800W
 Wheel Diameter 210 mm (8-1/4")
 Hole Diameter 25.4 mm (1")
 Max Cutting Capacity 0°: 75.5 mm (3")
 45°: 57 mm (2-1/4")
 50°: 51.5 mm (2")
 No Load Speed (RPM) 5,200
 Net weight 4.8 kg (10.6 lbs.)

5012B **153** **WJ** S.R.P. 14,100.00

AC 82 mm (3-1/4") 750 W Power Planer, 1,400 W, 1,600 m/min speed Electric Chain Saw




Continuous rating Input	1,140W
Chain speed per minute	1,600m (5,240ft)
Guide bar length	300mm (12")
Chain blade	Pitch : 3/8"
	Gauge : 0.050"
Net weight	4.4kg (9.6lbs)

MJ **2.5** Years Limited Warranty

5103N **153** **WJ** S.R.P. 30,100.00

AC 335 mm (13-1/8") 1,750 W Circular Saw




Continuous rating Input	1,750W
Wheel Diameter	335 mm (13-1/8")
Hole Diameter	25/ 25.4 mm (1")
Max Cutting Capacity	0°: 128 mm (5")
	45°: 91 mm (3-5/8")
No Load Speed (RPM)	2,900
Net weight	8.9 kg (19.6 lbs.)

MJ **2.5** Years Limited Warranty

6301 **106** **WJ** S.R.P. 11,400.00

AC 13 mm (1/2") 700 W Drill with Keyed Chuck




Continuous rating input	700W
Capacity	Steel: 13mm (1/2")
	Wood: 25mm (1")
No load speed (rpm)	1,300
Net weight	3.1 Kg (6.7 lbs)

MJ **2.5** Years Limited Warranty

6412 **64** **WJ** S.R.P. 3,650.00

AC 10 mm (3/8") 450 W Variable Speed Reversing Drill




Continuous rating Input	450W
Capacity	Steel: 10 mm (3/8")
	Wood: 25 mm (1")
	Wood (Self-feed bit): 50 mm (2")
Chuck capacity	1.5 - 10 mm (1/16 - 3/8")
No Load Speed (RPM)	0 - 3,400
Net weight	1.3 kg (2.9 lbs.)

MJ **2.5** Years Limited Warranty

6510LVR **64** **WJ** S.R.P. 10,450.00

AC 10 mm (3/8") 330 W Variable Speed Reversing Drill with Keyless Chuck




Continuous rating input	330W
Capacity	Steel: 10mm (3/8")
	Wood: 25mm (1")
Chuck capacity	1.5 - 10 mm (1/16 - 3/8")
No load speed (rpm)	0 - 1,200
Net weight	0.9 Kg (2.0 lbs)

MJ **2.5** Years Limited Warranty

6905B **64** **WJ** S.R.P. 21,450.00

AC 1/2" (12.7 mm) 294 N-m (217 ft.lbs.) Impact Wrench




Continuous rating input	440W
Fastening Capacities	Standard Bolt: M12 - M20 (1/2" - 3/4")
	High Strength Bolt: M12 - M16 (1/2" - 5/8")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	1,700
Impacts Per Minute (IPM)	2,000
Max Fastening Torque	294 N-m (217 ft.lbs.)
Net weight	2.8 kg (6.2 lbs.)

MJ **2.5** Years Limited Warranty

6922NB **411** **WJ** S.R.P. 92,800.00

AC M16 (5/8") / M20 (3/4") / M22 (7/8") 804 N-m (593 ft.lbs.) Shear Wrench




Continuous rating Input	1,330W
Capacity	Bolt: M16, M20, M22 (5/8, 3/4, 7/8")
No Load Speed (RPM)	18
Max fastening torque	804 N-m (593 ft.lbs.)
Net weight	4.9 kg (10.8 lbs.)

MJ **2.5** Years Limited Warranty

5057KB **153** **WJ** S.R.P. 23,400.00

AC 185 mm (7-1/4") 1,400 W Circular Saw with Dust Collection




Continuous rating Input	1,400W
Wheel Diameter	185 mm (7-1/4")
Hole Diameter	15.88/ 20/ 30 mm (5/8/ 13/16/ 1-3/16")
Max Cutting Capacity	0°: 60 mm (2-3/8")
	45°: 30 mm (1-1/8")
No Load Speed (RPM)	5,800
Net weight	5.1 kg (11.2 lbs.)

MJ **2.5** Years Limited Warranty

5606B **303** **WJ** S.R.P. 7,050.00

AC 160 mm (6-1/4") 1,050 W Circular Saw




Continuous rating input	950W
Blade Diameter	160 mm (6-1/4")
Max Cutting Capacity	90°: 55 mm (2-1/8")
	45°: 36 mm (1-3/8")
No Load Speed (RPM)	5,200
Net weight	3.1 kg (6.8 lbs.)

MJ **2.5** Years Limited Warranty

6307 **419** **WJ** S.R.P. 7,000.00

AC 13 mm (1/2") 530 W Variable Speed Reversing Drill




Continuous rating input	530W
Capacity	Steel: 13mm (1/2")
	Wood: 25mm (1")
No load speed (rpm)	0 - 2,500
Net weight	2.4 Kg (3.1 lbs)

MJ **2.5** Years Limited Warranty

6501 **70** **WJ** S.R.P. 6,400.00

AC 405 mm (16") 1,430 W Portable Cut-Off 6.5 mm (1/4") 230 W High Speed Drill with Keyed Chuck




Continuous rating input	230W
Capacity	Steel: 6.5mm (1/4")
	Wood: 9mm (11/32")
Chuck capacity	1.5 - 10 mm (1/16 - 3/8")
No load speed (rpm)	4,500
Net weight	0.9 Kg (2.0 lbs)

MJ **2.5** Years Limited Warranty

6904VH **415** **WJ** S.R.P. 17,650.00

AC 1/2" (12.7 mm) 196 N-m (145 ft.lbs.) Impact Wrench




Continuous rating input	360W
Fastening Capacities	Standard Bolt: M10 - M16 (3/8" - 5/8")
	High Strength Bolt: M10 - M12 (3/8" - 1/2")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	High / Low: 0 - 2,400 / 0 - 2,100
Impacts Per Minute (IPM)	High / Low: 0 - 3,000 / 0 - 2,500
Max Fastening Torque	196 N-m (145 ft.lbs.)
Net weight	1.8 kg (4 lbs.)

MJ **2.5** Years Limited Warranty

6906 **100** **WJ** S.R.P. 34,100.00

AC 3/4" (19 mm) 588 N-m (441 ft.lbs.) Impact Wrench




Continuous rating Input	850W
Capacity	Standard bolt: M16 - M22 (5/8 - 7/8")
	High strength bolt: M16 - M20 (5/8 - 3/4")
Square drive	19 mm (3/4")
No Load Speed (RPM)	1,700
Impacts per minute (IPM)	1,600
Max fastening torque	588 N-m (441 ft.lbs.)
Net weight	5.6 kg (12.2 lbs.)

MJ **2.5** Years Limited Warranty



9005N **100** **WJ** S.R.P. 12,650.00

AC 1,020 W, 125mm (5") Angle Grinder, Trigger Switch



Continuous rating input	1,020W
Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 125mm (5")
	Wire cup brush: 90mm (3-1/2")
No Load Speed (RPM)	11,000
Net weight	2.5 kg (5.5 lbs.)
MJ Spindle size	M16 x 2.0

MJ **2.5** Years Limited Warranty



9031	411	S.R.P.	15,700.00
		30 mm x 533 mm (1-3/16" x 21") 550 W Variable Speed Belt Sander	
		Continuous rating Input	550W
		Belt size	30 x 533 mm (1-3/16 x 21")
		Belt speed	200 - 1,000 m/min (656 - 3,280 ft/min)
		Net weight	2.1 kg (4.6 lbs.)

9045B	100	S.R.P.	13,150.00
		1/2 Sheet 330 W Finishing Sander	
		Continuous rating input	520W
		Pad Size	114 x 234 mm (4-1/2" x 9-1/4")
		Abrasive Paper Size	114 x 280 mm (4-1/2" x 11")
		Orbits Per Minute (OPM)	10,000
		Net weight	2.6 kg (5.7 lbs.)

906H	65	S.R.P.	13,450.00
		(1/4") 320 W Die Grinder	
		Continuous rating input	320W
		Collet capacity	6 mm or (1/4")
		No Load Speed (RPM)	27,000
		Net weight	1.9 kg (4.2 lbs.)

9218PBL	100	S.R.P.	13,200.00
		180 mm (7") 860 W Sander-Polisher	
		Continuous rating Input	480W
		Capacity	Wool Bonnet: 180 mm (7")
		No Load Speed (RPM)	1,400
		Net weight	2.7 kg (5.9 lbs.)
		Spindle size	M14 x 2.0

9237CB	303	S.R.P.	17,500.00
		180 mm (7") 1,200 W Variable Speed Polisher	
		Continuous rating Input	1,200W
		Capacity	Wool bonnet: 180 mm (7")
		No Load Speed (RPM)	0 - 3,200
		Net weight	3.2 - 3.4 kg (7 - 7.5 lbs.)

9404	303	S.R.P.	17,300.00
		100 mm x 610 mm (4" x 24") 1,010 W Variable Speed Belt Sander	
		Continuous rating Input	1,010W
		Belt size	100 x 610 mm (4 x 24")
		Belt speed	210 - 440 m/min (690 - 1,440 ft/min)
		Net weight	4.8 kg (10.6 lbs.)

9500NB	411	S.R.P.	7,600.00
		100 mm (4") 570 W Angle Grinder, Toggle Switch	
		Continuous rating Input	570W
		Wheel Diameter	100 mm (4")
		Hole Diameter	16 mm (5/8")
		No Load Speed (RPM)	12,000
		Net weight	1.9 kg (3.5 - 4.3 lbs.)

9520B	411	S.R.P.	7,750.00
		670 W, 100mm (4") Angle Grinder, Toggle Switch	
		Continuous rating input	670W
		Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 100mm (4")
		Wire cup brush: 75mm (3")	
		Hole Diameter	16 mm (5/8")
		No Load Speed (RPM)	12,000
		Net weight	1.3 kg (2.9 lbs.)
		Spindle size	M10 x 1.50

9533	411	S.R.P.	9,050.00
		720 W, 100mm (4") Angle Grinder, Toggle Switch	
		Continuous rating input	720W
		Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 100mm (4")
		Hole Diameter	16 mm (5/8")
		No Load Speed (RPM)	12,000
		Net weight	1.4 kg (3.11 lbs.)
		Spindle size	M10 x 1.50





9553B	325	S.R.P.	4,000.00
		710 W, 100mm (4") Angle Grinder, Toggle Switch	
		Continuous rating input	710W
		Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 100mm (4")
		Wire cup brush: 75mm (3")	
		Hole Diameter	16 mm (5/8")
		No Load Speed (RPM)	11,000
		Net weight	1.5 - 1.9 kg (3.3 - 4.1 lbs.)
		Spindle size	M10 x 1.50

9553BKX	325	S.R.P.	5,100.00
		710 W, 100mm (4") Angle Grinder, Toggle Switch	
		Continuous rating input	710W
		Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 100mm (4")
		Wire cup brush: 75mm (3")	
		Hole Diameter	16 mm (5/8")
		No Load Speed (RPM)	11,000
		Net weight	1.5 - 1.9 kg (3.3 - 4.1 lbs.)
		Spindle size	M10 x 1.50

9556HNSET	325	S.R.P.	4,250.00
		840 W, 100mm (4") Angle Grinder, Slide Switch	
		Continuous rating input	840W
		Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 100mm (4")
		Wire cup brush: 75mm (3")	
		Hole Diameter	16 mm (5/8")
		No Load Speed (RPM)	11,000
		Net weight	1.6 - 2 kg (3.6 - 4.4 lbs.)
		Spindle size	M10 x 1.50

9556HP	325	S.R.P.	4,400.00
		840 W, 100mm (4") Angle Grinder, Paddle Switch	
		Continuous rating input	840W
		Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 100mm (4")
		Wire cup brush: 75mm (3")	
		Hole diameter	16 mm (5/8")
		No Load Speed (RPM)	11,000
		Net weight	1.6 - 2 kg (3.6 - 4.4 lbs.)
		Spindle size	M10 x 1.50

9557HN	325	S.R.P.	4,400.00
		840 W, 115mm (4-1/2") Angle Grinder, Slide Switch	
		Continuous rating input	840W
		Capacity	Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 115mm (4-1/2")
		Hole diameter	22.23 mm (7/8")
		No Load Speed (RPM)	11,000
		Net weight	1.7 - 2.2 kg (3.8 - 4.8 lbs.)
		Spindle size	M10 x 1.50



9558HN **325** W **S.R.P.** 5,200.00

AC 840 W, 125 mm (5") Angle Grinder, Slide Switch

Continuous rating input Capacity 840W
Depressed center wheel, Cut-off wheel & Diamond cutting wheel: 125 mm (5")
22.23 mm (7/8")

Hole diameter 22.23 mm (7/8")
No Load Speed (RPM) 11,000
Net weight 1.7 - 3 kg (3.8 - 6.6 lbs.)
Spindle size M10 x 1.50

2.5 Years Limited Warranty

9902 **303** W **S.R.P.** 15,750.00

AC 76 mm x 533 mm (3" x 21") 1,010 W Belt Sander

Continuous rating Input 1,010W
Belt size 76 x 533 mm (3 x 21")
Belt speed 440 m/min (1,440 ft/min)
Net weight 4.3 kg (9.5 lbs.)

2.5 Years Limited Warranty

AT1022AZ **S.R.P.** 3,500.00

MC 18 Ga, 10 - 22mm Pneumatic Stapler

Capacity Length: 10 - 22 mm (13/32 - 7/8")
Gauge: 18 Ga
Magazine capacity 100
Operating Pressure 0.45 MPa (65 PSI)
Net weight 1.3 kg (2.86 lbs.)

1.5 Years Limited Warranty

BO3711 **64** W **S.R.P.** 5,350.00

AC 1/3 Sheet 190 W Variable Speed Finishing Sander with Built-In Dust Extraction System

Continuous rating Input 190W
Pad Size 93 x 185 mm (3-5/8 x 7-1/4")
Abrasive Paper Size 93 x 228 mm (3-5/8 x 9")
Orbits per minute (OPM) 4,000 - 11,000
Strokes Per Minute (SPM) 8,000 - 22,000
Orbit Diameter 2.0 mm (1/16")
Net weight 1.6 kg (3.5 lbs.)

2.5 Years Limited Warranty

BO4556 **419** W **S.R.P.** 4,550.00

AC 1/4 Sheet 200 W Finishing Sander

Continuous rating Input 200W
Pad Size 112 x 102 mm (4-3/8 x 4")
Abrasive Paper Size 114 x 140 mm (4-1/2 x 5-1/2")
Orbits per minute (OPM) 14,000
Net weight 1.1 kg (2.5 lbs.)

2.5 Years Limited Warranty

BO5031 **419** W **S.R.P.** 8,000.00

AC 125 mm (5") 300 W Variable Speed Random Orbit Sander with Built-In Dust Extraction System

Continuous rating Input 300W
Pad Diameter 123 mm (4-7/8")
Abrasive disc size 125 mm (5")
Orbits per minute (OPM) 4,000 - 12,000
Net weight 1.3 kg (3 lbs.)

2.5 Years Limited Warranty

CA5000X **303** W **S.R.P.** 36,900.00

AC 118 mm (4-5/8") 1,300 W Aluminum Groove Cutter, Mechanical Brake, Soft Start

Continuous rating Input 1,300W
Wheel Diameter 118 mm (4-5/8")
Hole Diameter 20 mm (13/16")
Max cutting capacity w/ Cutter blade w/ Guide rail: 11 mm (7/16")
No Load Speed (RPM) 2,200 - 6,400
Net weight 4.7 kg (10.4 lbs.)

2.5 Years Limited Warranty

9741 **100** W **S.R.P.** 24,000.00

AC 100 x 120 mm (4" x 4-3/4") Wheel Sander

Continuous rating Input 860W
Wheel Diameter 100 x 120 mm (4 x 4-3/4")
No Load Speed (RPM) 3,500
Net weight 4.2 kg (9.3 lbs.)

2.5 Years Limited Warranty

AF504Z **S.R.P.** 4,900.00

MC 18 Ga, 15 - 50mm Pneumatic Brad Nailer

Capacity Length: 15 - 50 mm (19/32 - 2")
Gauge: 18 Ga
Operating Pressure 0.41 - 0.69 MPa (60 - 100 PSI)
Net weight 1.5 kg (3.3 lbs.)

1.5 Years Limited Warranty

BHX2500 **S.R.P.** 17,700.00

MC 24.5ml (1.6 Hp) Petrol Blower

Displacement 24.5mL
Fuel tank 0.52L
Max. air volume 8.91m³ / min (316cu.ft / min)
The velocity of the wind (without blower pipes) 64.6m/s
Sound pressure level 88.7dB(A)
Sound power level 102dB(A)
Vibration level 5.2m/s²
Net weight 4.4kg (9.8lbs)

1.5 Years Limited Warranty

BO4510H **419** W **S.R.P.** 3,700.00

AC 1/4 Sheet 170 W Finishing Sander

Continuous rating Input 170W
Pad Size 110 x 100 mm (4-5/16 x 3-15/16")
Abrasive Paper Size 114 x 140 mm (4-1/2 x 5-1/2")
Orbits per minute (OPM) 12,000
Net weight 1.1 kg (2.4 lbs.)
Power supply cord 2.5 m (8.2 ft)

2.5 Years Limited Warranty

BO4901 **419** W **S.R.P.** 11,600.00

AC 1/2 Sheet 330 W Finishing Sander

Continuous rating Input 330W
Pad Size 115 x 229 mm (4-1/2 x 9")
Abrasive Paper Size 115 x 280 mm (4-1/2 x 11")
Orbits per minute (OPM) 10,000
Net weight 2.8 kg (6.2 lbs.)

2.5 Years Limited Warranty

BO5041 **64** W **S.R.P.** 10,000.00

AC 125 mm (5") 300 W Variable Speed Random Orbit Sander with Built-In Dust Extraction System

Continuous rating Input 300W
Pad Diameter 123 mm (4-7/8")
Abrasive disc size 125 mm (5")
Orbits per minute (OPM) 4,000 - 12,000
Net weight 1.4 kg (3.1 lbs.)




2.5 Years Limited Warranty

CC300DWE **S.R.P.** 12,900.00

10.8 V 10.8V Li-Ion Cordless 85 mm (3-3/8") Cutter, Wet Type

Blade Diameter 85 mm (3-3/8")
Max Cutting Capacity 90°: 25.5 mm (1")
45°: 16.5 mm (5/8")
No Load Speed (RPM) 1,400
Tank capacity Water: 0.5 L
Net weight 1.6 kg (3.6 lbs.)

2.5 Years Limited Warranty



CL106FDWYW	S.R.P. 6,200.00
12V max CXT Li-Ion 1.3 m³/min, 3.1 kPa Cordless Cleaner	
	Capacity 600 mL Continuous Use (min.) using BL1016: 21 mins Max air flow 1.3 m³/min Max sealed suction 3.1 kPa (316 mmH₂O) Dimensions (L x W x H) 958x100x150 mm (37-3/4"x3-15/16"x5-7/8") Net weight 1.0 - 1.1 kg (2.1 - 2.5 lbs.) 1 pc. 1.5Ah Battery, 1 unit Standard Charger
1.5 Years Limited Warranty	MC

CL106FDZW	S.R.P. 2,700.00
12V max CXT Li-Ion 1.3 m³/min, 3.1 kPa Cordless Cleaner	
	Capacity 600 mL Continuous Use (min.) using BL1016: 21 mins Max air flow 1.3 m³/min Max sealed suction 3.1 kPa (316 mmH₂O) Dimensions (L x W x H) 958x100x150 mm (37-3/4"x3-15/16"x5-7/8") Net weight 1.0 - 1.1 kg (2.1 - 2.5 lbs.) Battery, Charger NOT INCLUDED
1.5 Years Limited Warranty	MC

CL114FDWI	S.R.P. 5,800.00
12Vmax Li-Ion Cordless Cleaner Built-In Battery	
	Capacity Cloth Dust Bag / Paper Dust Bag: 500 / 330 mL Continuous Use (min.) Powerful / High / Normal: 10 / 18 / 55 Max air flow 1.4 m³/min Max sealed suction 5.0 kPa Dimensions (L x W x H) w/ Pipe & Nozzle: 983 x 113 x 136 mm (38-3/4 x 4-7/16 x 5-3/8") Net weight 1.1 kg (2.4 lbs.)
1.5 Years Limited Warranty	MC

CL117FDX1	S.R.P. 6,400.00
10.8V Li-Ion Cordless 3-Speed Cleaner with LED Light, Built-In Battery	
	Capacity Dust Bag: 650 mL Continuous Use (min.) Powerful / High / Normal: 10 / 18 / 55 Max Air Flow 1.0 m³/min Max Sealed Suction 5.0 kPa (510 mmHO) Dimensions (L x W x H) 992 x 110 x 136 mm (39 x 4-5/16 x 5-3/8") Net weight 1.0 kg (2.2 lbs.)
1.5 Years Limited Warranty	MC

CL121DZ	S.R.P. 6,550.00
12Vmax CXT Li-Ion Cordless 3-Speed Cleaner	
	Capacity Cloth Dust Bag / Paper Dust Bag: 500 / 330 mL Continuous use (min.) (BL1021B): Max / High / Normal: 13 / 16 / 33 Max air flow 1.3 m³/min Max sealed suction 4.6 kPa (470 mmHO) Max Air Flow Blowing: 0.3 m³/min Max air velocity Blowing: 76 m/s (270 kph) Net weight 1.7 - 1.8 kg (3.7 - 4.0 lbs.) Battery, Charger NOT INCLUDED
1.5 Years Limited Warranty	MC

CLX230X1	S.R.P. 11,850.00
Cordless CXT Hammer Driver Drill, Jig Saw Combo	
	HP333D 12Vmax CXT Li-Ion Cordless 10 mm (3/8") 28 N-m (250 in.lbs.) Hammer Driver Drill JV101D 12V max CXT Li-Ion Cordless Top Handle Jig Saw Include: 2 pcs. (1.5Ah) Battery, Charger, Screw bit, Jigsaw Blades...
2.5 Years Limited Warranty	MC

CLX246SX1	S.R.P. 11,500.00
Cordless CXT Blower, Cleaner Combo	
	UB100D 12Vmax CXT Cordless Variable 3-Speed Blower CL107DFW 12Vmax CXT Li-Ion Cordless 3-Speed Cleaner with LED Light Capacity: 500 ml, Max air flow: 1.4 m³/min, 5.0 kPa. Include: 1 pc. (1.5Ah) Battery, Charger, Tool bag.
2.5 Years Limited Warranty	MC

CP100DZ	S.R.P. 3,100.00
12V max CXT Li-Ion Cordless Multi-Cutter	
	Max Cutting Capacity 6 mm (1/4") No Load Speed (RPM) 300 Dimensions (L x W x H) 272 x 66 x 120 mm (10-3/4 x 2-5/8 x 4-3/4") Net weight 0.72 - 0.88 kg (1.6 - 1.9 lbs.) Battery, Charger NOT INCLUDED
2.5 Years Limited Warranty	MC

DA3010	S.R.P. 11,850.00
10 mm (3/8") 450 W Angle Drill with Keyed Chuck	
	Continuous rating Input 450W Capacity Steel: 10 mm (3/8") Wood: 25 mm (1") Chuck capacity 1.5 - 10 mm (1/16 - 3/8") No Load Speed (RPM) 0 - 2,400 Net weight 1.6 kg (3.5 lbs.)
2.5 Years Limited Warranty	MJ

DA332DZ	S.R.P. 5,500.00
12V max CXT Li-Ion Cordless 10 mm (3/8") Angle Drill	
	Capacity Steel: 10 mm (3/8") Wood: 12 mm (1/2") Hole saw: 24 mm (15/16") Chuck capacity 1.5 - 10 mm (1/16 - 3/8") No Load Speed (RPM) 0 - 1,100 Net weight 1.2 - 1.3 kg (2.6 - 2.9 lbs.) Battery, Charger NOT INCLUDED
2.5 Years Limited Warranty	MC


DA333DZ	S.R.P. 5,500.00
12V max CXT Li-Ion Cordless 10 mm (3/8") Angle Drill	
	Capacity Steel: 10 mm (3/8") Wood: 12 mm (1/2") Hole saw: 24 mm (15/16") Chuck capacity 0.8 - 10 mm (1/32 - 3/8") No Load Speed (RPM) 0 - 1,100 Net weight 1.2 - 1.4 kg (2.7 - 3 lbs.) Battery, Charger NOT INCLUDED
2.5 Years Limited Warranty	MC

DA4000LR	S.R.P. 23,700.00
13 mm (1/2") 710 W Angle Drill with Keyed Chuck	
	Continuous rating Input 710W Steel: 13 mm (1/2") Wood (Self-feed bit) Hi: 65 mm (2-9/16") Wood (Self-feed bit) Lo: 118 mm (4-5/8") Capacity 2 - 13 mm (1/16 - 1/2") Chuck capacity High: 0 - 900 No Load Speed (RPM) Low: 0 - 400 Net weight 4 kg (8.9 lbs.) Battery, Charger NOT INCLUDED
2.5 Years Limited Warranty	MJ


DAS180Z	S.R.P. 9,500.00
18V LXT BL Cordless Air Duster	
	Air volume 0-1.1 m³/min Air velocity 0-150 m/s Air pressure 0-18.0 kPa Blowing force Mode 1: 0-1.1 N / Mode 4: 0-2.8 N Max Sealed Suction 9.3 kPa Continuous Use (min.) BL1860B, Mode 1: 55 / Mode 4: 15 Net weight 1.2 - 1.7 kg (2.6 - 3.7 lbs.) Battery, Charger NOT INCLUDED
2.5 Years Limited Warranty	MC


DBO180Z	S.R.P. 8,650.00
18V LXT Li-Ion Cordless 125 mm (5") 3-Speed Random Orbit Sander with Built-In Dust Extraction System	
	Pad Diameter 123 mm (4-7/8") Abrasive disc size 125 mm (5") Orbits per minute (OPM) 7,000 / 9,500 / 11,000 Net weight 1.4 - 1.7 kg (3 - 3.7 lbs.) Battery, Charger NOT INCLUDED
2.5 Years Limited Warranty	MC

- Variable Speed
- Mechanical 2-Speed
- Torque Setting 20
- Orbital Cutting
- Soft Start
- Brake
- Electronic 3-Speed
- Torque Limiter
- Bayonet Shank Jig Saw Blade
- Dust Collection
- Reversing
- Torque Setting 18
- Built-in Job Light


DBO380Z	S.R.P.	8,650.00
LXT	18V BL 1/3 Sheet Cordless Finishing Sander with Built-In Dust Extraction System	
	Pad size	93 x 185 mm (3-5/8 x 7-1/4")
	Abrasive paper size	Rectangular: 93 x 228 mm (3-5/8 x 9")
	Orbits per minute (OPM)	4,000/ 8,000/ 12,000
	Orbit diameter	2.0 mm (1/16")
	Continuous run time	using BL1860B: 50 min
	Net weight	1.9 - 2.2 kg (4.2 - 4.9 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	


DBO482Z	S.R.P.	6,300.00
LXT	18V LXT Li-Ion 1/4 Sheet Cordless Finishing Sander	
	Pad size	112 x 102 mm (4-3/8 x 4")
	Abrasive paper size	Square: 114 x 102 mm (4-1/2 x 4")
	Orbits per minute (OPM)	High: 14,000 / Low: 11,000
	Strokes per minute (SPM)	High: 28,000 / Low: 22,000
	Orbit diameter	1.5 mm (1/16")
	Net weight	1.4 - 1.8 kg (3.1 - 4.0 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	


DCF102ZO	S.R.P.	5,600.00
LXT	18V LXT Li-Ion Cordless 180 mm (7-1/8") Automatic Swing Fan	
	Continuous Use	using BL1860B Low / Mid / High: w/o oscillation 21 hr / 11.5 hr / 9.5 hr
	Max Air Velocity	High / Mid / Low: 180 / 150 / 120 m/min
	Air flow	High / Mid / Low: 4.6 / 3.8 / 3.0 m³/min
	Fan Diameter	180 mm (7-1/8")
	Dimensions (L x W x H)	185 x 272 x 284 mm (7-1/4 x 10-3/10 x 11-1/8")
	Net weight	1.3 - 2.0 kg (2.9 - 4.4 lbs.)
1.5 Years Limited Warranty	AC Adapter, Battery, Charger NOT INCLUDED	


DCL180Z	S.R.P.	3,750.00
LXT	18V LXT Li-Ion Cordless 650 ml Cleaner	
	Capacity	650 mL
	Continuous Use (min.)	using BL1830B: 20
	Max Sealed Suction	4.2kPa
	Max. Air Flow	1.4m³/min
	Dimensions (L x W x H)	999x114x152 mm (39-1/4"x4-1/2"x6")
	Net weight	1.2 kg (2.7 lbs.)
1.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	


DCL184Z	S.R.P.	6,650.00
LXT	18V LXT Li-Ion Cordless 3-Speed Cleaner	
	Capacity	Cloth Dust Bag / Paper Dust Bag: 500 / 330 mL
	Continuous use (3.0Ah)	Max / High / Normal: 20 / 30 / 80
	Max Air Flow	Cleaning: 1.4 m³/min
	Max sealed suction	5.4 kPa (550 mmHO)
	Max air velocity	Blowing: 100 m/s
	Dimensions (L x W x H)	365 x 138 x 202 mm (14-3/8 x 5-7/16 x 8")
	Net weight	1.8 - 2.2 kg (4.0 - 4.9 lbs.)
1.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	


DCO180Z	S.R.P.	6,150.00
LXT	18V LXT Li-Ion Cordless 6.35 mm (1/4") Cut-Out Tool	
	Collet capacity	3.18, 6.35 mm or 1/8, 1/4"
	No Load Speed (RPM)	30,000
	Dimensions (L x W x H)	296 x 77 x 118 mm (11-5/8 x 3 x 4-5/8")
	Net weight	1.5 - 1.8 kg (3.3 - 4 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	


DCU604Z	S.R.P.	304,150.00
LXT	18V X2 (36V) LXT BL Battery Powered Wheelbarrow, 300 Kg Capacity	
	Max load capacity	300 kg
	Traveling speed	Forward, High / Low: 5 / 1.5 km/h Reverse: 1.0 km/h
	Max climbing capacity	12°
	Traveling distance	w/ BL1860B x4: 7.5 Km
	Net weight	119 - 120 kg (262 - 265 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	


DBO381Z	S.R.P.	9,700.00
LXT	18V BL AWS 1/3 Sheet Cordless Finishing Sander with Built-In Dust Extraction System	
	Pad size	93 x 185 mm (3-5/8 x 7-1/4")
	Abrasive paper size	Rectangular: 93 x 228 mm (3-5/8 x 9")
	Orbits per minute (OPM)	4,000/ 8,000/ 12,000
	Orbit diameter	2.0 mm (1/16")
	Continuous run time	w/ BL1860B: 50 min
	Net weight	1.9 - 2.2 kg (4.2 - 4.9 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	

DCC500Z	S.R.P.	10,900.00
LXT	18V LXT BL AWS ADT Cordless 125 mm (5") Cutter, Dry Type	
	Blade diameter	125 mm (5")
	Hole Diameter	20 mm (13/16")
	Max Cutting Capacity	0°: 40 mm (1-9/16")
	No Load Speed (RPM)	45°: 27 mm (1-1/16")
	Dimensions (L x W x H)	8,800
	Net weight	2.5 - 3.0 kg (5.5 - 6.6 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	



DCF301Z	S.R.P.	7,450.00
LXT	18V LXT Li-Ion Cordless 330 mm (13") Automatic Swing Fan	
	Continuous Use	using BL1860B Low / Mid / High w/o oscillation 6.7 hr / 3.2 hr / 2 hr
	Max Air Velocity	High / Mid / Low: 14.4 / 10.2 / 6.6 kph
	Air Flow	High / Mid / Low: 21 / 15 / 10 m³/min
	Fan Diameter	330 mm (13")
	Dimensions (L x W x H)	240 x 434 x 560 mm
	Net weight	4.0 - 4.7 kg (8.9 - 10.4 lbs.)
1.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	

DCL180ZW	S.R.P.	3,750.00
LXT	18V LXT Li-Ion Cordless 650 ml Cleaner	
	Capacity	650 mL
	Continuous Use (min.)	using BL1830B: 20
	Max Sealed Suction	4.2kPa
	Max. Air Flow	1.4m³/min
	Dimensions (L x W x H)	999x114x152 mm (39-1/4"x4-1/2"x6")
	Net weight	1.2 kg (2.7 lbs.)
1.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	

DCL281FZW	S.R.P.	7,150.00
LXT	18V LXT Li-Ion BL Cordless 750 ml Cleaner	
	Capacity	750 mL
	Continuous Use (min.)	using BL1860B Low / Mid / High 100 min / 40 min / 30 min
	Max Sealed Suction	8.2kPa
	Max. Air Flow	1.5m³/min
	Dimensions (L x W x H)	999x114x152 mm (39-1/4"x4-1/2"x6")
	Net weight	1.2 kg (2.7 lbs.)
1.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	

DCU180Z	S.R.P.	54,150.00
LXT	18V LXT BL XPT Battery Powered Wheelbarrow, 130 Kg (290 Lbs.) Capacity	
	Max run time (min)	w/ BL1860B x2: 120
	Max load capacity	130 kg (290 lbs.)
	Traveling speed	Forward, High / Low: 0 - 3.5 / 0 - 1.5 km/h Reverse: 0 - 1 km/h
	Max climbing capacity	12°
	Net weight	39.3 - 44.8 kg (86.5 - 98.7 lbs.)
2.5 Years Limited Warranty	Battery, Charger, CARRIER SET PN: 199116-7, BUCKET SET PN: 198494-2 NOT INCLUDED	

DDA350Z	S.R.P.	9,650.00
LXT	18V LXT Li-Ion Cordless 10 mm (3/8") Angle Drill, Keyed Chuck	
	Capacity	Steel: 10 mm (3/8") Wood: 25 mm (1") Hole saw: 50 mm (2")
	Chuck capacity	1.5 - 10 mm (1/16 - 3/8")
	No Load Speed (RPM)	0 - 1,800
	Net weight	1.5 - 1.8 kg (4.1 - 3.4 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED	



DDA450Z	S.R.P. 14,650.00
	18V LXT BL XPT Cordless Angle Drill with Keyed Chuck
Capacity	Steel: 13 mm (1/2") Wood (Hole saw) Hi: 101 mm (4") Wood (Hole saw) Lo: 127 mm (5") 2 - 13 mm (1/16 - 1/2")
Chuck capacity	Hi: 0 - 1,400 / Lo: 0 - 450
No load speed (RPM)	Hi: 26 N-m (230 in.lbs.) Lo: 70 N-m (620 in.lbs.)
Max fastening torque	3.2 - 3.5 kg (7.1 - 7.7 lbs.)
Net weight	Battery, Charger NOT INCLUDED

DDF083Z	S.R.P. 6,550.00
	18V LXT BL XPT Brushless Cordless 6.35 mm (1/4") Hex 40 N-m (350 in.lbs.) Driver Drill
Capacity	Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
Chuck capacity	6.35 mm (1/4")
No Load Speed (RPM)	High: 0 - 1,700 / Low: 0 - 500
Max fastening torque	Hard: 40 N-m (350 in.lbs.) Soft: 23 N-m (210 in.lbs.)
Net weight	1.1 - 1.4 kg (2.4 - 3 lbs.)
	Battery, Charger NOT INCLUDED

DDF453Z	S.R.P. 4,050.00
	18V LXT Li-Ion Cordless 13 mm (1/2") 38 N-m Driver Drill
Capacity	Steel: 13 mm (1/2") Wood (Self-feed bit): 72 mm (2-13/16") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 1,300 / Low: 0 - 400
Max fastening torque	Hard: 42 N-m / Soft: 27 N-m
Max lock torque	38 N-m (340 in.lbs.)
Net weight	1.7 - 2 kg (3.7 - 4.4 lbs.)
	Battery, Charger NOT INCLUDED

DDF484RFE	S.R.P. 22,450.00
	18V LXT BL Brushless Cordless 13 mm (1/2") 60 N-m Driver Drill
Capacity	Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 2,000 / Low: 0 - 500
Max fastening torque	Hard: 54 N-m / Soft: 30 N-m
Max lock torque	60 N-m (530 in.lbs.)
Net weight	1.7 - 2 kg (3.7 - 4.4 lbs.)
	INCLUDE: 2 pcs 3.0Ah battery, 1 unit Charger, Carrying case.

DDF485Z	S.R.P. 6,050.00
	18V LXT BL Cordless 13 mm (1/2") 50 N-m Driver Drill
Capacity	Steel: 13 mm (1/2") Wood: 38 mm (1-1/2")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 1,900 / Low: 0 - 500
Max fastening torque	Hard: 50 N-m / Soft: 27 N-m
Max lock torque	50 N-m (440 in.lbs.)
Net weight	1.4 - 1.7 kg (3.1 - 3.8 lbs.)
	Battery, Charger NOT INCLUDED

DDF486Z	S.R.P. 12,400.00
	18V LXT BL XPT Cordless 13 mm (1/2") 125 N-m Driver Drill
Capacity	Steel: 13 mm (1/2") Wood (Auger-Bit): 50 mm (2") Wood (Hole saw): 152 mm (6")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 2,100 / Low: 0 - 550
Max fastening torque	Hard: 130 N-m / Soft: 65 N-m
Max lock torque	125 N-m (1,100 in.lbs.)
Net weight	2.3 - 2.6 kg (5.1 - 5.7 lbs.)
	Battery, Charger NOT INCLUDED

DDF487Z	S.R.P. 6,900.00
	18V LXT BL XPT Cordless 13 mm (1/2") 40 N-m Driver Drill
Capacity	Steel: 13 mm (1/2") Wood (Self-feed bit): 35 mm (1-3/8") Wood (Hole saw): 51 mm (2") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 1,700 / Low: 0 - 500
Max fastening torque	Hard: 40 N-m / Soft: 25 N-m
Net weight	1.3 - 1.6 kg (2.9 - 3.5 lbs.)
	Battery, Charger NOT INCLUDED

DF001DW	S.R.P. 4,100.00
	3.6V Li-Ion In-Line Cordless 6.0 N-m Screwdriver
Fastening capacities	Wood screw: Dia. 3.8 x 32 mm (1/8 x 1-1/4")
No Load Speed (RPM)	220
Max fastening torque	Hard / Soft: 4.0 / 3.0 N-m (35 / 27 in.lbs.)
Max lock torque	6.0 N-m (53 in.lbs.)
Net weight	0.36 kg (0.79 lbs.)
	Battery, Charger NOT INCLUDED

DF010DS	S.R.P. 6,600.00
	7.2V Li-Ion Cordless 5 mm (3/16") Driver Drill
Capacity	Steel: 5 mm (3/16") Wood: 6 mm (1/4")
No load speed (rpm)	Hi: 650 Lo: 200
Max fastening torque	Hard / Soft: 5.6 / 3.6 N-m
Net weight	0.55kg (1.21lbs)
	1 pc. Battery, Charger, Carrying case.





DF331DZ	S.R.P. 3,050.00
	12V max CXT BL Cordless 10mm (3/8"), 28 N-m Driver Drill
Capacity	Steel: 10 mm (3/8") Wood: 21 mm (13/16")
No load speed (rpm)	Hi: 0-1,700 Lo: 0-450
Max tightening torque	Hard / Soft: 30 / 14 N-m
Max lock torque	28N.m (250in.lbs)
Net weight	1.1kg (2.4lbs)
	Battery, Charger NOT INCLUDED

DF332DWYE	S.R.P. 11,600.00
	12Vmax CXT BL XPT Cordless 10 mm (3/8") 32 N-m Driver Drill
Capacity	Steel: 10 mm (3/8") Wood: 28 mm (1-1/8") 0.8 - 10 mm (1/32 - 3/8")
Chuck capacity	High: 0 - 1,500 / Low: 0 - 450
No Load Speed (RPM)	Hard: 35 N-m / Soft: 21 N-m
Max fastening torque	32 N-m (280 in.lbs.)
Max lock torque	1 - 1.2 kg (2.3 - 2.6 lbs.)
Net weight	INCLUDE: 2 pcs. 1.5 Ah Battery, Charger, Carrying case.

DF332DZ	S.R.P. 6,950.00
	12Vmax CXT BL XPT Cordless 10 mm (3/8") 32 N-m Driver Drill
Capacity	Steel: 10 mm (3/8") Wood: 21 mm (13/16") 0.8 - 10 mm (1/32 - 3/8")
Chuck capacity	High: 0 - 1,700 / Low: 0 - 450
No Load Speed (RPM)	Hard: 30 N-m / Soft: 14 N-m
Max fastening torque	28 N-m (250 in.lbs.)
Max lock torque	1.1 - 1.2 kg (2.4 - 2.7 lbs.)
Net weight	Battery, Charger NOT INCLUDED


DF333DWYE	S.R.P. 7,750.00
	12Vmax CXT Li-Ion Cordless 10 mm (3/8") 28 N-m Driver Drill
Capacity	Steel: 10 mm (3/8") Wood: 21 mm (13/16") 0.8 - 10 mm (1/32 - 3/8")
Chuck capacity	High: 0 - 1,700 / Low: 0 - 450
No Load Speed (RPM)	Hard: 30 N-m / Soft: 14 N-m
Max fastening torque	28 N-m (250 in.lbs.)
Max lock torque	1.1 - 1.2 kg (2.4 - 2.7 lbs.)
Net weight	INCLUDE: 2 pcs. 1.5 Ah Battery, Charger, Carrying case.

DF333DZ	S.R.P. 3,200.00
	12Vmax CXT Li-Ion Cordless 10 mm (3/8") 28 N-m Driver Drill
Capacity	Steel: 10 mm (3/8") Wood: 21 mm (13/16") 0.8 - 10 mm (1/32 - 3/8")
Chuck capacity	High: 0 - 1,700 / Low: 0 - 450
No Load Speed (RPM)	Hard: 30 N-m / Soft: 14 N-m
Max fastening torque	28 N-m (250 in.lbs.)
Max lock torque	1.1 - 1.2 kg (2.4 - 2.7 lbs.)
Net weight	Battery, Charger NOT INCLUDED.



DF488D002 18V Li-Ion Cordless 13 mm (1/2") 38 N-m Driver Drill, G-Battery S.R.P. 11,650.00

G-Battery



Capacity	Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 1,400 / Low: 0 - 400
Max fastening torque	Hard: 42 N-m / Soft: 24 N-m
Max lock torque	38 N-m (340 in.lbs.)
Net weight	1.7 kg (3.7 lbs.)

INCLUDE: 2 pcs. 1.5 Ah Battery, Charger, Carrying case.

DF488D004 18V Li-Ion Cordless 13 mm (1/2") 38 N-m Driver Drill, G-Battery S.R.P. 12,000.00

G-Battery




Capacity	Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 1,400 / Low: 0 - 400
Max fastening torque	Hard: 42 N-m / Soft: 24 N-m
Max lock torque	38 N-m (340 in.lbs.)
Net weight	1.7 kg (3.7 lbs.)

INCLUDE: 2 pcs. 2.0 Ah Battery, Charger, Carrying case.

DFN350Z 18V LXT XPT Cordless 18 Ga 35 mm (1-3/8") Brad Nailer S.R.P. 23,600.00

LXT




Capacity	Length: 15 - 35 mm (5/8 - 1-3/8") Gauge: 18 Ga
Magazine Capacity	110
Shot q'ty on a single full battery charge	using BL1850B: 4,000
Net weight	2.1 - 2.4 kg (4.6 - 5.3 lbs.)

Battery, Charger NOT INCLUDED.

DFR550Z 18V LXT Li-Ion Cordless 4,000 RPM 55 mm (2-3/16") Auto Feed Screwdriver with Silent Clutch S.R.P. 14,150.00

LXT




Screw strip	4 x 25 - 55 mm (5/32 x 1 - 2-3/16")
Driving shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	4,000
Dimensions (L x W x H)	424 x 80 x 238 mm (16-3/4 x 3-1/8 x 9-3/8")
Net weight	2.1 - 3.1 kg (4.6 - 6.9 lbs.)

Battery, Charger NOT INCLUDED.

DFS451Z 18V LXT Li-Ion Cordless 0-4,000 RPM Screwdriver with LED Light, Silent Clutch S.R.P. 16,500.00

LXT



Capacity	Drywall screw: 4 mm (5/32")
Driving shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 4,000
Net weight	1.5 - 1.8 kg (3.2 - 4 lbs.)

Battery, Charger NOT INCLUDED.

DGA402RF 18V LXT Li-Ion Cordless 100mm (4") Angle Grinder, Anti-Restart Function, Slide Switch Lock-On S.R.P. 16,000.00

LXT



Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	11,000
Net weight	1.9 - 2.51 kg (4.19 - 5.54 lbs.)

INCLUDE: 1 pc. 3.0 Ah Battery, Charger, Carrying case.

DGA402Z 18V LXT Li-Ion Cordless 100mm (4") Angle Grinder, Anti-Restart Function, Slide Switch Lock-On S.R.P. 6,450.00

LXT




Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	11,000
Net weight	1.9 - 2.51 kg (4.19 - 5.54 lbs.)

Battery, Charger NOT INCLUDED.

DGA406Z 18V LXT BL ADT AFT XPT Cordless 100mm (4") Angle Grinder, Anti-Restart Function, Electric Brake, Slide Switch Lock-On S.R.P. 9,800.00

LXT




Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	8,500
Net weight	2.18 - 2.77 kg (4.81 - 6.12 lbs.)

Battery, Charger NOT INCLUDED.

DGA700Z 18V X2 (36V) LXT BL ADT AFT XPT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Large Trigger Switch S.R.P. 14,600.00

LXT



Wheel Diameter	180 mm (7")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	7,800
Net weight	5.0 - 6.0 kg (11.02 - 13.23 lbs.)

Battery, Charger NOT INCLUDED.

DHG181ZK 18V LXT Cordless Heat Gun S.R.P. 9,450.00

LXT




Max output	10 W
Air temperature	Dial 1: Ambient temperature Dial 2: 150°C / Dial 3: 250°C / Dial 4: 350°C Dial 5: 450°C / Dial 6: 550°C
Air flow	Stage 1: 120 L/min / Stage 2: 200 L/min
Continuous run time	using 6.0 Ah, Stage 1: 30 min *Stage 2: 21 min
Net weight	1.0 - 1.4 kg (2.2 - 3.1 lbs.)

INCLUDE: Glass protection nozzle, Wide slot nozzle, Reactor nozzle, Reduction nozzle. Battery, Charger NOT INCLUDED.

DHP453RFX2 18V LXT Li-Ion Cordless 13 mm (1/2") 38 N-m Hammer Driver Drill S.R.P. 22,050.00

LXT




Capacity	Masonry: 13 mm (1/2") Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts per minute (IPM)	High: 0 - 19,500 / Low: 0 - 6,000
No Load Speed (RPM)	High: 0 - 1,300 / Low: 0 - 400
Max fastening torque	Hard: 42 N-m / Soft: 27 N-m
Max lock torque	38 N-m (340 in.lbs.)

INCLUDE: 2 pcs. 3.0Ah Battery 1 Fast charger, Asstd Bits.

DHP453RFX4 18V LXT Li-Ion Cordless 13 mm (1/2") 38 N-m Hammer Driver Drill S.R.P. 21,650.00

LXT




Capacity	Masonry: 13 mm (1/2") Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts per minute (IPM)	High: 0 - 19,500 / Low: 0 - 6,000
No Load Speed (RPM)	High: 0 - 1,300 / Low: 0 - 400
Max fastening torque	Hard: 42 N-m / Soft: 27 N-m
Max lock torque	38 N-m (340 in.lbs.)

INCLUDE: 2 pcs. 3.0Ah Battery 1 Fast charger, Asstd Bits.

DHP453Z 18V LXT Li-Ion Cordless 13 mm (1/2") 38 N-m Hammer Driver Drill S.R.P. 4,500.00

LXT




Capacity	Masonry: 13 mm (1/2") Steel: 13 mm (1/2") Wood: 36 mm (1-7/16")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts per minute (IPM)	High: 0 - 19,500 / Low: 0 - 6,000
No Load Speed (RPM)	High: 0 - 1,300 / Low: 0 - 400
Max fastening torque	Hard: 42 N-m / Soft: 27 N-m
Max lock torque	38 N-m (340 in.lbs.)

Battery, Charger NOT INCLUDED.

DHP482Z 18V LXT Li-Ion XPT Cordless 13 mm (1/2") 54 N-m Hammer Driver Drill S.R.P. 6,050.00

LXT




Capacity	Masonry: 13 mm (1/2") Steel: 13 mm (1/2") Wood: 38 mm (1-1/2")
Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts per minute (IPM)	High: 0 - 28,500 / Low: 0 - 9,000
No Load Speed (RPM)	High: 0 - 1,900 / Low: 0 - 600
Max fastening torque	Hard: 62 N-m / Soft: 36 N-m
Max lock torque	54 N-m (480 in.lbs.)

Battery, Charger NOT INCLUDED.



DHP484RFE 18V LXT BL XPT Cordless S.R.P. 23,200.00

LXT



13 mm (1/2") 60 N-m (530 in.lbs.) Hammer Driver Drill Capacity

Masonry: 13 mm (1/2")
 Steel: 13 mm (1/2")
 Wood: 38 mm (1-1/2")


Chuck capacity: 1.5 - 13 mm (1/16 - 1/2")
 Impacts per minute (IPM): High: 0 - 30,000 / Low: 0 - 7,500
 No Load Speed (RPM): High: 0 - 2,000 / Low: 0 - 500
 Max fastening torque: Hard: 54 N-m / Soft: 30 N-m
 Max lock torque: 60 N-m (530 in.lbs.)

INCLUDE: 2 pcs. 3.0 Ah Battery, 1 Charger, Carrying case.

2.5 Years Limited Warranty

DHP484Z 18V LXT BL XPT Cordless S.R.P. 9,600.00

LXT



13 mm (1/2") 60 N-m (530 in.lbs.) Hammer Driver Drill Capacity

Masonry: 13 mm (1/2")
 Steel: 13 mm (1/2")
 Wood: 38 mm (1-1/2")


Chuck capacity: 1.5 - 13 mm (1/16 - 1/2")
 Impacts per minute (IPM): High: 0 - 30,000 / Low: 0 - 7,500
 No Load Speed (RPM): High: 0 - 2,000 / Low: 0 - 500
 Max fastening torque: Hard: 54 N-m / Soft: 30 N-m
 Max lock torque: 60 N-m (530 in.lbs.)

Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHP485Z 18V LXT BL XPT Cordless S.R.P. 6,600.00

LXT



13 mm (1/2") 50 N-m Hammer Driver Drill Capacity

Masonry: 13 mm (1/2") / Steel: 13 mm (1/2")
 Wood: 38 mm (1-1/2") / Wood (Self-feed bit): 76 mm (3")


Chuck capacity: 1.5 - 13 mm (1/16 - 1/2")
 Impacts per minute (IPM): High: 0 - 28,500 / Low: 0 - 7,500
 No Load Speed (RPM): High: 0 - 1,900 / Low: 0 - 500
 Max fastening torque: Hard: 50 N-m / Soft: 27 N-m
 Max lock torque: 50 N-m (440 in.lbs.)

Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHP486Z 18V LXT BL XPT Cordless S.R.P. 15,550.00

LXT



13 mm (1/2") 125 N-m Hammer Driver Drill Capacity

Masonry: 16 mm (5/8")
 Steel: 13 mm (1/2")
 Wood (Self-feed bit): 76 mm (3")


Chuck capacity: 1.5 - 13 mm (1/16 - 1/2")
 Impacts per minute (IPM): High: 0 - 31,500 / Low: 0 - 8,250
 No Load Speed (RPM): High: 0 - 2,100 / Low: 0 - 550
 Max fastening torque: Hard: 130 N-m / Soft: 65 N-m
 Max lock torque: 125 N-m (1,100 in.lbs.)

Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHP487Z 18V LXT BL XPT Cordless S.R.P. 7,450.00

LXT



13 mm (1/2") 40 N-m Hammer Driver Drill Capacity

Masonry: 13 mm (1/2") / Steel: 13 mm (1/2")
 Wood (Self-feed bit): 35 mm (1-3/8")


Chuck capacity: 1.5 - 13 mm (1/16 - 1/2")
 Impacts per minute (IPM): High: 0 - 25,500 / Low: 0 - 7,500
 No Load Speed (RPM): High: 0 - 1,700 / Low: 0 - 500
 Max fastening torque: Hard: 40 N-m / Soft: 25 N-m
 Max lock torque: 40 N-m (350 in.lbs.)
 Net weight: 1.4 - 1.7 kg (3.1 - 3.7 lbs.)

Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHP489Z 18V LXT BL XPT Cordless S.R.P. 12,100.00

LXT



13 mm (1/2") 110 N-m Hammer Driver Drill Capacity

Masonry: 16 mm (5/8")
 Steel: 13 mm (1/2")
 Wood (Self-feed bit): 51 mm (2")


Chuck capacity: 1.5 - 13 mm (1/16 - 1/2")
 Impacts per minute (IPM): High: 0 - 27,000 / Low: 0 - 8,250
 No Load Speed (RPM): High: 0 - 1,800 / Low: 0 - 550
 Max fastening torque: Hard: 70 N-m / Soft: 36 N-m
 Max lock torque: 110 N-m (970 in.lbs.)

Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHR165RF 430 18V LXT Cordless S.R.P. 16,600.00

LXT



16 mm (5/8") Rotary Hammer, SDS-PLUS

Impact energy: 1.3 J
 Capacity: Concrete (w/ TCT bit): 16 mm (5/8")
 Concrete (w/ Diamond core bit): 32 mm
 Steel: 13 mm (1/2")
 Wood: 24 mm (15/16")


Blows per minute (BPM): 0 - 5,300
 No Load Speed (RPM): 0 - 1,600

INCLUDES: 1 pc 3.0 Ah Battery, 1 Fast Charger.

2.5 Years Limited Warranty

DHR171FJX1 18V LXT BL XPT Cordless S.R.P. 30,250.00

LXT



17 mm (11/16") Rotary Hammer, SDS-PLUS

Impact energy: EPTA-Procedure 05/2009: 1.2 J
 Capacity: Concrete: 17 mm (11/16")
 Steel: 10 mm (3/8")
 Wood: 13 mm (1/2")


Blows per minute (BPM): 0 - 4,800
 No Load Speed (RPM): 0 - 680
 Net weight: 2.1 - 2.8 kg (4.6 - 6.2 lbs.)

INCLUDES: 2 pcs 3.0 Ah Battery, 1 Fast Charger, Assorted Bits, Makpac Case.

2.5 Years Limited Warranty

DHR183Z 18V LXT BL AVT XPT Cordless S.R.P. 12,500.00

LXT



18 mm (11/16") Rotary Hammer, SDS-PLUS

Impact energy: EPTA-Procedure 05/2009: 1.7 J
 Capacity: Concrete: 18 mm (11/16")
 Steel: 13 mm (1/2")
 Wood: 24 mm (15/16")


Blows per minute (BPM): 0 - 5,000
 No Load Speed (RPM): 0 - 1,100
 Net weight: 1.9 - 2.9 kg (4.2 - 6.4 lbs.)

Battery, Charger NOT INCLUDED.

2.5 Years Limited Warranty

DHR241RFE 441 18V LXT Cordless S.R.P. 24,100.00

LXT



20 mm (13/16") Rotary Hammer, SDS-PLUS

Impact energy: 1.9 J
 Capacity: Masonry: 20 mm (13/16")
 Steel: 13 mm (1/2")
 Wood: 26 mm (1")


Blows per minute (BPM): 0 - 4,000
 No Load Speed (RPM): 0 - 1,100
 Net weight: 3.2 - 4 kg (7.1 - 8.8 lbs.)

INCLUDES: 2 pcs 3.0 Ah Battery, 1 Fast Charger, Carrying Case.

2.5 Years Limited Warranty

DHR242Z 18V LXT BL XPT Cordless S.R.P. 13,800.00

LXT



24 mm (15/16") Rotary Hammer, SDS-PLUS

Impact energy: 2 J
 Capacity: Masonry: 24 mm (15/16")
 Steel: 13 mm (1/2")
 Wood: 27 mm (1-1/16")


Blows per minute (BPM): 0 - 4,700
 No Load Speed (RPM): 0 - 950
 Net weight: 3.1 - 3.8 kg (6.7 - 8.4 lbs.)

Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHS661Z 18V LXT BL AWS ADT XPT S.R.P. 15,200.00

LXT



Cordless 165 mm (6-1/2") Circular Saw

Wheel Diameter: 165 mm (6-1/2")
 Hole Diameter: 15.88 / 19 / 20 / 25.4 / 30 mm (5/8 / 3/4 / 13/16 / 1 / 1-3/16")


Max Cutting Capacity: 0°: 57 mm (2-1/4") / 45°: 41 mm (1-5/8")
 No Load Speed (RPM): 5,000
 Net weight: 2.9 - 3.2 kg (6.4 - 7.1 lbs.)

NOT COMPATIBLE WITH GUIDERAIL
Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHS710Z 442 18V X2 (36V) LXT Li-Ion S.R.P. 14,150.00

LXT



Cordless 190 / 185 mm (7-1/2" / 7-1/4") Circular Saw

Wheel Diameter: 185 / 190 mm (7-1/2" / 7-1/4")
 Hole Diameter: 20 mm
 Max Cutting Capacity: 0°: 68.5 / 66 mm (2-11/16 / 2-5/8")
 45°: 49 / 47.5 mm (1-15/16 / 1-7/8")


No Load Speed (RPM): 4,800
 Net weight: 3.9 - 4.6 kg (8.6 - 10.1 lbs.)

NOT COMPATIBLE WITH GUIDERAIL
Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

DHS783Z 18V X2 (36V) LXT BL XPT AWS S.R.P. 20,650.00

LXT








ADT Cordless 185 mm (7-1/4") Magnesium Circular Saw

Wheel Diameter: 185 / 190 mm (7-1/2" / 7-1/4")
 Hole Diameter: 20 mm
 Max Cutting Capacity: 0°: 62.5 / 60 mm (2-7/16 / 2-3/8")
 45°: 44.5 / 43 mm (1-3/4 / 1-11/16")

No Load Speed (RPM): 6,000
 Net weight: 4.5 - 5.1 kg (9.9 - 11.3 lbs.)

COMPATIBLE WITH GUIDERAIL
Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty



DHS900Z	18V X2 (36V) LXT BL XPT AWS ADT Cordless 235 mm (9-1/4") Magnesium Circular Saw	S.R.P.	25,850.00
	Wheel Diameter 235 mm (9-1/4") Hole Diameter 25.4 mm Max Cutting Capacity 0": 85 mm (3-3/8") 45": 61 mm (2-3/8") No Load Speed (RPM) 4,500 Net weight 5.3 - 6.0 kg (11.7 - 13.2 lbs.)		
	COMPATIBLE WITH GUIDERAIL Battery, Charger NOT INCLUDED		

DHS901Z	18V X2 (36V) LXT BL XPT AWS ADT Cordless 235 mm (9-1/4") Magnesium Circular Saw	S.R.P.	24,050.00
	Wheel Diameter 235 mm (9-1/4") Hole Diameter 25.4 mm Max Cutting Capacity 0": 85 mm (3-3/8") 45": 61 mm (2-3/8") No Load Speed (RPM) 4,500 Net weight 5.8 - 6.4 kg (12.8 - 14.1 lbs.)		
	NOT COMPATIBLE WITH GUIDERAIL		

DHW800ZK	18V X2 (36V) LXT BL XPT Cordless 8 MPa (1160 psi) High Pressure Washer	S.R.P.	29,400.00
	Max permissible pressure 8 MPa (1160 psi) Regular pressure High / Low: 5.5 / 3.0 MPa Max water flow 380 L/h (6.3 L/min) Regular flow High / Low: 330 / 240 L/h (5.5 / 4.0 L/min) Pump speed (RPM) High / Low: 3,450 / 2,390 Max suction height 1 m (3.3 ft.) Max run time (min) using BL1860B X2 High / Low: 15 / 34 Tank 50 L Net weight 7.1 - 7.7 kg (15.6 - 17.0 lbs.)		
	Battery, Charger NOT INCLUDED		

DJR185Z	18V LXT Li-Ion Cordless Compact Recipro Saw	S.R.P.	5,450.00
	Length of stroke 13 mm (1/2") Strokes per minute (SPM) 0 - 3,000 Capacity Wood: 50 mm (2") Pipe: 50 mm (2") Net weight 1.5 - 1.7 kg (3.3 - 3.8 lbs.)		
	Battery, Charger NOT INCLUDED		

DJR186Z	18V LXT Li-Ion XPT Cordless Recipro Saw	S.R.P.	7,350.00
	Length of stroke 32 mm (1-1/4") Strokes per minute (SPM) 0 - 2,800 Capacity Wood: 255 mm (10") Pipe: 130 mm (5-1/8") Net weight 3.5 - 3.8 kg (7.6 - 8.3 lbs.)		
	Battery, Charger NOT INCLUDED		

DJR189Z	18V LXT BL XPT Cordless Recipro Saw	S.R.P.	11,450.00
	Length of stroke 22 mm (7/8") Strokes per minute (SPM) 0 - 3,100 Capacity Wood: 255 mm (10") Pipe: 130 mm (5-1/8") Net weight 2.2 - 2.5 kg (4.9 - 5.5 lbs.)		
	Battery, Charger NOT INCLUDED		

DJV180Z	18V LXT Li-Ion Cordless Top Handle Jig Saw	S.R.P.	11,850.00
	Capacity Wood: 135 mm (5-5/16") Length of stroke Steel: 10 mm (3/8") Strokes per minute (SPM) 26 mm (1") Bevel range 0 - 2,600 0 - 45° Net weight 2.7 - 3 kg (6 - 6.7 lbs.)		
	Battery, Charger NOT INCLUDED		

DJV182RF	18V LXT BL SOFT NO LOAD Cordless Top Handle Jig Saw	S.R.P.	24,400.00
	Capacity Wood: 135 mm (5-5/16") Steel: 10 mm (3/8") Length of stroke 26 mm (1") Strokes per minute (SPM) 800 - 3,500 Bevel range 0 - 45° Net weight 2.4 - 2.7 kg (5.2 - 5.9 lbs.)		
	INCLUDE: 1 pc. 3.0 Ah Battery, Charger, Carrying case		

DJV182Z	18V LXT BL SOFT NO LOAD Cordless Top Handle Jig Saw	S.R.P.	16,600.00
	Capacity Wood: 135 mm (5-5/16") Steel: 10 mm (3/8") Length of stroke 26 mm (1") Strokes per minute (SPM) 800 - 3,500 Bevel range 0 - 45° Net weight 2.4 - 2.7 kg (5.2 - 5.9 lbs.)		
	Battery, Charger NOT INCLUDED		




DJV184Z	18V LXT BL XPT SOFT NO LOAD Cordless Top Handle Jig Saw	S.R.P.	11,850.00
	Capacity Wood: 135 mm (5-5/16") Mild steel: 10 mm (3/8") Aluminum: 20 mm (25/32") Length of stroke 23 mm (7/8") Strokes per minute (SPM) 0 - 3,000 Bevel range 0 - 45° Net weight 2.1 - 2.4 kg (4.6 - 5.3 lbs.)		
	Battery, Charger NOT INCLUDED		

DJV185Z	18V LXT BL XPT SOFT NO LOAD Cordless Body Handle Jig Saw	S.R.P.	10,950.00
	Capacity Wood: 135 mm (5-5/16") Mild steel: 10 mm (3/8") Aluminum: 20 mm (25/32") Length of stroke 23 mm (7/8") Strokes per minute (SPM) 800 - 3,000 Bevel range 0 - 45° Net weight 2.0 - 2.3 kg (4.4 - 5.1 lbs.)		
	Battery, Charger NOT INCLUDED		



DK1202	10.8V Li-Ion Combo Kit	S.R.P.	10,700.00
	HP330D Capacity Steel / Wood / Masonry: 10 / 21 / 8 mm Chuck Capacity 0.8 - 10 mm (1/32 - 3/8") Impacts Per Minute (IPM) High / Low: 0 - 22,500 / 0 - 6,000 No Load Speed (RPM) High / Low: 0 - 1,500 / 0 - 400 Max Lock Torque 22 N·m (200 in.lbs.) MR051 Frequency Band FM / AM: 87.5 - 108 MHz / 522 - 1,620 kHz 2 - 1.3 Ah Battery, Charger, Tool Bag, 1 - HP330D, 1 - AM-FM Radio		

DKP180RF	18V LXT Li-Ion Cordless 82 mm (3-1/4") Planer	S.R.P.	20,950.00
	Planing width 82 mm (3-1/4") Planing depth 2.0 mm (5/64") Shipping 9 mm (11/32") No load speed (RPM) 15,000 Net weight 3.2 - 3.5 kg (7.1 - 7.9 lbs.)		
	INCLUDE: 1 - 3.0 Ah Battery, Charger, Carrying case.		

DKP180Z	18V LXT Li-Ion Cordless 82 mm (3-1/4") Planer	S.R.P.	11,350.00
	Planing width 82 mm (3-1/4") Planing depth 2.0 mm (5/64") Shipping 9 mm (11/32") No load speed (RPM) 15,000 Net weight 3.2 - 3.5 kg (7.1 - 7.9 lbs.)		
	Battery, Charger NOT INCLUDED		



DKT360Z  	18V X2 (36V) LXT Cordless Kettle Boiling time (approx. / min) 8 (0.8L water from 23 °C) Water tank capacity 0.8 L Dimensions (L x W x H) Kettle on Power supply stand: 233 x 263 x 307 mm (9-1/8 x 10-3/8 x 12-1/8") Net weight 2.7 - 3.4 kg (6.0 - 7.5 lbs.) Using 2 pcs. fully charge BL1860B can boil approx. 1.7 L MC Battery, Charger NOT INCLUDED	S.R.P. 10,550.00	DLM330Z  	18V LXT XPT Cordless 33 cm (13") Lawn Mower Cutting width 330 mm (13") Cutting height adjustment Adjustment range: 20 - 75 mm / Stage: 8 No Load Speed (RPM) 4,300 Continuous Use (min.) Using BL1860B: 21 (405 m ²) Wheel diameter 140 / 180 mm (5-1/2 / 7-1/8") Grass box Capacity: 30 L (1,014 oz) Net weight 11.6 - 12.5 kg (25.6 - 27.6 lbs.) MC Battery, Charger NOT INCLUDED	S.R.P. 12,900.00
DLM380Z  	18V X2 (36V) LXT XPT Cordless 38 cm (15") 2-in-1 Mower Cutting width 380 mm (15") Cutting height adjustment 25 - 75 mm (1" - 2-15/16") No Load Speed (RPM) 3,700 Continuous Use (min.) Using BL1860B x2: 34 (560 m ²) Wheel diameter 140 / 190 mm (5-1/2 / 7-1/2") Grass box 40 L Net weight 14.5 kg (32.0 lbs.) MC Battery, Charger NOT INCLUDED	S.R.P. 18,200.00	DLM432CT2  	18V X2 (36V) LXT XPT Cordless 430 mm (17") Mower Cutting width 430 mm (17") Cutting height adjustment 20 - 75 mm No Load Speed (RPM) 3,600 Continuous Use (min.) Using BL1860B x2: 36 (560 m ²) Wheel diameter 140 / 160 mm (5-1/2 / 6-5/16") Grass box 40 L Net weight 14.5 kg (32 lbs.) MC INCLUDE: 2 pcs BL1850B (5.0Ah), 2 Port Standard Charger.	S.R.P. 53,100.00
DLM432Z  	18V X2 (36V) LXT XPT Cordless 430 mm (17") Mower Cutting width 430 mm (17") Cutting height adjustment 20 - 75 mm No Load Speed (RPM) 3,600 Continuous Use (min.) Using BL1860B x2: 36 (560 m ²) Wheel diameter 140 / 160 mm (5-1/2 / 6-5/16") Grass box 40 L Net weight 14.5 kg (32 lbs.) MC Battery, Charger NOT INCLUDED	S.R.P. 28,850.00	DLS111Z  	18V X2 (36V) LXT BL AWS ADT Cordless 260 mm (10-1/4") Slide Compound Miter Saw Wheel Diameter 255 - 260 mm (10 - 10-1/4") Hole Diameter 15.88/ 25.4/ 30 mm (5/8/ 1/ 1-3/16") Max Cutting Capacity 0° Miter: 91 x 279 x 68 x 310 mm (3-5/8 x 11 x 2-11/16 x 12-1/4") 45° Miter, L/R: 91 x 197 x 68 x 218 mm (3-5/8 x 7-3/4 x 2-11/16 x 8-5/8") No Load Speed (RPM) 4,400 Net weight 26.6 - 27.3 kg (58.6 - 60.2 lbs.) MC Battery, Charger NOT INCLUDED	S.R.P. 43,300.00
DLW140Z  	18V X2 (36V) LXT BL 355 mm (14") Toolless Portable Cut-Off Wheel Diameter 355 mm (14") Hole Diameter 25.4 mm (1") Capacity at 0° Round: 127 mm (5") Capacity at 45° Round: 127 mm (5") Rectangular: 115 x 103 mm (4-1/2 x 4-1/16") Net weight 17.2 - 17.8 kg (37.9 - 39.3 lbs.) MC Battery, Charger NOT INCLUDED	S.R.P. 20,150.00	DLX2398  	18V LXT BL XPT Cordless DUR192L OPE Combo Kit Cutting Width Nylon Cutting Head: 300 mm (11-3/4") No Load Speed (RPM) High / Low: 0 - 4,500 / 0 - 6,000 Spindle size M10 x 1.25 LHC Max run time (min) NYLON: NO LOAD (6.0Ah): 55 DUB184 Max air velocity 52.1 m/s (116 MPH) (187 KPH) Blowing force 10.9 N Continuous Use (min.) Using BL1860B: 12 MC INCLUDE: 2pcs 3.0Ah battery, 1 Charger, 1 - DUR192L, 1 - DUB184	S.R.P. 27,850.00
DLX2423AJ  	18V LXT BL XPT Cordless Sub-compact Combo Kit DDF487 Driver Drill Capacity Steel: 13 mm (1/2"), Wood: 36 mm (1-7/16") Max fastening torque Hard: 40 N·m / Soft: 25 N·m DTD157 Impact Driver Capacity Machine screw: M4 - M8 mm (5/32 - 5/16") Standard bolt: M5 - M14 (3/16 - 9/16") High strength bolt: M5 - M12 (3/16 - 1/2") Max fastening torque 140 N·m (1,240 in.lbs.) MC INCLUDE: 2pcs 2.0Ah battery, 1 Charger, 1 - DDF487, 1 - DTD157	S.R.P. 28,050.00	DLX2494S  	18V LXT BL XPT Cordless DUB185 Blower OPE Combo Kit Blowing force 3.1 N Max Sealed Suction 5.8 kPa No Load Speed (RPM) 0 - 18,000 Run time (min) 6.0 Ah: High / Mid / Low: 25 / 60 / 156 DUM111 Grass Shear Cutting Width 160 mm (6-5/16") Strokes Per Minute (SPM) 2,500 Continuous Use (min.) 6.0 Ah : 250	S.R.P. 15,400.00
DMC300Z  	18V LXT BL AFT XPT Cordless 76 mm (3") Compact Cut Off Wheel diameter 76 mm (3") Hole diameter 9.5, 10.0 mm (3/8, 13/32") Wheel plate thickness 1.0 mm (1/32") No load speed (RPM) 20,000 Max cutting capacity w/ Dust cover attachment: 13.5 mm (1/2") w/o Dust cover attachment: 16.0 mm (5/8") Dimensions (L x W x H) 271 x 104 x 182 mm Net weight 1.2 - 1.7 kg (2.6 - 3.7 lbs.) MC Battery, Charger NOT INCLUDED.	S.R.P. 8,200.00	DMP180Z  	18V LXT XPT Cordless Inflator Max Air Pressure 830 kPa (121 PSI) [8.3 bar] Air Discharge Amount 200 kPa: 12 L/min 700 kPa: 8 L/min 830 kPa: 7 L/min Hose Length 65 cm (25-1/2") Net weight 1.4 - 1.7 kg (3.1 - 3.8 lbs.) MC Battery, Charger NOT INCLUDED.	S.R.P. 4,250.00
DMR050  	18V LXT Li-Ion Cordless Flashlight Radio Run Time (hrs) Radio Up to: 35 using BL1850B Practical max output 2.0 W - 3.0 Ah / 1.5 W - 1.3 Ah Frequency Band FM / AM: 522 - 1.629 MHz / 87.5 - 108 kHz Dimensions (L x W x H) 263 x 75 x 179 mm (10-3/8 x 2-15/16 x 7") Net weight 0.92 - 1.3 kg (2 - 2.9 lbs.) MC	S.R.P. 5,900.00	DMR108N  	12Vmax-18V CXT LXT Li-Ion Cordless Bluetooth Job Site Frequency Band 87.5 - 108 MHz / 522 - 1,710 kHz Speaker Size Woofer: Dia. 89 mm x2 Dimensions (L x W x H) w/ Handle in Upright Position : 262 x 163 x 431 mm (10-3/8 x 6-3/8 x 17") Net weight 4.3 - 4.9 kg (9.5 - 10.8 lbs.) Runtime using BL1850B 28 hrs MC Battery, Charger NOT INCLUDED.	S.R.P. 12,650.00



DMR114	S.R.P. 15,750.00
12Vmax-18V CXT LXT Li-Ion Cordless Bluetooth Job Site	
	Frequency Band: DMR114: 87.5 - 108 MHz / 522 - 1,710 kHz Speaker Size: Sides: Dia. 63.5 mm x2, Bottom: Dia. 101.6 mm Dimensions (L x W x H) w/ Handle in Upright Position: 268 x 164 x 437 mm (10-1/2x6-1/2x17-1/4") Net weight: 5.1 - 5.6 kg (11.3 - 12.3 lbs.) Runtime using BL1850B: 17 hrs
1.5 Years Limited Warranty	MC Battery, Charger NOT INCLUDED.

DMR203	S.R.P. 11,400.00
12Vmax / 18V CXT LXT TWS Cordless Bluetooth Job Site Speaker	
	Speaker Size: Woofer: Dia. 101.6 mm, Tweeter: Dia. 36 mm, Passive Radiator: Dia. 89 mm Dimensions (L x W x H): 217 x 206 x 285 mm (8-1/2x8-1/8x11-1/4") Net weight: 2.7 - 3.4 kg (6.0 - 7.5 lbs.) Runtime using BL1850B: 26 hrs
1.5 Years Limited Warranty	MC Battery, Charger NOT INCLUDED.

DP2010	S.R.P. 4,000.00
6.5 mm (1/4") 370 W High Speed Variable Speed Reversing Drill	
	Continuous rating Input: 370W Capacity: Steel: 6.5 mm (1/4"), Wood: 15 mm (9/16"), Wood (Self-feed bit): 30 mm (1-3/16") Chuck capacity: 0.5 - 6.5mm (1/64 - 1/4") No Load Speed (RPM): 0 - 4,200 Net weight: 1 kg (2.2 lbs.)
2.5 Years Limited Warranty	

DP4700	S.R.P. 11,500.00
13 mm (1/2") 510 W Drill with Keyed Chuck	
	Continuous rating input: 510W Capacity: Steel: 13mm (1/2"), Wood: 25mm (1") No load speed (rpm): 0 - 550 Net weight: 2.2 Kg (4.8 lbs)
2.5 Years Limited Warranty	

DPJ180Z	S.R.P. 16,250.00
18V LXT Li-Ion Cordless Plate Joiner	
	Wheel Diameter: 100 mm (4") Hole Diameter: 22 mm (7/8") No Load Speed (RPM): 6,500 Net weight: 2.8 - 3.1 kg (6.2 - 6.8 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED.

DPO600RTE	S.R.P. 42,400.00
18V LXT BL XPT Cordless 150 mm (6") Random Orbit Polisher	
	Pad Size: 150 mm (6") Orbits Per Minute (OPM): Normal Mode: 0 - 6,800, Finishing mode: 0 - 5,200 No Load Speed (RPM): Normal Mode: 0 - 780, Finishing mode: 0 - 600 Orbit Diameter: 5.5 mm (7/32") Net weight: 3.1 - 3.6 kg (6.9 - 7.9 lbs.)
2.5 Years Limited Warranty	INCLUDE: 1 pc. 5.0 Ah Battery, Charger, Tool bag..

DPT353Z	S.R.P. 19,700.00
18V LXT Li-Ion Cordless 23 GA 35 mm (1-3/8") Pin Nailer	
	Capacity: Length: 15, 18, 25, 30, 35 mm (5/8, 11/16, 1, 1-3/16, 1-3/8") Dia.: 0.6 mm (1/32") Gauge: 23 Ga Magazine capacity: 120 Dimensions (L x W x H): 257 x 79 x 226 mm (10-1/8 x 3-1/8 x 8-7/8") Net weight: 2 - 2.3 kg (4.4 - 5.1 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED

DMR200	S.R.P. 8,000.00
12Vmax / 18V CXT LXT Cordless Bluetooth Job Site Speaker	
	Speaker Size: Woofer: Dia. 101.6 mm, Tweeter: Dia. 36 mm Dimensions (L x W x H): 211 x 203 x 286 mm (8-5/16 x 8 x 11-1/4") Net weight: 2.9 - 3.4 kg (6.4 - 7.4 lbs.) Runtime using BL1850B: 31 hrs
1.5 Years Limited Warranty	Battery, Charger NOT INCLUDED.

DMR300	S.R.P. 18,600.00
12Vmax / 18V CXT LXT Cordless Bluetooth Job Site Speaker with Battery charging function	
	Frequency Band: FM / AM : 87.5 - 108 MHz / 520 - 1,710 kHz Speaker Size: Woofer: Dia. 89 mm x2, Dimensions (L x W x H): 268 x 185 x 427 mm Net weight: 6.1 - 6.6 kg (13.5 - 14.6 lbs.) Runtime using BL1850B: 20.5 hrs Charging Time: 84 mins for BL1850B (5.0 Ah)
1.5 Years Limited Warranty	MC Battery, Charger NOT INCLUDED.



DP4010	S.R.P. 6,850.00
13 mm (1/2") 720 W Variable 2-Speed Reversing Drill	
	Continuous rating Input: 720W Capacity: Steel Hi: 8 mm (5/16"), Steel Lo: 13 mm (1/2"), Wood Hi: 25 mm (1"), Wood Lo: 40 mm (1-9/16") No Load Speed (RPM): High: 0 - 2,900 / Low: 0 - 1,200 Net weight: 2.3 kg (5 lbs.)
2.5 Years Limited Warranty	

DPB182Z	S.R.P. 15,650.00
18V LXT Li-Ion Cordless Portable Band Saw	
	Capacity: Round: 64 mm (2-1/2") Blade Length: 835 mm (32-7/8") Blade Speed: 3.2 m/s (630 ft/min.) Blade Size: Length: 835 mm (32-7/8"), Width: 13 mm (1/2"), Thickness: 0.5 mm (0.02") Net weight: 3.8 - 4.1 kg (8.3 - 9.0 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED.

DPO500Z	S.R.P. 21,300.00
18V LXT BL XPT Cordless 125 mm (5") Random Orbit Polisher	
	Pad Size: 125 mm (5") Orbits Per Minute (OPM): Normal Mode: 0 - 6,800, Finishing mode: 0 - 5,200 No Load Speed (RPM): Normal Mode: 0 - 780, Finishing mode: 0 - 600 Orbit Diameter: 5.5 mm (7/32") Net weight: 3.1 - 3.6 kg (6.9 - 7.9 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED.


DPO600Z	S.R.P. 21,400.00
18V LXT BL XPT Cordless 150 mm (6") Random Orbit Polisher	
	Pad Size: 150 mm (6") Orbits Per Minute (OPM): Normal Mode: 0 - 6,800, Finishing mode: 0 - 5,200 No Load Speed (RPM): Normal Mode: 0 - 780, Finishing mode: 0 - 600 Orbit Diameter: 5.5 mm (7/32") Net weight: 3.1 - 3.6 kg (6.9 - 7.9 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED

DPV300Z	S.R.P. 14,100.00
18V LXT BL XPT Cordless Sander Polisher	
	Pad / disc diameter: Twist-on / Twist-off style: 50 mm (2") Hook & Loop Style: 80 mm (3-1/8") Backing pad diameter: Twist-on / Twist-off style: 46 mm (1-13/16") Hook & Loop Style: 75 mm (2-15/16") Disc paper diameter: 50 mm (2") No Load Speed (RPM): Polishing: 0 - 2,800 / Sanding: 0 - 9,500 Continuous Use (min.) Using BL1850B: 34 Net weight: 1.3 - 1.6 kg (2.9 - 3.5 lbs.)
2.5 Years Limited Warranty	Battery, Charger NOT INCLUDED



DRT50SFx8 S.R.P. 16,250.00

18V LXT BL Cordless 1/4" Variable Speed Trimmer




Collet size	1/4"
Base inner	30 mm (1-3/16")
No Load Speed (RPM)	10,000 - 30,000
Dimensions (L x W x H)	134 x 89 x 226 mm (5-1/4 x 3-1/2 x 8-7/8")
Net weight	1.8 - 2.1 kg (3.9 - 4.6 lbs.)

2.5 Years Limited Warranty **INCLUDE: 1 pc. 3.0 Ah Battery, Standard Charger, Tool bag.**

DRT50ZJX9 S.R.P. 17,800.00

18V LXT BL Cordless 1/4" Variable Speed Trimmer



Collet size	1/4"
Base inner	30 mm (1-3/16")
No Load Speed (RPM)	10,000 - 30,000
Dimensions (L x W x H)	134 x 89 x 226 mm (5-1/4 x 3-1/2 x 8-7/8")
Net weight	1.8 - 2.1 kg (3.9 - 4.6 lbs.)

2.5 Years Limited Warranty **INCLUDE: Trimmer Base Assy, Plunge Base Assy, Tilt Base Assy, Template Guide, Straight Guide, Grip 36, Guide Holder, Trimmer Guide Assy, Guide Rule Adapter, Dust Nozzle X2..**
Battery, Charger NOT INCLUDE

DSP601Z S.R.P. 23,000.00

18V X2 (36V) LXT BL XPT Cordless 165 mm (6-1/2") Plunge Cut Saw



Wheel Diameter	165 mm (6-1/2")
Hole Diameter	20 mm (13/16")
Bevel capacity	-1 - 48°
0°: 56 mm (2-3/16")	
Max Cutting Capacity	45°: 40 mm (1-9/16")
No Load Speed (RPM)	2,500 - 4,900
Net weight	4.4 - 5.0 kg (9.7 - 11.0 lbs.)

2.5 Years Limited Warranty **Wireless Unit, Battery, Charger NOT INCLUDED.**

DSS611Z S.R.P. 7,850.00

18V LXT Li-Ion Cordless 165 mm (6-1/2") Circular Saw




Wheel Diameter	165 mm (6-1/2")
Hole Diameter	20 mm
Max Cutting Capacity	0°: 57 mm (2-1/4")
45°: 40 mm (1-9/16")	
No Load Speed (RPM)	3,700
Net weight	2.9 - 3.2 kg (6.4 - 7.1 lbs.)

2.5 Years Limited Warranty **NOT COMPATIBLE WITH GUIDERAIL**
Battery, Charger NOT INCLUDED.

DST121Zk S.R.P. 24,700.00

18V LXT Li-Ion XPT Cordless 10 mm J, 23 GA 35 mm (1-3/8") Pin Nailer




Staple	Width: 10 mm (N/A*)
	Length: 13 - 25 mm (1/2 - 1")
	Size: 1.2 x 0.6 mm
Magazine Capacity	100
Shots per full charger bat	4,000 using BL1850B (5.0 Ah)
Net weight	2.2 - 2.5 kg (4.9 - 5.5 lbs.)

2.5 Years Limited Warranty **Battery, Charger NOT INCLUDED.**

DST421Zk S.R.P. 24,700.00

18V LXT Li-Ion XPT Cordless 4 mm J, 23 GA 35 mm (1-3/8") Pin Nailer




Staple	Width: 4 mm
	Length: 13 - 25 mm (1/2 - 1")
	Size: 1.2 x 0.6 mm
Magazine Capacity	100
Shots per full charger bat	4,000 using BL1850B (5.0 Ah)
Net weight	2.2 - 2.5 kg (4.9 - 5.5 lbs.)

2.5 Years Limited Warranty **Battery, Charger NOT INCLUDED.**

DTD152RF S.R.P. 12,500.00

18V LXT XPT Cordless 165 N-m Impact Driver




Capacity	Machine screw: M4 - M8 (5/32 - 5/16")
	Standard bolt: M5 - M16 (3/16 - 5/8")
	High strength bolt: M5 - M12 (3/16 - 1/2")
Hex shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,900
Impacts per minute (IPM)	0 - 3,500
Max fastening torque	165 N-m (1,460 in.lbs.)
Net weight	1.3 - 1.6 kg (2.8 - 3.5 lbs.)

2.5 Years Limited Warranty **INCLUDE: 1 pc. 3.0 Ah Battery, Charger, Carrying case..**

DRT50Z S.R.P. 10,100.00

18V LXT BL Cordless 1/4" Variable Speed Trimmer




Collet size	1/4"
Base inner	30 mm (1-3/16")
No Load Speed (RPM)	10,000 - 30,000
Dimensions (L x W x H)	134 x 89 x 226 mm (5-1/4 x 3-1/2 x 8-7/8")
Net weight	1.8 - 2.1 kg (3.9 - 4.6 lbs.)

2.5 Years Limited Warranty **Battery, Charger NOT INCLUDED.**

DS4012 S.R.P. 13,650.00

13 mm (1/2") 750 W D-Handle Drill



Continuous rating Input Capacity	750W
	Steel: 13 mm (1/2")
	Wood: 36 mm (1-7/16")
	Wood (Self-feed bit): 127 mm (5")
Chuck capacity	2 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	0 - 600
Net weight	2.8 kg (6.2 lbs.)

DSS611RF S.R.P. 16,450.00

18V LXT Li-Ion Cordless 165 mm (6-1/2") Circular Saw




Wheel Diameter	165 mm (6-1/2")
Hole Diameter	20 mm
Max Cutting Capacity	0°: 57 mm (2-1/4")
45°: 40 mm (1-9/16")	
No Load Speed (RPM)	3,700
Net weight	2.9 - 3.2 kg (6.4 - 7.1 lbs.)

2.5 Years Limited Warranty **NOT COMPATIBLE WITH GUIDERAIL**
INCLUDE: 1 pc. 3.0 Ah Battery, Charger, Carrying case.

DST121RFE S.R.P. 35,900.00

18V LXT Li-Ion XPT Cordless 10 mm J, 23 GA 35 mm (1-3/8") Pin Nailer




Staple	Width: 10 mm (N/A*)
	Length: 13 - 25 mm (1/2 - 1")
	Size: 1.2 x 0.6 mm
Magazine Capacity	100
Shots per full charger bat	4,000 using BL1850B (5.0 Ah)
Net weight	2.2 - 2.5 kg (4.9 - 5.5 lbs.)

2.5 Years Limited Warranty **INCLUDE: 2 pcs. 3.0 Ah Battery, Charger, Carrying case.**

DST421RFE S.R.P. 35,900.00

18V LXT Li-Ion XPT Cordless 4 mm J, 23 GA 35 mm (1-3/8") Pin Nailer




Staple	Width: 4 mm
	Length: 13 - 25 mm (1/2 - 1")
	Size: 1.2 x 0.6 mm
Magazine Capacity	100
Shots per full charger bat	4,000 using BL1850B (5.0 Ah)
Net weight	2.2 - 2.5 kg (4.9 - 5.5 lbs.)

2.5 Years Limited Warranty **INCLUDE: 2 pcs. 3.0 Ah Battery, Charger, Carrying case.**

DTD146Z S.R.P. 5,450.00

18V LXT XPT Cordless 160 N-m Impact Driver




Capacity	Machine screw : M4 - M8 (5/32" - 5/16")
	Standard bolt : M5 - M14 (3/16" - 9/16")
	High tensile bolt : M5 - M12 (3/16" - 1/2")
	Coarse thread (in length): 22 - 125mm
Impacts per minute (ipm)	0-3,200
No load speed (rpm)	0-2,300
Max. fastening torque	160N.m (1,420in.lbs)
Net weight	1.3kg (2.8lbs)

2.5 Years Limited Warranty **Battery, Charger NOT INCLUDED.**





DTD152Z S.R.P. 5,100.00

18V LXT XPT Cordless 165 N-m Impact Driver



Capacity	Machine screw: M4 - M8 (5/32 - 5/16")
	Standard bolt: M5 - M16 (3/16 - 5/8")
	High strength bolt: M5 - M12 (3/16 - 1/2")
Hex shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,900
Impacts per minute (IPM)	0 - 3,500
Max fastening torque	165 N-m (1,460 in.lbs.)
Net weight	1.3 - 1.6 kg (2.8 - 3.5 lbs.)

2.5 Years Limited Warranty **Battery, Charger NOT INCLUDED.**



DTD155RF	18V LXT BL XPT Cordless A-Mode (Assist Mode) 140 N-m Impact Driver	S.R.P.	14,000.00
	Capacity	Machine Screw: M4 - M8 mm (5/32" - 5/16") Standard Bolt: M5 - M14 (3/16" - 9/16") High Strength Bolt: M5 - M12 (3/16" - 1/2")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	Hard / Soft: 0 - 3,000 / 0 - 1,300	
	Impacts per minute (IPM)	Hard / Soft: 0 - 3,900 / 0 - 1,600	
	Max fastening torque	140 N-m (1,240 in.lbs.)	
	Net weight	1.2 - 1.5 kg (2.6 - 3.2 lbs.)	
	INCLUDE: 1 pc. 3.0 Ah Battery, Charger, Carrying case..		

DTD156Z	18V LXT Cordless 155 N-m-m Impact Driver	S.R.P.	3,650.00
	Capacity	Machine screw: M4 - M8 (5/32 - 5/16") Standard bolt: M5 - M14 (3/16 - 9/16") High strength bolt: M5 - M12 (3/16 - 1/2")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	0 - 2,500	
	Impacts per minute (IPM)	0 - 3,000	
	Max fastening torque	155 N-m (1,370 in.lbs.)	
	Net weight	1.3 - 1.6 kg (2.8 - 3.5 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTD157Z	18V LXT BL XPT Cordless A-Mode (Assist Mode) 140 N-m Impact Driver	S.R.P.	7,400.00
	Capacity	Machine screw: M4 - M8 mm (5/32 - 5/16") Standard bolt: M5 - M14 (3/16 - 9/16") High strength bolt: M5 - M12 (3/16 - 1/2")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	Hard / Soft: 0 - 3,000 / 0 - 1,300	
	Impacts per minute (IPM)	Hard / Soft: 0 - 4,100 / 0 - 2,000	
	Max fastening torque	140 N-m (1,240 in.lbs.)	
	Net weight	1.2 - 1.5 kg (2.6 - 3.3 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTD171Z	18V LXT BL XPT Cordless Wood/Bolt/T-Mode 180 N-m Impact Driver	S.R.P.	9,750.00
	Capacity	Machine Screw: M4 - M8 (5/32 - 5/16"), Standard Bolt: M5 - M16 (3/16 - 5/8") High Strength Bolt: M5 - M14 (3/16 - 9/16")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	Max.: 0 - 3,600	
	Impacts per minute (IPM)	Max.: 0 - 3,800	
	Max fastening torque	180 N-m (1,590 in.lbs.)	
	Net weight	1.2 - 1.6 kg (2.7 - 3.4 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTL061Z	18V LXT Li-Ion Cordless 60 N-m Angle Impact Driver	S.R.P.	11,500.00
	Capacity	Machine screw: M4 - M8 (5/32 - 5/16") Standard bolt: M4 - M12 (5/32 - 1/2") High strength bolt: M4 - M8 (5/32 - 5/16")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	0 - 2,000	
	Impacts per minute (IPM)	0 - 3,000	
	Max fastening torque	60 N-m (530 in.lbs.)	
	Net weight	1.4 - 2 kg (3.1 - 4.3 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTM52Z	18V LXT BL AVT XPT Cordless Toolless Multi Tool	S.R.P.	11,950.00
	Oscillations per minute (OPM)	10,000 - 20,000	
	Oscillation angle	Left / Right / Total: 1.8° / 1.8° / 3.6°	
	Dimensions (L x W x H)	322 x 95 x 126 mm (12-5/8 x 3-3/4 x 5")	
	Net weight	1.7 - 2.0 kg (3.7 - 4.4 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTW1002Z	18V LXT BL Cordless 3-Speed 1/2" (12.7 mm), 1,000 N-m Impact Wrench	S.R.P.	20,900.00
	Fastening capacities	Standard bolt: M12 - M30 (1/2 - 1-1/4") High strength bolt: M10 - M24 (3/8 - 1") 12.7 mm (1/2")	
	Square drive	12.7 mm (1/2")	
	No Load Speed (RPM)	Hard / Mid / Soft: 0 - 1,800 / 0 - 1,000 / 0 - 900	
	Impacts per minute (IPM)	Hard / Mid / Soft: 0 - 2,200 / 0 - 2,000 / 0 - 1,800	
	Max fastening torque	1,000 N-m (740 ft.lbs.)	
	Net weight	3.3 - 3.6 kg (7.3 - 8 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTD155Z	18V LXT BL XPT Cordless A-Mode (Assist Mode) 140 N-m Impact Driver	S.R.P.	6,650.00
	Capacity	Machine Screw: M4 - M8 mm (5/32" - 5/16") Standard Bolt: M5 - M14 (3/16" - 9/16") High Strength Bolt: M5 - M12 (3/16" - 1/2")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	Hard / Soft: 0 - 3,000 / 0 - 1,300	
	Impacts per minute (IPM)	Hard / Soft: 0 - 3,900 / 0 - 1,600	
	Max fastening torque	140 N-m (1,240 in.lbs.)	
	Net weight	1.2 - 1.5 kg (2.6 - 3.2 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTD157RTJ	18V LXT BL XPT Cordless A-Mode (Assist Mode) 140 N-m Impact Driver	S.R.P.	26,250.00
	Capacity	Machine screw: M4 - M8 mm (5/32 - 5/16") Standard bolt: M5 - M14 (3/16 - 9/16") High strength bolt: M5 - M12 (3/16 - 1/2")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	Hard / Soft: 0 - 3,000 / 0 - 1,300	
	Impacts per minute (IPM)	Hard / Soft: 0 - 4,100 / 0 - 2,000	
	Max fastening torque	140 N-m (1,240 in.lbs.)	
	Net weight	1.2 - 1.5 kg (2.6 - 3.3 lbs.)	
	INCLUDE: 1 pc. 5.0 Ah Battery, Charger, Makpac case..		

DTD170Z	18V LXT BL XPT Cordless A-Mode (Assist Mode) T-Mode 4-Speed 175 N-m Impact Driver	S.R.P.	11,350.00
	Capacity	Machine Screw: M4 - M8 (5/32" - 5/16") Standard Bolt: M5 - M16 (3/16" - 5/8") High Strength Bolt: M5 - M14 (3/16" - 9/16")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	Max.: 0 - 3,600	
	Impacts per minute (IPM)	Max.: 0 - 3,800	
	Max fastening torque	175 N-m (1,550 in.lbs.)	
	Net weight	1.2 - 1.5 kg (2.6 - 3.3 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTD172Z	18V LXT BL XPT Cordless Wood/Bolt/T-Mode 180 N-m Impact Driver	S.R.P.	9,750.00
	Capacity	Machine Screw: M4 - M8 (5/32 - 5/16"), Standard Bolt: M5 - M16 (3/16 - 5/8") High Strength Bolt: M5 - M14 (3/16 - 9/16")	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	Max.: 0 - 3,600	
	Impacts per minute (IPM)	Max.: 0 - 3,800	
	Max fastening torque	180 N-m (1,590 in.lbs.)	
	Net weight	1.2 - 1.5 kg (2.6 - 3.3 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTM50Z	18V LXT Li-Ion Cordless Multi Tool	S.R.P.	7,100.00
	Oscillations per minute (OPM)	6,000 - 20,000	
	Dimensions (L x W x H)	307 x 80 x 122 mm (12-1/4 x 3-1/8 x 4-13/16")	
	Net weight	1.8 - 2.2 kg (3.9 - 4.8 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTW1001Z	18V LXT BL Cordless 3-Speed 3/4" (19 mm), 1,050 N-m Impact Wrench	S.R.P.	21,150.00
	Fastening capacities	Standard bolt: M12 - M30 (1/2 - 1-1/4") High strength bolt: M10 - M24 (3/8 - 1") 19 mm (3/4")	
	Square drive	19 mm (3/4")	
	No Load Speed (RPM)	Hard / Mid / Soft: 0 - 1,800 / 0 - 1,000 / 0 - 900	
	Impacts per minute (IPM)	Hard / Mid / Soft: 0 - 2,200 / 0 - 2,000 / 0 - 1,800	
	Max fastening torque	1,050 N-m (780 ft.lbs.)	
	Net weight	3.4 - 3.7 kg (7.5 - 8.2 lbs.)	
	Battery, Charger NOT INCLUDED.		

DTW190JX1	18V LXT Li-Ion Cordless 1/2" (12.7 mm) 190 N-m Impact Wrench	S.R.P.	21,600.00
	Fastening capacities	Standard bolt: M8 - M16 (5/16 - 5/8") High strength bolt: M8 - M12 (5/16 - 1/2")	
	Square drive	12.7 mm (1/2")	
	No Load Speed (RPM)	0 - 2,300	
	Impacts per minute (IPM)	0 - 3,000	
	Max fastening torque	190 N-m (140 ft.lbs.)	
	Net weight	1.4 - 1.8 kg (3.2 - 3.9 lbs.)	
	INCLUDE: 9pcs. Impact socket set, Extension Bar. 2 pcs. (3.0Ah) Battery, 1 Charger. MAKPAC case.		



DTW190RF	18V LXT Li-Ion Cordless 1/2" (12.7 mm) 190 N-m Impact Wrench	S.R.P. 14,200.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M8 - M16 (5/16 - 5/8") High strength bolt: M8 - M12 (5/16 - 1/2") 12.7 mm (1/2") 0 - 2,300 0 - 3,000 190 N-m (140 ft.lbs.) 1.4 - 1.8 kg (3.2 - 3.9 lbs.)
INCLUDE: 1 pc. (3.0Ah) Battery, 1 Charger, Carrying case.		

DTW190SFX7	18V LXT Li-Ion Cordless 1/2" (12.7 mm) 190 N-m Impact Wrench	S.R.P. 10,350.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M8 - M16 (5/16 - 5/8") High strength bolt: M8 - M12 (5/16 - 1/2") 12.7 mm (1/2") 0 - 2,300 0 - 3,000 190 N-m (140 ft.lbs.) 1.4 - 1.8 kg (3.2 - 3.9 lbs.)
INCLUDE: 1 pc. (3.0Ah) Battery, 1 Std. Charger		

DTW190Z	18V LXT Li-Ion Cordless 1/2" (12.7 mm) 190 N-m Impact Wrench	S.R.P. 4,300.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M8 - M16 (5/16 - 5/8") High strength bolt: M8 - M12 (5/16 - 1/2") 12.7 mm (1/2") 0 - 2,300 0 - 3,000 190 N-m (140 ft.lbs.) 1.4 - 1.8 kg (3.2 - 3.9 lbs.)
Battery, Charger NOT INCLUDED.		

DTW251RF	18V LXT Li-Ion Cordless 1/2" (12.7 mm) 230 N-m Impact Wrench	S.R.P. 17,350.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M10 - M16 (3/8 - 5/8") High strength bolt: M10 - M14 (3/8 - 9/16") 12.7 mm (1/2") 0 - 2,100 0 - 3,200 230 N-m (170 ft.lbs.) 1.5 - 1.8 kg (3.2 - 3.9 lbs.)
INCLUDE: 1 pc. (3.0Ah) Battery, 1 Charger, Carrying case.		

DTW251Z	18V LXT Li-Ion Cordless 1/2" (12.7 mm) 230 N-m Impact Wrench	S.R.P. 8,300.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M10 - M16 (3/8 - 5/8") High strength bolt: M10 - M14 (3/8 - 9/16") 12.7 mm (1/2") 0 - 2,100 0 - 3,200 230 N-m (170 ft.lbs.) 1.5 - 1.8 kg (3.2 - 3.9 lbs.)
Battery, Charger NOT INCLUDED.		

DTW253Z	18V LXT Li-Ion Cordless 3/8" (9.5 mm) 210 N-m Impact Wrench	S.R.P. 8,450.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M8 - M16 (5/16 - 5/8") High strength bolt: M6 - M12 (1/4 - 1/2") 9.5 mm (3/8") 0 - 2,100 0 - 3,200 210 N-m (155 ft.lbs.) 1.3 - 1.6 kg (2.8 - 3.6 lbs.)
Battery, Charger NOT INCLUDED.		

DTW285Z	18V LXT BL XPT Cordless 1/2" (12.7 mm) 230 N-m Impact Wrench	S.R.P. 12,450.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard Bolt: M10 - M20 (3/8 - 3/4") High Strength Bolt: M10 - M16 (3/8 - 5/8") 12.7 mm (1/2") Hard / Med / Soft: 0 - 2,800 / 0 - 2,100 / 0 - 1,600 Hard / Med / Soft: 0 - 3,500 / 0 - 2,600 / 0 - 1,800 280 N-m (210 ft.lbs.) 1.5 - 1.8 kg (3.2 - 3.9 lbs.)
Battery, Charger NOT INCLUDED.		

DTW300FJX3	18V LXT BL XPT Cordless 1/2" (12.7 mm) 330 N-m Impact Wrench	S.R.P. 31,800.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard Bolt: M10 - M20 (3/8 - 3/4") High Strength Bolt: M10 - M16 (3/8 - 5/8") 12.7 mm (1/2") Hard / Med / Soft: 0 - 4,000 / 3,400 / 2,600 / 1,800 Hard / Med / Soft: 0 - 3,200 / 2,600 / 1,800 / 1,000 330 N-m (240 ft.lbs.) 1.5 - 1.8 kg (3.2 - 3.9 lbs.)
2 - 3.0Ah Battery, 1 - Fast Charger, 1 set Socket Bit with extension.		

DTW300Z	18V LXT BL XPT Cordless 1/2" (12.7 mm) 330 N-m Impact Wrench	S.R.P. 13,500.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard Bolt: M10 - M20 (3/8 - 3/4") High Strength Bolt: M10 - M16 (3/8 - 5/8") 12.7 mm (1/2") Hard / Med / Soft: 0 - 4,000 / 3,400 / 2,600 / 1,800 Hard / Med / Soft: 0 - 3,200 / 2,600 / 1,800 / 1,000 330 N-m (240 ft.lbs.) 1.5 - 1.8 kg (3.2 - 3.9 lbs.)
Battery, Charger NOT INCLUDED.		

DTW700Z	18V LXT BL XPT Cordless 1/2" (12.7 mm) 700 N-m Impact Wrench	S.R.P. 18,050.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M10 - M24 (3/8 - 1") High Strength Bolt: M12, M16 (7/16, 5/8") 12.7 mm (1/2") 4/3/2/1: 0 - 2,200 / 0 - 1,900 / 0 - 1,200 / 0 - 500 4/3/2/1: 0 - 2,700 / 0 - 2,400 / 0 - 1,700 / 0 - 1,000 700 N-m (520 ft.lbs.) 2.3 - 2.7 kg (5.1 - 6.0 lbs.)
Battery, Charger NOT INCLUDED.		

DTW701Z	18V LXT BL XPT Cordless 1/2" (12.7 mm) 700 N-m Impact Wrench	S.R.P. 18,100.00
	Fastening capacities Square drive No Load Speed (RPM) Impacts per minute (IPM) Max fastening torque Net weight	Standard bolt: M10 - M24 (3/8 - 1") High Strength Bolt: M12, M16 (7/16, 5/8") 12.7 mm (1/2") 4/3/2/1: 0 - 2,200 / 0 - 1,900 / 0 - 1,200 / 0 - 500 4/3/2/1: 0 - 2,700 / 0 - 2,400 / 0 - 1,700 / 0 - 1,000 700 N-m (520 ft.lbs.) 2.3 - 2.7 kg (5.1 - 6.0 lbs.)
Battery, Charger NOT INCLUDED.		

DUB184Z	18V LXT BL XPT Cordless Variable Speed Blower	S.R.P. 9,700.00
	Max air volume Max air velocity Blowing force No Load Speed (RPM) Continuous Use (min.) Dimensions (L x W x H) Net weight	13.0 m³/min (459 CFM) 52.1 m/s (116 MPH) 10.9 N 0 - 18,000 Using BL1860B: 12 825 x 160 x 285 mm 2.5 - 3.0 kg (5.4 - 6.7 lbs.)
Battery, Charger NOT INCLUDED.		

DUB185Z	18V LXT Cordless Variable 3-Speed Blower	S.R.P. 3,700.00
	Blowing force Max Sealed Suction No Load Speed (RPM) Run time (min) Net weight	3.1 N 5.8 kPa 0 - 18,000 Using BL1850(B), High / Mid / Low: 21 / 50 / 130 1.6 - 2.1 kg (3.5 - 4.6 lbs.)
Battery, Charger NOT INCLUDED.		

DUB187Z	18V LXT BL XPT Cordless Blower Vacuum	S.R.P. 11,350.00
	Runtime using BL1860B (6.0Ah): 14 min. No load speed (RPM) Max air volume (Vacuum) Max sealed suction Dust bag capacity Max air volume (Blower) Max air velocity (Blower) Dimensions (L x W x H) Net weight	9,000-13,500 6.1 m³/min 3.3 kPa 25 L 4.2 m³/min 64.0 m/s 1,168 x 164 x 416 mm 3.7 - 4.0 kg (8.2 - 8.8 lbs.)
Battery, Charger NOT INCLUDED.		



DUB361Z	430	S.R.P.	10,400.00
	18V X2 (36V) LXT XPT Cordless 2-Speed Blower	Max air volume Max air velocity No Load Speed (RPM) Dimensions (L x W x H) Net weight	High: 4.4 m ³ /min (155 CFM) Low: 2.6 m ³ /min (92 CFM) High: 93 m/s (208 MPH) Low: 57 m/s (128 MPH) High: 17,000 / Low: 10,000 905 x 141 x 194 mm (35-5/8 x 5-5/8 x 7-5/8") 3.1 - 3.2 kg (6.8 - 7.1 lbs.)
			Battery, Charger NOT INCLUDED.

DUB362PT4X	S.R.P.	42,000.00	
	18V X2 (36V) LXT BL XPT Cordless Variable 6-Speed Blower	Max air volume Max air velocity No Load Speed (RPM) Dimensions (L x W x H) Net weight	Runtime using BL1860B (6.0Ah): 13 - 90 min. 13.4 m ³ /min (473 CFM) 54 m/s (120 MPH) 11,400 - 21,500 w/ 3-stage telescopic long nozzle: 830 x 880 x 930 mm (205 x 295 x 32-3/4") 3.5 - 4.2 kg (7.7 - 9.3 lbs.)
			INCLUDE: 4 pcs. 5.0 Ah Battery, 2 Port Charger, Tool Bag.

DUB362Z	S.R.P.	15,700.00	
	18V X2 (36V) LXT BL XPT Cordless Variable 6-Speed Blower	Max air volume Max air velocity No Load Speed (RPM) Dimensions (L x W x H) Net weight	Runtime using BL1860B (6.0Ah): 13 - 90 min. 13.4 m ³ /min (473 CFM) 54 m/s (120 MPH) 11,400 - 21,500 w/ 3-stage telescopic long nozzle: 830 x 880 x 930 mm (205 x 295 x 32-3/4") 3.5 - 4.2 kg (7.7 - 9.3 lbs.)
			INCLUDE: 4 pcs. 4.0 Ah Battery, 2 Port Charger, Tool Bag.

DUB363PT2V	S.R.P.	44,050.00	
	18V X2 (36V) LXT BL XPT Cordless Variable Speed Blower	Max air volume Blowing force No Load Speed (RPM) Dimensions (L x W x H) Net weight	Runtime using BL1860B (6.0Ah): 9.7 - 75 min. 13.4 m ³ /min (473 CFM) 14.4 N 0 - 7,850 1,396 x 604 x 415 mm (55 x 23-3/4 x 16-3/8") 4.5 - 6.6 kg (9.9 - 14.6 lbs.)
			INCLUDE: 2 pcs. 5.0Ah Battery, Dual port charger

DUB363Z	S.R.P.	19,400.00	
	18V X2 (36V) LXT BL XPT Cordless Variable Speed Blower	Max air volume Blowing force No Load Speed (RPM) Dimensions (L x W x H) Net weight	Runtime using BL1860B (6.0Ah): 9.7 - 75 min. 13.4 m ³ /min (473 CFM) 14.4 N 0 - 7,850 1,396 x 604 x 415 mm (55 x 23-3/4 x 16-3/8") 4.5 - 6.6 kg (9.9 - 14.6 lbs.)
			Battery, Charger NOT INCLUDED.

DU101SF	S.R.P.	19,050.00	
	18V LXT BL XPT Cordless 100 mm (4") Pruning Saw	Guide bar length Chain speed Chain oil tank volume Dimensions (L x W x H) Net weight Work amount (BL1830B)	100 mm (4") 8.0 m/s (480 m/min) (1,570 FPM) 55 mL (1.9 USoz) 408 x 90 x 249 mm (16 x 3-1/2 x 9-3/4") 1.6-2.0 kg (3.5-4.4 lbs.) 210 cuts Ø 50 mm cedar rod
			INCLUDE: 1 PC. 3.0 Ah Battery, Standard Charger.

DU101Z	S.R.P.	11,500.00	
	18V LXT BL XPT Cordless 100 mm (4") Pruning Saw	Guide bar length Chain speed Chain oil tank volume Dimensions (L x W x H) Net weight Work amount (BL1830B)	100 mm (4") 8.0 m/s (480 m/min) (1,570 FPM) 55 mL (1.9 USoz) 408 x 90 x 249 mm (16 x 3-1/2 x 9-3/4") 1.6-2.0 kg (3.5-4.4 lbs.) 210 cuts Ø 50 mm cedar rod
			Battery, Charger NOT INCLUDED.

DU150Z	S.R.P.	12,400.00	
	18V LXT BL XPT Cordless 150 mm (6") Pruning Saw	Guide bar length Chain speed Chain oil tank volume Dimensions (L x W x H) Net weight Work amount (BL1830B)	150 mm (6") 8.0 m/s (480 m/min) (1,570 FPM) 55 mL (1.9 USoz) 459 x 90 x 249 mm (18 x 3-1/2 x 9-3/4") 1.7-2.0 kg (3.7-4.4 lbs.) Work amount (BL1830B)
			Battery, Charger NOT INCLUDED.

DU254Z	S.R.P.	15,400.00	
	18V LXT BL XPT Cordless 250 mm (10") Chain Saw	Guide bar length Chain speed Chain oil tank volume Work amount (BL1850B) Dimensions (L x W x H) Net weight	250 mm (10") 0 - 24 m/s (0 - 1,440 m/min) 140 mL (4.7 US oz) 160 cuts (Ø50 mm cedar timber) 482 x 184 x 191 mm (19 x 7-1/4 x 7-1/2") 2.8 - 3.2 kg (6.2 - 6.9 lbs.)
			Battery, Charger NOT INCLUDED.



DU407X2Z	S.R.P.	15,300.00	
	18V LXT BL XPT Cordless 400 mm (16") Chain Saw	Guide bar length Chain oil tank volume Work amount (BL1860B) Dimensions (L x W x H) Net weight	400 mm (16") 150 mL (5.1 US oz) 100 cuts (Ø100 mm x Ø100 mm square cedar timber) 796 x 214 x 234 mm (31-1/4 x 8-3/8 x 9-1/4") 4.2 - 4.4 kg (9.3 - 9.7 lbs.)
			Battery, Charger NOT INCLUDED.







DUH523Z	S.R.P.	8,850.00	
	18V LXT BL XPT Cordless 520 mm (20-1/2") Hedge Trimmer	Blade Length Max Cutting Capacity Continuous Runtime (min) Strokes Per Minute (SPM) Dimensions (L x W x H) Net weight	520 mm (20-1/2") 15 mm (9/16) w/ BL1850B: 125 2,700 938 x 195 x 193 mm (37 x 7-5/8 x 7-5/8") 3 - 3.4 kg (6.7 - 7.5 lbs.)
			Battery, Charger NOT INCLUDED.







DUH604SZ	S.R.P.	28,100.00	
	18V LXT BL XPT Cordless 600 mm (23-5/8") Hedge Trimmer	Max Cutting Capacity Blade length Strokes Per Minute (SPM) Continuous Use (min.) Dimensions (L x W x H) Net weight	18 mm (11/16") 600 mm (23-5/8") 3 / 2 / 1: 4,400 / 3,600 / 2,000 Using BL1860B 3 / 2 / 1: 70 / 90 / 200 1,061 x 282 x 143 mm (41-3/4 x 11-1/8 x 5-5/8") 3.4 - 3.9 kg (7.5 - 8.6 lbs.)
			Battery, Charger NOT INCLUDED.







DUH606RF	S.R.P.	18,600.00	
	18V LXT BL XPT Cordless 600 mm (23-5/8") Hedge Trimmer	Max Cutting Capacity Blade length Strokes Per Minute (SPM) Continuous Use (min.) Dimensions (L x W x H) Net weight	20.0 mm (13/16") 600 mm (23-5/8") 4,000 Using BL1860B: 70 1,016 x 207 x 185 mm (40 x 8-1/8 x 7-1/4") 2.7 - 3.0 kg (6.0 - 6.6 lbs.)
			INCLUDE: 1 PC. 3.0 Ah Battery, Charger.







DUH607Z	S.R.P.	9,700.00	
	18V LXT BL XPT Cordless 600 mm (23-5/8") Hedge Trimmer	Max Cutting Capacity Blade length Strokes Per Minute (SPM) Continuous Use (min.) Dimensions (L x W x H) Net weight	15 mm (9/16") 600 mm (23-5/8") 2,700 Using BL1830B: 60 1,029 x 209 x 188 mm (40-1/2 x 8-1/4 x 7-3/8") 2.8 - 3.1 kg (6.2 - 6.8 lbs.)
			Battery, Charger NOT INCLUDED.















DUH651RF2 442 mm	S.R.P. 30,350.00
	18V X2 (36V) LXT XPT Cordless 600 mm Hedge Trimmer
Max Cutting Capacity 15 mm (9/16") Blade length 600 mm (23-5/8") Strokes Per Minute (SPM) 2,700 Continuous Use (min.) Using BL1830B: 60 Dimensions (L x W x H) 1,029 x 209 x 188 mm (40-1/2 x 8-1/4 x 7-3/8") Net weight 2.8 - 3.1 kg (6.2 - 6.8 lbs.)	INCLUDE: 2 pcs. 3.0 Ah Battery, Charger.
    	







DUH651Z 442 mm	S.R.P. 19,200.00
	18V X2 (36V) LXT XPT Cordless 600 mm Hedge Trimmer
Max Cutting Capacity 15 mm (9/16") Blade length 600 mm (23-5/8") Strokes Per Minute (SPM) 2,700 Continuous Use (min.) Using BL1830B: 60 Dimensions (L x W x H) 1,029 x 209 x 188 mm (40-1/2 x 8-1/4 x 7-3/8") Net weight 2.8 - 3.1 kg (6.2 - 6.8 lbs.)	Battery, Charger NOT INCLUDED..
    	







DUH754SZ	S.R.P. 29,350.00
	18V LXT BL XPT Cordless 750 mm Hedge Trimmer
Max Cutting Capacity 18 mm (11/16") Blade length 750 mm (29-1/2") Strokes Per Minute (SPM) 3 / 2 / 1: 4,400 / 3,600 / 2,000 Continuous Use (min.) Using BL1860B 3 / 2 / 1: 65 / 80 / 190 Dimensions (L x W x H) 1,200 x 282 x 143 mm (47-1/4 x 11-1/8 x 5-5/8") Net weight 3.4 - 3.9 kg (7.5 - 8.6 lbs.)	Battery, Charger NOT INCLUDED..
    	

DUM604Z	S.R.P. 6,100.00
	18V LXT Li-Ion Cordless 16 cm (6-5/16") Grass Shear
Cutting Width 160 mm (6-5/16") Depth adjustment 15 / 20 / 25 mm (9/16 / 13/16 / 1") Strokes Per Minute (SPM) 2,500 Continuous Use (min.) Using BL1860B: 250 Dimensions (L x W x H) 337 x 177 x 131 mm (13-1/4 x 7 x 5-1/8") Net weight 1.4 - 1.8 kg (3.2 - 3.9 lbs.)	Battery, Charger NOT INCLUDED..
    	







DUN461WZ	S.R.P. 10,100.00
	18V LXT XPT Cordless 460 mm Pole Hedge Trimmer
Blade length 460 mm (18-1/8") Max Cutting Capacity 18 mm (11/16") Strokes Per Minute (SPM) 3,600 Continuous Use (min.) Using BL1850B: 122 Dimensions (L x W x H) 1,889 - 2,511 x 87 x 134 mm (74-1/2 - 99 x 3-7/16 x 5-1/4") Net weight 3.0 - 3.3 kg (6.6 - 7.3 lbs.)	Battery, Charger NOT INCLUDED.
    	







DUN500WZ	S.R.P. 26,850.00
	18V LXT BL XPT Cordless 500 mm Pole Hedge Trimmer
Max Cutting Capacity 23.5 mm (15/16") Blade length 500 mm (19-3/4") Strokes Per Minute (SPM) High / Mid / Low: 4,400 / 3,600 / 2,000 Cycles per minute (CPM) High / Mid / Low: 2,200 / 1,800 / 1,000 Continuous Use (min.) w/ BL1860B High / Mid / Low: 60 / 90 / 190 Dimensions (L x W x H) 2,115 x 97 x 137 mm (83-1/4 x 3-13/16 x 5-3/8") Net weight 3.9 - 4.3 kg (8.6 - 9.5 lbs.)	Battery, Charger NOT INCLUDED.
    	







DUN600LZ	S.R.P. 21,000.00
	18V LXT BL XPT Cordless 600 mm Pole Hedge Trimmer
Max Cutting Capacity 23.5 mm (15/16") Blade length 600 mm (23-5/8") Strokes Per Minute (SPM) High / Mid / Low: 4,400 / 3,600 / 2,000 Cycles per minute (CPM) High / Mid / Low: 2,200 / 1,800 / 1,000 Continuous Use (min.) w/ BL1860B High / Mid / Low: 55 / 80 / 180 Dimensions (L x W x H) 2,050 x 230 x 178 mm (80-1/2 x 9 x 7") Net weight 3.7 - 4.1 kg (8.2 - 9.0 lbs.)	Battery, Charger NOT INCLUDED.
    	







DUP361ZN	S.R.P. 75,600.00
	18V X2 (36V) LXT XPT Battery Powered Pruning Shears
Capacity Max cutting: 33 mm Max blade opening: 54 mm Dimensions (L x W x H) 305 x 43 x 106 mm (12 x 1-11/16 x 4-3/16") Net weight 0.8 kg (1.8 lbs.)	Battery, Charger NOT INCLUDED.
    	







DUR181Z	S.R.P. 6,200.00
	18V LXT Li-Ion Cordless String Trimmer, Loop Handle
Cutting Width Trimmer head: 260 mm (10-1/4") No Load Speed (RPM) 7,800 Max run time (min) w/ BL1830B: 45 Dimensions (L x W x H) 1,229 - 1,433 x 267 x 186 - 257 mm (48-1/2 - 56-1/2 x 10-1/2 x 7-3/8 - 10-1/8") Net weight 2.8 - 3.1 kg (6.2 - 6.9 lbs.)	Battery, Charger NOT INCLUDED.
    	


DUR187UZ	S.R.P. 12,200.00
	18V LXT BL ADT XPT Cordless Grass Trimmer, Bike Handle
Cutting Width Nylon Cutting Head: 300 mm (11-3/4") No Load Speed (RPM) High / Medium / Low: 6,000 / 5,000 / 4,000 Spindle Size M8 x 1.25 LH Max run time (min) Nylon Cutting Head, BL1860B: Mode: 3 / 2 / 1: 66 / 100 / 168 Dimensions (L x W x H) 1,791x600x472 mm (70-1/2"x23-5/8"x18-5/8") Net weight 3.2 - 3.5 kg (7.0 - 7.6 lbs.)	Battery, Charger NOT INCLUDED.
    	

DUR190LZX3	S.R.P. 14,000.00
	18V LXT BL ADT AFT Cordless 3-Speed Grass Trimmer, Loop Handle
Cutting Width Metal blade: 230 mm (9") Nylon Cutting Head: 300 mm (11-3/4") No Load Speed (RPM) 3,500 - 6,000 Max run time (min) Nylon Head: 3 / 2 / 1: 66 / 89 / 210 using BL1860B Metal blade: 3 / 2 / 1: 81 / 113 / 243 Dimensions (L x W x H) 1,791x600x472 mm (70-1/2"x23-5/8"x18-5/8") Net weight 3.2 - 3.5 kg (7.0 - 7.6 lbs.)	Battery, Charger NOT INCLUDED..
    	

DUR191URT3	S.R.P. 28,500.00
	18V LXT BL ADT AFT XPT Cordless 3-Speed Grass Trimmer, Split Shaft, Bike Handle
Cutting Width Metal blade: 230 mm (9") Nylon Cutting Head: 300 mm (11-3/4") No Load Speed (RPM) 3,500 - 6,000 Max run time (min) Nylon Head: 3 / 2 / 1: 66 / 89 / 210 using BL1860B Metal blade: 3 / 2 / 1: 81 / 113 / 243 Dimensions (L x W x H) 1,791x600x472 mm (70-1/2"x23-5/8"x18-5/8") Net weight 3.4 - 3.7 kg (7.5 - 8.2 lbs.)	INCLUDE: 2 pcs. 5.0 Ah Battery, Charger, 3T Metal blade, Nut 10, Cup.
    	

DUR191UZX3	S.R.P. 15,450.00
	18V LXT BL ADT AFT XPT Cordless 3-Speed Grass Trimmer, Split Shaft, Bike Handle
Cutting Width Metal blade: 230 mm (9") Nylon Cutting Head: 300 mm (11-3/4") No Load Speed (RPM) 3,500 - 6,000 Max run time (min) Nylon Head: 3 / 2 / 1: 66 / 89 / 210 using BL1860B Metal blade: 3 / 2 / 1: 81 / 113 / 243 Dimensions (L x W x H) 1,791x600x472 mm (70-1/2"x23-5/8"x18-5/8") Net weight 3.4 - 3.7 kg (7.5 - 8.2 lbs.)	Battery, Charger NOT INCLUDED..
    	

DUR192LZ	S.R.P. 8,950.00
	18V LXT BL XPT Cordless 2-Speed Grass Trimmer, Loop Handle
Cutting Width Nylon Cutting Head: 300 mm (11-3/4") No Load Speed (RPM) High / Low: 0 - 4,500 / 0 - 6,000 Spindle size M10 x 1.25 LH Max run time w/ load (min) using BL1850B: Nylon head: Hi / Lo: 18 / 34 Dimensions (L x W x H) 1,670 x 186 x 246 mm (65-3/4 x 7-3/8 x 9-11/16") Net weight 2.7 - 3.0 kg (6.0 - 6.6 lbs.)	Battery, Charger NOT INCLUDED.
    	



DUR193Z		S.R.P.	6,750.00
	18V LXT XPT Cordless Grass Trimmer, Loop Handle		
MC	Cutting Width Nylon Head: 260 mm (10-1/4") No Load Speed (RPM) 7,800 Work amount w/ load using BL1830B: 25 min Net weight 2.3 - 2.6 kg (5.1 - 5.7 lbs.)		
	Battery, Charger NOT INCLUDED.		

DUR194ZX1		S.R.P.	9,800.00
	18V LXT XPT Cordless 2-Speed Grass Trimmer, Loop Handle		
MC	Cutting Width Metal blade: 200 mm (7-7/8") Nylon Cutting Head: 280 mm (11") No Load Speed (RPM) High / Low: 6,000 / 4,500 Spindle size M10 x 1.25 LH Runtime using BL1860B (No Load) Nylon head: Hi / Lo: 65 / 90 Metal blade: Hi / Lo: 105 / 185 Dimensions (L x W x H) 1,630 x 288 x 236 mm (64 x 11-3/8 x 9-1/4") Net weight 2.6 - 2.9 kg (5.7 - 6.4 lbs.)		
	Battery, Charger NOT INCLUDED.		

DUR361URF2		S.R.P.	39,150.00
	18V X2 (36V) LXT BL ADT AFT XPT Cordless 2-Speed Grass Trimmer, Bike Handle		
MC	Cutting Width Metal Blade: 230 mm (9") No Load Speed (RPM) 3,500 - 7,300 Spindle Size M8 x 1.25 LH Runtime using BL1860B (No Load) Nylon head: Hi / Lo: 75 / 150 min Metal blade: Hi / Lo: 180 / 360 min Dimensions (L x W x H) 1,816x600x458 mm (71-1/2"x23-5/8"x18") Net weight 5.1 - 5.8 kg (11.3 - 12.7 lbs)		
	INCLUDE: 2 pcs. 6.0 Ah Battery, Charger.		

DUR361UZ		S.R.P.	28,400.00
	18V X2 (36V) LXT BL ADT AFT XPT Cordless 2-Speed Grass Trimmer, Bike Handle		
MC	Cutting Width Metal Blade: 230 mm (9") No Load Speed (RPM) 3,500 - 7,300 Spindle Size M8 x 1.25 LH Runtime using BL1860B (No Load) Nylon head: Hi / Lo: 75 / 150 min Metal blade: Hi / Lo: 180 / 360 min Dimensions (L x W x H) 1,816x600x458 mm (71-1/2"x23-5/8"x18") Net weight 5.1 - 5.8 kg (11.3 - 12.7 lbs)		
	Battery, Charger NOT INCLUDED.		

DUX18Z		S.R.P.	10,450.00
	18V LXT BL AFT XPT Cordless Multi Function Power Head		
MC	No Load Speed (RPM) High: 0 - 9,700 / Low: 0 - 6,800 Max. output 0.47 kW Runtime using BL1860B EN401MP (Hedge Trimmer): Hi: 43 min EN408MP (Grass Trimmer): Hi: 25 min Nylon Hi: 41 min Metal EM407MP (Rotary Scissor): Hi: 20 min UB401MP (Blower): Hi: 10 min 983 x 318 x 175 mm Net weight 2.8 - 10.3 kg (6.2 - 22.7 lbs.)		
	Battery, Charger, Attachments NOT INCLUDED.		

DUX18ZX1		S.R.P.	14,950.00
	18V LXT BL AFT XPT Cordless Multi Function Power Head		
MC	No Load Speed (RPM) High: 0 - 9,700 / Low: 0 - 6,800 Max. output 0.47 kW Runtime using BL1860B EN401MP (Hedge Trimmer): Hi: 43 min EN408MP (Grass Trimmer): Hi: 25 min Nylon Hi: 41 min Metal EM407MP (Rotary Scissor): Hi: 20 min UB401MP (Blower): Hi: 10 min 983 x 318 x 175 mm Net weight 2.8 - 10.3 kg (6.2 - 22.7 lbs.)		
	INCLUDE: EM408MP Battery, Charger, NOT INCLUDED.		

DUX60Z		S.R.P.	16,050.00
	18V LXT BL AFT XPT Cordless Multi Function Power Head		
MC	No Load Speed (RPM) Hi: 0 - 9,700 / Med: 0 - 8,200 / Lo: 0 - 5,700 Max. output 0.6 kW Runtime using BL1860B EN401MP (Hedge Trimmer): Hi: 55 min EN408MP (Grass Trimmer): Hi: 40 min Nylon Hi: 58 min Metal EM407MP (Rotary Scissor): Hi: 26 min UB401MP (Blower): Hi: 14 min 1,011 x 320 x 216 mm Net weight 4.1 - 8.7 kg (8.9 - 19.2 lbs.)		
	Battery, Charger, Attachments NOT INCLUDED.		

DVC261Z		S.R.P.	17,050.00
	18V X2 (36V) LXT BL XPT Cordless HEPA Backpack Vacuum Cleaner		
MC	Capacity Paper Dust Bag: 2.0 L Cloth Dust Bag: 1.5 L w/ BL1860B x2: 1 / 2 / 3: 140 / 75 / 40 Continuous Use (min.) 1.8 m³/min Max air flow 11 kPa Max sealed suction 11 kPa Dimensions (L x W x H) 230 x 152 x 373 mm Net weight 3.9 - 4.5 kg (8.6 - 10.0 lbs.)		
	Battery, Charger NOT INCLUDED.		

DVC265ZX		S.R.P.	20,450.00
	18V X2 (36V) LXT BL AWS Cordless HEPA Backpack Vacuum Cleaner (For Dust Collection)		
MC	Capacity Filter bag: 1.5 L / Paper dust bag: 2.0L Cloth Dust Bag: 5.5 L w/ BL1860B x2: Hi: 40 / Lo: 75 Continuous Use (min.) 1.8 m³/min Max air flow 11 kPa Max sealed suction 11 kPa Dimensions (L x W x H) 230x152x373mm (9"x6"x14-3/4") Net weight 3.8 - 4.3 kg		
	Wireless unit, Battery, Charger NOT INCLUDED.		




DVC560Z		S.R.P.	26,950.00
	18V X2 (36V) LXT BL Cordless 5 L HEPA Upright Cleaner		
MC	Capacity Dust: 5 L w/ BL1860B x2 Max / Normal / Low Noise: 30 / 60 / 120 Continuous Use (min.) 1.9 m³/min Max Air Flow 1.9 m³/min Max Sealed Suction 12 kPa Dimensions (L x W x H) 326 x 318 x 1,146 mm Net weight 8.3 - 9.0 kg (18.3 - 19.8 lbs.)		
	Battery, Charger NOT INCLUDED.		

DVC660Z		S.R.P.	18,850.00
	18V X2 (36V) LXT BL Cordless HEPA Backpack Vacuum Cleaner		
MC	Capacity Paper Dust Bag: 6.0 L / Cloth Dust Bag: 5.5 L w/ BL1860B x2: 1 / 2 / 3: 140 / 75 / 40 Continuous Use (min.) 1.5 m³/min Max air flow 11 kPa Max sealed suction 11 kPa Dimensions (L x W x H) 297 x 174 x 523 mm Net weight 6.1 - 6.7 kg (13.4 - 14.8 lbs.)		
	Battery, Charger NOT INCLUDED.		

DVC750LZ		S.R.P.	11,450.00
	18V LXT BL XPT Cordless 7.5 L Dust Class L HEPA Portable 2-Speed Vacuum Cleaner (Wet & Dry)		
MC	Capacity Dust / Water: 7.5 / 4.5 L w/ BL1850B (High): 30 / (Normal): 60 Continuous Use (min.) High / Normal: 1.6 / 1.3 m³/min Max Air Flow High / Normal: 6.7 / 4.2 kPa Max Sealed Suction 418 x 251 x 278 mm (16-1/2" x 9-7/8" x 11") Dimensions (L x W x H) 4.3 - 4.6 kg (9.4 - 10.1 lbs.)		
	Battery, Charger NOT INCLUDED.		

DVC860LZ		S.R.P.	34,300.00
	Corded / 18V X2 (36V) LXT Cordless 8 L Dust Class L Vacuum Cleaner (Wet & Dry)		
MC	Capacity Dust / Water: 8 / 6 L w/ BL1850B x2: Dial 1: 65 / Dial 5: 30 Continuous Use (min.) AC / DC: 3.6 / 2.1 m³/min Max Air Flow AC / DC: 24 / 9 kPa Max Sealed Suction 366 x 334 x 368 mm Dimensions (L x W x H) 8.6 - 9.2 kg (19 - 20.3 lbs.)		
	Battery, Charger NOT INCLUDED.		

DVC864LZ		S.R.P.	29,900.00
	18V X2 (36V) LXT BL AWS XPT Cordless 8 L Dust Class L HEPA Vacuum Cleaner Dry only (For Dust Extraction)		
MC	Capacity Dust: 8 L w/ BL1850B x2: 40 Continuous Use (min.) 2.1 m³/min Max air flow 9.8 kPa Max sealed suction 366x334x368 mm Dimensions (L x W x H) 7.7 - 8.4 kg (17.1-18.4 lbs.)		
	With Built-in Wireless Unit. Battery, Charger NOT INCLUDED.		



DVF154Z S.R.P. 25,150.00

LXT 18V LXT Li-Ion Cordless 15 L Garden Sprayer

Max Pressure 0.3 MPa (3 kgf/cm²)
 Chemical tank 15 L
 Dimensions (L x W x H) 345x235x525 mm (13-5/8"x9-1/4"x20-3/4")
 Net weight 4.1 - 4.4 kg (9.1 - 9.7 lbs)

2.5 Years Limited Warranty

MJ Battery, Charger NOT INCLUDED.

DWR180Z S.R.P. 9,050.00

LXT 18V LXT Li-Ion Cordless 47.5 N·m (420 in.lbs.) Ratchet Wrench

Capacity Standard bolt: M5 - M12 (3/16 - 1/2")
 High strength bolt: M5 - M10 (3/16 - 3/8")
 9.5 / 6.35 mm (3/8 / 1/4")
 Square drive 0 - 800
 No Load Speed (RPM) 47.5 N·m (420 in.lbs.)
 Max fastening torque 13 mm (1/2")
 Flats width Diameter: 31 mm (1-7/32")
 Angle head size Height: 25.5 mm (1")
 1.2 - 1.6 kg (2.6 - 3.5 lbs.)

2.5 Years Limited Warranty

MC Battery, Charger NOT INCLUDED.

EA3503S40B S.R.P. 17,550.00

2.5 2 Stroke 400mm (16") Petrol Chain Saw

Guide bar length 400mm (16")
 Chain blade Pitch / Gauge : 3/8" / 1.1mm (.043") / 1.3mm (.050")
 Displacement 35.0mL
 Engine power 1.7kW / 2.4PS
 Fuel tank 0.4L
 Chain oil tank 0.29L
 Dimensions (L x W x H) 415x269x273mm (16-3/8"x10-5/8"x10-3/4")
 Power head weight 4.5kg (9.9lbs)

1.5 Years Limited Warranty

MC

EB7660TH S.R.P. 32,150.00

MM4 4 Stroke 75.6ml • 3.0 kW (4.1 PS) Petrol Blower

Displacement 75.6 mL
 Power Rating 3.0 kW (4.1 PS)
 Max Air Volume 20 m³/min (706 CFM)
 Max Air Velocity 92 m/s (205 MPH)
 Fuel Tank Capacity 1.9 L (64 oz.)
 No Load Speed (RPM) 2,800 - 7,200
 Max Torque 4.7 N·m
 Dimensions (L x W x H) 332x460x480 mm
 Net weight 11.9 - 12.1 kg (26.2 - 26.7 lbs.)

1.5 Years Limited Warranty

MC

EBH340U S.R.P. 22,200.00

MM4 4 Stroke 33.5mL • 1.07 kW • 1.7 PS Petrol Brushcutter

Displacement 33.5mL
 Engine power 1.07kW / 1.5PS
 Fuel tank 0.65L
 Spindle size M10 x 1.25LH
 Dimensions 1,900x645x510mm (L x W x H) (74-3/4"x25-3/8"x20")
 Net weight 7.5kg (16.5lbs)

1.5 Years Limited Warranty

MC

EK7651HX1 S.R.P. 75,500.00

MM4 4 Stroke 75.6 mL • 3.0 kW • 4.1 PS Petrol Power Cutter

Wheel diameter 355mm (14")
 Engine 75.6mL
 Max. cutting depth 122mm (4-13/16")
 No load speed (rpm) 4,300
 Circumferential speed 80m/s
 Engine power 3.0kW / 4.1PS
 Fuel tank 1.0L
 Dimension (LxWxH) 780x310x455mm
 Net weight 12.4kg (27.2lbs)

1.5 Years Limited Warranty

MC

EM3400U S.R.P. 15,100.00

2.5 2 Stroke 24.5 mL • 0.73 kW • 1.0 PS Petrol Power Cutter

Displacement 34.0mL
 Engine power 1.15kW / 1.6PS
 Fuel mixture 50 : 1
 Fuel tank 0.75L
 Spindle size M10 x 1.25LH
 Dimensions 1,815x650x435mm (L x W x H) (71-1/2"x25-1/2"x17-1/8")
 Net weight 6.4kg (14.1lbs)

1.5 Years Limited Warranty

MC

EW120R S.R.P. 26,650.00

MM4 4 Stroke 33.5mL • 1.07 kW • 1.7 PS Petrol Brushcutter

Displacement 24.5 mL
 Engine power 1.07 kW / 1.5 PS
 Fuel tank 0.5 L
 Suction & Discharge Ø 25.4 mm (1")
 Max Pumping Capacity 130 L/min (34 gal/min)
 Total Head 35 m (115 ft)
 Dimensions (L x W x H) 333 x 213 x 319 mm
 Net weight 5.3 kg (11.7 lbs.)

1.5 Years Limited Warranty

MJ

FS2700 S.R.P. 7,900.00

419 570 W 0-2,500 RPM 6 Stage Adjustable Torque Screwdriver with LED Light

Continuous rating Input 570W
 Capacity Self-drilling screw: 6 mm (1/4")
 Machine screw: 8 mm (5/16")
 Wood screw: 6.2 mm (1/4")
 Driving shank (Hex) 6.35 mm (1/4")
 No Load Speed (RPM) 0 - 2,500
 Dimensions (L x W x H) 301 x 70 x 207 mm
 Net weight 1.8 kg (4 lbs.)

2.5 Years Limited Warranty

MC

FS4000 S.R.P. 6,000.00

419 570 W 0-4,000 RPM Drywall Screwdriver

Continuous rating Input 570W
 Capacity Drywall screw: 5 mm (3/16")
 Self-drilling screw: 6 mm (1/4")
 6.35 mm (1/4")
 Driving shank (Hex) 6.35 mm (1/4")
 No Load Speed (RPM) 0 - 4,000
 Dimensions (L x W x H) 269 x 65 x 207 mm (10-5/8 x 2-9/16 x 8-1/8")
 Net weight 1.3 kg (2.9 lbs.)

2.5 Years Limited Warranty

MC

GA4040C S.R.P. 9,650.00

325 100 mm (4") 1,400 W SJS II Variable Speed Angle Grinder, Anti-Restart Function, Soft Start, Slide Switch

Continuous rating Input 1,400W
 Wheel Diameter 100 mm (4")
 Hole Diameter 16 mm (5/8")
 No Load Speed (RPM) 2,800 - 11,000
 Dimensions (L x W x H) 303 x 117 x 111 mm (11-7/8 x 4-5/8 x 4-3/8")
 Net weight 2.3 - 2.6 kg (5.1 - 5.7 lbs.)

2.5 Years Limited Warranty

MC

GA5020 S.R.P. 6,800.00

303 125 mm (5") 1,050 W SJS Angle Grinder, Finger Trigger Switch

Continuous rating Input 1,050W
 Wheel Diameter 125 mm (5")
 Hole Diameter 22.23 mm (7/8")
 No Load Speed (RPM) 12,000
 Dimensions (L x W x H) 356 x 139 x 120 mm (14 x 5-1/2 x 4-3/4")
 Net weight 2.7 - 3.9 kg (6 - 8.6 lbs.)

2.5 Years Limited Warranty

MC

GA5080 S.R.P. 14,550.00

325 125 mm (5") 1,400 W X-LOCK Angle Grinder, Soft Start, Slide Switch, X-LOCK

Continuous rating Input 1,400W
 Wheel Diameter 125 mm (5")
 Hole Diameter 22.23 mm (7/8")
 Max cutting depth 31 mm (1-1/4")
 No Load Speed (RPM) 12,000
 Dimensions (L x W x H) 309 x 141 x 113 mm (12-1/8 x 5-9/16 x 4-7/16")
 Net weight 2.5 - 3.6 kg (5.5 - 7.9 lbs.)

2.5 Years Limited Warranty

MC




GA5080R S.R.P. 14,850.00















325 125 mm (5") 1,400 W Angle Grinder, 18,000.00 Soft Start, Anti-Restart, Slide Switch, X-LOCK

Continuous rating Input 1,400W
 Wheel Diameter 125 mm (5")
 Hole Diameter 22.23 mm (7/8")
 Max cutting depth 31 mm (1-1/4")
 No Load Speed (RPM) 12,000
 Dimensions (L x W x H) 309 x 141 x 113 mm (12-1/8 x 5-9/16 x 4-7/16")
 Net weight 2.5 - 3.6 kg (5.5 - 7.9 lbs.)

2.5 Years Limited Warranty

MC



 <p>GA6020 303 WV</p> <p>150 mm (6") 1,050 W SJS Angle Grinder, Finger Trigger Switch</p> <p>Continuous rating Input 1,050W Wheel Diameter 150 mm (6") Hole Diameter 22.23 mm (7/8") No Load Speed (RPM) 10,000 Dimensions (L x W x H) 356 x 169 x 120 mm (14 x 6-5/8 x 4-3/4")</p> <p>Net weight 2.8 - 3.2 kg (6.1 - 7.1 lbs.)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 5,950.00</p>	 <p>GA7020 204 WV</p> <p>180 mm (7") 2,200 W Angle Grinder, Large Trigger Switch</p> <p>Continuous rating Input 2,200W Wheel Diameter 180 mm (7") Hole Diameter 22.23 mm (7/8") No Load Speed (RPM) 8,500 473 x 200 x 140 mm (18-5/8 x 7-7/8 x 5-1/2")</p> <p>Dimensions (L x W x H) 473 x 200 x 140 mm (18-5/8 x 7-7/8 x 5-1/2") Net weight 5.56 - 6.06 kg (12.26 - 13.36 lbs.)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 8,800.00</p>
 <p>GA9020 204 WV</p> <p>230 mm (9") 2,200 W Angle Grinder, Large Trigger Switch</p> <p>Continuous rating Input 2,200W Wheel Diameter 230 mm (9") Hole Diameter 22.23 mm (7/8") No Load Speed (RPM) 6,600 473 x 200 x 140 mm (18-5/8 x 7-7/8 x 5-1/2")</p> <p>Dimensions (L x W x H) 473 x 200 x 140 mm (18-5/8 x 7-7/8 x 5-1/2") Net weight 5.76 - 8.05 kg (12.7 - 17.8 lbs.)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 7,300.00</p>	 <p>GB602W</p> <p>150 mm (6") 250 W Bench Grinder</p> <p>Continuous rating Input 250W Wheel Diameter 150 mm (6") Wheel width 6.4 mm (1/4") / 16 mm (5/8") Hole Diameter 12.7 mm (1/2") H.P. 1/3 No Load Speed (RPM) 2,850 (50 Hz) / 3,450 (60 Hz) 375 x 348 x 286 mm (14-9/64 x 13-45/64 x 11-17/64")</p> <p>Dimensions (L x W x H) 375 x 348 x 286 mm (14-9/64 x 13-45/64 x 11-17/64") Net weight 9.27 - 8.93 kg (19.69 - 20.44 lbs.)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 8,200.00</p>
 <p>GB801</p> <p>205 mm (8") 550 W Bench Grinder</p> <p>Continuous rating Input 550W Wheel Diameter 205 mm (8") Wheel width 19 mm (3/4") Hole Diameter 15.88 mm (5/8") H.P. 3/4 No Load Speed (RPM) 2,850 (50 Hz) / 3,450 (60 Hz) 395 x 265 x 333 mm (15-9/16 x 10-7/16 x 13-7/64")</p> <p>Dimensions (L x W x H) 395 x 265 x 333 mm (15-9/16 x 10-7/16 x 13-7/64") Net weight 19.91 - 19.63 kg</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 17,250.00</p>	 <p>GD0601 325 WV</p> <p>1/4" 400 W Die Grinder</p> <p>Continuous rating Input 400W Collet size 3 / 6 mm (1/8 / 1/4") Wheel Diameter 38 mm (1-1/2") No Load Speed (RPM) 25,000 359 x 82 x 82 mm (14-1/8 x 3-1/4 x 3-1/4")</p> <p>Dimensions (L x W x H) 359 x 82 x 82 mm (14-1/8 x 3-1/4 x 3-1/4") Net weight 1.68 - 1.84 kg (3.7 - 4.06 lbs.)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 5,250.00</p>
 <p>GD0603 64 WV</p> <p>1/4" 240 W Die Grinder</p> <p>Continuous rating Input 240W Collet size 1/4" Wheel Diameter 23 mm No Load Speed (RPM) 28,000 Diameter of grip 65 mm 289 x 64 x 67 mm (11-3/8 x 2-1/2 x 2-5/8")</p> <p>Dimensions (L x W x H) 289 x 64 x 67 mm (11-3/8 x 2-1/2 x 2-5/8") Net weight 0.98 kg (2.16 lbs.)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 4,900.00</p>	 <p>GS5000 204 WV</p> <p>125 mm (5") 750 W Straight Grinder</p> <p>Continuous rating Input 750W Wheel Diameter 125 mm (5") Hole Diameter 12.7, 20 mm (1/2, 3/4") No Load Speed (RPM) 5,600 590 x 189 x 116 mm (23-1/4 x 7-7/16 x 4-9/16")</p> <p>Dimensions (L x W x H) 590 x 189 x 116 mm (23-1/4 x 7-7/16 x 4-9/16") Net weight 5 - 5.2 kg (11 - 11.5 lbs.)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 16,300.00</p>
 <p>HG5030</p> <p>1,600 W Heat Gun</p> <p>Continuous rating Input 1,600W Air Temperature (°C) Stage 1: 350 / 300 Stage 2: 500 / 500 233 x 80 x 208 mm (9-1/8 x 3-1/8 x 8-3/16")</p> <p>Dimensions (L x W x H) 233 x 80 x 208 mm (9-1/8 x 3-1/8 x 8-3/16") Net weight 0.56 kg (1.2 lbs.) Power supply cord 2.0 m (6.6 ft)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 2,950.00</p>	 <p>HG5030K</p> <p>1,600 W Heat Gun</p> <p>Continuous rating Input 1,600W Air Temperature (°C) Stage 1: 350 / 300 Stage 2: 500 / 500 233 x 80 x 208 mm (9-1/8 x 3-1/8 x 8-3/16")</p> <p>Dimensions (L x W x H) 233 x 80 x 208 mm (9-1/8 x 3-1/8 x 8-3/16") Net weight 0.56 kg (1.2 lbs.) Power supply cord 2.0 m (6.6 ft)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 3,100.00</p>
 <p>HG6530VK</p> <p>2,000 W Heat Gun</p> <p>Continuous rating Input 2,000W Air Temperature (°C) 50 - 650 Air flow Stage 1: 500 L/min Stage 2: 280 L/min Stage 3: 550 L/min 257 x 85 x 206 mm (10-1/8 x 3-3/8 x 8-1/8")</p> <p>Dimensions (L x W x H) 257 x 85 x 206 mm (10-1/8 x 3-3/8 x 8-1/8") Net weight 0.72 kg (1.6 lbs.) Power supply cord 2.0 m (6.6 ft)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 6,500.00</p>	 <p>HM0810TA 105 WV</p> <p>7.2 J Demolition Hammer, Sliding Chuck, 17 mm Hex Shank</p> <p>Continuous rating Input 900W Impact energy EPTA-Procedure 05/2009: 7.2 J Blows per minute (BPM) 2,900 Net weight 6.3 kg (13.9 lbs.) Power supply cord 5.0 m (16.4 ft)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 19,750.00</p>
 <p>HM0871CSET 350 WV</p> <p>8.1 J AVT SOFT NO LOAD Demolition Hammer, SDS-MAX</p> <p>Continuous rating Input 1,100W Impact energy EPTA-Procedure 05/2009: 8.1 J Blows per minute (BPM) 1,100 - 2,650 466 x 116 x 230 mm (18-3/8 x 4-9/16 x 9")</p> <p>Dimensions (L x W x H) 466 x 116 x 230 mm (18-3/8 x 4-9/16 x 9") Net weight 5.6 - 5.8 kg (12.4 - 12.8 lbs.) Power supply cord 5.0 m (16.4 ft)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 27,500.00</p>	 <p>HM1111C 175 WV</p> <p>11.2 J AVT SOFT NO LOAD Demolition Hammer, SDS-MAX</p> <p>Continuous rating Input 1,300W Impact energy EPTA-Procedure 05/2009: 11.2 J Blows per minute (BPM) 1,100 - 2,650 528 x 126 x 247 mm (20-3/4 x 5 x 9-3/4")</p> <p>Dimensions (L x W x H) 528 x 126 x 247 mm (20-3/4 x 5 x 9-3/4") Net weight 7.8 - 8 kg (17.3 - 17.6 lbs.) Power supply cord 4.0 m (13.1 ft)</p> <p>2.5 Years Limited Warranty</p>	<p>S.R.P. 40,350.00</p>



Double Insulation



Electronic 2-Speed



17mm Hex Shank



Soft Start



Built-in Job Light



Variable Speed



Electronic 3-Speed



SDS-MAX Shank



Constant Speed



Dust Collection



21mm Hex Shank



Carrying Case

HM1201 155 MJ	(13.0 J: Makita Standard) Demolition Hammer, 21 mm Hex Shank	S.R.P.	37,900.00
	Continuous rating Input Blows per minute (BPM) Net weight Power supply cord	1,130W 2,000 9.1 kg (20.1 lbs.) 5.0 m (16.4 ft)	

HM1213C 175 MJ	18.6 J AVT SOFT NO LOAD Demolition Hammer, SDS-MAX	S.R.P.	33,250.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	1,510W EPTA-Procedure 05/2009: 18.6 J 950 - 1,900 576 x 149 x 265 mm (22-3/4 x 5-7/8 x 10-3/8") 10.8 kg (23.7 lbs.) 5.0 m (16.4 ft)	

HM1214C 175 MJ	19.9 J AVT SOFT NO LOAD Demolition Hammer, SDS-MAX	S.R.P.	51,150.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	1,510W EPTA-Procedure 05/2009: 19.9 J 950 - 1,900 700 x 129 x 265 mm (27-1/2 x 5-1/8 x 10-3/8") 12.3 kg (27.1 lbs.) 5.0 m (16.4 ft)	

HM1306 204 MJ	21.7 J Demolition Hammer, 30 mm Hex Shank	S.R.P.	42,500.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	1,510W EPTA-Procedure 05/2009: 21.7 J 1,450 652 x 121 x 231 mm (25-3/4 x 4-3/4 x 9-1/8") 15.1 kg (33.3 lbs.) 5.0 m (16.4 ft)	

HM1317C 175 MJ	25.0 J AVT SOFT NO LOAD Electric Breaker, 30 mm Hex Shank	S.R.P.	61,900.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	1,510W EPTA-Procedure 05/2009: 25 J 730 - 1,450 715 x 129 x 266 mm (28-1/8 x 5-1/8 x 10-1/2") 17 kg (37.5 lbs.) 5.0 m (16.4 ft)	

HM1502 218 MJ	49.1 J Electric Breaker, 28.6 mm Hex Shank	S.R.P.	67,950.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	1,850W EPTA-Procedure 05/2009: 49.1 J 1,300 809 x 130 x 266 mm (31-3/4 x 5-1/8 x 10-1/2") 19.7 kg (43.4 lbs.) 4.0 m (13.1 ft)	

HM1511 218 MJ	48.9 J AVT SOFT NO LOAD Electric Breaker, 30 mm Hex Shank	S.R.P.	64,450.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	1,850W EPTA-Procedure 05/2009: 48.9 J 1,300 781 x 130 x 266 mm (30-3/4 x 5-1/8 x 10-1/2") 19.2 kg (42.3 lbs.) 4.0 m (13.1 ft)	

HM1512 218 MJ	48.5 J AVT SOFT NO LOAD Electric Breaker, 28.6 mm Hex Shank	S.R.P.	70,650.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	1,850W EPTA-Procedure 05/2009: 48.5 J 1,300 781 x 130 x 266 mm (30-3/4 x 5-1/8 x 10-1/2") 19.2 kg (42.3 lbs.) 4.0 m (13.1 ft)	

HM1812SET 218 MJ	72.8 J AVT SOFT NO LOAD Electric Breaker, 28.6 mm Hex Shank	S.R.P.	95,200.00
	Continuous rating Input Impact energy Blows per minute (BPM) Dimensions (L x W x H) Net weight Power supply cord	2,000W EPTA-Procedure 05/2009: 72.8 J 870 843 x 210 x 608 mm (33-1/4 x 8-1/4 x 24") 31.3 kg (69 lbs.) 5.0 m (16.4 ft)	

HP1630 85 MMT	16 mm (5/8") 710 W Hammer Drill with Keyed Chuck	S.R.P.	4,900.00
	Continuous rating Input Capacity Chuck capacity Blows per minute (BPM) No Load Speed (RPM) Net weight	710W Concrete: 16 mm (5/8") Steel: 13 mm (1/2") Wood: 30 mm (1-3/16") 1.5 - 13 mm (1/16 - 1/2") 0 - 48,000 0 - 3,200 2.1 kg (4.6 lbs.)	

HP1630KSET 85 MMT	16 mm (5/8") 710 W Hammer Drill with Keyed Chuck	S.R.P.	5,600.00
	Continuous rating Input Capacity Chuck capacity Blows per minute (BPM) No Load Speed (RPM) Net weight	710W Concrete: 16 mm (5/8") Steel: 13 mm (1/2") Wood: 30 mm (1-3/16") 1.5 - 13 mm (1/16 - 1/2") 0 - 48,000 0 - 3,200 2.1 kg (4.6 lbs.)	

HP1640K 419 MC	16 mm (5/8") 680 W Hammer Drill with Keyed Chuck	S.R.P.	6,200.00
	Continuous rating Input Capacity Chuck capacity Blows per minute (BPM) No Load Speed (RPM) Net weight	680W Concrete: 16 mm (5/8") Steel: 13 mm (1/2") Wood: 30 mm (1-3/16") 1.5 - 13 mm (1/16 - 1/2") 0 - 44,800 0 - 2,800 2 kg (4.4 lbs.)	

HP1640KX3 419 MC	16 mm (5/8") 680 W Hammer Drill with Keyed Chuck	S.R.P.	6,400.00
	Continuous rating Input Capacity Chuck capacity Blows per minute (BPM) No Load Speed (RPM) Net weight	680W Concrete: 16 mm (5/8") Steel: 13 mm (1/2") Wood: 30 mm (1-3/16") 1.5 - 13 mm (1/16 - 1/2") 0 - 44,800 0 - 2,800 2 kg (4.4 lbs.)	

HP2050 419 MC	20 mm (3/4") 720 W 2-Speed Hammer Drill with Keyed Chuck	S.R.P.	9,050.00
	Capacity Chuck capacity Impacts per minute (IPM) No Load Speed (RPM) Net weight	Concrete: 20 mm (3/4") Steel Hi: 8 mm (5/16") / Lo: 13 mm (1/2") Wood Hi: 25 mm (1") / Lo: 40 mm (1-9/16") 1.5 - 13 mm (1/16 - 1/2") High: 0 - 58,000 / Low: 0 - 24,000 High: 0 - 2,900 / Low: 0 - 1,200 2.5 kg (5.6 lbs.)	



Double Insulation



Reversing



Torque Setting 18



Torque Limiter



Built-in Job Light



Variable Speed



Mechanical 2-Speed



Torque Setting 20




Keyless Chuck



Carrying Case




Brake



Torque Setting 16



Torque Setting 21



Constant Speed

HP331DWAX8 12Vmax CXT BL Cordless 10 mm (3/8") 32 N-m Hammer Driver Drill S.R.P. 12,150.00

CXT

Capacity Steel / Wood / Masonry : 10 / 21 / 8 mm (3/8" / 13/16" / 5/16")
 High / Low: 0 - 25,500 / 0 - 6,750
 No Load Speed (RPM) High / Low: 0 - 1,700 / 0 - 450
 Max Fastening Torque Hard / Soft: 30 / 14 N-m (270 / 130 in.lbs.)
 Max lock torque 28 N-m (250 in.lbs.)
 Net weight 1.1 - 1.3 kg (2.5 - 2.9 lbs)

2.5 Years Limited Warranty

INCLUDE: 1 pc. 2.0 Ah Battery, Charger, Tool bag, 17pcs. Combination Set, ADP08, COOL BOX (Type 3).

HP331DZ 12Vmax CXT BL Cordless 10 mm (3/8") 32 N-m Hammer Driver Drill S.R.P. 3,800.00

CXT

Capacity Steel / Wood / Masonry : 10 / 21 / 8 mm (3/8" / 13/16" / 5/16")
 High / Low: 0 - 25,500 / 0 - 6,750
 No Load Speed (RPM) High / Low: 0 - 1,700 / 0 - 450
 Max Fastening Torque Hard / Soft: 30 / 14 N-m (270 / 130 in.lbs.)
 Max lock torque 28 N-m (250 in.lbs.)
 Net weight 1.1 - 1.3 kg (2.5 - 2.9 lbs)

2.5 Years Limited Warranty

Battery, Charger NOT INCLUDED.

HP332DWYE 12V max CXT BL XPT Cordless 10 mm (3/8") 32 N-m Hammer Driver Drill S.R.P. 13,050.00

CXT

Capacity Masonry: 8 mm (5/16") / Steel: 10 mm (3/8")
 Wood: 28 mm (1-1/8")
 Chuck capacity 0.8 - 10 mm (1/32 - 3/8")
 Impacts per minute (IPM) High: 0 - 22,500 / Low: 0 - 6,750
 No Load Speed (RPM) High: 0 - 1,500 / Low: 0 - 450
 Max fastening torque Hard: 35 N-m / Soft: 21 N-m
 Max lock torque 32 N-m (280 in.lbs.)
 Net weight 1.1 - 1.3 kg (2.4 - 2.8 lbs.)

2.5 Years Limited Warranty

INCLUDE: 2 pcs. 1.5 Ah Battery, Charger, Carrying case.

HP332DZ 12V max CXT BL XPT Cordless 10 mm (3/8") 32 N-m Hammer Driver Drill S.R.P. 7,500.00

CXT

Capacity Masonry: 8 mm (5/16") / Steel: 10 mm (3/8")
 Wood: 28 mm (1-1/8")
 Chuck capacity 0.8 - 10 mm (1/32 - 3/8")
 Impacts per minute (IPM) High: 0 - 22,500 / Low: 0 - 6,750
 No Load Speed (RPM) High: 0 - 1,500 / Low: 0 - 450
 Max fastening torque Hard: 35 N-m / Soft: 21 N-m
 Max lock torque 32 N-m (280 in.lbs.)
 Net weight 1.1 - 1.3 kg (2.4 - 2.8 lbs.)

2.5 Years Limited Warranty

1 x BL64100 (10 Ah), 1 DC64WA Charger (5 Hrs Charge time)

HP333DWYE 12Vmax CXT Li-Ion Cordless 10 mm (3/8") 28 N-m Hammer Driver Drill S.R.P. 8,250.00

CXT

Capacity Masonry: 8 mm (5/16") / Steel: 10 mm (3/8")
 Wood: 21 mm (13/16")
 Chuck capacity 0.8 - 10 mm (1/32 - 3/8")
 Impacts per minute (IPM) High: 0 - 25,500 / Low: 0 - 6,750
 No Load Speed (RPM) High: 0 - 1,700 / Low: 0 - 450
 Max fastening torque Hard: 30 N-m / Soft: 14 N-m
 Max lock torque 28 N-m (250 in.lbs.)
 Net weight 1.1 - 1.3 kg (2.4 - 2.9 lbs.)

2.5 Years Limited Warranty

Battery, Charger NOT INCLUDED.

HP333DWYX3 12Vmax CXT Li-Ion Cordless Hammer Driver Drill S.R.P. 7,300.00

CXT

Capacity Masonry: 8 mm (5/16") / Steel: 10 mm (3/8")
 Wood: 21 mm (13/16")
 Chuck capacity 0.8 - 10 mm (1/32 - 3/8")
 Impacts per minute (IPM) High: 0 - 25,500 / Low: 0 - 6,750
 No Load Speed (RPM) High: 0 - 1,700 / Low: 0 - 450
 Max fastening torque Hard: 30 N-m (270 in.lbs.)
 Soft: 14 N-m (130 in.lbs.)
 Net weight 1.1 - 1.3 kg (2.4 - 2.9 lbs.)

2.5 Years Limited Warranty

1 x BL1016 (1.5Ah), Charger in a box

HP488D002 18V Li-Ion Cordless 13 mm (1/2") 38 N-m Hammer Driver Drill, G-Battery S.R.P. 12,050.00

G-Battery

Capacity Masonry: 13 mm (1/2") / Steel: 13 mm (1/2")
 Wood: 36 mm (1-7/16")
 1.5 - 13 mm (1/16 - 1/2")
 Chuck capacity 0.8 - 10 mm (1/32 - 3/8")
 Impacts per minute (IPM) High: 0 - 21,000 / Low: 0 - 6,000
 No Load Speed (RPM) High: 0 - 1,400 / Low: 0 - 400
 Max fastening torque Hard: 42 N-m / Soft: 24 N-m
 Max lock torque 38 N-m (340 in.lbs.)
 Net weight 1.8 kg (4.0 lbs.)

1.5 Years Limited Warranty

INCLUDE: 2 pcs. 1.5 Ah battery, Fast charger, Carrying case.

HP488D006 18V Li-Ion Cordless 13 mm (1/2") 38 N-m Hammer Driver Drill, G-Battery S.R.P. 12,400.00

G-Battery

Capacity Masonry: 13 mm (1/2") / Steel: 13 mm (1/2")
 Wood: 36 mm (1-7/16")
 1.5 - 13 mm (1/16 - 1/2")
 Chuck capacity 0.8 - 10 mm (1/32 - 3/8")
 Impacts per minute (IPM) High: 0 - 21,000 / Low: 0 - 6,000
 No Load Speed (RPM) High: 0 - 1,400 / Low: 0 - 400
 Max fastening torque Hard: 42 N-m / Soft: 24 N-m
 Max lock torque 38 N-m (340 in.lbs.)
 Net weight 1.8 kg (4.0 lbs.)

1.5 Years Limited Warranty

INCLUDE: 2 pcs. 2.0 Ah battery, Fast charger, Carrying case.

HR140DWYE1 12V max CXT Cordless 14 mm (9/16") Rotary Hammer, SDS-PLUS S.R.P. 15,300.00

CXT

Impact energy EPTA-Procedure 05/2009: 1.0 J
 Capacity Concrete: 14 mm (9/16")
 Steel: 10 mm (3/8") / Wood: 13 mm (1/2")
 Impacts per minute (IPM) 0 - 4,900
 No Load Speed (RPM) 0 - 850
 Net weight 1.9 - 2.6 kg (4.3 - 5.6 lbs.)

2.5 Years Limited Warranty

INCLUDE: 2 pcs. 1.5 Ah battery, Charger, Ass'd bits, Carrying case.

HR166DWYE1 12V max CXT BL Cordless 16 mm (5/8") Rotary Hammer, SDS-PLUS S.R.P. 18,050.00

CXT

Impact energy EPTA-Procedure 05/2009: 1.1 J
 Capacity Concrete: 16 mm (5/8")
 Steel: 10 mm (3/8") / Wood: 13 mm (1/2")
 Impacts per minute (IPM) 0 - 4,800
 No Load Speed (RPM) 0 - 680
 Net weight 1.8 - 2.4 kg (4.1 - 5.4 lbs.)

2.5 Years Limited Warranty

INCLUDE: 2 pcs. 1.5 Ah battery, Charger, Ass'd bits, Carrying case.

HR166DZ 12V max CXT BL Cordless 16 mm (5/8") Rotary Hammer, SDS-PLUS S.R.P. 8,950.00

CXT

Impact energy EPTA-Procedure 05/2009: 1.1 J
 Capacity Concrete: 16 mm (5/8")
 Steel: 10 mm (3/8")
 Wood: 13 mm (1/2")
 Impacts per minute (IPM) 0 - 4,800
 No Load Speed (RPM) 0 - 680
 Net weight 1.8 - 2.4 kg (4.1 - 5.4 lbs.)

2.5 Years Limited Warranty

Battery, Charger NOT INCLUDED.

HR1841F 18 mm (11/16") 1.4 J AVT Rotary Hammer, SDS-PLUS, LED Job Light S.R.P. 9,550.00

AVT

Continuous rating Input 470W
 Impact energy EPTA-Procedure 05/2009: 1.4 J
 Capacity Concrete: 18 mm (11/16")
 Steel: 13 mm (1/2")
 Wood: 24 mm (15/16")
 Blows per minute (BPM) 0 - 4,800
 No Load Speed (RPM) 0 - 2,100
 Net weight 2 - 2.5 kg (4.5 - 5.4 lbs.)
 Power supply cord 2.5 m (8.2 ft)

2.5 Years Limited Warranty

HR2020 20 mm (3/4") 2.2 J Rotary Hammer, SDS-PLUS S.R.P. 9,450.00

AVT

Continuous rating input 660W
 Capacity Concrete: 20 mm (3/4")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Impact per minute (ipm) 0 - 4,050
 No load speed (rpm) 0 - 1,050
 Net weight 2.3 Kg (5.1 lbs)

2.5 Years Limited Warranty

Battery, Charger NOT INCLUDED.

HR2460 24 mm (15/16") 2.4 J Rotary Hammer, SDS-PLUS S.R.P. 9,200.00

AVT

Continuous rating Input 780W
 Impact energy EPTA-Procedure 05/2009: 2.4 J
 Capacity Concrete: 24 mm (15/16")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Blows per minute (BPM) 0 - 4,500
 No Load Speed (RPM) 0 - 1,100
 Net weight 2.8 - 3.2 kg (6.1 - 7 lbs.)

2.5 Years Limited Warranty



Double Insulation



Variable Speed



Brake



Reversing



Mechanical 2-Speed



Torque Setting 16



Torque Setting 18



Torque Setting 20



Torque Setting 21



Torque Limiter



Keyless Chuck



Constant Speed



Built-in Job Light



Carrying Case

HR2470X5 **325 Wh** S.R.P. 12,650.00

AC **AVT** **T₂+T** 24 mm (15/16") 2.4 J Combination Hammer, **SDS-PLUS**



Continuous rating Input 780W
 Impact energy EPTA-Procedure 05/2009: 2.4 J
 Capacity Concrete: 24 mm (15/16")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Blows per minute (BPM) 0 - 4,500
 No Load Speed (RPM) 0 - 1,100
 Net weight 2.9 - 3.3 kg (6.4 - 7.3 lbs.)



HR2651 **325 Wh** S.R.P. 14,850.00

AC **AVT** **T₂+T** 26 mm (1") 2.4 J AVT Combination Hammer, **SDS-PLUS**



Continuous rating Input 800W
 Impact energy EPTA-Procedure 05/2009: 2.4 J
 Capacity Concrete: 26 mm (1")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Blows per minute (BPM) 0 - 4,600
 No Load Speed (RPM) 0 - 1,200
 Net weight 3.1 kg (6.8 lbs.)



HR2631FX2 **325 Wh** S.R.P. 12,700.00

AC **AVT** **T₂+T** 26 mm (1") 2.4 J AVT Combination Hammer, **SDS-PLUS**



Continuous rating Input 800W
 Impact energy EPTA-Procedure 05/2009: 2.4 J
 Capacity Concrete: 26 mm (1")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Blows per minute (BPM) 0 - 4,600
 No Load Speed (RPM) 0 - 1,200
 Net weight 2.9 - 3.4 kg (6.4 - 7.4 lbs.)



HR2810SET **325 Wh** S.R.P. 19,100.00

AC **T₂+T** 28 mm (1-1/8") 2.8 J Combination Hammer, **SDS-PLUS**



Continuous rating Input 800W
 Impact energy EPTA-Procedure 05/2009: 2.8 J
 Capacity Concrete (w/ TCT bit): 28 mm (1-1/8")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Blows per minute (BPM) 0 - 4,500
 No Load Speed (RPM) 0 - 1,100
 Net weight 3.4 - 3.8 kg (7.5 - 8.5 lbs.)



HR3001CJ **351 Wh** S.R.P. 21,550.00

AC **T₂+T** 30 mm (1-3/16") 3.9 J Combination Hammer, **SDS-PLUS**



Continuous rating Input 1,050W
 Impact energy EPTA-Procedure 05/2009: 3.9 J
 Capacity Masonry: 30 mm (1-3/16")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Blows per minute (BPM) 0 - 4,500
 No Load Speed (RPM) 0 - 840
 Net weight 4.1 - 4.5 kg (9.0 - 9.9 lbs.)



HR3011FCJ **351 Wh** S.R.P. 23,250.00

AC **AVT** **T₂+T** 30 mm (1-3/16") 3.9 J AVT Combination Hammer, **SDS-PLUS**



Continuous rating Input 1,050W
 Impact energy EPTA-Procedure 05/2009: 3.9 J
 Capacity Masonry: 30 mm (1-3/16")
 Steel: 13 mm (1/2") / Wood: 32 mm (1-1/4")
 Blows per minute (BPM) 0 - 4,500
 No Load Speed (RPM) 0 - 840
 Net weight 4.4 - 4.8 kg (9.7 - 10.6 lbs.)



HR4002 **350 Wh** S.R.P. 32,150.00

AC **T₂+T** 40 mm (1-9/16") 6.1 J Rotary Hammer, **SDS-MAX**



Continuous rating Input 1,050W
 Impact energy EPTA-Procedure 05/2009: 6.1 J
 Capacity Concrete (w/ TCT bit): 40 mm (1-9/16")
 Blows per minute (BPM) 2,500
 No Load Speed (RPM) 680
 Net weight 6.6 - 6.8 kg (14.6 - 15 lbs.)



HR4013C **350 Wh** S.R.P. 45,600.00

AC **AVT SOFT NO LOAD** **T₂+T** 40 mm (1-9/16") 8.0 J AVT SOFT NO LOAD Rotary Hammer, **SDS-MAX**



Continuous rating Input 1,100W
 Impact energy EPTA-Procedure 05/2009: 8 J
 Capacity Concrete (w/ TCT bit): 40 mm (1-9/16")
 Blows per minute (BPM) 1,450 - 2,900
 No Load Speed (RPM) 250 - 500
 Net weight 6.8 - 6.9 kg (14.9 - 15.3 lbs.)



HR4030C **350 Wh** S.R.P. 34,050.00

AC **T₂+T** 40 mm (1-9/16") 9.2 J Rotary Hammer, 17 mm Hex Shank



Continuous rating Input 1,100W
 Impact energy EPTA-Procedure 05/2009: 9.2 J
 Capacity Concrete (w/ TCT bit): 40 mm (1-9/16")
 Blows per minute (BPM) 1,300 - 2,600
 No Load Speed (RPM) 230 - 460
 Net weight 6.9 kg (15.2 lbs.)



HR4511C **175 Wh** S.R.P. 57,500.00

AC **AVT** **T₂+T** 45 mm (1-9/16") 9.4 J AVT SOFT NO LOAD Rotary Hammer, **SDS-MAX**



Continuous rating Input 1,350W
 Impact energy EPTA-Procedure 05/2009: 9.4 J
 Capacity Concrete (w/ TCT bit): 45 mm (1-3/4")
 Blows per minute (BPM) 1,250 - 2,750
 No Load Speed (RPM) 130 - 280
 Net weight 9 - 9.1 kg (19.8 - 20.1 lbs.)



HR5202C **175 Wh** S.R.P. 56,400.00

AC **AVT** **T₂+T** 52 mm (2-1/16") 19.1 J Rotary Hammer, **SDS-MAX**



Continuous rating Input 1,510W
 Impact energy EPTA-Procedure 05/2009: 19.1 J
 Capacity Concrete (w/ TCT bit): 52 mm (2")
 Blows per minute (BPM) 1,100 - 2,250
 No Load Speed (RPM) 150 - 310
 Net weight 10.9 - 11.1 kg (24.1 - 24.4 lbs.)



HR5212C **175 Wh** S.R.P. 60,800.00

AC **AVT SOFT NO LOAD** **T₂+T** 52 mm (2-1/16") 20.0 J AVT SOFT NO LOAD Rotary Hammer, **SDS-MAX**



Continuous rating Input 1,510W
 Impact energy EPTA-Procedure 05/2009: 20 J
 Capacity Concrete (w/ TCT bit): 52 mm (1-3/4")
 Blows per minute (BPM) 1,100 - 2,250
 No Load Speed (RPM) 150 - 310
 Net weight 11.9 - 12 kg (26.2 - 26.5 lbs.)



HS0600 **153 Wh** S.R.P. 16,700.00

AC 260 mm (10-1/4") 2,000 W Circular Saw



Continuous rating Input 2,000W
 Wheel Diameter 255 - 270 mm (10 - 10-5/8")
 Hole Diameter 25.4 mm (1")
 Max Cutting Capacity 0°: 97 mm (3-13/16") / 45°: 68 mm (2-11/16")
 No Load Speed (RPM) 4,300
 Net weight 6.9 kg (15.2 lbs.)


















HS7010 **303 Wh** S.R.P. 9,450.00



AC 185 mm (7-1/4") 1,600 W Circular Saw



Continuous rating Input 1,600W
 Wheel Diameter 185 mm (7-1/4")
 Hole Diameter 20 mm
 Max Cutting Capacity 0°: 65 mm (2-9/16") / 45°: 44 mm (1-3/4")
 No Load Speed (RPM) 5,500
 Net weight 4 kg (8.9 lbs.)



HW1200  2.5 Years Limited Warranty MC	12 MPa (120 Bar) High Pressure Washer with Self-Priming Function Continuous rating Input 1,800W Max pressure 12 Mpa (120 bar, 1,740 PSI) Max ow rate 420 L/h Max feed temperature 40°C (104°F) High pressure hose length 10 m (33 ft.) Dimensions (L x W x H) 292 x 358 x 830 mm (11-1/2 x 14-1/8 x 32-3/4") Net weight 11 kg (24.3 lbs.) Power supply cord 5.0 m (16.4 ft)	S.R.P. 16,550.00	HW1300  2.5 Years Limited Warranty MC	13 MPa (130 Bar) High Pressure Washer with Self-Priming Function Continuous rating Input 1,800W Max pressure 13 Mpa (130 bar, 1,885 PSI) Max ow rate 450 L/h Max feed temperature 40°C (104°F) High pressure hose length 10 m (33 ft.) Dimensions (L x W x H) 292 x 358 x 830 mm (11-1/2 x 14-1/8 x 32-3/4") Net weight 12.7 kg (28 lbs.) Power supply cord 5.0 m (16.4 ft)	S.R.P. 26,250.00
JN1601 411  2.5 Years Limited Warranty MC	1.6 mm (16 Ga) Nibbler Continuous rating Input Capacity 550W Steel up to 400 N/mm ² : 1.6 mm Steel up to 600 N/mm ² : 1.2 mm Steel up to 800 N/mm ² : 0.8 mm Aluminum up to 200 N/mm ² : 2.5 mm Outside edge: 50 mm (2") Inside edge: 45 mm (1-3/4") Strokes Per Minute (SPM) 2,200 Net weight 1.6 kg (3.6 lbs.)	S.R.P. 20,150.00	JN3201 303  2.5 Years Limited Warranty MJ	3.2 mm (10 Ga) Nibbler Continuous rating Input Capacity 710W Steel up to 400 N/mm ² : 3.2 mm Steel up to 600 N/mm ² : 2.0 mm Steel up to 800 N/mm ² : 1.5 mm Aluminum up to 200 N/mm ² : 3.5 mm Outside edge: 128 mm (5-1/16") Inside edge: 120 mm (4-3/4") Strokes Per Minute (SPM) 1,300 Net weight 3.4 kg (7.4 lbs.)	S.R.P. 27,000.00
JR3051TK 303  2.5 Years Limited Warranty MC	1,200 W Recipro Saw Continuous rating Input 1,200W Length of Stroke 30 mm (1-3/16") Strokes Per Minute (SPM) 0 - 3,000 Capacity Pipe: 130 mm (5-1/8") Wood: 255 mm (10") 3.2 - 3.3 kg (7.1 - 7.3 lbs.)	S.R.P. 9,950.00	JS1601 459  2.5 Years Limited Warranty MJ	1.6 mm (16 Ga) Straight Metal Shear Continuous rating Input Capacity 380W Steel up to 400 N/mm ² : 1.6 mm Steel up to 600 N/mm ² : 1.2 mm Steel up to 800 N/mm ² : 0.8 mm Aluminum up to 200 N/mm ² : 2.5 mm Min. cutting radius 250 mm (9-7/8") Strokes Per Minute (SPM) 4,500 Net weight 1.4 kg (3.2 lbs.)	S.R.P. 16,600.00
JS1602 459  2.5 Years Limited Warranty MJ	1.6 mm (16 Ga) Metal Shear Continuous rating Input Capacity 380W Steel up to 400 N/mm ² : 1.6 mm Steel up to 600 N/mm ² : 1.2 mm Steel up to 800 N/mm ² : 0.8 mm Aluminum up to 200 N/mm ² : 2.5 mm Min. cutting radius 30 mm (1-3/16") Strokes Per Minute (SPM) 4,000 Net weight 1.6 kg (3.4 lbs.)	S.R.P. 16,850.00	JS3201 303  2.5 Years Limited Warranty MJ	3.2 mm (10 Ga) Metal Shear Continuous rating Input Capacity 710W Steel up to 400 N/mm ² : 3.2 mm Steel up to 600 N/mm ² : 2.5 mm Steel up to 800 N/mm ² : 1.5 mm Aluminum up to 200 N/mm ² : 4.0 mm Min. cutting radius 50 mm (2") Strokes Per Minute (SPM) 1,600 Net weight 3.4 kg (7.5 lbs.)	S.R.P. 20,550.00
JV101DWYE  2.5 Years Limited Warranty MC	12V max CXT Li-Ion Cordless Top Handle Jig Saw Max cutting capacity at 0° Wood / Aluminum / Mild Steel: 65 / 4 / 2 mm (2-9/16 / 5/32 / 1/16") Length of stroke 18 mm (11/16") Strokes per minute (SPM) 0 - 2,900 Bevel range 0 - 45° Net weight 1.8 - 1.9 kg (3.9 - 4.3 lbs.) INCLUDE: 2 pcs. 1.5Ah battery, Charger, Carrying case.	S.R.P. 9,650.00	JV101DZ  2.5 Years Limited Warranty MC	12V max CXT Li-Ion Cordless Top Handle Jig Saw Max cutting capacity at 0° Wood / Aluminum / Mild Steel: 65 / 4 / 2 mm (2-9/16 / 5/32 / 1/16") Length of stroke 18 mm (11/16") Strokes per minute (SPM) 0 - 2,900 Bevel range 0 - 45° Net weight 1.8 - 1.9 kg (3.9 - 4.3 lbs.) Battery, Charger NOT INCLUDED.	S.R.P. 4,400.00
JV103DZ  2.5 Years Limited Warranty MC	12V max CXT BL SOFT NO LOAD Cordless Top Handle Jig Saw Max cutting capacity at 0° Wood / Aluminum / Mild Steel: 90 / 20 / 10 mm (3-1/2 / 13/16 / 3/8") Length of stroke 23 mm (7/8") Strokes per minute (SPM) 800 - 3,000 Bevel range 0 - 45° Net weight 1.9 - 2 kg (4.1 - 4.4 lbs.) Battery, Charger NOT INCLUDED.	S.R.P. 8,650.00	LB1200F  2.5 Years Limited Warranty MC	305 mm (12") 900 W Band Saw Continuous rating Input 900W Blade length 2,240 mm (88") Capacity Thickness of cut: 165 mm (6-1/2") Throat: 305 mm (12") Blade speed High: 1,000 m/min (16.7 m/s) Low: 500 m/min (8.3 m/s) Dimensions (L x W x H) 615 x 775 x 1,600 mm Net weight 82 kg (181.2 lbs.)	S.R.P. 54,600.00
LD030P  1.5 Years Warranty One Time Replacement Hungary	30 m Laser Distance Measure Measuring range 0.2 - 30 m Operating temperature 0 - 40°C Storage temperature -25 - 70°C Max measuring tolerance 3.0 mm / 10 m Diameter of laser point 6 mm 10 m Laser type Laser class 2: 635 nm Dimensions (H x D x W) 117 x 53 x 25 mm (4.5 x 2.14 x 1") Net weight 0.1 kg (0.22 lbs.) Battery NOT INCLUDED.	S.R.P. 5,400.00	LD050P  1.5 Years Warranty One Time Replacement Hungary	50 m Laser Distance Measure Measuring range 0.05 - 50 m Power supply Cell battery: AAA 1.5V x 2 pcs Net weight 0.1 kg (0.22 lbs.) Battery NOT INCLUDED.	S.R.P. 7,200.00



LD080P S.R.P. 12,100.00

AAA Alkaline Battery

80 m Laser Distance Measure



Measuring range 0.05 - 80 m
 Power supply Cell battery: AAA 1.5V x 2 pcs
 Net weight 0.14 kg (0.31 lbs.)

1.5 Years Warranty
 One Time Replacement

Hungary Battery NOT INCLUDED.

LD080PI S.R.P. 14,050.00

AAA Alkaline Battery

80 m Laser Distance Measure, Inclination Sensor



Measuring range 0.05 - 80 m
 Power supply Cell battery: AAA 1.5V x 2 pcs
 Net weight 0.14 kg (0.31 lbs.)

1.5 Years Warranty
 One Time Replacement

Hungary Battery NOT INCLUDED.

LS1018L 153 S.R.P. 35,850.00



260 mm (10-1/4") 1,430 W Slide Compound Miter Saw, Laser

Continuous rating Input 1,430W
 Wheel Diameter 255 - 260 mm (10 - 10-1/4")
 Miter angle 47 / 60° L 47, 60° R
 Bevel angle 45 / 45° L 45, 45° R
 Max Cutting Capacity
 0°: 91 x 305 mm (3-5/8 x 12")
 45°: 91 x 215 mm (3-5/8 x 8-1/2")
 No Load Speed (RPM) 4,300
 Dimensions (L x W x H) 825 x 536 x 633 mm
 Net weight 20.6 kg (45.4 lbs.)

2.5 Years Limited Warranty



MC

LS1019L 153 S.R.P. 45,150.00



260 mm (10-1/4") 1,510 W Slide Compound Miter Saw, Laser

Continuous rating Input 1,510W
 Wheel Diameter 255 - 260 mm (10 - 10-1/4")
 Bevel angle 48° L 48° R
 Miter angle 60° L 60° R
 Max Cutting Capacity
 0° Miter: 68 x 310 mm (2-11/16 x 12-1/4")
 45° Miter, L/R: 91 x 197 mm (3-5/8 x 7-3/4")
 No Load Speed (RPM) 3,200
 Dimensions (L x W x H) 805 x 644 x 660 mm
 Net weight 26.3 kg (57.9 lbs.)

2.5 Years Limited Warranty



MC

LS1040SET 153 S.R.P. 21,650.00



260 mm (10-1/4") 1,510 W Slide Compound Miter Saw, Laser

Continuous rating Input 1,650W
 Wheel Diameter 255 - 260 mm (10/ 10-1/4")
 Bevel angle 45° L
 Max Cutting Capacity
 0°: 90.5 x 95 mm (3-9/16 x 3-3/4")
 45°: 90.5 x 67 mm (3-9/16 x 2-5/8")
 No Load Speed (RPM) 4,600
 Dimensions (L x W x H) 530 x 476 x 532 mm (20-7/8 x 18-3/8 x 21")
 Net weight 12.4 kg (27.3 lbs.)
 Power supply cord 2.5 m (8.2 ft)

2.5 Years Limited Warranty



MC

LS1219L 153 S.R.P. 55,700.00



305 mm (12") 1,800 W Slide Compound Miter Saw, Laser

Continuous rating Input 1,800W
 Wheel Diameter 305 mm (12")
 Bevel angle 48° L 48° R
 Miter angle 60° L 60° R
 Max Cutting Capacity
 0° Miter: 107 x 363 mm (4-1/4 x 14-1/4")
 45° Miter, L/R: 107 x 255 mm (4-1/4 x 10")
 No Load Speed (RPM) 3,200
 Dimensions (L x W x H) 898 x 664 x 725 mm
 Net weight 29.5 kg (65 lbs.)

2.5 Years Limited Warranty



MC

LS1221 153 S.R.P. 52,400.00



305 mm (12") 1,650 W Compound Miter Saw

Continuous rating Input 1,650W
 Wheel Diameter 305 mm (12")
 Bevel angle 45° L
 Max Cutting Capacity
 0°: 98 x 153 mm (3-7/8 x 6")
 45°: 70 x 149 mm (2-3/4 x 5-7/8")
 No Load Speed (RPM) 4,000
 Dimensions (L x W x H) 674 x 610 x 607 mm
 Net weight 16.8 kg (37 lbs.)

2.5 Years Limited Warranty



MJ

LS1440 153 S.R.P. 79,000.00



355 mm (14") 1,380 W Miter Saw

Continuous rating Input 1,380W
 Wheel Diameter 305 mm (12")
 Bevel angle 0°: 122 x 152 mm (4-13/16 x 6")
 45°: 122 x 115 mm (4-13/16 x 4-1/2")
 Max Cutting Capacity
 355 mm (14")
 25, 25.4 mm (1")
 No Load Speed (RPM) 3,200
 Dimensions (L x W x H) 530 x 596 x 435 mm
 Net weight 34.2 kg (75.4 lbs.)

2.5 Years Limited Warranty



MJ

LW1401 203 S.R.P. 11,000.00



355 mm (14") 2,200 W Portable Cut-Off

Continuous rating Input 2,200W
 Wheel Diameter 355 mm (14")
 No Load Speed (RPM) 3,800
 Cutting capacity 127 mm (5")
 Dimensions (L x W x H) 500 x 295 x 640 mm (19-3/4 x 11-5/8 x 25-1/4")
 Net weight 18.3 kg (40.3 lbs.)

2.5 Years Limited Warranty



MC

M0600B 64 S.R.P. 2,600.00



10mm (3/8") 350 W Drill

Continuous rating input 350W
 Capacity Steel: 10 mm (3/8")
 Wood: 20 mm (13/16")
 No Load Speed (RPM) 0-3,000
 Dimensions (L x W x H) 230x66x176mm (9"x2-5/8"x6-15/16")
 Net weight 1.2kg (3.2lbs)
 Power supply cord 2.0m (6.6ft)

1.5 Years Limited Warranty



MMT

M0800M 85 S.R.P. 2,400.00



10mm (3/8") 500 W Hammer Drill

Continuous rating input 500W
 Capacity Concrete: 10 mm (3/8") / Steel: 10 mm (3/8")
 Wood: 20 mm (13/16")
 Impacts Per Minute (IPM) 0 - 43,500
 No Load Speed (RPM) 0-2,900
 Dimensions (L x W x H) 254x70x196mm (10"x2-3/4"x7-3/4")
 Net weight 1.6kg (3.4lbs)
 Power supply cord 2.0m (6.6ft)

1.5 Years Limited Warranty



MC

M0801B 85 S.R.P. 3,150.00



13mm (1/2") 500 W Hammer Drill

Continuous rating input 500W
 Capacity Concrete: 16 mm (5/8") / Steel: 13 mm (1/2")
 Wood: 20 mm (13/16")
 Impacts Per Minute (IPM) 0 - 43,500
 No Load Speed (RPM) 0 - 2,900
 Dimensions (L x W x H) 262x70x196mm (10-3/8"x2-3/4"x7-3/4")
 Net weight 1.7kg (3.7lbs)
 Power supply cord 2.0m (6.6ft)

1.5 Years Limited Warranty



MMT

M0900B 459 S.R.P. 2,900.00



100mm (4") 540 W Angle Grinder, Slide Switch

Continuous rating input 540W
 Wheel diameter 100mm (4")
 No Load Speed (RPM) 12,000
 Dimensions (L x W x H) 251x118x93mm (9-7/8"x4-5/8"x3-5/8")
 Net weight 1.6kg (3.4lbs)
 Power supply cord 2.0m (6.6ft)

1.5 Years Limited Warranty



MC

M0910B 459 S.R.P. 2,900.00






100mm (4") 850 W Angle Grinder, Toggle Switch

Continuous rating input 540W
 Wheel diameter 100mm (4")
 No Load Speed (RPM) 12,000
 Dimensions (L x W x H) 251x118x93mm (9-7/8"x4-5/8"x3-5/8")
 Net weight 1.6kg (3.4lbs)
 Power supply cord 2.0m (6.6ft)





1.5 Years Limited Warranty




MC



M1100KB 303 	82 mm (3-1/4") 750 W Power Planer S.R.P. 10,500.00 Continuous rating input 750W Planing Width 82 mm (3-1/4") Planing Depth 3 mm (1/8") Shipping 20 mm (3/4") No Load Speed (RPM) 18,000 Dimensions (L x W x H) 390x175x140mm (15-3/8"x6-7/8"x5-1/2") Net weight 4.7kg (10.4lbs) Power supply cord 2.0m (6.6ft)	M1902B 411 	82 mm (3-1/4") 500 W Power Planer S.R.P. 4,450.00 Continuous rating input 500W Planing Width 82 mm (3-1/4") Planing Depth 1 mm (1/32") Shipping 9mm (11/32") No Load Speed (RPM) 16,000 Dimensions (L x W x H) 285x157x160mm (11-1/4"x6-3/16"x6-5/16") Net weight 2.7kg (6.0lbs) Power supply cord 2.0m (6.6ft)
M2401B 203 	355mm (14") 2,000 W Portable Cut Off S.R.P. 11,050.00 Continuous rating input 2,000W Wheel diameter 355 mm (14") No load speed (rpm) 3,800 Dimension (LxWxH) 500x280x620mm (19-3/4"x11"x24-3/8") Net weight 15.7 kg (34.6 lbs) Power supply cord 2.5 m (8.2 ft)	M2402B 203 	355mm (14") 2,000 W Portable Cut Off S.R.P. 11,100.00 Continuous rating input 2,000W Wheel diameter 355 mm (14") No load speed (rpm) 3,800 Dimension (LxWxH) 500x280x620mm (19-3/4"x11"x24-3/8") Net weight 15.7 kg (34.6 lbs) Power supply cord 2.5 m (8.2 ft)
M3602B 203 	1/2" 1,650 W Plunge Router with Anti-Restart Function S.R.P. 11,600.00 Continuous rating input 1,650 W Collet Capacity 1/2" Plunge Capacity 0 - 60 mm (0 - 2-3/8") No Load Speed (RPM) 22,000 Dimensions (L x W x H) 148 x 284 x 300 mm (5-7/8 x 11-1/8 x 11-3/4") Net weight 5.7 kg (12.6 lbs.) Power supply cord 2.0 m (6.6 ft)	M3700B 411 	1/4" 530 W Fixed Base Trimmer S.R.P. 4,250.00 Continuous rating input 530W Capacity Collet: 6mm or 1/4" Plunge Capacity 0 - 42 mm (0 - 1-5/8") No Load Speed (RPM) 35,000 Dimensions (L x W x H) 82x90x199mm (3-1/4"x3-1/2"x7-7/8") Net weight 1.4kg (3.1lbs) Power supply cord 2.0m (6.6ft)
M3702B 411 	1/4" 530 W Fixed Base Trimmer with Anti-Restart Function S.R.P. 5,550.00 Continuous rating input 530 W Collet Capacity 1/4" No Load Speed (RPM) 35,000 Plunge Capacity 0 - 42 mm (0 - 1-5/8") Dimensions (L x W x H) 82 x 90 x 211 mm (3-1/4 x 3-1/2 x 8-5/16") Net weight 1.5 kg (3.3 lbs.) Power supply cord 2.0 m (6.6 ft)	M4000B 85 	530 W Blower S.R.P. 3,300.00 Continuous rating input 530W Air volume 1.2-2.9m³/min No Load Speed (RPM) 8,500-16,000 Dimensions (L x W x H) 427x161x212mm (16-3/4"x6-3/8"x8-3/8") Net weight 1.5kg (3.4lbs) Power supply cord 2.0m (6.6ft)
M4301B 64 	450 W Top Handle Jig Saw, 3 Orbital Settings Plus Straight Cutting S.R.P. 4,100.00 Continuous rating input 450W Max Cutting Capacity at 90° Wood: 65 mm (2-9/16") Length of Stroke Steel: 6 mm (1/4") Strokes Per Minute (SPM) 18 mm (11/16") Dimensions (L x W x H) 0 - 3,100 214x75x202mm (8-3/8"x2-15/16"x8") Net weight 1.9 kg (4.2 lbs) Power supply cord 2.0 m (6.6 ft)	M4302B 411 	450 W Top Handle Variable Speed Jig Saw S.R.P. 6,700.00 Continuous rating input 450W Max Cutting Capacity at 90° Wood: 55 mm (2-3/16") Length of Stroke Steel: 6 mm (1/4") Strokes Per Minute (SPM) 26 mm (1") Dimensions (L x W x H) 0 - 3,100 219x85x191mm (8-5/8"x3-3/8"x7-1/2") Net weight 2.6 kg (5.7 lbs) Power supply cord 2.0 m (6.6 ft)
M4302M 411 	450 W Top Handle Variable Speed Jig Saw S.R.P. 5,150.00 Continuous rating input 450W Max Cutting Capacity at 90° Wood: 55 mm (2-3/16") Length of Stroke Steel: 6 mm (1/4") Strokes Per Minute (SPM) 26 mm (1") Dimensions (L x W x H) 0 - 3,100 219x85x191mm (8-5/8"x3-3/8"x7-1/2") Net weight 2.6 kg (5.7 lbs) Power supply cord 2.0 m (6.6 ft)	M4500B 303 	1,010W Recipro Saw S.R.P. 5,700.00 Continuous rating input 1,010W Length of Stroke 28 mm (1-1/8") Strokes Per Minute (SPM) 0 - 2,800 Capacity Pipe: 130 mm (5-1/8") Wood: 255 mm (10") Dimensions (L x W x H) 457x98x174mm (18"x3-7/8"x6-7/8") Net weight 3.1 kg (6.9 lbs) Power supply cord 2.0 m (6.6 ft)
M5801B 303 	185 mm (7-1/4") 1,050 W Circular Saw S.R.P. 5,750.00 Continuous rating input 1,050W Max Cutting Capacity at 90°: 66mm (2-5/8") at 45°: 44mm (1-3/4") Blade Diameter 185 mm (7-1/4") No Load Speed (RPM) 4,900 Dimensions (L x W x H) 284x231x243mm (11-1/8"x9-1/8"x9-9/16") Net weight 3.7kg (8.1lbs) Power supply cord 2.0m (6.6ft)	M6200B 303 	13mm (1/2") 800 W Drill S.R.P. 4,850.00 Continuous rating input 800W Capacity Steel: 13 mm (1/2") Wood: 36 mm (1-7/16") No Load Speed (RPM) 0-700 Dimensions (L x W x H) 267x86x388mm (10-1/2"x3-3/8"x15-1/4") Net weight 2.7kg (6.0lbs) Power supply cord 2.0m (6.6ft)




<p>M6200M 303 </p> <p>AC Makita</p> <p>13mm (1/2") 800 W Drill</p> <p>Continuous rating input 800W Capacity Steel: 13 mm (1/2") Wood: 36 mm (1-7/16") No Load Speed (RPM) 0-700 Dimensions (L x W x H) 267x86x388mm (10-1/2"x3-3/8"x15-1/4") Net weight 2.7kg (6.0lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>	<p>M6500B 64 </p> <p>AC Makita</p> <p>6.5mm (1/4") 230 W High Speed Drill</p> <p>Continuous rating input 230W Capacity Steel: 6.5 mm (1/4") Wood: 9 mm (11/32") No Load Speed (RPM) 4,500 Dimensions (L x W x H) 200x63x164mm (7-7/8"x2-1/2"x6-1/2") Net weight 0.92kg (2.0lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>
<p>M6500M 64 </p> <p>AC Makita</p> <p>6.5mm (1/4") 230 W High Speed Drill</p> <p>Continuous rating input 230W Capacity Steel: 6.5 mm (1/4") Wood: 9 mm (11/32") No Load Speed (RPM) 4,500 Dimensions (L x W x H) 200x63x164mm (7-7/8"x2-1/2"x6-1/2") Net weight 0.92kg (2.0lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>	<p>M8103KX2B 85 </p> <p>AC Makita</p> <p>13mm (1/2") 430 W Hammer Drill</p> <p>Continuous rating input 430W Capacity Concrete: 13 mm (1/2") / Steel: 13 mm (1/2") Wood: 18 mm (11/16") No Load Speed (RPM) 0 - 3,000 Impacts Per Minute (IPM) 0 - 33,000 Dimensions (L x W x H) 255x72x193mm (10"x2-13/16"x7-5/8") Net weight 1.8 kg (3.9 lbs) Power supply cord 2.0 m (6.6 ft)</p> <p> </p>
<p>M8103KX2M 85 </p> <p>AC Makita</p> <p>13mm (1/2") 430 W Hammer Drill</p> <p>Continuous rating input 430W Capacity Concrete: 13 mm (1/2") / Steel: 13 mm (1/2") Wood: 18 mm (11/16") No Load Speed (RPM) 0 - 3,000 Impacts Per Minute (IPM) 0 - 33,000 Dimensions (L x W x H) 255x72x193mm (10"x2-13/16"x7-5/8") Net weight 1.8 kg (3.9 lbs) Power supply cord 2.0 m (6.6 ft)</p> <p> </p>	<p>M8600B 105 </p> <p>AC Makita</p> <p>7.2 J Demolition Hammer, 17mm Hex Shank</p> <p>Continuous rating input 900W Impacts Per Minute (IPM) 2,900 Impact energy 7.2J Dimensions (L x W x H) 406x99x232mm (16"x3-7/8"x9-1/8") Net weight 5.4kg (12.0lbs) Power supply cord 2.5m (8.2ft)</p> <p> </p>
<p>M8700BSET 459 </p> <p>AC Makita</p> <p>1.9 J 22mm (7/8") SDS-Plus Rotary Hammer</p> <p>Continuous rating input 710W Capacity Concrete: 22 mm (7/8") / Steel: 13 mm (1/2") Wood: 32 mm (1-1/4") Impacts Per Minute (IPM) 0 - 4,350 No Load Speed (RPM) 0 - 1,100 Dimensions (L x W x H) 362x71x194mm (14-1/4"x2-13/16"x7-5/8") Net weight 2.5kg (5.6lbs) Power supply cord 5.0m (16.4ft)</p> <p> </p>	<p>M9000B 203 </p> <p>AC Makita</p> <p>180mm (7") 2,000 W Angle Grinder</p> <p>Continuous rating input 2,000W Wheel diameter 180mm (7") No Load Speed (RPM) 8,500 Dimensions (L x W x H) 439x200x141mm (17-1/4"x7-7/8"x5-9/16") Net weight 5.4 kg (12.0 lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>
<p>M9002B 303 </p> <p>AC Makita</p> <p>125mm (5") 1,050 W Angle Grinder</p> <p>Continuous rating input 1,050W Wheel diameter 125mm (5") No Load Speed (RPM) 11,000 Dimensions (L x W x H) 361x140x124mm (14-1/4"x5-1/2"x4-7/8") Net weight 2.8kg (6.1lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>	<p>M9002M 303 </p> <p>AC Makita</p> <p>125mm (5") 1,050 W Angle Grinder</p> <p>Continuous rating input 1,050W Wheel diameter 125mm (5") No Load Speed (RPM) 11,000 Dimensions (L x W x H) 361x140x124mm (14-1/4"x5-1/2"x4-7/8") Net weight 2.8kg (6.1lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>
<p>M9200B 419 </p> <p>AC Makita</p> <p>1/4 Sheet 180 W Finishing Sander</p> <p>Continuous rating input 180W Pad Size 112 x 102 mm (4-3/8" x 4") Abrasive Paper Size 114 x 140 mm (4-1/2" x 5-1/2") Orbits Per Minute (OPM) 14,000 Dimensions (L x W x H) 110x112x133mm (4-5/16"x4-3/8"x5-1/4") Net weight 0.89kg (2.0lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>	<p>M9201B 64 </p> <p>AC Makita</p> <p>1/3 Sheet 180 W Finishing Sander</p> <p>Continuous rating input 180W Pad Size 93 x 185 mm (3-5/8" x 7-1/4") Abrasive Paper Size 93 x 228 mm (3-5/8" x 9") Orbits Per Minute (OPM) 12,000 Dimensions (L x W x H) 214x92x147mm (8-3/8"x3-5/8"x5-3/4") Net weight 1.3kg (2.9lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>
<p>M9202B 419 </p> <p>AC Makita</p> <p>125 mm (5") 240 W Random Orbit Sander</p> <p>Continuous rating input 240W Pad Size 123 mm (4-7/8") Abrasive Disc Size 125mm (5") Orbits Per Minute (OPM) 12,000 Strokes Per Minute (SPM) 24,000 Orbit Diameter 2.8 mm (1/8") Dimensions (L x W x H) 127x123x142mm (5"x4-7/8"x5-5/8") Net weight 1.1 kg (2.4 lbs) Power supply cord 2.0 m (6.6 ft)</p> <p> </p>	<p>M9400B 153 </p> <p>AC Makita</p> <p>100 x 610mm (4" x 24") 940 W Belt Sander</p> <p>Continuous rating input 940W Belt size 100 x 610mm (4"x 24") Belt speed 380m / min. (1,250ft/ min) Dimensions (L x W x H) 354x175x169mm (14"x6-7/8"x6-5/8") Net weight 6.2kg (13.7lbs) Power supply cord 2.0m (6.6ft)</p> <p> </p>



M9513B **325** W **AC** S.R.P. 3,600.00

100mm (4") 850 W Angle Grinder, Toggle Switch



Continuous rating input 850W
 Wheel diameter 100mm (4")
 No Load Speed (RPM) 11,000
 Dimensions (L x W x H) 273 x 118 x 101 mm (10-3/4 x 4-5/8 x 4")
 Net weight 1.8 kg (4.0 lbs.)
 Power supply cord 2.0m (6.6ft)

1.5 Years Limited Warranty

M9800B **459** W **AC** S.R.P. 5,100.00

200 W Multi Tool



Continuous rating input 200W
 Oscillations Per Minute (OPM) 22,000
 Left / Right / Total: 1.6° / 1.6° / 3.2°
 Oscillation 283x68x98 mm
 Dimensions (L x W x H) 283x68x98 mm
 Net weight 1.2 kg
 Power supply cord 2.0 m

1.5 Years Limited Warranty

M9800BKX2 **459** W **AC** S.R.P. 7,050.00

200 W Multi Tool




Continuous rating input 200W
 Oscillations Per Minute (OPM) 22,000
 Left / Right / Total: 1.6° / 1.6° / 3.2°
 Oscillation 283x68x98 mm
 Dimensions (L x W x H) 283x68x98 mm
 Net weight 1.2 kg
 Power supply cord 2.0 m

1.5 Years Limited Warranty

MLT100 **153** W **AC** S.R.P. 30,700.00

260 mm (10-1/4") 1,500 W Table Saw




Continuous rating input 1,500W
 Max Cutting Capacity 90°: 93 mm (3-5/8") / 45°: 64 mm (2-1/2")
 Blade Diameter 260 mm (10-1/4")
 No Load Speed (RPM) 4,300
 Bevel Capacity 0° - 45°
 Table Size (L x W) 620 x 610 mm (24-3/8" x 24")
 Net weight 34.8 - 35.1 kg (76.7 - 77.4 lbs.)
 Power supply cord 2.5 m (8.2 ft)

2.5 Years Limited Warranty

MLT100 Stand - WST03 S.R.P. 18,600.00


PN: JM27000300
Foldable, Adjustable Height
MLT100 Stand with Wheels



MC

MP100DZ S.R.P. 4,300.00

12Vmax CXT Li-Ion Cordless Inflator



Max Air Pressure 830 kPa (121 PSI) [8.3 bar]
 Air Discharge Amount 200 kPa: 10 L/min
 Hose Length 65 cm (25-1/2")
 Vibration Level 3.8 m/s²
 Vibration K Factor 1.5 m/s²
 Sound Pressure Level 72 dB(A)
 Noise K Factor 3 dB(A)
 Dimensions (L x W x H) 235 x 74 x 173 mm
 Net weight 1.2 - 1.3 kg (2.6 - 3.0 lbs.)

2.5 Years Limited Warranty

N1900B **51** W **AC** S.R.P. 11,000.00

82 mm (3-1/4") 580 W Power Planer




Continuous rating input 580W
 Planing Width 82 mm (3-1/4")
 Planing Depth 1 mm (1/32")
 No Load Speed (RPM) 16,000
 Overall Length 290 mm (11-3/8")
 Net weight 2.8 kg (6.1 lbs.)
 Power supply cord 2.5 m (8.2 ft)
 Shiplapping 9mm (11/32")

2.5 Years Limited Warranty

N3701 **51** W **AC** S.R.P. 10,700.00

1/4" 440 W Trimmer




Continuous rating Input 440W
 Collet size 6/ N/A mm (N/A/ 1/4")
 Base inner 35 mm (1-3/8")
 No Load Speed (RPM) 30,000
 Overall height 181 mm (7-1/8")
 Net weight 1.6 kg (3.4 lbs.)
 Power supply cord 2.5 m (8.2 ft)

2.5 Years Limited Warranty

N5900B **153** W **AC** S.R.P. 11,900.00

235 mm (9-1/4") 2,000 W Circular Saw




Continuous rating Input 2,000W
 Wheel Diameter 235 mm (9-1/4")
 Hole Diameter 25 mm (1")
 Max Cutting Capacity 0°: 85 mm (3-3/8") / 45°: 60 mm (2-3/8")
 No Load Speed (RPM) 4,100
 Overall length 380 mm (15")
 Net weight 6.8 kg (14.8 lbs.)
 Power supply cord 2.5 m (8.2 ft)

2.5 Years Limited Warranty

N9500N **411** W **AC** S.R.P. 7,850.00

100 mm (4") 570 W Angle Grinder, Toggle Switch




Continuous rating Input 570W
 Wheel Diameter 100 mm (4")
 Hole Diameter 16 mm (5/8")
 No Load Speed (RPM) 12,000
 Overall length 245 mm (9-5/8")
 Net weight 1.6 - 1.9 kg (3.5 - 4.2 lbs.)
 Power supply cord 2.5 m (8.2 ft)

2.5 Years Limited Warranty

PC5001C **251** W **AC** S.R.P. 44,550.00

125 mm (5") 1,400 W Concrete Planer




Continuous rating Input 1,400W
 Wheel Diameter 125 mm (5")
 Hole Diameter 22.23 mm (7/8")
 No Load Speed (RPM) 10,000
 Dimensions (L x W x H) 479 x 182 x 195 mm (18-13/16 x 7-1/8 x 7-5/8")
 Net weight 4 kg (8.9 lbs.)
 Power supply cord 5 m (16.4 ft)

2.5 Years Limited Warranty

PF0410 S.R.P. 5,500.00

25 mm (1") 400 W Dirty Water Submersible Pump




Continuous rating Input 400W
 Suction & discharge dia. 25 mm (1")
 Max pumping capacity 140 L/min (37 gal/min)
 Delivery head max 5 m (16 ft)
 Submersion depth 5 m (16 ft)
 Min. suction level 40 mm (1-4/7")
 Grain size inlet 35 mm (1-3/8")
 Dimensions (L x W x H) 160 x 168 x 345 mm
 Net weight 4.3 kg (9.5 lbs.)

1.5 Years Limited Warranty

PF1010 S.R.P. 7,250.00

30 mm (1-3/16") 1,100 W Dirty Water Submersible Pump




Continuous rating Input 1,100W
 Suction & discharge dia 30 mm (1-3/16")
 Max pumping capacity 240 L/min (63 gal/min)
 Delivery head max 10 m (33 ft)
 Submersion depth 5 m (16 ft)
 Min. suction level 40 mm (1-4/7")
 Grain size inlet 35 mm (1-3/8")
 Dimensions (L x W x H) 160 x 168 x 380 mm
 Net weight 6.6 kg (14.6 lbs.)

1.5 Years Limited Warranty



PF1110 S.R.P. 9,000.00

40 mm (1-9/16") 1,100 W Dirty Water Submersible Pump




Continuous rating Input 1,100W
 Suction & discharge dia 40 mm (1-9/16")
 Max pumping capacity 250 L/min (66 gal/min)
 Delivery head max 10 m (33 ft)
 Submersion depth 5 m (16 ft)
 Min. suction level 50 mm (2")
 Grain size inlet 35 mm (1-3/8")
 Dimensions (L x W x H) 160 x 185 x 355 mm
 Net weight 7 kg (15.4 lbs.)

1.5 Years Limited Warranty



PJ7000 **459** **W** S.R.P. 14,550.00

701 W Plate Joiner




Continuous rating Input	701W
Blade diameter	100 mm (4")
Wheel Diameter	100 mm (4")
Hole Diameter	22 mm (7/8")
No Load Speed (RPM)	11,000
Dimensions (L x W x H)	302 x 139 x 145 mm
Net weight	2.8 kg (6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

2.5 Years Limited Warranty

PM7650H S.R.P. 42,000.00

75.6 mL 4 Stroke Mist Blower




Displacement	75.6 mL
Fuel Tank Capacity	1.8 L
Chemical tank Capacity	15 L
Max Air Volume	14.1 m³/min (497 cu.ft./min)
The velocity of the wind	85m/s (306 kph)
Sound Pressure Level	98.3 dB(A)
Sound Power Level	110.7 dB(A)
Vibration Level	3.5 m/s²
Dimensions (L x W x H)	420x440x595mm
Net weight	13.3kg (29.3lbs)

1.5 Years Limited Warranty

PO5000C **325** **W** S.R.P. 18,850.00

125 mm (5") 900 W Random Orbit Polisher




Continuous rating Input	900W
Pad Size	125 mm (5")
Orbits Per Minute (OPM)	0 - 6,800
Strokes Per Minute (SPM)	0 - 13,600
No Load Speed (RPM)	0 - 780
Orbit Diameter	5.5 mm (7/32")
Dimensions (L x W x H)	451 x 123 x 134 mm
Net weight	2.8 - 3 kg (6.2 - 6.5 lbs.)
Power supply cord	4.0 m (13.1 ft)

2.5 Years Limited Warranty

PV301DZ S.R.P. 14,100.00

12Vmax CXT BL XPT Cordless Sander Polisher




Pad / disc diameter	Twist-on / Twist-off style: 50 mm (2") Hook & Loop Style: 80 mm (3-1/8")
Brush pad capacity	80 mm (3-1/8")
Disc paper diameter	50 mm (2")
No Load Speed (RPM)	Polishing: 0 - 2,800 / Sanding: 0 - 9,500
Continuous Use (min.)	w/ BL1041B: 18
Dimensions (L x W x H)	139 x 67 x 249 mm (5-1/2 x 2-5/8 x 9-3/4")
Net weight	1.1 - 1.2 kg (2.4 - 2.6 lbs.)

Battery, Charger NOT INCLUDED

2.5 Years Limited Warranty

PW5001C **325** **W** S.R.P. 22,050.00

125 mm (5") 900 W Stone Polisher




Continuous rating Input	900W
Wheel Diameter	100 - 125 mm (4 - 5")
Capacity	Pad: 100 - 125 mm (4 - 5")
No Load Speed (RPM)	2,000 - 4,000
Overall length	359 mm (14-1/8")
Thread	M14x2.0
Net weight	2.3 - 2.6 kg (5.1 - 5.7 lbs.)
Power supply cord	4.0 m (13.1 ft)

2.5 Years Limited Warranty

RBC411U S.R.P. 22,850.00

40.2 mL, 1.40 kW / 2.0 PS, 2 Stroke Petrol Brushcutter




Displacement	40.2 mL
Engine power	1.40 kW / 2.0 PS
Fuel Tank Capacity	1.1 L
Spindle Size	M10 x 1.25LH
Dimensions (L x W x H)	1,710x670x430 mm (67-1/2"x26-3/8"x17")
Net weight	7.3 kg (16.1 lbs)

1.5 Years Limited Warranty

RP0900 **106** **W** S.R.P. 7,500.00

1/4" 900 W Plunge Router




Continuous rating Input	900W
Collet size	6/ N/A/ 8 mm (N/A/ 1/4/ N/A")
Plunge capacity	0 - 35 mm (0 - 1-3/8")
Base inner	64 mm (2-1/2")
No Load Speed (RPM)	27,000
Dimensions (L x W x H)	110 x 256 x 217 mm
Net weight	2.7 kg (6 lbs.)
Power supply cord	2.5 m (8.2 ft)

2.5 Years Limited Warranty

RP1111C **303** **W** S.R.P. 22,100.00

1/4" 1,100 W Variable Speed Plunge Router with Soft Start




Continuous rating Input	1,100W
Collet size	6/ N/A/ 8 mm (N/A/ 1/4/ N/A")
Plunge capacity	0 - 57 mm (0 - 2-1/4")
No Load Speed (RPM)	8,000 - 27,500
Dimensions (L x W x H)	110 x 269 x 260 mm (4-5/16 x 10-5/8 x 10-1/4")
Net weight	3.3 kg (7.3 lbs.)
Power supply cord	4.0 m (13.1 ft)

2.5 Years Limited Warranty

RP2301FC **203** **W** S.R.P. 24,500.00

1/4" / 3/8" / 1/2" 2,100 W Variable Speed Plunge Router with Electric Brake, Soft Start, Dual LED Lights




Continuous rating Input	2,100W
Collet size	1/4", 3/8", 1/2"
Plunge capacity	0 - 70 mm (0 - 2-3/4")
No Load Speed (RPM)	9,000 - 22,000
Dimensions (L x W x H)	155 x 294 x 312 mm (6-1/8 x 11-5/8 x 12-1/4")
Net weight	6.1 kg (13.5 lbs.)
Power supply cord	4.0 m (13.1 ft)

2.5 Years Limited Warranty

RP2302FC **203** **W** S.R.P. 23,300.00

1/2" 2,300 W Variable Speed Plunge Router with Soft Start, Twin LED Lights




Continuous rating Input	2,300W
Collet size	1/2"
Plunge capacity	0 - 70 mm (0 - 2-3/4")
No Load Speed (RPM)	9,000 - 23,000
Dimensions (L x W x H)	155 x 294 x 327 mm
Net weight	6.2 kg (13.7 lbs.)
Power supply cord	4.0 m (13.1 ft)

2.5 Years Limited Warranty

RP2303FC **203** **W** S.R.P. 24,550.00

2,100 W Variable Speed Plunge Router with Electric Brake, Soft Start, Twin LED Lights




Continuous rating Input	2,100W
Collet size	12/ N/A mm (N/A/ 1/2")
Plunge capacity	0 - 70 mm (0 - 2-3/4")
No Load Speed (RPM)	9,000 - 23,000
Dimensions (L x W x H)	155 x 294 x 327 mm
Net weight	6.2 kg (13.7 lbs.)
Power supply cord	4.0 m (13.1 ft)

2.5 Years Limited Warranty

RT0700C **411** **W** S.R.P. 7,500.00

1/4" 710 W Variable Speed Trimmer




Continuous rating Input	710W
Collet size	1/4"
Base inner	30 mm (1-3/16")
No Load Speed (RPM)	10,000 - 30,000
Dimensions (L x W x H)	89 x 89 x 200 mm (3-1/2 x 3-1/2 x 7-7/8")
Net weight	1.8 - 2.7 kg (3.9 - 6 lbs.)
Power supply cord	2.5 m (8.2 ft)

2.5 Years Limited Warranty

RT0702CX3 **411** **W** S.R.P. 16,000.00

1/4" 710 W Variable Speed Trimmer with Anti-Restart Function



Continuous rating Input	710W
Collet size	1/4"
Base inner	30 mm (1-3/16")
No Load Speed (RPM)	10,000 - 34,000
Dimensions (L x W x H)	89 x 89 x 210 mm (3-1/2 x 3-1/2 x 8-1/4")
Net weight	1.8 - 2.8 kg (4.0 - 6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

2.5 Years Limited Warranty

SG1251J **325** **W** S.R.P. 29,950.00

125 mm (5") 1,400 W SJS Wall Chaser with Soft Start



Continuous rating Input	1,400W
Blade diameter	125 mm (5")
Capacity	Depth: 0 - 30 mm (0 - 1-3/16") Width: 6 - 30 mm (1/4 - 1-3/16")
No Load Speed (RPM)	10,000
Dimensions (L x W x H)	350 x 151 x 178 mm (13-3/4 x 5-15/16 x 7")
Net weight	4.3 kg (9.5 lbs.)
Power supply cord	5.0 m (16.4 ft)

2.5 Years Limited Warranty



Double Insulation

Variable Speed


Mechanical 2-Speed



Electronic 3-Speed



Soft Start



Constant Speed



Hook & Loop



Dust Collection



Depth Adjustment



Auto Firing Stop



Anti Vibration






Primer pump







Capacitor Discharge Ignition







Auto Decompression



SJ401		S.R.P.	16,000.00
	406 mm (16") 50 W Variable Speed Scroll Saw		
	Continuous rating Input	50W	
	Capacity	Thickness of cut: 50 mm (2") Throat: 406 mm (16")	
	Length of Stroke	18 mm (11/16")	
	Strokes Per Minute (SPM)	400 - 1,600	
	Overall length	600 mm (23-5/8")	
	Net weight	14 kg (30.87 lbs.)	
			


SK10GD		S.R.P.	29,250.00
	12V max CXT Li-Ion XPT Rechargeable Green Multi Line Laser		
	Leveling accuracy	+/- 1 mm / 10 m	
	Self-leveling range	4°	
	Number of laser lines	2 (1V1H)	
	Laser type	Laser class 2: 515 nm	
	Operating temperature	-10 - 40°C	
	Protection class	IP54	
	Net weight	1.4 - 1.6 kg (3.1 - 3.5 lbs.)	
	Battery, Charger NOT INCLUDED		
			



SK312GDZ		S.R.P.	78,900.00
	12V max CXT Li-Ion XPT Rechargeable Green Multi Line Laser		
	Leveling accuracy	+/- 1 mm / 10 m	
	Self-leveling range	2°	
	Laser fan angle	Horizontal: 110° / Vertical: 130°	
	Number of laser lines	4 (3V1H)	
	Laser type	Laser class 2: 515 nm	
	Protection class	IP54	
	Net weight	1.5 - 1.6 kg (3.3 - 3.5 lbs.)	
	Battery, Charger NOT INCLUDED		
			



SK700D		S.R.P.	29,900.00
	12V max CXT Li-Ion XPT Rechargeable Red Multi Line Laser		
	Light output power	Less than 2.0 mW	
	Leveling accuracy	+/- 2 mm / 10 m	
	Line width	at 5 m: 2.0 mm	
	Self-leveling range	4°	
	Number of laser lines	8 (4V4H)	
	Laser type	Laser class 2: 630 - 645 nm	
	Protection class	IP54	
	Dimensions (L x W x H)	168 x 104 x 153 mm	
	Net weight	0.99 - 1.2 kg (2.2 - 2.7 lbs.)	
	Battery, Charger NOT INCLUDED		
			



SKR200Z		S.R.P.	50,550.00
	Automatic Self-Leveling Laser Level		
	Operating range	Rotating beam (diameter): 200 m Plumb beam (up to): 30 m	
	Rotation speed (rpm)	0, 300, 450, 600	
	Leveling accuracy	1 mm / 10 m	
	Leveling range	6°	
	Operating time	60 (approx. hours)	
	Power supply	Cell battery: 2 pcs	
	Net weight	1.6 kg (3.5 lbs.)	
			



TB131		S.R.P.	19,600.00
	13 mm (1/2") 250 W Compact drilling machine		
	Continuous rating input	250W	
	HP	1/3	
	Drilling capacity	Steel: 13mm (1/2") Wood: 24mm (15/16")	
	No load speed (60Hz)	690, 1070, 1560, 2280, 3200 rpm	
	Net weight	20 Kg (44.1 lbs)	
	Power supply cord	1.75 m (5.7 ft.)	
			



TD090DWE		S.R.P.	9,850.00
	10.8V Li-Ion Cordless 90 N·m (800 in.lbs.) Impact Driver		
	Capacity	Machine screw: M4 - M8 mm Standard bolt: M5 - M12 High strength bolt: M5 - M10	
	Driving shank (Hex)	6.35 mm (1/4")	
	No Load Speed (RPM)	0 - 2,400	
	Impacts per minute (IPM)	0 - 3,000	
	Max fastening torque	90 N·m (800 in.lbs.)	
	Net weight	0.92 kg (2 lbs.)	
	2 pcs. 1.3 Ah Battery, Charger.		
			



SK106GDZ		S.R.P.	37,650.00
	12V max CXT Li-Ion XPT Rechargeable Green 4-Point Cross Line Laser		
	Measuring range	Up to: 35 m	
	Leveling accuracy	With detector: Up to: 80 m +/- 3 mm / 10 m	
	Self-leveling range	4	
	Laser fan angle	Horizontal: 180° / Vertical: 170°	
	Number of laser points	4 / Lines: 2 (1V1H)	
	Laser type	Laser class 2: 525 nm	
	Dimensions (L x W x H)	138 x 64 x 102 mm	
	Net weight	0.69 - 0.85 kg (1.5 - 1.9 lbs.)	
	Battery, Charger NOT INCLUDED		
			

SK20GD		S.R.P.	35,400.00
	12V max CXT Li-Ion XPT Rechargeable Green Multi Line Laser		
	Leveling accuracy	+/- 1 mm / 10 m	
	Self-leveling range	4°	
	Number of laser lines	3 (2V1H)	
	Laser type	Laser class 2: 515 nm	
	Operating temperature	-10 - 40°C	
	Protection class	IP54	
	Net weight	1.4 - 1.6 kg (3.1 - 3.5 lbs.)	
	Battery, Charger NOT INCLUDED		
			





SK40GDZ		S.R.P.	49,750.00
	12V max CXT Li-Ion XPT Rechargeable Green Multi Line Laser		
	Leveling accuracy	+/- 1 mm / 10 m	
	Self-leveling range	4°	
	Number of laser lines	5 (4V1H)	
	Laser type	Laser class 2: 515 nm	
	Operating temperature	-10 - 40°C	
	Protection class	IP54	
	Net weight	1.4 - 1.6 kg (3.1 - 3.5 lbs.)	
	Battery, Charger NOT INCLUDED		
			

SK700GD		S.R.P.	44,850.00
	12V max CXT Li-Ion XPT Rechargeable Green Multi Line Laser		
	Light output power	Less than 2.0 mW	
	Leveling accuracy	+/- 2 mm / 10 m	
	Line width	at 5 m: 2.0 mm	
	Self-leveling range	4°	
	Number of laser lines	8 (4V4H)	
	Laser type	Laser class 2: 510 - 530 nm	
	Protection class	IP54	
	Dimensions (L x W x H)	168 x 104 x 153 mm	
	Net weight	0.99 - 1.2 kg (2.2 - 2.7 lbs.)	
	Battery, Charger NOT INCLUDED		
			

SP6000		S.R.P.	22,800.00
	165 mm (6-1/2") 1,300 W Plunge Cut Circular Saw		
	Continuous rating Input	1,300W	
	Wheel Diameter	165 mm (6-1/2")	
	Hole Diameter	20 mm (13/16")	
	Blade diameter	165 mm (6-1/2")	
	Max Cutting Capacity	0°: 56 mm (2-3/16") / 45°: 40 mm (1-9/16")	
	No Load Speed (RPM)	2,200 - 6,400	
	Dimensions (L x W x H)	341 x 225 x 250 mm	
	Net weight	4.1 kg (9 lbs.)	
			

TD0101		S.R.P.	4,750.00
	100 N·m (74 ft.lbs.) Impact Driver		
	Continuous rating Input	230W	
	Capacity	Machine screw: M4 - M8 Standard bolt: M5 - M14 High strength bolt: M5 - M10	
	Driving shank (Hex)	6.35 mm (1/4")	
	No Load Speed (RPM)	0 - 3,600	
	Impacts per minute (IPM)	0 - 3,200	
	Max fastening torque	100 N·m (74 ft.lbs.)	
	Net weight	0.99 kg (2.2 lbs.)	
			

TD110DWYE		S.R.P.	10,250.00
	12V max CXT Li-Ion Cordless 110 N·m Impact Driver		
	Capacity	Machine screw: M4 - M8 mm Standard bolt: M5 - M12 High strength bolt: M5 - M10	
	Hex shank	6.35 mm (1/4")	
	No Load Speed (RPM)	0 - 2,600	
	Impacts per minute (IPM)	0 - 3,500	
	Max fastening torque	110 N·m (970 in.lbs.)	
	Net weight	1 - 1.2 kg (2.3 - 2.6 lbs.)	
	2 pcs. 1.5 Ah Battery, Charger.		
			



TD110DZ S.R.P. 3,400.00

12V max CXT Li-Ion Cordless 110 N-m Impact Driver

Capacity Machine screw: M4 - M8 mm
Standard bolt: M5 - M12
High strength bolt: M5 - M10
6.35 mm (1/4")

Hex shank
No Load Speed (RPM) 0 - 2,600
Impacts per minute (IPM) 0 - 3,500
Max fastening torque 110 N-m (970 in.lbs.)
Net weight 1 - 1.2 kg (2.3 - 2.6 lbs.)

Battery, Charger. NOT INCLUDED

TD111DZ S.R.P. 6,100.00

12V max CXT BL XPT Cordless A-Mode (Assist Mode) 135 N-m Impact Driver

Capacity Machine screw: M4 - M8 mm
Standard bolt: M5 - M14
High strength bolt: M5 - M12
6.35 mm (1/4")

Hex shank
No Load Speed (RPM) Hard / Soft: 0 - 3,000 / 0 - 1,300
Impacts per minute (IPM) Hard / Soft: 0 - 3,900 / 0 - 1,600
Max fastening torque 135 N-m (1,200 in.lbs.)
Net weight 0.97 - 1.1 kg (2.1 - 2.5 lbs.)

Battery, Charger. NOT INCLUDED

TM30DWYE S.R.P. 10,550.00

12V max CXT Li-Ion Cordless Multi Tool

Oscillations per minute (OPM) 6,000 - 20,000
Oscillation angle Left / Right / Total: 1.6° / 1.6° / 3.2°
Dimensions (L x W x H) 277 x 65 x 98 mm (10-7/8 x 2-9/16 x 3-7/8")
Net weight 1.1 - 1.3 kg (2.3 - 2.9 lbs.)

INCLUDE: 2 pcs. 1.5 Ah Battery, Charger.

TW1000 153 S.R.P. 49,750.00

1" (25.4 mm) 1,000 N-m (738 ft.lbs.) Impact Wrench

Continuous rating Input 1,200W
Fastening capacities Standard bolt: M24 - M30 (15/16 - 1-3/16")
High strength bolt: M22 - M24 (7/8 - 15/16")

Square drive 25.4 mm (1")
No Load Speed (RPM) 1,400
Impacts per minute (IPM) 1,500
Max fastening torque 1,000 N-m (738 ft.lbs.)
Net weight 8.8 kg (19.4 lbs.)

TW140DZ S.R.P. 3,100.00

12Vmax CXT Li-Ion Cordless 3/8" (9.5 mm) 140 N-m Impact Wrench

Fastening capacities Standard bolt: M8 - M16 (5/16 - 5/8")
High strength bolt: M6 - M12 (1/4 - 1/2")
9.5 mm (3/8")

Square drive
No Load Speed (RPM) 0 - 2,600
Impacts per minute (IPM) 0 - 3,200
Max fastening torque 140 N-m (100 ft.lbs.)
Net weight 1 - 1.2 kg (2.3 - 2.7 lbs.)

Battery, Charger. NOT INCLUDED

UB100DZ S.R.P. 3,100.00

12Vmax CXT Cordless Variable 3-Speed Blower

Blowing force 1.8 N
Max Sealed Suction 4.0 kPa
No Load Speed (RPM) 0 - 15,800
Run time (min) w/ BL1016, High / Mid / Low: 8 / 20 / 45
Dimensions (L x W x H) 508 x 155 x 202 mm (20 x 6-1/8 x 8")
Net weight 1.4 - 1.9 kg (3.1 - 4.2 lbs.)

UB1103 303 S.R.P. 5,150.00

600 W Variable Speed Blower

Continuous rating Input 600W
Max air volume 0 - 4.1 m³/min
Max air velocity 0 - 91 m/s
Air pressure 0 - 5.7 kPa
No Load Speed (RPM) 0 - 16,000
Dimensions (L x W x H) 479 x 185 x 178 mm (18-7/8 x 7-1/4 x 7")
Net weight 1.9 - 2.2 kg (4.3 - 4.8 lbs.)
Power supply cord 2.5 m (8.2 ft)

TD111DWYE S.R.P. 11,600.00

12V max CXT BL XPT Cordless A-Mode (Assist Mode) 135 N-m Impact Driver

Capacity Machine screw: M4 - M8 mm
Standard bolt: M5 - M14
High strength bolt: M5 - M12
6.35 mm (1/4")

Hex shank
No Load Speed (RPM) Hard / Soft: 0 - 3,000 / 0 - 1,300
Impacts per minute (IPM) Hard / Soft: 0 - 3,900 / 0 - 1,600
Max fastening torque 135 N-m (1,200 in.lbs.)
Net weight 0.97 - 1.1 kg (2.1 - 2.5 lbs.)

INCLUDE: 2 pcs. 1.5 Ah Battery, Charger.

TM3000CX1 459 S.R.P. 10,550.00

320 W Multi Tool

Continuous rating Input 320W
Strokes Per Minute (SPM) 6,000 - 20,000
Dimensions (L x W x H) 275 x 64 x 92 mm (10-7/8 x 2-1/2 x 3-5/8")
Net weight 1.4 - 1.5 kg (3.2 - 3.3 lbs.)
Power supply cord 5.0 m (16.4 ft)

TW0350 411 S.R.P. 18,650.00

1/2" (12.7 mm) 350 N-m (260 ft.lbs.) Impact Wrench

Continuous rating Input 400W
Fastening capacities Standard bolt: M12 - M22 (1/2 - 7/8")
High strength bolt: M12 - M16 (1/2 - 5/8")
12.7 mm (1/2")

No Load Speed (RPM) 2,000
Impacts per minute (IPM) 2,000
Max fastening torque 350 N-m (260 ft.lbs.)
Net weight 3 kg (6.6 lbs.)

TW140DWYEX S.R.P. 8,800.00

12Vmax CXT Li-Ion Cordless 3/8" (9.5 mm) 140 N-m Impact Wrench

Fastening capacities Standard bolt: M8 - M16 (5/16 - 5/8")
High strength bolt: M6 - M12 (1/4 - 1/2")
9.5 mm (3/8")

Square drive
No Load Speed (RPM) 0 - 2,600
Impacts per minute (IPM) 0 - 3,200
Max fastening torque 140 N-m (100 ft.lbs.)
Net weight 1 - 1.2 kg (2.3 - 2.7 lbs.)

INCLUDE: 2 pcs. 1.5 Ah Battery, Charger.

TW202DZ S.R.P. 4,600.00

18V Li-Ion G-BATTERY Cordless Impact Wrench

Square drive 12.7 mm (1/2")
Capacity Standard bolt: M8 - M16 (5/16 - 5/8")
High strength bolt: M8 - M12 (5/16 - 1/2")

No Load Speed (RPM) 0 - 2,300 RPM
Impacts per minute (IPM) 0 - 2,300 RPM
Max fastening torque 0 - 3,000 BPM
200 N-m
Net weight 1.5 kg

Battery, Charger NOT INCLUDED

UB1102 303 S.R.P. 4,450.00

600 W Blower






Continuous rating Input 600W
Max air volume 4.1 m³/min
Max air velocity 91 m/s
Air pressure 5.7 kPa
No Load Speed (RPM) 16,000
Dimensions (L x W x H) 479 x 185 x 178 mm (18-7/8 x 7-1/4 x 7")
Net weight 1.9 - 2.2 kg (4.3 - 4.8 lbs.)
Power supply cord 2.5 m (8.2 ft)

UC100DWA S.R.P. 15,950.00

12Vmax CXT BL XPT Cordless 100 mm (4") Pruning Saw

Guide bar length 100 mm (4")
Chain speed 8.0 m/s (480 m/min)
Chain oil tank volume 55 mL (1.9 USoz)
Dimensions (L x W x H) 398 x 90 x 226 mm (15-5/8 x 3-1/2 x 8-7/8")
Net weight 1.5-1.6 kg (3.3-3.5 lbs.)
Work Amount (BL1021B) 73 cuts @ 50 mm cedar rod

INCLUDE: 1 pc. 2.0 Ah Battery, Charger.



UC4041A **132** **W** 400 mm (16"), 1,800 W S.R.P. 8,550.00
 Electric Chain Saw, Toolless Tension Adjustment

	Continuous rating Input	1,800W
	Chain speed per minute	870 m (2,900 ft)
	Guide bar length	400 mm (16")
	Dimensions (L x W x H)	455 x 245 x 200 mm
	Net weight	4.7 kg (10.5 lbs.)
	Power supply cord	0.3 m (0.98 ft)

2.5 Years Limited Warranty

UM110DWYX **G-Battery** S.R.P. 8,450.00
 18V Li-Ion Cordless 110 mm (4-5/16") Grass Shear, G-Battery

	Cutting Width	Grass shear blade: 110 mm (4-5/16") Hedge trimmer blade: 200 mm (7-7/8")
	Depth adjustment	15 / 20 / 25 mm (9/16 / 13/16 / 1")
	Strokes Per Minute (SPM)	2,500
	Continuous Use (min.)	w/ BL1815G: 65
	Dimensions (L x W x H)	w/ BL1815G: 331 x 120 x 130 mm
	Net weight	1.4 - 1.5 kg (3.1 - 3.3 lbs.)

1.5 Years Limited Warranty
 INCLUDE: Blade cover, Grass shear blade (black coating), Hedge trimmer blade (black coating), 1 pc. 1.5 Ah Battery, Charger.

UM600DZ S.R.P. 4,800.00
 12Vmax CXT Li-Ion Cordless 16 cm (6-5/16") Grass Shear

	Cutting Width	160 mm (6-5/16")
	Depth adjustment	15 / 20 / 25 mm (9/16 / 13/16 / 1")
	Strokes Per Minute (SPM)	2,500
	Continuous Use (min.)	w/ BL1016: 35
	Dimensions (L x W x H)	329 x 177 x 131 mm (13 x 7 x 5-1/8")
	Net weight	1.3 - 1.5 kg (2.8 - 3.3 lbs.)

2.5 Years Limited Warranty
 Battery, Charger NOT INCLUDED..

UN460WDZ S.R.P. 8,250.00
 12Vmax CXT XPT Cordless 460 mm Pole Hedge Trimmer

	Blade length	460 mm (18-1/8")
	Max Cutting Capacity	18 mm (11/16")
	Strokes Per Minute (SPM)	3,600
	Continuous Use (min.)	w/ BL1041B: 53
	Dimensions (L x W x H)	1,889 - 2,511 x 87 x 134 mm
	Net weight	2.8 - 3.0 kg (6.2 - 6.6 lbs.)

2.5 Years Limited Warranty

UP100DZ S.R.P. 59,300.00
 12Vmax CXT BL XPT Cordless Pruning Shears

	Capacity	Max cutting: 25 mm (1")
	Work amount using BL1021B (2.0 Ah)	about 2,200pcs When cutting ø15mm branches of Japanese cypress
	Dimensions (L x W x H)	308 x 65 x 98 mm (12-1/8 x 2-9/16 x 3-7/8")
	Net weight	0.89 - 1.1 kg (2.0 - 2.4 lbs.)

2.5 Years Limited Warranty
 Battery, Charger NOT INCLUDED..

UT2204 **303** **W** S.R.P. 17,050.00
 220 mm (8-5/8") 850 W Mixer (for High viscosity liquid)

	Continuous rating Input	850W
	Blade diameter	220 mm (8-5/8")
	No Load Speed (RPM)	550
	Shank size of tool holder	M12 or M14
	Dimensions (L x W x H)	929 x 89 x 152 mm (36-1/2 x 3-1/2 x 6")
	Net weight	2.7 kg (5.9 lbs.)

2.5 Years Limited Warranty
 Power supply cord 2.5 m (8.2 ft)

VC3210LX1 **173** **W** S.R.P. 30,000.00
 32 L Dust Class L GYUPPA Vacuum Cleaner (Wet & Dry)

	Continuous rating Input	1,050W
	Max peak air flow	2.0 m³/min
	Max sealed suction	22.0 kPa (2,240 mmHO)
	Tank capacity	Dust: 32 L Water: 27 L
	Dimensions (L x W x H)	552 x 398 x 685 mm (21-3/4 x 15-5/8 x 27")
	Net weight	14.5 kg (32 lbs.)

2.5 Years Limited Warranty
 Power supply cord 5.0 m (16.4 ft)

UH6570X **419** **W** S.R.P. 13,500.00
 650 mm (25-1/2"), 550 W Hedge Trimmer

	Continuous rating Input	550W
	Blade length	650 mm (25-1/2")
	Strokes Per Minute (SPM)	3,200
	Dimensions (L x W x H)	1,042 x 223 x 206 mm
	Net weight	3.8 - 3.9 kg (8.4 - 8.5 lbs.)
	Power supply cord	0.3 m (0.98 ft)

2.5 Years Limited Warranty

UM600DWYE S.R.P. 10,850.00
 12Vmax CXT Li-Ion Cordless 16 cm (6-5/16") Grass Shear

	Cutting Width	160 mm (6-5/16")
	Depth adjustment	15 / 20 / 25 mm (9/16 / 13/16 / 1")
	Strokes Per Minute (SPM)	2,500
	Continuous Use (min.)	w/ BL1016: 35
	Dimensions (L x W x H)	329 x 177 x 131 mm (13 x 7 x 5-1/8")
	Net weight	1.3 - 1.5 kg (2.8 - 3.3 lbs.)

2.5 Years Limited Warranty
 INCLUDE: 1 pc. 1.5 Ah Battery, Charger.

UM600DZX S.R.P. 5,750.00
 12Vmax CXT Li-Ion Cordless 16 cm (6-5/16") Grass Shear

	Cutting Width	160 mm (6-5/16")
	Depth adjustment	15 / 20 / 25 mm (9/16 / 13/16 / 1")
	Strokes Per Minute (SPM)	2,500
	Continuous Use (min.)	w/ BL1016: 35
	Dimensions (L x W x H)	329 x 177 x 131 mm (13 x 7 x 5-1/8")
	Net weight	1.3 - 1.5 kg (2.8 - 3.3 lbs.)

2.5 Years Limited Warranty
 INCLUDE: Hedge trimmer attachment, Chip reciever.
 Battery, Charger NOT INCLUDED..

UP100DSMJ S.R.P. 66,500.00
 12Vmax CXT BL XPT Cordless Pruning Shears

	Capacity	Max cutting: 25 mm (1")
	Work amount using BL1021B (2.0 Ah)	about 2,200pcs When cutting ø15mm branches of Japanese cypress
	Dimensions (L x W x H)	308 x 65 x 98 mm (12-1/8 x 2-9/16 x 3-7/8")
	Net weight	0.89 - 1.1 kg (2.0 - 2.4 lbs.)

2.5 Years Limited Warranty
 INCLUDE: 1 pc. 4.0 Ah Battery, Fast Charger, Makpac case.

UT1305 **303** **W** S.R.P. 15,100.00
 165 mm (6-1/2") 850 W Mixer (for Low viscosity liquid)

	Continuous rating Input	850W
	Blade diameter	165 mm (6-1/2")
	No Load Speed (RPM)	1,300
	Shank size of tool holder	M12
	Dimensions (L x W x H)	942 x 87 x 152 mm (37 x 3-7/16 x 6")
	Net weight	2.6 kg (5.7 lbs.)

2.5 Years Limited Warranty
 Power supply cord 2.5 m (8.2 ft)

VC1310LX1 **173** **W** S.R.P. 23,400.00
 13 L Dust Class L GYUPPA Vacuum Cleaner (Wet & Dry)




	Continuous rating Input	1,050W
	Max peak air flow	2.0 m³/min
	Max sealed suction	22.0 kPa (2,240 mmHO)
	Tank capacity	Dust: 13 L Water: 7 L
	Dimensions (L x W x H)	366 x 334 x 420 mm
	Net weight	9.6 kg (21.2 lbs.)

2.5 Years Limited Warranty
 Power supply cord 5.0 m (16.4 ft)

WR100DWYE S.R.P. 13,200.00
 12Vmax CXT XPT Cordless 47.5 N-m Ratchet Wrench

	Capacity	Standard bolt: M5 - M12 High strength bolt: M5 - M10
	Square drive	9.5 / 6.35 mm (3/8 / 1/4")
	No Load Speed (RPM)	0 - 800
	Max fastening torque	47.5 N-m (420 in.lbs.)
	Net weight	1.0 - 1.2 kg (2.3 - 2.7 lbs.)

2.5 Years Limited Warranty
 INCLUDE: 2 pc. 1.5 Ah Battery, Charger..



<p>LXT 18V LITHIUM-ION</p> <p>MKP3PG184 6.0 Ah 198091-4 S.R.P. 36,500.00</p> <p>MAKPAC 3 (196649-3) + 4 pcs BL1860B (197424-0) + 1 unit DC18RD 2 Port Fast Charger (196933-6)</p>  <p>Charging time: 55 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>MKP1RG184 6.0 Ah 198140-7 S.R.P.</p> <p>MAKPAC 3 (196649-3) + 4 pcs BL1860B (197424-0) + 1 unit DC18RC Single Port Fast Charger (630718-5)</p>  <p>CURRENTLY NOT AVAILABLE</p> <p>Charging time: 55 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>MKP3PG182 6.0 Ah 198077-8 S.R.P. 22,600.00</p> <p>MAKPAC 3 (196649-3) + 2 pcs BL1860B (197424-0) + 1 unit DC18RD 2 Port Fast Charger (196933-6)</p>  <p>Charging time: 55 mins</p>
<p>LXT 18V LITHIUM-ION</p> <p>MKP1RG182 6.0 Ah 198116-4 S.R.P. 21,100.00</p> <p>MAKPAC 1 (196647-7) + 2 pcs BL1860B (197424-0) + 1 unit DC18RC Single Port Fast Charger (630718-5)</p>  <p>Charging time: 55 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>MKP3PT182 5.0 Ah 197629-2 S.R.P. 21,600.00</p> <p>MAKPAC 3 (196649-3) + 2 pcs BL1850B (632F15-1) + 1 unit DC18RD 2 Port Fast Charger (196933-6)</p>  <p>Charging time: 45 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>MKP1RT182 5.0 Ah 197624-2 S.R.P.</p> <p>MAKPAC 1 (196647-7) + 2 pcs BL1850B (632F15-1) + 1 unit DC18RC Single Port Fast Charger (630718-5)</p>  <p>CURRENTLY NOT AVAILABLE</p> <p>Charging time: 45 mins</p>
<p>LXT 18V LITHIUM-ION</p> <p>MKP1RT181 5.0 Ah 198624-5 S.R.P. 12,000.00</p> <p>MAKPAC 1 (196647-7) + 1 pc BL1850B (632F15-1) + 1 unit DC18RC Single Port Fast Charger (630718-5)</p>  <p>Charging time: 45 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>MKP1RF182 3.0 Ah 197952-5 S.R.P.</p> <p>MAKPAC 1 (196647-7) + 2 pcs BL1830B (632G12-3) + 1 unit DC18RC Single Port Fast Charger (630718-5)</p>  <p>CURRENTLY NOT AVAILABLE</p> <p>Charging time: 22 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>MKP1RF181 3.0 Ah 197624-2 S.R.P.</p> <p>MAKPAC 1 (196647-7) + 1 pc BL1830B (632G12-3) + 1 unit DC18RC Single Port Fast Charger (630718-5)</p>  <p>CURRENTLY NOT AVAILABLE</p> <p>Charging time: 22 mins</p>
<p>LXT 18V LITHIUM-ION</p> <p>DC18RCBL1830B 3.0 Ah S.R.P. 8,000.00</p> <p>1 pc BL1830B (632G12-3) + 1 unit DC18RC Single Port Fast Charger (630718-5) + Carton box</p>  <p>Charging time: 22 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>Starter Kit 3.0 Ah 199994-5 S.R.P. 7,250.00</p> <p>1 pc BL1830B (632G12-3) + 1 unit DC18SD Single Port Standard Charger + Carton box</p>  <p>Charging time: 60 mins</p>	<p>LXT 18V LITHIUM-ION</p> <p>BL1860B 197422-4 S.R.P. 8,960.00</p> <p>ENERGY CAPACITY 108 Wh 6.0 Ah</p> 
<p>LXT 18V LITHIUM-ION</p> <p>BL1850B 632F15-1 S.R.P. 6,600.00</p> <p>ENERGY CAPACITY 90 Wh 5.0 Ah</p> 	<p>LXT 18V LITHIUM-ION</p> <p>BL1830B 632G12-3 S.R.P. 6,000.00</p> <p>ENERGY CAPACITY 54 Wh 3.0 Ah</p> 	<p>LXT 18V LITHIUM-ION</p> <p>DC18RD 196933-6 S.R.P. 9,600.00</p> <p>2 PORT FAST CHARGER CHARGING TIME BL1830B: 22 mins BL1850B: 45 mins BL1860B: 55 mins</p> 

DC18RC 630718-5
S.R.P. 5,000.00

SINGLE PORT FAST CHARGER

CHARGING TIME
BL1830B: 22 mins
BL1850B: 45 mins
BL1860B: 55 mins

DC18SE 194621-9
S.R.P. 6,430.00

SINGLE PORT AUTO CHARGER

CHARGING TIME
BL1830B: 60 mins
BL1850B: 110 mins
BL1860B: 130 mins

DC18WC 630D27-6
S.R.P. 3,100.00

SINGLE PORT BUDGET CHARGER

CHARGING TIME
BL1830B: 80 mins
BL1850B: 130 mins
BL1860B: 160 mins

G-Battery

BL1815G 198186-3
S.R.P. 3,740.00

ENERGY CAPACITY
90 Wh

1.5 Ah

G-Battery

DS18WA 195423-6
S.R.P. 5,000.00

SINGLE PORT CHARGER

CHARGING TIME
BL1815G: 70 mins
BL1820G: 90 mins

G-Battery

DC18WB 191W37-7
S.R.P. 2,500.00

SINGLE PORT CHARGER

CHARGING TIME
BL1815G: 80 mins
BL1820G: 105 mins

CXE 12Vmax LITHIUM ION

MKP1SA122 2.0 Ah 197658-5
S.R.P. 9,080.00

MAKPAC 1 (196647-7)
+
2 pcs BL1021B (197396-9)
+
1 unit DC10SB Fast Charger (197363-1)

Charging time: 30 mins

CXE 12Vmax LITHIUM ION

MKP1WY122 1.5 Ah 197644-6
S.R.P. 6,710.00

MAKPAC 1 (196647-7)
+
2 pcs BL1016 (197393-5)
+
1 unit DC10WD Standard Charger (197343-0)

Charging time: 50 mins

CXE 12Vmax LITHIUM ION

MKP1WM122 4.0 Ah 197648-8
S.R.P. 11,600.00

MAKPAC 1 (196647-7)
+
2 pcs BL1041B (632F63-0)
+
1 unit DC10WD Standard Charger (197343-0)

Charging time: 130 mins

CXE 12Vmax LITHIUM ION

MKP1SM122 4.0 Ah 197641-2
S.R.P. 10,480.00

MAKPAC 1 (196647-7)
+
2 pcs BL1041B (632F63-0)
+
1 unit DC10SB Fast Charger (197363-1)

Charging time: 60 mins

CXE 12Vmax LITHIUM ION

BL1021B 197396-9
S.R.P. 2,520.00

ENERGY CAPACITY
21.6 Wh

2.0 Ah

CXE 12Vmax LITHIUM ION

BL1041B 632F63-0
S.R.P. 3,680.00

ENERGY CAPACITY
43.2 Wh

4.0 Ah

CXE 12Vmax LITHIUM ION

DC10WD 197343-0
S.R.P. 3,140.00

STANDARD CHARGER

CHARGING TIME
BL1016: 50 min
BL1021B: 70 min
BL1041B: 130 min

CXE 12Vmax LITHIUM ION

DC10SB 630996-7
S.R.P. 3,620.00

FAST CHARGER

CHARGING TIME
BL1016: 22 min
BL1021B: 30 min
BL1041B: 60 min