

KEMILUX takes care of your heavy duty cleaning



HG-2 EXTRA

Provides clean and clear surfaces

HG-2 EXTRA is an acidic cleaning and descaling agent.

In food production, to avoid problems with bacteria of a finished product, it is important to maintain a consistently high cleaning procedure. Regarding cleaning procedures it is important to change from an alkaline to an acidic environment. Food processing companies that daily clean with a basic/alkaline cleaning agents such as S-2 EXTRA by KEMILUX are advised to use HG-2 EXTRA to change the pH value. Alternating between S-2 EXTRA and HG-2 EXTRA prevents the build up of resistant bacteria.



More than 50 years of experience

KEMILUX offers you a complete range of quality cleaning agents. KEMILUX has more than 50 years of experience as a supplier for industrial, marine environment and food processing plants. We are ISO 9001 certified and qualified in the Achilles JQS.

KEMILUX

www.kemilux.com



HG-2 EXTRA

- Product:** Descaling cleaning agent for food processing and fishing industries.
- Properties:** HG-2 EXTRA simultaneously descales and cleanses. Results in clean and clear surfaces.
- Usage:** Apply with atomizer, sponge or brush. Take effect: 10-15 minutes. Do not let the solvent dry. If the solvent dries, apply again. Rinse with plenty of water.
- Storage:** Store in tightly closed original container. Keep in a non-freezing place. Store securely and keep out of the reach of children.
- Approval:** The product complies with the general requirements set by the General Food Law for products used in food producing industries. This means, that if the product is used and dosed correctly or under the right conditions, the product does not release components to food products to an extent that may endanger human health.
- Warning:** Avoid contact with materials that contain chlorine, poisonous gas may be generated. Keep the product away from nylon and galvanized steel.
- Safety:** Please find information about handling and disposal in the Safety Data Sheet.

The Safety Data Sheet can be accessed here: www.kemilux.com



INSTR. FOR USE AND DOSAGE

DOSAGE:	approx. 10%
DOSAGE FOR FOAMING	
EQUIPMENT:	approx. 4-6%
TEMPERATURE:	5-40 C°
TAKE EFFECT:	10-15 minutes

PRODUCT DATA

APPEARANCE:	Clear, colourless liquid
STATE:	Liquid
ODOUR:	Faint
DENSITY G/ML:	1,10
PH CONCENTR.:	0,5
PH VALUE WHEN MIXED:	1,4

HG-2 Extra is recommended for:

- Food processing industries
- Floors and walls in production facilities
- Machines
- Industrial kitchens
- Machine parts
- Running rust



PACKAGING: 10L, 20L, 210L, 1000L

KEMILUX