Champion

The Dishwashing Machine Specialists

Project		
Item No		
Quantity		

STANDARD FEATURES

- **NEW** Factory authorized startup
- **ENERGY STAR® Qualified**
- **NEW Exclusive** Built-in booster configured for both 40° and 70° Rise
- Field convertible from straight to corner operation
- Dual NSF listed as both a dishwasher and potwasher
- Rinse Sentry ensures 180°F final rinse
- Auto start starts unit when hood is closed
- Single point electrical connection
- High efficiency 2 HP pump
- Up to 60 racks per hour
- Self draining pump
- Automatic tank fill
- Detergent/chemical connections
- Interchangeable upper and lower spray arms
- Automatic drain valve drains wash tank when power is off
- Vent fan control (with 120 Volt interwiring by others)
- Bottom mounted digital controls
- PRV (Mounted Pressure Reducing Valve)
- Sloped hood keeps hot vapors away from operator
- Standard and Heavy Duty wash cycles
- 4 selectable cycles
- 27" [686mm] extended clearance

DH50001

DH5000T High Temperature Hood-type Dishwashing Machine











OPTIONS & ACCESSORIES

☐ Drain Water Tempering Kit
☐ Door interlock – locks door closed during the vent fan cycle
☐ Hot water coil with gas booster
(contact factory for info)
☐ Single phase option
Racks
☐ Peg
☐ Flat
☐ Sheet Pan rack
☐ Corner operation splash baffle
☐ NEW Champion ION scale prevention system

SPECIFIER STATEMENT

Specified unit will be Champion model DH5000T high temperature hood-type dishwashing machine.

Features sloped hood, electronic controls, Rinse Sentry, Auto start, interchangeable stainless steel wash and rinse arms, up to 60 racks/hr., .85 US gals [3.37 liters, 0.74 imp. gals]/rack. 1 year parts and labor warranty.

> Champion Industries, Inc. 3765 Champion Blvd., Winston-Salem, NC 27105 Tel: 336/661-1556 Fax: 336/661-1979

> > 2674 N. Service Road Jordan Station, Ontario, Canada LOR 1S0 Tel: 800/263-5798 Fax: 905/562-4618


> > > www.championindustries.com

Champion The Dishwashing Machine Specialists


DH5000T

DH5000T High Temperature Hood-type Dishwashing Machine

Shipping weight crated: 300 lbs.




Typical Table Construction



Utilities

- **Electrical** Machine Connection (See Electrical Box)
- **Hot Water** 3/4" NPT Hot Water 110° - 140°F/43° - 60°C 20-22 PSI Flow Pressure
- 3 2" [51mm] OD Connection 15 GPM Max Flow
- **Exhaust** 250 CFM Hood Required



90-15/16

Side

View

Warning: Plumbing, electrical connections should be made by qualified personnel who will observe all the applicable plumbing, sanitary and safety codes and the National Electrical Code.

Electric Heat, No Booster				
Voltage	Rated Amps	Minimum Supply Circuit Ampacity	Maximum Overcurrent Protective Device	
208-240/60/1	35-39	45	45	
208-240/60/3	21-24	30	30	
460-480/60/3	11	20	20	

Machine and Built-in Booster				
Voltage	Rated Amps	Minimum Supply Circuit Ampacity	Maximum Overcurrent Protective Device	
208-240/60/1	71-81	100	100	
208-240/60/3	42-48	60	60	
460-480/60/3	20-21	30	30	

Due to an ongoing value analysis program at Champion, specifications contained in this catalog are subject to change without notice.


Champion Industries, Inc.

3765 Champion Blvd., NC 27105 • 336/661-1556 • Fax: 336/661-1979 •

2674 N. Service Road, Jordan Station, Ontario, Canada LOR 1SO • 800/263-5798 • Fax: 905/562-4618

ChampionIndustries.com • ChampionIndustries.com/canada • sales@moyerdiebellimited.com

Dimensions shown in inches and [mm]



Straight Thru Configuration



Corner Configuration

SPECIFICATIONS

Capacities

lotor horsepower	2 HP
Wash tank (gal.) [liters/imp gal.]	9.5 [36/7.9]
Racks per hr.	60

Water consumption

Gal. per hr. (max. use)	47
[liters/imp gal.]	[177/39]
Gal. per rack (dishwasher)	0.85
[liters/imp gal.]	[3.2/0.7]
Gal. per rack (pot & pan washer)	1.18
[liters/imp gal.]	[4.5/0.98]

Temperature °F/°C

Wash	150/66
Rinse	180/82
Heating	
Tank heat, electric	5.2 kW

7.5-10 kW

Electric Booster Time cycle in seconds

Dish	washer	Mode	Pot/Pan Mode		
Wash	35	65	214	334	
Rinse	10	10	15	15	
Sanitary Dwell	15	15	11	11	
Total cycle	60	90	240	360	

an Ali Group Company

