

Item #	

Job _____


MetroMax® Q Mobile Polymer Shelving / Stem Caster Carts

Quick-to-adjust, corrosion resistant mobile shelving offers a sturdy, long lasting movable storage solution or transport cart. Rigid one-piece shelf frame with wraparound corners provides complete 360° capture of the wedge and post to ensure stability, and overall strength. Shelves have polymer shelf mats that are impact resistant for long life and quick-to-remove for easy routine cleaning. The shelf frames have a durable epoxy coating over an electroplated substrate. Shelves offer a 20 year warranty against corrosion. Rust proof polymer posts offer a lifetime warranty against corrosion. Shelf mats and posts have built-in Microban® antimicrobial product protection. Proprietary quick-release corner release enables fast, notool shelf adjustment. Each cart can safely store or transport 900lbs. (408kg). Units assemble easily — Shelves mount on four one-piece wedges along grooved, numbered posts. Shelves adjust on 1" (25mm) increments.

- Preconfigured Units: include shelves, posts, and casters under one easy to order model number. Choose models that fit the application: Rust resistant polymer casters for wet conditions. Chrome plated casters for general storage areas.
- Forever Strong: Proven corner connection and four-sided shelf frame with center truss(es) assures stability and impact resistance over thresholds in mobile uses: 800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1219mm) 600 lbs. (272kg) per shelf for lengths of 54" (1372mm) or longer Mobile unit: up to 900lbs (408kg) evenly distributed.
- Life-Long Rust Resistant: Shelves offer a 20 year warranty against rust and corrosion. Polymer posts are rust-proof; lifetime warranty against rust and corrosion.
- Easy to Clean and Maintain: Polymer mats can be easily removed and cleaned in a sink or commercial washer / dish machine.
- Microban® Antimicrobial Product Protection: built into the shelf mats and posts to inhibit the growth of bacteria, mold, mildew, and fungus that cause odors and product degradation. Microban product protection keeps the product "cleaner between cleanings".
- Quick-to-Adjust: Patented corner release allows shelves to be adjusted without tools.
 Simply flip each corner release, relocate the wedge connectors on the posts, and reposition the shelf. Quickly adjust shelves to reclaim wasted vertical space.
- Efficient Use of Space: Shelves adjust on 1" (25mm) increments along the post to maximize the use of available vertical space.
- Fast, Easy Assembly: Shelves are ready to use right out of the box. One-piece
 wedges securely attach to the posts Raised beads on the back of each wedge snap
 into the grooves on the post. Window on wedge aligns with numbers on the post to
 locate the desired shelf position. Shelf seats into position over the posts and wedges. A
 unit can be assembled without tools in minutes.
- Four-shelf models consists of sectioned open grid (vented) polymer shelf mats that promote air circulation and light penetration. Built-in ship's edge helps contain supplies.
- · Five-shelf models have one solid bottom shelf with a one-piece removable shelf mat.
- · NSF Listed for all environments.
- · Maximum Versatility: Complete line of accessories are found on spec sheet 9.25.













MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.



InterMetro Industries Corporation

18x36

18x48

18x60

24x36

24x48

24x60

Width/Length (in.)

457x914

457x1219

457x1524

610x914

610x1219

610x1524

We put space to work.

Rust Resistant,

5PCX caster

5MPX caster

MetroMax® Q Mobile Shelving

Material Specifications:

- Shelf Mats: Injection-molded polypropylene with exclusive built-in Microban® antimicrobial product protection.
- Shelf frames and epoxy-coated posts: Steel with electroplated substrate and highly durable, abrasion-resistant epoxy finish. The adjustable foot is reinforced nylon.
- Polymer Post: Pultrusions continuous glass fibers and thermoset resin composite with built-in Microban® antimicrobial product protection.
- Shelf Wedge Connector: Reinforced nylon.
- Temperature: -20°F (-29°C) to 125°F (52°C) continuous use, with intermittent exposure to 200°F (93°C) for cleaning.
- Visit metro.com/service-support for cleaning guidelines.

Mobile Shelving units include shelves, posts, stem casters & bumpers.

- "-MP-" models include (2) swivel and (2) swivel/brake rust resistant polymer casters with polyurethane horns.
 "EGX3" models include 2 swivel & 2 swivel/brake polyurethane casters with plated horns.
- 4-shelf models include (4) open grid shelves.
- 5-shelf models include (4) open grid shelves and a solid bottom MetroMax i shelf.
- Note the heights of doorways. Models with 75-5/16" (1913mm) and shorter are best suited to clear doorways.

4-Shelf Open Grid Mats - Unit Height 67 5/16 (1710mm)							
Nominal Width/Length (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		Cat. No. Polymer Caster Polyurethane Tread	Cat. No. Plated Caster Polyurethane Tread		
18x36	457x914	54.0	24.5	MQ-183668G-MP-4	Q336EG3		
18x42	457x1060	60.8	27.6	MQ-184268G-MP-4			
18x48	457x1219	68.0	30.8	MQ-184868G-MP-4	Q356EG3		
18x60	457x1524	82.0	37.2	MQ-186068G-MP-4	Q366EG3		
21x36	530x914	60.8	27.6	MQ-213668G-MP-4	Q436EG3		
21x42	530x1060	66.4	30.1	MQ-214268G-MP-4			
21x48	530x1219	73.2	33.2	MQ-214868G-MP-4	Q456EG3		
21x60	530x1524	89.2	40.5	MQ-216068G-MP-4	Q466EG3		
24x36	610x914	67.6	30.7	MQ-243668G-MP-4	Q536EG3		
24x42	610x1060	75.6	34.3	MQ-244268G-MP-4			
24x48	610x1219	78.4	35.6	MQ-244868G-MP-4	Q556EG3		
24x60	610x1524	96.4	43.7	MQ-246068G-MP-4	Q566EG3		

-4-Shelf - Unit Height 75 5/16 - (1913mm)						
	App Pkd. (lbs.)		Cat. No. Polymer Caster Polyurethane Tread			
	54.8	24.9	MQ-183676G-MP-4			
	61.6	27.9	MQ-184276G-MP-4			
	68.8	31.2	MQ-184876G-MP-4			
	82.8	37.6	MQ-186076G-MP-4			
	61.6	27.9	MQ-213676G-MP-4			
	67.2	30.5	MQ-214276G-MP-4			
	74.0	33.6	MQ-214876G-MP-4			
	90.0	40.8	MQ-216076G-MP-4			
	68.4	31.0	MQ-243676G-MP-4			
	72.4	32.8	MQ-244276G-MP-4			
	79.2	35.9	MQ-244876G-MP-4			
	07.0	444	MO 0460760 MD 4			

97.2 44.1 MQ-246076G-MP-4











Utility Carts - 39-1/4" (997mm tall)

(lbs.)

72.8 33.0

42.0

48.4

40.3

Note: 79-5/16" (2015mm) tall unit uses 74" (1890mm) posts (MX74UP).

(kg)

92.7

106.8

88.8

105.3 47.8

124.8 56.6

Quick Adjust MetroMax Q shelves, polymer posts, and Type 304 Stainless handle

5-Shelf (4) Open Grid, (1) solid Unit Height 79 5/16 (2015mm)

Cat. No. Polymer Caster Polyurethane Tread

MQ-183680G-MP-5

MQ-184880G-MP-5

MQ-186080G-MP-5

MQ-243680G-MP-5

MQ-244880G-MP-5

MQ-246080G-MP-5

Actual Dimensions including Bumpers: Add 2-5/16" (59mm) to width and 1-3/4" (45mm) to length.

· Corrosion resistant polymer horn casters can safely move up to 900lbs (408kg)

Nominal Width/Length			Actual Width/Length			Approx. Pkd. Wt.			
(in.)	(mm)	(in.)	(mm)	Description	(lbs.)	(kg)	Cat. No.		
18x30	457x760	20 ⁵ / ₁₆ x 34 ¹ / ₂	516 x 876	2-shelf	30.0	13.6	MQUC1830G-25		
24x36	610x914	26 ⁵ / ₁₆ x 40 ¹ / ₂	668 x 1029	2-shelf	40.4	18.3	MQUC2436G-25		
18x30	457x760	20 ⁵ / ₁₆ x 34 ¹ / ₂	516 x 876	3-shelf	40.4	18.3	MQUC1830G-35		
24x36	610x914	26 ⁵ / ₁₆ x 40 ¹ / ₂	668 x 1029	3-shelf	56.0	25.4	MQUC2436G-35		



5Q337EG3

5Q357EG3

5Q367EG3

5Q537EG3

5Q557EG3

5Q567EG3

