

## Door-Type Dishwashing Machines

### Standard Features

- Automatic tank fill
- Control circuit, 120-Volt
- Built-in stainless steel electric booster
- Detergent/chemical connection provisions
- Water pressure regulating valve (unmounted)
- Door safety switch
- Automatic drain valve
- Vent fan control
- Stainless steel enclosure panels
- Interchangeable upper and lower spray arms
- Low-water tank heat cut-off
- Racks: 1 peg rack and 1 flat rack



		Standard Voltages	Approx. Ship. Wt.
<b>High Temperature</b>			
<b>DH6000</b>	Electric (no booster)	208-240/60/1 or	300 lbs.
	Electric (70°F rise)	208-240/60/3 or 480/60/3	
<b>ENERGY STAR® Qualified</b>			
<b>DH6000-VHR</b>	Ventless Heat Recovery Option	208-240/60/1 or	350 lbs.
	Electric (70°F rise)	208-240/60/3 or 480/60/3	
<b>ENERGY STAR® Qualified</b>			
<b>DH6000</b>	Electric (70°F rise)	208-240/60/1 or 208-240/60/3	300 lbs.
<b>ENERGY STAR® Qualified</b>			
<b>DH2000</b>	Electric	208-240/60/1 or 208-240/60/3	300 lbs.
<b>Low Temperature</b>			
<b>DL2000</b>	Electric	115/60/1	218lbs.

### Options

Drain Water Tempering Kit (unmounted)	
Peg or Flat Racks (specify type)	(each)
Water Pressure Regulating Valve (unmounted – standard when machine has booster)	
Shock Arrestor (unmounted)	
Side Panels for DH2000 (standard on DH6000)	
Flanged Feet	
Splash Shield (for corner DH6000) (mounted to machine)	
Door Interlock Switch (DH6000 VHR only)	
ION Scale Prevention System (unmounted)	

NON STANDARD VOLTAGES: Contact Factory for availability and price. NOTE: Options prices apply only when ordered with machine.