

ALBATROSS PLAST-WIPE

Effective Date: January 1, 2006

General Description:

Plast-Wipe press side wash works quickly and efficiently on plastisol inks to open dried or clogged images during production runs. It has a moderate evaporation rate and will not leave any solvent residue on the screen. It is also ideal from quickly washing the screen after the press run. Plast Wipe has a higher flashpoint than lacquer thinner, alcohols & ketones.

Advantages:

- No hazardous ingredients
- Removes plastisol inks
- Conditions screens
- Meets SARA Title III Requirements
- Moderate evaporation rate

Directions for Use:

1. To remove ink from screen images: Card excess ink off of screen. Apply Plast-Wipe to squeegee side of screen. Wipe off ink.
2. To clean screen following production run: Scrape off remaining ink. Apply Plast-Wipe to both side of screen. Wipe off ink.

Packaging/Shipping Specifications:

Item No.	Package Size	Case Pack	Case Weight	Hazmat Information
4007	1-Gallon (3.8 liters)	4 Containers	37 lbs.	Non-Hazardous
4008	5-Gallon (19 liters)	1 Pail	45 lbs.	Non-Hazardous
4009	55-Gallon (209 ltrs)	1 Drum	450 lbs.	Non-Hazardous

Physical Properties:

Appearance: Clear Colorless Liquid

Solubility in Water: Soluble

Odor: Mild / Citrus

Chemical Family: Isoparaffinic Hydrocarbon & Glycol ether blend.

Environmental:

Volatile Organic Compound (VOC): Yes – 798 grams per liter

Hazardous Air Pollutant (HAP): No

Ozone Depleting Substance: No

SARA 313 Chemicals: No

Consult material safety data sheet for all safety and handling information.