

# NEW PRODUCT SERIES

Technical Information Spec-sheet

## AQUABLU

Official Distributor

(800) 971-1442

www.aquablumosaics.com



# International Wholesale Tile, LLC

SERIES NAME

**ARGOS**

### TECHNICAL CHARACTERISTICS

Available Formats:	19x22 Hex Atelier White		
Style Description:	Cement	Glaze Application Method:	Inkjet
Visual Characteristics:	Satin Hex	Number of Faces/Screens:	16
Thickness in mm:	10	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Satin
Rectified or Pressed	Pressed	Recommended Grout Joint:	3 MM

### PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.56
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GA-GLA/GHA-5		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ARGOS**

## TECHNICAL CHARACTERISTICS

Available Formats:	19x22 Hex Black & White		
Style Description:	Plain Color	Glaze Application Method:	Inkjet
Visual Characteristics:	Solid Color Hex	Number of Faces/Screens:	1
Thickness in mm:	10	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	White Residential/Commercial Black Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Textured
Rectified or Pressed	Pressed	Recommended Grout Joint:	3 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.39
Scratch Hardness (MOHS)	6	Breaking Strength:	>1300
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	4-White/3-Black	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GA-GLA/GHA-5		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ARGOS**

## TECHNICAL CHARACTERISTICS

Available Formats:	19x22 Dolomite		
Style Description:	Dolomite Marble	Glaze Application Method:	Inkjet
Visual Characteristics:	Marble Hex	Number of Faces/Screens:	20
Thickness in mm:	10	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Satin
Rectified or Pressed	Pressed	Recommended Grout Joint:	3 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.39
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GA-GLA/GHA-5		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ARGOS**

## TECHNICAL CHARACTERISTICS

Available Formats:	19x22 Thassos Gold		
Style Description:	Calacatta Gold Marble	Glaze Application Method:	Inkjet
Visual Characteristics:	Marble Hex	Number of Faces/Screens:	20
Thickness in mm:	10	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Satin
Rectified or Pressed	Pressed	Recommended Grout Joint:	3 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.39
Scratch Hardness (MOHS)	7	Breaking Strength:	>1300
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GA-GLA/GHA-5		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*

**AQUABLU**

Official Distributor  
(800) 971-1442

[www.aquablumosaics.com](http://www.aquablumosaics.com)