

# NEW PRODUCT SERIES

Technical Information Spec-sheet

## AQUABLU

Official Distributor

(800) 971 1442

www.aquablumosaics.com



# International Wholesale Tile, LLC

SERIES NAME

**ESAMARINE**

### TECHNICAL CHARACTERISTICS

Available Formats:	6.25X7.25 Glossy Hex		
Style Description:		Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	20
Thickness in mm:	8.5 mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Polished
Rectified:	Pressed	Recommended Grout Joint:	2 MM

### PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

### PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	5.38	Pieces per Carton:	22
SqFt per Pallet:	538	Pounds per Carton:	
Boxes per Pallet:	100	SqFt per Container:	
Pallets per Container:	22		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.