

NEW PRODUCT SERIES

Technical Information Spec-sheet

AQUABLU

Official Distributor

(800) 971 1442

www.aquablumosaics.com



International Wholesale Tile, LLC

SERIES NAME

FORM

TECHNICAL CHARACTERISTICS

Available Formats:	8x8, 7x8		
Style Description:	Cement	Glaze Application Method:	Inkjet
Visual Characteristics:	Cement	Number of Faces/Screens:	20
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2, V3, V4	Dynamic COF:	>.55/R9
Scratch Hardness (MOHS)	6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Class A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".