



<b>MATERIAL</b>	LIMESTONE	<b>WEIGHT</b>	
		LEDGER PANEL	10.00 LBS PER PC
<b>ORIGIN</b>	TURKEY	DOGEAR CORNER	10.00 LBS PER SET
<b>FINISH</b>	NATURAL	<b>CASE/CRATE QTY</b>	
		LEDGER PANEL	6 PCS/180 PCS
<b>JOINT SYSTEM</b>	INTERLOCKING	DOGEAR CORNER	6 SETS/180 SETS
<b>PART NUMBER</b>		<b>COLOR</b>	LINEN
LEDGER PANEL	LIMLYMRAAPANELN		
DOGEAR CORNER	LIMLYMRAADOGearn	<b>GROUT LINE</b>	NO GROUT REQUIRED
<b>DIMENSIONS</b>		<b>APPLICATIONS RESIDENTIAL</b>	
LEDGER PANEL	6"X24" (NOMINAL)	EXTERIOR, INTERIOR, WALLS, KITCHEN BACKSPASHES, FACADES	
DOGEAR CORNER	6"X6", 6"X18" (NOMINAL)	FEATURE WALLS, FIREPLACES, CHIMNEYS, RETAINING WALLS	
		STONE PILLARS, STONE COLUMNS, POOL SURROUNDS, AND ANY	
<b>THICKNESS</b>	1/2"-1-1/4"	OTHER VERTICAL APPLICATIONS	
<b>SOLD BY</b>		<b>APPLICATIONS COMMERCIAL</b>	
LEGER PANEL	PC	EXTERIOR, INTERIOR, HOSPITALITY, RETAIL, LANDSCAPE, FEATURE WALL	
DOGEAR CORNER	SET		

**Limestone Disclaimer:**

All Limestones should be cleaned and/or washed of any residue or dust on the surface of the stone prior to installation, grouting, and sealing. Allow 24-48 hours for drying prior to installation. Sealing limestone is highly recommended, please contact a professional for the most appropriate sealer for your application.

**WARNING: READ PRIOR TO INSTALLATION:**

Natural stones are products of nature and are prone to variations in color, texture, shading and veining that may differ from displays. Variations are not considered flaws as no two pieces of stone are alike, Prior to installation, ensure enough material, including waste is purchased for the entire project. Mix product from various cartons, and lay out all tiles and coordinating pieces to ensure optimal blending prior to installation. Natural stone products should be sealed prior to grouting. NO CLAIMS WILL BE ACCEPTED AFTER THE MATERIAL HAS BEEN INSTALLED

**AQUABLU**

Official Distributor

(800) 971-1442

www.aquablumosaics.com