NEW PRODUCT SERIES

Technical Information Spec-sheet



Official Distributor (800) 971 1442 www.aguablumosaics.com





SERIES NAME

MILANO

TECHNICAL CHARACTERISTICS				
Available Formats:	8.5x9.75			
Style Description:	Embossed Hex	Glaze Application Method:		
Visual Characteristics:	Embossed Hex	Number of Faces/Screens:		
Thickness in mm:		Number of Punches/Molds:	1	
Modular Suitability:	Yes	Body Type:	Porcelain	
Application:	Residential	Color Body Unglazed:	Off White	
Recycled Content:		Surface Type:	Satin/Flat	
Post or Pre Customer				
Rectified or Pressed	Pressed	Recommended Grout Joint:	2 MM	

PRODUCT TESTING INFORMATION				
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)				
Water Absorption:	<0.5%	Static COF:		
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.42	
Scratch Hardness (MOHS)	6	Breaking Strength:	>1300 N	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant	
PEI/Abrasion Resistance:	White- 3, Black- 2	Deep Abrasion Test		
		<175mm ² :		
Chemical Resistance:	Resistant			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".