

Colors








Red 2"x10"



Taupe 2"x10"



White Brick 2"x10"



Charcoal 2"x10"

Cobble 2"x10"

Fog 2"x10"

Putty 2"x10"

				<u> </u>	
Size	Thickness	IVORY	RED	TAUPE	WHITE BRICK
2-1/3X10	3/8"	NCAPIVOBRI2X10	NCAPREDBRI2X10	NCAPTAUBRI2X10	NCAPWHIBRI2X10
5x10	3/8"	NCAPIVOBRI5X10	NCAPREDBRI5X10	NCAPTAUBRI5X10	
Size	Thickness	FOG	COBBLE	PUTTY	CHARCOAL
2-1/3X10	3/8"	NCAPEOGBRI2X10	NCAPCOBBRI2X10	NCAPPUTBRI2X10	NCAPCHABRI2X10

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	•	•	•						
LIGHT COMMERCIAL	•	•	•	IV	V4	DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
HEAVY COMMERCIAL		•	•						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed	
Resistant	Resistant	Pressed	Glazed	

The new "brick" tiles will add to the existing cotto and wood planks of this great looking, trend forward series, Capella. The brick tiles can be featured as a back splash or to compliment the cotto or wood planks for both floor and wall applications. Available in two realistic brick sizes 21/3"x10" and 5"x10".

Technical Information

Primary Colors: Beige, Ivory, Red, White Material Type: Glazed Porcelain

Finish: Matte

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Features At A Glance

- · Real brick looks created with porcelain
- Classic 21/3 x10 in four colors and 5 x10 sizing in 3 different colors
- Ink Jet technology with 3D punch for realistic brick looks Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer: Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile. To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns. *No claims accepted after tile installation.