MSI

Making Dream Surfaces Attainable







AQUABLU

Official Distributor (800) 971-1442 www.aquablumosaics.com Dekora

Porcelain Collection

Colors







Ardesia Black 6"x24"

Keywood Multicolor 6"X24"

Midnight Mount 6"X24"







Rocky Gold 6"x24"

Palisade Grey 6"X24"

Rain Forest Taupe 6"x24"







Canyon Cream 6"x24"

Rain Forest Natural 6"x24"

Carrara White 6"X24"

SI	Size Ir		ess A	ARDESIA BLACK		CANYON CREAM		AM CARRAR	A WHII		KEYWOODN	IULTICOLOF	K MIIDN	MIDNIGHT MOUNT	
бх	6x24 3/8"			NARDBLK6X24		NCANCRE6X24		4 NCARW	NCARWHI6x24		NKEYMUL6X24		NMIDMOU6X24		
Si	Size Thickne		ess	PALISADE GREY			RAIN	JRAL	_ RAIN FOREST		TAUPE	ROCKY GOLD			
бх	(24	4 3/8"		NPALGRE6X24			NRAIFORNAT6X24			NRAIFORTAU6		X24	.4 NROCGOL6X24		
Д	APPLICATIONS		Floorii	ng Counters	Wall	PEI Rating	Variation	COF	Freeze/Th	naw	Breaking Strength	Water Absorption	Hardness	Chemical Resistance	
	RESIDENTIAL				•										
LIGH	LIGHT COMMERCIAL				•	IV	V4	DCOF - > 0.42 wet	Resista	nt	nt > 275	< 0.5%	7	Resistant	
HEAVY COMMERCIAL				•											

Thickness Appesia PLACK CANYON CREAM CARRADA WHITE KEYWOOD MILLTICOLOR MIDNICHT MOUNT

Our Dekora line gives you everything you love about ledger panels, but without any of the maintenance. Offering 5 different porcelain ledger panels, feel free to decorate that outdoor island grill or frame your fireplace in the simple beauty of Dekora line. These panels come in a familiar 6"X24" size to fit perfectly into your outdoor or indoor design.

Technical Information

Primary Colors: Beige, Gray, Gold Material Type: Glazed Porcelain

Finish: Matte

Polished: Hardeness / Mohs 5 Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Features At A Glance

- Stone ledger panel looks created with porcelain
- · Classic 6X24 sizing in 5 different colors
- Ink Jet technology with 3D punch for realistic stacked stone looks

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.