

Everlife® — FROM MSI

Waterproof Rigid Core Flooring

- **GreenGuard Gold® Certified**
- **FloorScore® Certified**
- **Installs on all grade-levels**
- **Pre-attached 1mm IXPE backing for quiet comfort.**
- **Coordinating trims available** (Tmold, surface reducer, end cap, and stair nose)
- **100% Waterproof**
- **Uniclic® Locking System for easy installation**

CYRUS SERIES:

Size: 7"x48" (nominal), 2.38 sqft/ piece
Thickness: 5mm


(4mm core + 1mm IXPE back)
Wear layer: 12mil
Warranty: lifetime limited residential, 10-year limited light commercial

PRESCOTT SERIES:

Size: 7" x 48" (nominal), 2.38 sqft./ piece
Thickness: 6.5mm (5.5mm core + 1mm IXPE back)
Wear layer: 20mil
Warranty: lifetime limited residential, 10-year limited light commercial, 5-year limited commercial.



STABLE 7X48




SANDINO (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



WHITFIELD GRAY (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



RYDER (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



EXOTIKA (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer




FAUNA (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



AKADIA (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer




FINELY (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



KATELLA ASH (Cyrus Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer




MEZCLA (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer




LUDLOW (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer




WEATHERED BRINA (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



HAWTHORNE (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



STABLE (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



BRALY (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



BARRELL (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer

Glue-Down Flexible LVT

- **GreenGuard Gold Certified**
- **FloorScore Certified**
- **Installs on all grade-levels**
- **Coordinating trims available** (Tmold, surface reducer, end cap, and stair nose)

KATAVIA SERIES:

Size: 6"x48", 2.00 sqft./piece
Thickness: 2mm
Wear layer: 6mil
Warranty: 15 year limited residential


GLENRIDGE SERIES:

Size: 6"x48", 2.00 sqft./piece
Thickness: 2mm


Wear Layer: 12mil
Warranty: 25 year limited residential, 6-year limited light commercial

WILMONT SERIES:

Size: 6"x48", 7"x48" (Nominal)
2.47 sqft./piece
Thickness: 2.5mm
Wear Layer: 20mil
 Optional sound mitigation underlayment available
Warranty: lifetime limited residential, 15-year limited light commercial, 10-year limited commercial



TWILIGHT OAK (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



BLEACHED ELM (Katavia, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer



LIME WASHED OAK (Wilmont, Glenridge) 6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



SADDLE OAK (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



TAWNY BIRCH (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



RECLAIMED OAK (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



ELMWOOD ASH (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



WOODRIFT GRAY (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



COASTAL MIX (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer




CHARCOAL OAK (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer




MIDNIGHT MAPLE (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



AGED HICKORY (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



JATOBA (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



BURNISHED ACACIA (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer 7"x48", 2.5MM thick, 20 MIL wear layer