

NEW PRODUCT SERIES

Technical Information Spec-sheet

AQUABLU

Official Distributor

(800) 971 1442

www.aquablumosaics.com



**International
Wholesale
Tile, LLC**

SERIES NAME

Havana

TECHNICAL CHARACTERISTICS

Available Formats:	16x16, 8x16, 8x8, 8x8 Deco, 4x8, 4x8 Deco, 2x11, 4x8 BN, 4" Corner, 2" Corner, Stair Tread,		
Style Description:	Weathered Brick	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Cuban Inspired Weathered	Number of Faces/Screens:	
Thickness in mm:	10	Number of Punches/Molds:	10
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	0%	Surface Type:	Textured
Rectified:		Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	>450LB
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Class GA		

PACKING INFORMATION - 8x16 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.2	Pieces per Carton:	13
SqFt per Pallet:	604.80	Pounds per Carton:	45.81
Boxes per Pallet:	54	SqFt per Container:	13305.60
Pallets per Container:	22		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".