

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Brake Cleaner

Product no.

-

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

NA

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Noa Brands APS
Snaremoesvej 23
DK-7000 Fredericia
tlf: +45 40 91 07 02

Contact person

Anders Christiansen

E-mail

abc@noabrands.dk

SDS date

2016-03-08

SDS Version

1.0

1.4. Emergency telephone number

Use your national or local emergency number
See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H229
Aerosol 1; H222
Eye Irrit. 2; H319
STOT SE 3; H336

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Pressurised container: May burst if heated. (H229)
Extremely flammable aerosol. (H222)

Causes serious eye irritation. (H319)
 May cause drowsiness or dizziness. (H336)

Safety statement(s)	General	If medical advice is needed, have product container or label at hand. (P101). Keep out of reach of children. (P102).
	Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210).
	Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338).
	Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412).
	Disposal	Dispose of contents/container to an approved waste disposal plant. (P501).

Identity of the substances primarily responsible for the major health hazards

acetone, propan-2-ol

2.3. Other hazards

This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

Additional labelling

Repeated exposure may cause skin dryness or cracking. (EUH066)

Additional warnings

VOC

-

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME:	ethanol
IDENTIFICATION NOS.:	CAS-no: 64-17-5 EC-no: 200-578-6 Index-no: 603-002-00-5
CONTENT:	25-40%
CLP CLASSIFICATION:	Flam. Liq. 2, Eye Irrit. 2 H225, H319
NOTE:	S
NAME:	acetone
IDENTIFICATION NOS.:	CAS-no: 67-64-1 EC-no: 200-662-2 Index-no: 606-001-00-8
CONTENT:	25-40%
CLP CLASSIFICATION:	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 H225, H319, H336
NOTE:	S
NAME:	propan-2-ol
IDENTIFICATION NOS.:	CAS-no: 67-63-0 EC-no: 200-661-7 Index-no: 603-117-00-0
CONTENT:	15-25%
CLP CLASSIFICATION:	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 H225, H319, H336
NOTE:	S
NAME:	1-methoxypropan-2-ol
IDENTIFICATION NOS.:	CAS-no: 107-98-2 EC-no: 203-539-1 Index-no: 603-064-00-3
CONTENT:	5-10%
CLP CLASSIFICATION:	Flam. Liq. 3 H226
NOTE:	S
NAME:	carbon dioxide
IDENTIFICATION NOS.:	CAS-no: 124-38-9 EC-no: 204-696-9
CONTENT:	5-10%
CLP CLASSIFICATION:	Refrig. Liq. Gas H281

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.
 S = Organic solvent

Other informations

Eye Cat. 2 Sum = Sum(Ci/S(G)CLi) = 6,8 - 0

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes with water (20-30°C) for at least 15 minutes. Call a doctor.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material. Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Please be aware that this is a chemical that forms peroxides. The content of peroxide must be controlled regularly after opening for example every 6th month.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

carbon dioxide (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 5000 ppm | 9150 mg/m³

Short-term exposure limit (15-minute reference period): 15000 ppm | 27400 mg/m³

ethanol (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 1000 ppm | 1920 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

DNEL / PNEC

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

Skin protection

Special work clothing should be used.

Hand protection

Recommended: Nitrile rubber. : NA

Eye protection

Use safety glasses with a side shield.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Aerosol	Clear	Characteristic	-	-	0,9

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
-18	-	-
Explosion limits (Vol %)	Oxidizing properties	
-	-	

Solubility

Solubility in water	n-octanol/water coefficient
Insoluble	-

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
carbon dioxide	Rat	LC50	Inhalation	470000 ppm 0,5 h
1-methoxypropan-2-ol	Rat	LD50	Dermal	>5000mg/kg
1-methoxypropan-2-ol	Rat	LD50	Oral	>2000-
propan-2-ol	Rabbit	LD50	Dermal	<=5000mg/kg
propan-2-ol	Rat	LD50	Oral	>2000 mg/kg
propan-2-ol	Rat	LC50	Inhalation	5840 mg/kg
propan-2-ol	Rat	LC50	Inhalation	47,5mg/l 8 h
acetone	Rabbit	LD50	Dermal	66,1mg/l 4 h
acetone	Rat	LD50	Oral	7400 mg/kg
acetone	Rat	LC50	Inhalation	5800 mg/kg
ethanol	Rabbit	LD50	Dermal	32 mg/kg 4 h
ethanol	Rat	LD50	Oral	>17100 mg/kg
ethanol	Rat	LC50	Inhalation	10470 mg/kg 124,7 mg/l

Skin corrosion/irritation

No data available.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Test duration	Result
1-methoxypropan-2-ol	Fish	LC50		>100 mg/l
1-methoxypropan-2-ol	Algae	EC50		>100 mg/l
1-methoxypropan-2-ol	Daphnia	EC50		>100 mg/l
propan-2-ol	Algae	NOEC	8d	>1800 mg/l
propan-2-ol	Fish	LC50	96 h	8970-9280 mg/l
propan-2-ol	Daphnia	EC50	24 h	9714 mg/l
propan-2-ol	Crustacean	EC10	18 h	5175 mg/l
propan-2-ol	Crustacean	EC50		>1000mg/l
acetone	Daphnia	EC50	24 h	10000 mg/l
acetone	Fish	LC50	48 h	7505-11300 mg/l
acetone	Algae	NOEC	96 h	7000 mg/l
ethanol	Fish	LC50	48 h	8150 mg/l
ethanol	Fish	LC50	96h	1100 mg/l
ethanol	Daphnia	EC50	48 h	9268-14221 mg/l
ethanol	Algae	EC0	168 h	5000 mg/l
ethanol	Crustacean	EC0	16 h	6500 mg/l

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
1-methoxypropan-2-ol	Yes	No data available	No data available
propan-2-ol	Yes	Modified OECD Screening Test	95%
acetone	Yes	CO2 Evolution Test	90,9
ethanol	Yes	No data available	No data available

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
carbon dioxide	No	0,83	No data available
1-methoxypropan-2-ol	No	0,37	No data available
propan-2-ol	No	No data available	No data available
acetone	No	No data available	No data available
ethanol	No	No data available	No data available

12.4. Mobility in soil

carbon dioxide: Log Koc= 0,735677, Calculated from LogPow (High mobility potential.). 1-methoxypropan-2-ol: Log Koc= 0,371403, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

According to EC-Regulation 1907/2006 (REACH)

No data available

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code

16.05.04

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

ADR/RID

14.1. UN number 1950

14.2. UN proper shipping name

14.3. Transport hazard class(es) 2.1

14.4. Packing group -

Notes -

Tunnel restriction code -

IMDG

UN-no. 1950

Proper Shipping Name Aerosols

Class 2.1

PG* -

EmS F-D, S-U

MP** NO

Hazardous constituent -

▼ IATA/ICAO

UN-no.

Proper Shipping Name

Class

PG*

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC.

Demands for specific education

-

Additional information

Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.
Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers.
EC Regulation 1272/2008 (CLP).
EC regulation 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225 - Highly flammable liquid and vapour.
H226 - Flammable liquid and vapour.
H281 - Contains refrigerated gas; may cause cryogenic burns or injury.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2



Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

KAO

Date of last essential change (First cipher in SDS version)

-

Date of last minor change (Last cipher in SDS version)

-