

EXPION360®



LITHIUM IRON PHOSPHATE BATTERY DATA SHEET

EX-G24-80C (12.8 Vdc/80 Ah)

PERFORMANCE: Long Cycle Life
High Energy Density
High Discharge Current
Fast Charging
Maintenance Free
Low Weight

FEATURES: Certified compliant to UL 1973 with grade A UL Recognized cells
360-degree mounting with tie-down system accessories
Integrated Battery Management System (BMS) for safety and reliability
Oversized terminal connection pads
Premium fiberglass reinforced ABS plastic case

Electrical Parameters	
Nominal Voltage	12.8 Vdc
Rated Capacity	80 Ah
Energy	1024 Wh
Resistance	<5 mΩ
Efficiency	>99 %
Cycle Life	>4000 cycles at 1C, 100 % DoD
Cell Self-Discharge	<2 % per month
Cells in Series/Parallel	4S/24P

Mechanical Parameters	
Dimensions	10.2 in x 6.8 in x 8.6 in (260 mm x 173 mm x 218 mm)
Weight	24 lb (10.9 kg)
Terminal Thread	M 8 x 1.25
Battery Housing	ABS Plastic Case
Housing Protection	IP66
Housing Flammability Rating	UL-94 V-0
Cell Type (Chemistry)	Cylindrical (LiFePO ₄)

Discharge Parameters	
Continuous Discharge Current	60 A
Max. Discharge Current	80 A
Pulse Discharge Current	100 A (1 s)
Recommended Volt. Disconnect	10.5 Vdc
BMS Discharge Cut-off Voltage	9.2 Vdc
Short Circuit Protection	200 μs to 600 μs

Charge Parameters	
Charge Method	CC-CV
Recommended Charge Voltage	14.2 Vdc to 14.4 Vdc
Recommended Float Voltage	13.6 Vdc
Recommended Charge Current	20 A
Maximum Charge Current	40 A
BMS Charge Cut-off Voltage	14.6 Vdc

Compliance	
Certifications	UL 1642 For Cells, File no. MH64383
	UN3480, Class 9, UN38.3
	Certified compliant to UL 1973 by TEI Listing Services, File no. 22D01

Temperature Parameters	
Discharge Temperature	-4 °F to 140 °F (-20 °C to 60 °C)
Charge Temperature	32 °F to 140 °F (0 °C to 60 °C)
Storage Temperature	-4 °F to 113 °F (-20 °C to 45 °C)

NOTE: Do not mix with lead-acid batteries when recycling. See Expion360, Inc. user's manual for proper operation.

DISCLAIMER: While every precaution has been taken to ensure the accuracy of the contents within this document, Expion360, Inc. assumes no responsibility for errors or omissions. Specifications and product functionality may change without notice.

STORAGE: One discharge-recharge cycle every 6 months.



**UN
38.3**