

Description: Unlined nitrile gloves

- Features & Benefits:
- * Anti-slip pattern for good grip in wet and dry conditions
 - * Chlorine washed
 - * Compliant with (EC) No.1935/2004, EU 10/2011 & BFR XXI (Green)
 - * Extra long cuff to protect forearm
 - * Manufactured under a stringent quality management system
 - * Nitrile rubber for solvent resistance
 - * Outstanding abrasion resistance
 - * Straight cuff

Applications: Aircraft Industry, Automotive Industry, Food Industry, Laboratories, Metal Fabrication, Petrochemical Industry, Printing Industry, Facility maintenance, Ceramic industry

Elastomer: Nitrile rubber

Thickness: 0.55 +/- 0.05 mm

Lining: Unlined chlorinated

Former: Sand Patch, NIVS

Exterior: Chlorinated

Cuff Types: Straight

Treatments: Chlorinated

Colours: Blue B13, Green G8

AQL: 1.00



CE Certification: Conforms to PPE Regulation EU 2016/425 to (Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	8	218	220	398	460
	9	232	232	402	460
	10	260	258	422	460
	11	288	284	424	460

Circumference in mm, +/- 10 mm Tol. +/- 10 mm

Shelf Life 1 Years

EN 374-4

Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYP A



* Methanol (A)	Level 3	55.6
* Acetonitrile (C)	Level 1	80.4
* Carbon disulphide (E)	Level 1	72
* Toluene (F)	Level 1	76.4
* Diethylamine (G)	Level 2	84.6
* Ethyl acetate (I)	Level 1	83.7
* n-Heptane (J)	Level 6	17
* Sodium hydroxide 40% (K)	Level 6	8.1
* Sulphuric acid 96% (L)	Level 5	65.9
* Nitric acid 65% (M)	Level 3	82.8
* Acetic acid 99% (N)	Level 4	72.2
* Ammonium hydroxide 25% (O)	Level 6	2.5
* Hydrogen peroxide 30% (P)	Level 6	1.2
* Formaldehyde 37% (T)	Level 6	0.5

Note: Printed copies are valid only on the date printed

Printed Date: 05-Jan-2022

Revision:8

Published Date: 09-Jul-2021

DPL
Handling you with care

No: 400, Deans Road, Colombo 10, Sri Lanka

Phone: +94-0122-683-964

Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com

* Hydrofluoric acid 40% (S)

Level 5

X

Protection against Mechanical hazards**Performance**

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 4
Level 1
Level 0
Level 2
X

Protection against Micro-organisms risk**Performance**

EN ISO 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
n/a