

# **ULTRANE 500**

## Grip and skin protection for oily environments.

# WAPA 500 OLTRANE EN 255 4121A 500 1808 STANDAGO 100 ET GEL-EIT



EN388



4121A

GR

ISO 18889

DEXTERITY EN 420: CAT.3

0075

ISO 13997: 5 N

5/5



# SPECIFIC ADVANTAGES

## Durability

- Excellent abrasion resistance due to the nitrile coating Long lasting and cost effective glove: washable until 3 cleaning cycles (see laundering and drying conditions)
- Color adapted to dirty environements for a prolonged durability.

## **Productivity**

 Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

## Skin protection

- Oilproof, it repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free

## **Guaranteed quality**

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



## ) Additionnal benefits

Available in vending machine packaging

## **INDUSTRIES**

- Automotive/mechanical industry
- Mechanical industry
- Other industries
- Glass industry
- Agriculture sector

## **APPLICATIONS**

- Re-entry tasks
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil
- Handling glass sheets
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments





# **ULTRANE 500**

# LEGENDS

EN388

**MECHANICAL HAZARDS** 

PERFORMANCE LEVELS (X = NOT

Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance Tear resistance Blade cut resistance

ISO 18889

Abrasion resistance

PROTECTION FROM PESTICIDES

GR: Re-entry tasks

## PRODUCT DETAILS

Interior finish	Seamless textile support
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff caracteristic	Knitted Cuff
Colors of the gloves	Black
Length (cm)	23-28
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% HR)	1.1E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% HR)	4.4Ε+11 Ω

# LOGISTIC DETAILS

Packaging	1 pair/bag
	12 pairs/bag
	96 pairs/carton

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0075 | CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

