ULTRANITRIL 480

Prolonged contact (or immersion) | short wear

Ultra-long chemical protection

SPECIFIC ADVANTAGES

Durability

• Longer service life: excellent mechanical resistance (abrasion, perforation)



Productivity

Good grip on slippery objects, due to the embossed texture



Skin protection

• Excellent protection during intensive handling of high-risk chemical products



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



TYPE A

EN388



4102X

EN ISO 374-1 TYPE A



AJKOPT

DEXTERITY EN 420:

5/5

EN ISO 374-5



CAT.3



0334

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

APPLICATIONS

- Spray mixtures preparation
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Treating/degreasing metals with aggressive
- Handling drums of chemical products
- Application of pesticides
- Cleaning of printing-press rollers
- Maintenance

Edit 27/03/2021



ULTRANITRIL 480

Prolonged contact (or immersion) | short wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4 1 0 2 X

0-4 0-5 0-4 0-4 A-F P

| Impact protection (optional)

| Cut resistance according to ISO 13997

| Puncture resistance Tear resistance

EN ISO 374-1 TYPE A

CHEMICAL RISKS

Blade cut resistance



Abrasion resistance

A: Methanol

J: n-Heptane

K: Sodium hydroxide 40%

O: Ammonia 25%

P: Hydrogen peroxide 30%

T: Formaldehyde 37%



PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

| Interior finish | Chlorinated |
|----------------------|------------------|
| Exterior finish | Embossed texture |
| Material | Nitrile |
| Cuff caracteristic | Straight cuff |
| Colors of the gloves | Green |
| Length (cm) | 46 |
| Thickness (mm) | 0.55 |
| Size | 7 8 9 10 |

LOGISTIC DETAILS

| Packaging | 1 pair/bag 12 pairs/carton |
|-----------|-------------------------------|
|-----------|-------------------------------|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/16206/18/1069
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

