ULTRANITRIL 493

Prolonged contact (or immersion) | intermittent wear

Ultra-long chemical protection

SPECIFIC ADVANTAGES



• Longer service life: excellent mechanical resistance (abrasion, perforation)



Good grip on slippery objects, due to the embossed texture



• Excellent protection during intensive handling of high-risk chemical products

Guaranteed quality

- In compliance with guideline for requirements concerning personal protective equipment in plant protection according to BVL (Bundesamt für Verbraucherschutz und Lebensmittelsicherheit)
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

CHEMICAL PROTECTION **TYPE A**

EN388



ISO 18889

EN ISO 374-1 TYPE A



AJKOPT

DEXTERITY

EN ISO 374-5

EN 420: 5/5

CAT.3



0334

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Treating/degreasing metals with aggressive solvents
- Handling drums of chemical products
- Application of pesticides
- Cleaning of printing-press rollers





ULTRANITRIL 493

Prolonged contact (or immersion) | intermittent wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT

4 1 0 2 X 0-4 0-5 0-4 0-4 A-F Impact protection (optional) Cut resistance according to ISO 13997

Tear resistance Blade cut resistance Abrasion resistance

EN ISO 374-1

TYPE A



CHEMICAL RISKS

- A: Methanol J: n-Heptane
- K: Sodium hydroxide 40%

Puncture resistance

- O: Ammonia 25%
- P: Hydrogen peroxide 30%
- T: Formaldehyde 37%



PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff caracteristic	Straight cuff
Colors of the gloves	Green
Length (cm)	39
Thickness (mm)	0.55
Size	8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% HR)	8.3E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% HR)	1.2E+10 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag
	10 pairs/bag
	50 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/15/1212
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07-FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

