NEOTHERM

9KAGFZ-M00-GACCC

Fabric supported neoprene gauntlet with grip pattern Description:

Features & Benefits:

- * Excellent tactile properties * Grip pattern in the outer layer
- * Highest protection against aqueous acids
- * Liquid proof Neoprene layer
- * Resistance to contact heat
- * Resistance to flammability (Burning behavior): Level 4
- * Special seamless Kevlar liner for excellent cut resistance, comfort and

Automotive repairing, Bakeries, Casting/Molding, Ceramic/Cement Industries, Industrial/Domestic kitchens, Applications:

Power and Energy

Elastomer: Polychloroprene 1.90 +/- 0.10 mm Thickness: Seamless Kevlar Lining: Former: Reverse Lozenge, CVIL Finished smooth Exterior:

Gauntlet

Cuff Types:

Treatments:

Colours: Black D2 AQL: 1.00

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment

against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical	Size	Palm	Wrist	Cuff	Length
Dimensions:	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330
		Circum	Circumference in mm, +/- 5 mm		

Shelf Life 1 Years

EN 374-4

			2110711
otection against Chemical hazards		Performance	Degradation %
EN ISO 374-1/TYPE A			
_~	* Methanol (A)	Level 6	9.4
	* Sodium hydroxide 40% (K)	Level 6	17.6
	* Sulphuric acid 96% (L)	Level 6	40.4
	* Nitric acid 65% (M)	Level 6	38.1
AKLMNOPST	* Acetic acid 99% (N)	Level 6	43.5
	* Ammonium hydroxide 25% (O)	Level 5	16.8
	* Formaldehyde 37% (T)	Level 6	16.4
	* Hydrogen peroxide 30% (P)	Level 6	5.1
	* Hydrofluoric acid 40% (S)	Level 6	X

Note: Printed copies are valid only on the date printed

Printed Date: 03-Jan-2022 Published Date: 24-Oct-2019

> No: 400, Deans Road, Colombo 10, Sri Lanka Phone: +94-0122-683-964

Fax: +94-0122-699-018 E-Mail: postmast@dplgroup.com



Revision:2

NEOTHERM

9KAGFZ-M00-GACCC

Protection against Mechanical hazards

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 3

Performance

- Level 2
- Level 4 Level 3
- X

Performance

Protection against Micro-organisms risk

EN 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass

n/a

Performance

Level 4

Level 3

Level 4

Level 3

Protection against Thermal risks

EN 407



* Burning behavior

- * Contact heat
- * Convective heat
- * Radiant heat
- * Small splashes of molten metal
- * Large quantities of molten metal

Level 4 X

Note: Printed copies are valid only on the date printed

Printed Date: 03-Jan-2022



Revision:2 Published Date: 24-Oct-2019

No: 400, Deans Road, Colombo 10, Sri Lanka Phone: +94-0122-683-964 Fax: +94-0122-699-018

E-Mail: postmast@dplgroup.com