

## FEATURES & BENEFITS

- Class 5, SLC<sub>80</sub>31dB
- Hi Vis for visual identification
- Hearing protection for noise levels to 116bB(A)
- Robust steel wire construction for onsite demands
- Contemporary low profile design that withstands abuse without compromising comfort
- Fits a wide range of hard hats - 25mm wide tongue Solid, lightweight ear cup construction
- High quality ear cushions
- Balanced clamping force for comfort

## PRODUCT DETAILS

Clamp Force : 13N

### Materials of construction

- Arm : Stainless Steel
- Cup : ABS
- Insert : PU Foam
- Cushion : PU

Weight : 301.5gms

Colour : Hi Vis Yellow

Size : Standard One Size

Qty/Carton : 20



PRODUCT CODE: HHEMPYTS

## STANDARDS

AS / NZS1270 - Class 5 31dB

Certified by SAI Global - License number: SMKH25293

### ATTENUATION TABLE (ATTENTION IN DECIBELS)

Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	18.6	20.1	27.4	39.9	35.6	39.4	37.2
Standard Deviation	3.7	2.7	3.0	2.5	2.2	3.2	5.2
Mean-minus-standard deviation attenuation	14.9	17.4	24.4	37.4	33.4	36.2	32.0

SLC<sub>80</sub> Value is 30 (Class5)

Clamping Force 13N

Mass 301.5grams

Hearing protector Class 5 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110 dB (A) assuming an 85 dB (A) criterion.

A lower criterion may require a higher protector class.