## **SHEER PLUS**

## 8IAGFZ-G08-GACCC

Fabric supported nitrile gauntlet with grip pattern Description:

Features & Benefits:

- \* Fully coated for extra protection
- \* Unique liquid proof construction
- \* Grip pattern on glove to ensure secure grip in both wet and dry
- \* Cotton interlock liner absorbs perspiration and adds to comfort
- \* 2 Piece liner without seams in the working areas eliminates hand

irritation

- \* Extended gauntlet cuff to protect forearm
- \* Excellent abrasion resistance

Applications: Agriculture, Machine Tool Manufacturing, Paint and Varnish Manufacturing, Petrochemical Industry

Elastomer: Nitrile rubber Thickness: 0.85 +/- 0.10 mm Lining: Interlock

Former: Reverse Lozenge, CVIL Finished smooth Exterior:

Cuff Types: Gauntlet

Treatments:

Colours: Green G8 AQL: 1.00

CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment

against standards EN 374-1:2016+A1:2018, EN 374-5:2016, EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical	Size	Palm	Wrist	Cuff	Length
Dimensions:	7	214	206	296	330
	8	220	218	302	330
	9	244	234	310	330
	10	268	256	326	330
	11	278	268	330	330
		Circum	Circumference in mm, +/- 5 mm		Tol. +/- 10 mm

Shelf Life 1 Years

EN 374-4

Protection against Chemical hazards			Degradation %
EN 374/TYPE A			
	* Methanol (A)	Level 2	41.8
( )(=)	* n-Heptane (J)	Level 6	14
	* Sodium hydroxide 40% (K)	Level 6	-19.3
	* Sulphuric acid 96% (L)	Level 3	43.5
AJKLMNOPST	* Nitric acid 65% (M)	Level 2	36.4
	* Ammonium hydroxide 25% (O)	Level 4	-10.8
	* Hydrogen peroxide 30% (P)	Level 6	-0.2
	* Hydrofluoric acid 40% (S)	Level 3	X
	* Formaldehyde 37% (T)	Level 6	-7.0
	* Acetic acid 99% (N)	Level 4	24.5

Note: Printed copies are valid only on the date printed

Published Date: 03-Mar-2021

No: 400, Deans Road, Colombo 10, Sri Lanka Phone: +94-0122-683-964 Fax: +94-0122-699-018



Printed Date: 04-Jan-2022

E-Mail: postmast@dplgroup.com

Revision:4

## **SHEER PLUS**

# 8IAGFZ-G08-GACCC

#### Protection against Mechanical hazards Performance \* Abrasion resistance Level 4 EN 388 \* Blade cut resistance



Level 0 \* Tear resistance Level 1 \* Puncture resistance Level 1 \* TDM cut resistance X

### Protection against Micro-organisms risk Performance Pass \* Protection against bacteria and fungi



\* Protection against viruses n/a

Note: Printed copies are valid only on the date printed

Printed Date: 04-Jan-2022 Published Date: 03-Mar-2021 No: 400, Deans Road, Colombo 10, Sri Lanka

> Fax: +94-0122-699-018 E-Mail: postmast@dplgroup.com

Phone: +94-0122-683-964



Revision:4