

Description: Unlined natural rubber gloves, 43 mil, rolled cuff

- Features & Benefits:
- * Anatomically shaped to provide good fit
 - * Beaded cuff to improve tear resistance during donning and removal and help prevent droplets from travelling beyond the glove length
 - * Easy-on-easy-off
 - * Excellent abrasion resistance
 - * Extra long cuff to protect forearm
 - * Extra thick for added protection
 - * Low in soluble proteins
 - * Manufactured under a stringent quality management system
 - * Natural Rubber, No filter , No flock

Applications: Agriculture, Chemical Industry, Fishing, Animal husbandary

Elastomer: Natural rubber

Thickness: 1.10 +/- 0.10 mm

Lining: Unlined chlorinated

Former: Plain, NIVP

Exterior: Chlorinated

Cuff Types: Bead rolled

Treatments: Chlorinated

Colours: Black D1

AQL: 1.00



CE Certification: Conforms to PPE Regulation EU 2016/425 to(Complex Design) Personal Protective Equipment after assessment against standards EN 374-1:2016+A1:2018, EN 374-5:2016,EN 388:2016+A1:2018 and EN 420:2003+A1:2009

Conforms to: ASTM D4679 of 2002

Physical Dimensions:	Size	Palm	Wrist	Cuff	Length
	9	234	230	435	600
	10	262	250	449	600
	11	278	269	464	600
		Circumference in mm, +/- 5 mm		Tol. +/- 10 mm	

Shelf Life 1 Years

EN 374-4

Protection against Chemical hazards

Performance

Degradation %

EN ISO 374-1/TYPE A



* Methanol (A)	Level 6	0.4
* Sodium hydroxide 40% (K)	Level 6	-10.2
* Sulphuric acid 96% (L)	Level 4	31.4
* Nitric acid 65% (M)	Level 6	16.2
* Acetic acid 99% (N)	Level 5	20
* Ammonium hydroxide 25% (O)	Level 3	-8.1
* Hydrogen peroxide 30% (P)	Level 6	32.1
* Formaldehyde 37% (T)	Level 6	-4.4

Note: Printed copies are valid only on the date printed

Printed Date: 04-Jan-2022

Revision:3

Published Date: 09-Jul-2021

Protection against Mechanical hazards		Performance
---------------------------------------	--	-------------

EN 388



- * Abrasion resistance
- * Blade cut resistance
- * Tear resistance
- * Puncture resistance
- * TDM cut resistance

Level 4
Level 1
Level 2
Level 1
X

Protection against Micro-organisms risk		Performance
-----------------------------------------	--	-------------

EN ISO 374-5



- * Protection against bacteria and fungi
- * Protection against viruses

Pass
n/a

Protection against Thermal risks		Performance
----------------------------------	--	-------------

EN 407



- * Burning behavior
- * Contact heat
- * Convective heat
- * Radiant heat
- * Small splashes of molten metal
- * Large quantities of molten metal

X
Level 2
X
X
X
X