ChloroMatic[®]

Salt Water Chlorinators

Keep your pool clean and clear with the simple and reliable ChloroMatic. Australia's favourite chlorinator.

Now with the new Davey EziSet Digital Timer



Features & Benefits

- EziSet digital timer for quick and simple set-up
- Large, easy to read digital display and LED indicators
- Models available with reverse polarity electrolytic cells for low maintenance
- Large surface area of cell plates for high rate chlorine production
- High flow rate cell design for rapid pool turnover
- Made with corrosion resistant, UV stabilised materials for long service life
- Winter Mode setting to reduce sanitiser output during the colder months, saves energy and protects equipment
- 'Low salt', 'no flow' indicators and overload protection
- Flow detector stops electrolysis if no flow is present, preventing dangerous gas build-up
- Pump 'cut out' protects the pump when no water detected (on reverse polarity models)
- Light transformer available (on some models)
- Operating Salt Level: 4500 – 6000ppm

davey.com.au



ChloroMatic[®]

Salt Water Chlorinators



	Power Supply Enclosure				Cell Housing				ELECTRICAL DATA – All models				
All Models	Height	Width	Depth	Mounting Holes	Height	Width	Diam	Inlet/ Outlet	Plumbing Holes	Voltage (V)	Supply Freg/	Enclosure Class	Approval #
									194 from	(V)	Phase	IP	LL COM
Dimension (mm)	390	235 130	130	66	141	376	123	50	centre to centre	220-250	50Hz / 1	34	W/2333

		Chlorine Gas Production	Calcium Hypochlorite	*With optional 12V Pool	Max Pool Size (litres)							
	Model	g/hr (100%)	Equivalent g/hr (65%)	Light Transformer	Cool Climate	Temperate Climate	Hot Climate					
Reverse Polarity (Low Maintenance) Systems												
	MCS16C	16	25	V	80,000	50,000	35,000					
	MCS24C	24	37	V	120,000	75,000	55,000					
	MCS36C	36	55	×	180,000	112,000	80,000					
	MCS40C	40	62	×	200,000	125,000	100,000					
	Non-reversing Systems											
	MC16C	16	25	V	80,000	50,000	35,000					
	MC20C	20	31	V	100,000	62,000	44,000					
	MC30C	30	46	×	150,000	94,000	66,000					

*To order with optional light transformer add 'T' to the end of the model number.

IMPORTANT NOTES:

In 'hard water' applications (above 275ppm), reverse polarity systems will require regular (monthly) inspection and manual cleaning.
 The appropriate chlorinator size for your pool is dependent on the local climate and the bather load of the pool. Please note that chlorinator cell life can be increased with shorter running times during winter and lower output settings. Davey recommends that a chlorinator is run for between 6 - 8 hours a day during summer and between 2 - 4 hours during winter. A 24 hour super chlorination is recommended after heavy pool use.

Datasheet Disclaimer:

All details in this leaflet are accurate at the time of printing. This literature is not a complete guide to product usage. Further information is available from your Monarch Series dealer, Davey Customer Service Centre and from the relevant product Installation & Operating Instructions. This datasheet must be read in conjunction with the relevant Installation & Operating Instructions and all applicable statutory requirements. Product specifications may change without notice. ® Davey and ChloroMatic are registered trademarks of Davey Water Products Pty Ltd. © Davey Water Products Pty Ltd 2010.



Davey Water Products Pty Ltd Member of the GUD Group ABN 18 066 327 517

Head Office and Manufacturing 6 Lakeview Drive, Scoresby, Australia 3179 Ph: +61 3 9730 9222 Fax: +61 3 9753 4100 Website: davey.com.au

 Customer Service Centre

 Ph:
 1300 2 DAVEY (1300 232 839)

 Fax:
 1300 369 119

 E-mail:
 sales@davey.com.au

Interstate Offices Sydney • Brisbane • Adelaide Perth • Townsville

International

6 Lakeview Drive, Scoresby, Australia 3179 Ph: +61 3 9730 9121 Fax: +61 3 9753 4248 E-mail: export@davey.com.au

USA Website: daveyusa.com E-mail: export@davey.com.au Davey Water Products - New Zealand 7 Rockridge Avenue, Penrose, Auckland 1061 Ph: +64 9 570 9135 Fax: +64 9 527 7654 Website: daveynz.co.nz E-mail: sales@daveynz.co.nz

Customer Service Centre – New Zealand Ph: 0800 654 333

