



Nominal size	Small	Medium	Large	X-Large
<b>Effective top tube</b>	23.0"	24.0"	24.8"	25.4"
<b>Nominal head tube angle rigid fork and 100mm suspension fork</b>	69°	69°	69°	69°
<b>Nominal head tube angle 120mm suspension fork</b>	68.5°	68.5°	68.5°	68.5°
<b>Tuning Chip induced head/seat tube angle change</b>	±0.2°	±0.2°	±0.2°	±0.2°
<b>Head tube length</b>	3.5"	4.5"	5.1"	5.9"
<b>Nominal seat tube angle</b>	73°	73°	73°	73°
<b>Seat tube length</b>	15.0"	17.0"	19.0"	21.0"
<b>BB drop</b>	2.28 - 2.44"	2.28 - 2.44"	2.28 - 2.44"	2.28 - 2.44"
<b>Chainstay length</b>	16.93 - 17.72"	16.93 - 17.72"	16.93 - 17.72"	16.93 - 17.72"
<b>Wheelbase</b>	43.0 - 43.8"	44.0 - 44.8"	44.8 - 45.6"	45.5 - 46.3"
<b>Trail</b>	3.4"	3.4"	3.4"	3.4"
<b>Fork offset</b>	2.0"	2.0"	2.0"	2.0"
<b>Rigid fork axle to crown length</b>	19.1"	19.1"	19.1"	19.1"
<b>Stack</b>	22.9"	23.7"	24.3"	25.0"
<b>Reach</b>	16.0"	16.8"	17.4"	17.8"
<b>Standover</b>	27.4"	29.1"	30.7"	32.1"