



Nominal size	Small	Medium	Large	X-Large
Effective top tube	585 mm	610 mm	630 mm	645 mm
Nominal head tube angle rigid fork and 100mm suspension fork	69°	69°	69°	69°
Nominal head tube angle 120mm suspension fork	68.5°	68.5°	68.5°	68.5°
Tuning Chip induced head/seat tube angle change	±0.2°	±0.2°	±0.2°	±0.2°
Head tube length	90 mm	115 mm	130 mm	150 mm
Nominal seat tube angle	73°	73°	73°	73°
Seat tube length	381 mm	432 mm	483 mm	533 mm
BB drop	58-62 mm	58-62 mm	58-62 mm	58-62 mm
Chainstay length	430-450 mm	430-450 mm	430-450 mm	430-450 mm
Wheelbase	1092-1112 mm	1118-1138 mm	1139-1159 mm	1156-1176 mm
Trail	85.5 mm	85.5 mm	85.5 mm	85.5 mm
Fork offset	51 mm	51 mm	51 mm	51 mm
Rigid fork axle to crown length	485 mm	485 mm	485 mm	485 mm
Stack	581 mm	602 mm	616 mm	634 mm
Reach	407 mm	426 mm	442 mm	451 mm
Standover	697 mm	739 mm	780 mm	815 mm