



DELL
Wyse 3010
Thin Client

Specifications	Dell Wyse 3010 Thin Client
Operating system	Wyse Enhanced Linux
CPU	Marvell® ARMADA™ PXA 510 v7 1.0 GHz system-on-chip (SoC)
Memory	1GB Flash / 1GB RAM
Graphics	Integrated in SoC
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate Single: up to 1920x1200@60Hz; Color Depth: 32 bpp, Dual: up to 1920x1200@60Hz; color depth: 32 bpp Supports dual high-resolution displays
Networking	10/100/1000 Base-T Gigabit Ethernet Optional 802.11 b/g internal wireless (single antenna)
Security compliance	Security protocols supported for both wireless and 802.1x network based Authentication: EAP-TLS; EAP-LEAP; EAP-PEAP, EAP-MSCHAPv2, EAP-GTC; WEP; WPA Personal; WPA2 Personal; WPA Enterprise; WPA2 Enterprise
I/O peripheral support	One DVI-I port, DVI to VGA (DB-15) adapter included Dual display support with optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately) Four USB 2.0
Audio	Output: 1/8-inch mini jack, full 16-bit stereo, 48KHz sample rate Input: 1/8-inch mini jack, 8-bit microphone
Mountings	Horizontal stand. The same stand can be used for VESA wall mounting. Optional vertical stand

Device security	Built-in Kensington security slot (cable sold separately)
Dimensions	Height: 1 in (25 mm) Width: 6.9 in (177 mm) Depth: 4.69 in (119 mm) Weight: 1 lb (450 g)
Shipping weight	1.003 lbs. (0.455 kg)*
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz 65W, 19V DC Energy Star V5.0 Phase V external and EuP compliant power adapter Consumes less than 6 watts (Average)
Keyboard & Mouse	Yes
Temperature range	Horizontal position: 50° to 95° F (10° to 35° C) Vertical position, power button up: 50° to 104° F (10° to 40° C) Storage: 14° to 140° F (-10° to 60° C)
Humidity	20% to 80% condensing 10% to 95% non-condensing
Certifications	Ergonomics: German EKI-ITB 2000, ISO 9241-3/-8 Safety: cULus 60950, TÜV-GS, EN 60950 RF Interference: FCC Class B, CE, VCCI, C-Tick Environmental: WEEE, RoHS Compliant
Warranty	3 Years Dell Warranty.

