




SADDLEBAGS

Mounting and Use Instructions



- 1. Lower saddlebags onto seat as shown in Fig. 1.
- Adjust top straps to seat width and desired bag height. Bags should be as high and tight as possible.
- 3. Separate quick-release buckles from lower side straps.
- Attach female buckles to any rear tubular frame member of your motorcycle, as shown in Fig. 2 and Fig. 3. (see Fig. 4 for suggested spots).
- Connect male buckles on saddlebags to female buckles on frame. Tighten straps to hold bags snug against the bike.
- When loading saddlebags, keep weight evenly distributed and keep heavier objects low.
- Compress rear suspension with saddlebags in place, checking to make sure that brake caliper, swing arm, etc., do not come in contact with saddlebags.

Caution: Protect your saddlebags from sharp edges. If contact with a sharp edge in unavoidable, pad those edges with tape, old tire tube or similar material. Use your own good judgement when packing. Avoid contact with hot surfaces and exhaust pipes.

Cleaning: Open all zippers, remove all inserts and hardware, set machine on light or regular cycle, use cold or warm water and a mild detergent. Hang dry. Do not dry clean or put in dryer. Touch-up cleaning may be done with spray cleaners or detergent and water.

CHASE HARPER USA


3007 Bunsen Ave Unit F, Ventura, CA 93003 · (805) 477-9993





SADDLEBAGS

Mounting and Use Instructions



- 1. Lower saddlebags onto seat as shown in Fig. 1.
- Adjust top straps to seat width and desired bag height. Bags should be as high and tight as possible.
- 3. Separate quick-release buckles from lower side straps.
- Attach female buckles to any rear tubular frame member of your motorcycle, as shown in Fig. 2 and Fig. 3. (see Fig. 4 for suggested spots).
- Connect male buckles on saddlebags to female buckles on frame. Tighten straps to hold bags snug against the bike.
- When loading saddlebags, keep weight evenly distributed and keep heavier objects low.
- Compress rear suspension with saddlebags in place, checking to make sure that brake caliper, swing arm, etc., do not come in contact with saddlebags.

Caution: Protect your saddlebags from sharp edges. If contact with a sharp edge in unavoidable, pad those edges with tape, old tire tube or similar material. Use your own good judgement when packing. Avoid contact with hot surfaces and exhaust pipes.

Cleaning: Open all zippers, remove all inserts and hardware, set machine on light or regular cycle, use cold or warm water and a mild detergent. Hang dry. Do not dry clean or put in dryer. Touch-up cleaning may be done with spray cleaners or detergent and water.

CHASE HARPER USA


3007 Bunsen Ave Unit F, Ventura, CA 93003 · (805) 477-9993





SADDLEBAGS

Mounting and Use Instructions



- Lower saddlebags onto seat as shown in Fig. 1.
- Adjust top straps to seat width and desired bag height. Bags should be as high and tight as possible.
- 3. Separate quick-release buckles from lower side straps.
- Attach female buckles to any rear tubular frame member of your motorcycle, as shown in Fig. 2 and Fig. 3. (see Fig. 4 for suggested spots).
- Connect male buckles on saddlebags to female buckles on frame. Tighten straps to hold bags snug against the bike.
- When loading saddlebags, keep weight evenly distributed and keep heavier objects low.
- Compress rear suspension with saddlebags in place, checking to make sure that brake caliper, swing arm, etc., do not come in contact with saddlebags.

Caution: Protect your saddlebags from sharp edges. If contact with a sharp edge in unavoidable, pad those edges with tape, old tire tube or similar material. Use your own good judgement when packing. Avoid contact with hot surfaces and exhaust pipes.

Cleaning: Open all zippers, remove all inserts and hardware, set machine on light or regular cycle, use cold or warm water and a mild detergent. Hang dry. Do not dry clean or put in dryer. Touch-up cleaning may be done with spray cleaners or detergent and water.

CHASE HARPER USA


3007 Bunsen Ave Unit F, Ventura, CA 93003 · (805) 477-9993





SADDLEBAGS

Mounting and Use Instructions



- 1. Lower saddlebags onto seat as shown in Fig. 1.
- Adjust top straps to seat width and desired bag height. Bags should be as high and tight as possible.
- 3. Separate quick-release buckles from lower side straps.
- Attach female buckles to any rear tubular frame member of your motorcycle, as shown in Fig. 2 and Fig. 3. (see Fig. 4 for suggested spots).
- Connect male buckles on saddlebags to female buckles on frame. Tighten straps to hold bags snug against the bike.
- When loading saddlebags, keep weight evenly distributed and keep heavier objects low.
- Compress rear suspension with saddlebags in place, checking to make sure that brake caliper, swing arm, etc., do not come in contact with saddlebags.

Caution: Protect your saddlebags from sharp edges. If contact with a sharp edge in unavoidable, pad those edges with tape, old tire tube or similar material. Use your own good judgement when packing. Avoid contact with hot surfaces and exhaust pipes.

Cleaning: Open all zippers, remove all inserts and hardware, set machine on light or regular cycle, use cold or warm water and a mild detergent. Hang dry. Do not dry clean or put in dryer. Touch-up cleaning may be done with spray cleaners or detergent and water.

CHASE HARPER USA

3007 Bunsen Ave Unit F, Ventura, CA 93003 · (805) 477-9993