



Tones media

## Technical Data Sheet

**Product Name:** Perforated Vinyl

**Product Description:** Perforated film allowing one-way vision during day light (40% light)

PVC Film	Type	Calendered monomeric soft PVC film
	Thickness	140 Micron (5.5 mil)
	Shrinkage	$\leq 0.8\%$
	Opaque	>99%
	Surface Tension	$\geq 30 \text{ dn/cm}$
Adhesive	Adhesive Type	Clear solvent based permanent pressure sensitive glue
	Weight (g/m <sup>2</sup> )	22 $\pm$ 2
	Application Temperature	15°C ~ 40°C
	Average Peeling Force	$\geq 6 \text{ N/25mm}$
	Initial Adhesion Ball Tack	$\geq 3 \text{ N/25MM*25MM}$
	Holding Power	$\geq 1440 \text{ min}$
Release Paper	Type	Kraft paper
	Color	White
	Weight	140g $\pm$ 5g/ m <sup>2</sup>
	Release Force	0.05~0.2N/4cm
Shelf Life	1 year (Storage temperature of 22°C, relative humidity of 50~55%, in original packaging)	
Expected Durability	1 year Outdoors (subject to conditions including, storage, application, and weather)	
Applications	Outdoor and Indoor signage (usually applied on glass front)	
Printing compatibility	Solvent, Eco solvent, and Latex (Recommended original inks from Manufacturers)	

All data mentioned above is generated from lab testing, which we consider to be reliable. However, this information shall not be considered as warranty under any condition.

Above information is subject to change without prior notice.