

SAFETY DATA SHEET (SDS)

INTERIOR LIME PAINT - NEUTRAL BASE

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION:

Product Name: INTERIOR LIME PAINT

Product Number: 3868 (N)

Product Use: Water-thinned Paint

MANUFACTURER:

Rocky Rochon Paint

2405 ½ 10th Ave. East

Seattle, Wa. 98102

www.RockyRochonPaint.com

Manufacturer's Phone: 206-557-4737

Emergency (24-hour) Phone: 206-557-4737

Date of preparation: June 11 2021

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye contact, Skin contact, Inhalation, Ingestion

Potential Acute Exposure Effects:

Eyes: May cause slight irritation

Skin: May cause mild irritation

Inhalation: May cause irritation of respiratory tract

Ingestion: May be harmful if swallowed

Overexposure signs/symptoms:

Eyes: Watering, redness or irritation

Skin: Irritation, dryness

Inhalation: Respiratory tract irritation, coughing

Ingestion: No specific data

3. COMPOSITION / INFORMATION ON INGREDIENTS

REPORTABLE COMPONENTS	CAS NUMBER	% by WEIGHT
Calcium Carbonate	1317-65-3	5-10

Clay (Kaolin)	1332-58-7	5-10
Talc	14807-96-6	5-10

4. FIRST AID MEASURES

- Eyes:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- Skin:** Remove contaminated clothing. Wash thoroughly with soap and water.
- Inhalation:** Move to fresh air. Seek medical attention if symptoms continue.
- Ingestion:** Do not induce vomiting. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

Flammable Properties: This product is not flammable

Extinguishing Media: Use foam, carbon dioxide, dry powder, water fog , or an extinguishing agent appropriate for the surrounding fire.

Unusual Fire and Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat (due to build-up of pressure). Closed containers may explode when exposed to extreme heat. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Protective Equipment: Firefighters should wear self-contained breathing apparatus and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Prevent further leakage or spillage. Soak up with inert absorbent material and transfer to a suitable container for proper disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray mists or sanding dust. Provide adequate ventilation. Wear appropriate respiratory equipment if ventilation is inadequate. Wash thoroughly after handling.

Storage: Keep container closed when not in use. Transfer only to properly labeled containers.

Keep out of reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

	<u>OSHA TWA</u>	<u>ACGIH TWA</u>	<u>OSHA STEL</u>
Calcium Carbonate (d)	15 mg/m ³	10 mg/m ³	not established
Talc (d)	20 mppcf	2 mg/m ³	not established
Clay (Kaolin) (d)	15 mg/m ³	10 mg/m ³	not established

(d): Hazardous as dust when product is sanded

Engineering Measures: Use only in well ventilated areas. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment:

Eye / Face Protection: Wear safety glasses or goggles.

Skin Protection: Protective gloves and impervious clothing

Respiratory Protection: If exposure cannot be controlled below acceptable limits by ventilation, use an appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all manufacturers' instructions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Various
Odor:	Little or no odor
Vapor pressure:	Not available
Odor threshold:	Not available
Vapor density:	Not available
pH:	8 to 10
Density:	9.8 (lbs / gal)
Viscosity:	105 – 110 KU
Melting/freezing point:	Not available
Solubility (water):	Not available
Boiling point / range:	Not available
Flash point:	Not available
Evaporation rate:	< 1 (butyl acetate = 1.0)
Upper flammability limit:	Not available

Lower flammability limit: Not available
Auto-ignition temperature: Not available
Decomposition temperature: Not available

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid	None known.
Materials to avoid:	Strong oxidizing agents and strong acids.
Hazardous Decomposition Products:	None under normal use.
Hazardous Polymerization:	None under normal conditions.

11. TOXICOLOGICAL INFORMATION

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Disposal Instructions: Do not allow material to drain into sewers/water supplies. Dispose of in accordance with all federal, state and local regulations. Consider recycling.

14. TRANSPORT INFORMATION CONSIDERATIONS

Not regulated

15. REGULATORY INFORMATION

TSCA: All materials are listed or exempt.

16. OTHER INFORMATION

Hazardous Material Identification System (USA)

Health: 1
Flammability: 0
Physical Hazard: 0

Prepared by: Rocky Rochon Paint

The information contained herein is presented in good faith and is believed to be accurate as of the date prepared. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information available to them.