



Premium Masking Solutions

Q1® Floor Pro Board

Q1® Floor Pro Board is a reusable paper which provides a durable temporary floor protection for painting and renovation projects.

Compared to traditional floor protection boards, this masking paper is characterized by a longer length and lighter weight which make it very easy to use and reposition during masking operations.

Q1® Floor Pro Board is made of 100% recycled and biodegradable paper which protects any surfaces from paint spills and blocks moisture and liquids to get through to the surface, offering superior performance even in wet conditions.



Features & Benefits

- Prevents paint spills, moisture and liquids getting-through
- Easy-to-use and reusable product
- Longer and lighter compared to traditional floor boards
- 100% recycle and biodegradable paper

Available Colour

Kraft Brown

Product Reference

Part#	Size	Pcs / Pallet
Q1FPB	900mm x 45 m	60

Technical Data Sheet

Characteristics	Unit	Value	Test method
Total Weight	g/m ²	160	ISO 536
Moisture	%	8	ISO 287
Bursting strength	kPar	320	ISO 2758
Sizing COBB 60	g/m ²	50	ISO 535
SCT, DT	kN.m/kg	16.5	ISO 9895
CMT 30/50. DM	N.m ² /g	1,4	ISO 7263

Additional Information**Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Product Use

Q1® would advise that there are many factors beyond Q1®' control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.