

Specifications

Product Codes	1400MN: natural gas / 1400MP: propane
Product type	Direct Vent, Zero Clearance.
Input (BTU)	Natural gas: 36,000 / 18,500; Propane: 36,000 / 15,000
Vent Takeoff	4 x 6-5/8" co-axial. Top facing takeoff. Rear facing takeoff with elbow. Requires 24" vertical rise at appliance or after first elbow.
Venting System	Co-axial 4 x 6-5/8". Minimum vertical rise at appliance: 24". NO Co-Linear.
Gas convertible	Yes
Valve	GV60
Control	SYMAX Valor10 remote control or Remote Battery & Wall Switch Kit (included).
Batteries	Fireplace: Yes, in Remote Battery & Wall Switch Kit; Remote control handset: Yes.
Electrical	Via V-module (supplied) to operate remote control and lighting. Also, optional WiFi.
Lighting	Yes, operates with remote control or optional WiFi.
WiFi	Optional. Operated by Valor10 mobile application on smartphone.
Fan (Blower)	Optional. 1495CFK NEW . Operated by remote control or optional WiFi. NOTE: NO 1270RBK off appliance. Must be hooked to HeatShift LKD1 or LKD4.
HeatShift	Optional. 5" outlets at fireplace. Uses any LDK kits except LDK8 30" plenum.
Liners	Red bricks, LedgeStone, Fluted black, Plain black, Reflective glass, Herringbone.
Fuel beds	Logs: Driftwood, Birch, Traditional - All NEW.
Fronts / Trims	Yes, required. 1430CIK NEW.
Outdoor Installation	Yes, requires GV60CKO Outdoor Conversion Kit. NO electrical power connection allowed!
Comments	Decorative lighting supplied uses V-module. Electrical power should be installed, except if appliance is installed outdoor.