



F3500 shown with airmate.

STANDARD FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment & side mounted catalytic bypass
- Easy-to-read catalytic thermometer helps your stove reach maximum burn times & efficiency
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home and alcove approved
- 170° opening door for easy loading
- Heavy-duty 3/16 in. steel firebox
- 10-year, 100% coverage on original catalyst

OPTIONS

- Ash drawer with cover
- 2-speed blower
- Convector airmate
- Outside air kit
- Mobile home kit (Canada only)
- Wood venting

SPECIFICATIONS

Maximum BTU*	88,000
Typical sq. ft. heated**	1,500 - 2,500
EPA Efficiency	82% LHV / 76% HHV
Max log size	20"
Burn time	Up to 24 hours
Emissions	1.1 g/h
Firebox size	3.0 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE