

THE SCIENCE OF WARMTH

Since 1890, we've been pioneering and perfecting radiant heat technology that generates constant, comfortable warmth within your home.

AUTOFIRETM

Pioneered by Valor, AutoFire automatically adjusts the fire for optimum efficiency and enjoyment.



RADIANT HEAT

What's makes Valor unique? We put radiant heat technology into every fire. You can feel it.

CONVECTIVE HEAT

<u>Secondary Heat Exchanger</u> naturally improves convective heat—without a fan.

NO POWER. NO PROBLEM

Valor fireplaces heat without electricity—even in a power failure.

EFFICIENCY

Radiant zone heating is up to 25% more efficient than central forced air systems.

REMOTE CONTROL

Adjustable flame for constant, even warmth without having to cycle the fire on and off—or leave the sofa.

CERAMIC GLASS

Durable and robust ceramic glass improves radiant performance.

SUPERIOR ALUMINIZED STEEL

Aerodynamic aluminized steel firebox handles high temperatures, delivering efficient radiant warmth.



1 FIRE BEDS

We design all our expertly crafted logs and rocks as realistic-looking as possible, and engineer them to harness radiant heat from the flames and glowing embers. For a video of the fires, visit valor fireplaces.com/g3

TRADITIONAL LOGS



DRIFTWOOD



ROCKS + DECORATIVE ROCK






2 LINERS

Choose a firebox liner to complement the logs and front you select as well as the surround of your current fireplace. The tint of the ceramic glass window warms the liner colors, especially when the fire is on. To see more examples, visit your local Valor dealer or go to valor fireplaces com/93

FLUTED BLACK



REFLECTIVE GLASS



RED BRICK





3 FRONTS

Select a front that suits your home and style. All G3 fronts will need a surround, found on the next page, which helps finish the opening of your fireplace cavity. Your dealer can help you choose a surround that complements your front and fits your installation.

To see examples, visit your Valor dealer or go to valorfireplaces.com/g3

CLEARVIEW, VINTAGE IRON WITH BLACK



CONTEMPORARY, BLACK also in Vintage Iron



MATTE BLACK



CAST IRON, BLACK






CONTEMPORARY SURROUND, NICKEL (also in Copper and Black)



FENDERFIRE SINGLE DOOR VINTAGE IRON WITH BLACK



FENDERFIRE DOUBLE DOOR, VINTAGE IRON WITH BLACK





4 SURROUNDS

Surrounds fit behind or around your front. All our fronts are compatible with our surrounds, except the Picture Frame surround—exclusive to the Contemporary Surround front.

Choose from a variety of styles and sizes to cover your existing fireplace cavity. Your dealer can help you choose one that's compatible with your front and installation. To see examples with fronts, visit

3-SIDED SQUARE 2", BLACK

3-SIDED OVERSIZED, BLACK

3-SIDED SQUARE, BRUSHED NICKEL

25%" H x 34%" W



Also in Black or Vintage Iron 26" H x 37½" W x 2"D




3-SIDED DELUXE, BLACK



4-SIDED SQUARE, BLACK



3-SIDED CONTOUR, VINTAGE IRON



4-SIDED CONTOUR, BLACK



4-SIDED SQUARE PICTURE FRAME, BLACK



CAST IRON, VINTAGE IRON







You can see the craftsmanship in our fronts: made of steel and then powder-coated or plated with an artisan touch—durable, long-lasting finishes. Visit your local Valor dealer to see a finish in person or visit valorfireplaces.com/g3







REMOTE CONTROL

Every Valor fireplaces comes with a remote. Your remote lets you select and adjust your desired temperature—the fire automatically adjusts to maintain the temperature of the room. Your remote even allows you

to turn your pilot light on or off from the comfort of your sofa. No electricity needed: the remote is battery controlled.

For more information, visit







EFFICIENCY RATINGS


While the North American fireplace industry is largely self-regulated, at Valor we use recognized Canadian and US government testing methods to determine our energy efficiencies, and ensure our products perform in your home as rated. All our fireplaces are available as natural gas or propane.

SECONDARY HEAT EXCHANGER

The built-in Secondary Heat Exchanger naturally improves convective heat—removing the need for a fan. Your fire will heat up fast for immediate comfort—and with no need for electricity, you'll save money.

To find out more, visit valorfireplaces.com/efficiency





atural Gas nerGuide* igh ow ax Output*	70.3% 24,000 6,500 18,132	Natural Gas EnerGuide* High Low Max Output*	24, 6, 16
ronane		Propage	

EnerGuide* High

Μ

70.3% 24,000 Low 13,000 Max Output* 18,132

Na	itural Gas	
En	erGuide*	59%
Hig	gh	24,000
Lov	N	6,500
Ma	x Output*	16,169

EnerGuide* 24,000 High Low 13,000 Max Output* 16,169







* EnerGuide ratings and outputs have been determined without a fan/blower, using the CSA P.4.1-15 test method. Certified to ANSI Z21.88/CSA 2.33 Vented Gas Fireplace Heater American National Standard. CGA-2.17-91 Gas Fired Appliances for use at High Altitudes.


SPECIFICATIONS


DIRECT VENT 739



B-VENT 738








ALWAYS REFER TO THE
MANUAL FOR COMPLETE
INSTALLATION INSTRUCTIONS.
VALORFIREPLACES.COM/MANUALS

MINIMUM CAVITY DIMENSIONS



B-Vent (738)

3" single liner


Minimum depth (X) = 12-14" (305-357 mm)—varies with outer trim options.

Minimum height (Y) = 20" (508 mm); 24" (610 mm) when using 763BPB Backing Plate.

Minimum width of fireplace opening at front is 28" (711 mm).

Note: check that masonry step doesn't interfere with install dimensions or vent pipe.

VENTING + MANTEL CLEARANCES



Α	1"	1-6"	9"	12"
	(25 mm)	(25-152 mm)	(229 mm)	(305 mm)
В*	36"	39"	42"	45"
	(914 mm)	(991 mm)	(1067 mm)	(1143 mm)

^{*}Measure taken from the underside of the mantel to finished hearth or surface that the unit is sitting on.

Sidewall Clearances: minimum distance from side of appliance (liner box) to combustible wall—9" (229 mm)

OPTIONS

ENGINE

Direct Vent NG	739MN
Direct Vent LPG	739MP
B-Vent NG	738KN
B-Vent LPG	738KP

FUEL BEDS

Driftwood	739DWK
Traditional Logs	739LSK
Rocks	739RSK

LINERS

Fluted Black	739FBL
Red Brick	739VRL
Reflective Glass	739RGL

△ WARNING

This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm.

740CAP 758CCB 1225VFB

For more information go to www.P65Warnings.ca.gov

Note: Natural gas, in its original state, contains Benzene.

FRONTS

Clearview Black/Vintage Iron	745CFV	Select a fret for Clearview front:
Contemporary Black	741SFB	Clearview Access Panel Black
Contemporary Vintage Iron	741SVI	Clearview Cast fret Black/Vintage Iron
Traditional Cast Iron	742CFB	Ventana Fret Black
FenderFire Double Door Black/Vintage Iron	743FVI	
FenderFire Single Door Black/Vintage Iron	744FVI	
Contemporary Surround Black	765CSB	
Contemporary Surround Copper	765CSC	Direct Vant and
Contemporary Surround Brushed Nickel	765CSN	Direct Vent only.
Contemporary Surround Painted Nickel	765CSPN	
Matte Black	772MBF2	

SURROUNDS

Contour 3-sided Black Contour 3-sided Vintage Iron	746CTK 746VIK	26¾"h x 36½"w
Contour 4-sided Black	748CTK	30¼"h x 36½"w
Deluxe 3-sided Black	747DTK	26¾"h x 36½"w
Square 3-sided, 2" Black	767STB	25%"h x 34%"w
Square 3-sided Black	756STB	
Square 3-sided Vintage Iron	756STV	27%"h x 37½"w
Square 3-sided Brushed Nickel	756STP	
Square 4-sided Black	757STB	31%"h x 37½"w
Square 4-sided Vintage Iron	757STV	31/8 11 X 3/ /2 W
Cast Plate Vintage Iron	715CVI	29"h X 41"w
Oversized 3-sided Vintage Iron	753OTV	31"h x 45¾6"w
Square Picture Frame	764PFB	27%"h x 39½"w For Contemporary Surround fronts (765).

BACKING/CLOSURE PLATES

Backing Plate	763BPB	30½"h X 43"w. Direct vent only.
Oversized Closure Plate Black	750OCP	29½"h x 42"w max. coverage. Use with 3-sided Contour and Deluxe surrounds.

OPTIONAL

Decorative Rock	761DRK	Use with rock fuel bed only.	
Riser, Black	751LTK + 752BTK	40" w x 2 1⁄3" h	_
Riser, Vintage Iron	751LVK + 752BVK	40 W X Z ½ 11	
Valor Wall Switch	1265WSK	Direct vent only	





