



## **PVS-14**

## NIGHT VISION MONOCULAR

The AGM PVS-14 Night Vision Monocular is a rugged, lightweight, multi-purpose night vision device that has repeatedly proven itself in combat. The PVS-14 design was originally commissioned by the United States Military to enable nighttime operations. This monocular is used globally in some of the most challenging environments. The PVS-14 can be used as a handheld device, or mounted on the included head harness. With the proper accessories, it can also be mounted to combat helmets, providing night vision capabilities to daytime optical sights. The PVS-14 monocular conforms to 810G Military standards and demonstrates the highest quality form and function.

The PVS-14 monocular is a full-featured unit. Weighing less than 12.4 ounces/ 0.32 kilograms. The unit includes manual gain control, an automatic bright light shut-off feature, and a built-in Infrared (IR) illuminator. The bright light shut-off feature ensures that the high-quality photocathode tube is protected. AGM's PVS-14 includes an array of optional accessories to support virtually any operation.



- Compact, rugged design
- Waterproof
- Head or helmet-mountable for hands-free usage
- Manual gain control
- Ergonomic, simple, easy-to-operate controls
- Built-in Infrared illuminator and flood lens
- 3-year warranty







Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited.

## **SPECIFICATIONS**

Image Intensifier Tube	Gen 2+ or Gen 3
Magnification	1x (3x and 5x optional)
Lens System	26 mm; F/1.2
FOV	40°
Focus Range	0.25 m to infinity
Diopter Adjustment	-6 to +4 diopters
LED Indicators (in the FOV)	- Low Battery - IR On - Excessive Light Conditions
Manual Gain Control	Yes
Bright Light Cut-Off	Yes
Infrared Illuminator	Yes
Battery Type	One AA Alkaline
Battery Life (Operating)	Up to 50 hours at 20°C
Operating Temperature Range	-51° C to +49° C (-60° F to 120° F)
Storage Temperature Range	-51° C to +85° C (-60° F to 185° F)
Weight	0.32 kg (12.4 oz)
Dimensions (w/o lens cap and eyecup)	114 × 63× 69 mm (4.5 × 2.5 × 2.7 in)
Package Includes	Night Vision Monocular, Head Mount Assembly, Brow Pad, Eye Cup, Helmet/ Head Mount Adapter, System Soft Carrying Case, Daylight Filter, Shoulder Strap, Lens Paper, Diopter Lens Cap, Sacrificial Window, Demist Shield, Manual, Battery

Specifications are subject to change without notice. Images are for illustration purposes only.

## **OPTIONAL EQUIPMENT**

AGM Sioux850-P Long-Range Infrared Illuminator Comes included with Mount, Picatinny Adapter, Rechargeable Battland Charger (P/N 501SIOUP850IR1)  AGM Afocal Magnifier Lens Assembly, 3X (P/N 61023XA1)
,
AGM Afocal Magnifier Lens Assembly, 5X (P/N 61025XA1)
MICH Helmet Mount Assembly (P/N 6103MHM1)
PASGT Helmet Mount Assembly (P/N 6103PHM1)
AGM 51 degree FOV Lens Kit PVS-14/PVS-14 Omega (Kit includes Objective Lens and Eyepiece) (P/N 610150K1)
Hard Case (P/N 6610HCS1)





DISTRIBUTED BY: GoThermal (Pty) Ltd | TeleEye (SA) (Pty) Ltd

Unit 9, 4 Homestead Avenue, Bryanston, 2191South Africa

Sales@GoThermal.co.za +27 11 557 9200 www.GoThermal.co.za



MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

 $\label{localization} EUROPEAN\ OFFICE\ |\ \#6\ Andrey\ Lyapchev\ Blvd\ |\ Sofia,\ P.C.\ 1756\ |\ Bulgaria\ Tel.\ +35.988.560.0326\ |\ info@agmglobalvision.eu\ |\ www.agmglobalvision.eu\ |\ www.agmglobalvision.$