

Page 1 of 6

Section 1 - Identification of Chemical Product And Company

CDK STONE NZ Ltd Emergency Phone: 0800 764766

2/40 Canaveral Drive **NZ Emergency Services:** 111

Rosedale

Auckland Phone: 0800 803 932 +64 9 479 2424 **NEW ZEALAND** Fax:

Substance: Dye for resin

Paste Coloranti Universal Trade Name:

Product Use:

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: NON HAZARDOUS SUBSTANCE: according to the criteria of HSNO.

NOT REGULATED under NZS5433:2007 Transport of Dangerous Goods on Land

HSNO Signal Word:

Emergency Overview

Physical Description & colour: Coloured paste Characteristic

Odour:

Hazard Classification:

Non hazardous

Signal Word

Hazard Statements:

Non hazardous

Precautionary Statements

Prevention

Response

P301+330+312 IF SWALLOWED: Rinse mouth. Call a POSION CENTRE/ doctor/ physician/ first

aider if you feel unwell

P303+361+352 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with

plenty of water and soap.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do. Continue rinsing

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing P308+311 If exposed or concerned. Call a POISON CENTRE/ doctor/ physician/ first aider

Storage Disposal

> P501 Dispose of content/ container to an authorised hazardous or special waste collection point

in accordance with local regulation



Page 2 of 6

Section 3 - Composition/Information on Ingredients

IngredientsCAS NoConc.%Ingredients not contributing to classification100

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764766 from anywhere in New Zealand (13 1126 in Australia) and is available at all times. Have this SDS or product label with you when you call.

Eye Contact: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping

eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal

of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact: Immediately flush body and clothes with large amounts of water, using safety shower if available.

Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to

hospital, or doctor.

Inhalation: Remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false

teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or

doctor, without delay.

Ingestion: Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons

Information Centre or a doctor.

Note to Physician: Treat symptomatically

Section 5 - Fire Fighting Measures

Extinguishing Media: Preferred extinguishing media are water spray or fog, dry chemical, BCF or foam

Fire and Explosion Hazards: Combustible. Heating may cause expansion or decomposition leading to violent rupture of containers.

On combustion, may emit toxic fumes of carbon monoxide (CO).

Fire Fighting: Alert Fire & Emergency New Zealand and tell them location and nature of hazard. Wear full body

protective clothing with breathing apparatus. Fight fire from a safe distance, with adequate cover. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot.

Equipment should be thoroughly decontaminated after use

Fire Decomposition: Carbon monoxide (CO₂) and other pyrolysis products typical of burning organic

material.

Section 6 - Accidental Release Measures

Minor Spills: Clean up all spills immediately Avoid breathing vapours and contact with skin and eyes. Control

personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. Wipe up Collect residues in a flammable

waste container.

Major Spills: Clear area of personnel. Alert Fire & Emergency New Zealand and tell them location and nature of

hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite.



Page 3 of 6

Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

Section 7 - Handling and Storage

Handling: Avoid all personal contact, including inhalation. Wear protective clothing when risk of overexposure

occurs. Use in a well-ventilated area. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS.

Storage: Store in original containers. Store away from incompatible materials in a cool, dry, well-ventilated

area. Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access. Keep adsorbents for leaks and spills readily available Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling

recommendations contained within this SDS.

Packing as supplied by manufacturer. Check that containers are clearly labelled and free from leaks.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

Exposure limits

CAS no.	Substance or ingredient	WES-TWA	WES-STEL

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5-day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Engineering Controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh

Personal Protective Equipment

Eye Protection:Not required under normal conditions of useSkin Protection:Not required under normal conditions of useProtective Material Types:Not required under normal conditions of useRespirator:Not required under normal conditions of use



Page 4 of 6

Section 9 - Physical and Chemical Properties:

Physical Description & colour:

Odour:

Characteristic

pH:

not applicable

Vapour Pressure:

Relative Vapour Density:

Coloured paste

Characteristic

not applicable

no data

not available

Viscosity

Boiling Point: not applicable °C

Volatiles: negligible Water Solubility: miscible Freezing/Melting Point: no data **Specific Gravity:** 1.1 Flashpoint 100°C Auto ignition temp: 300°C **Evaporation Rate:** not available Coeff Octanol/water distribution no data

Section 10 - Stability and Reactivity

Stability Product is considered stable

Conditions to Avoid: Avoid contact with moisture. Reacts with mild steel, galvanized steel / zinc producing hydrogen gas

which may form an explosive mixture with air. Contact with alkaline materials liberates heat.

Incompatibilities: Segregate from alkalis, oxidisng agents and chemicals readily decomposed by acids i.e. cyanides,

sulfides, carbonates. Avoid reaction with oxidizing agents, i.e. nitrates, oxidizing acids, chlorine

bleaches, pool chlorine etc. as ignition may result

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Inhaled:

Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting

Ingestion

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion".

Skin Contact

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Styrene has been showed to be absorbed less through the skin than via the airways. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Eye Contact

There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation.

Chronic Health Effects

There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material



Page 5 of 6

TOXICITY AND IRRITATION

Ingredient	Oral LD ₅₀	Dermal LD ₅₀	Inhalation LC₅0

Section 12 - Ecological Information

This material and its container must be disposed of as hazardous waste. Avoid release to the environment.

gredient		Fish		(Crustacea	Algae	
	Persis		Persiste		Bioaccumulation	on Mobilit	:y
	H ₂ O/	Soil	Air				

Section 13 - Disposal Considerations

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container cannot be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled. The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance. Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

Section 14 - Transport Information

NOT REGULATED

Section 15 - Regulatory Information

HSNO Approval: Not applicable

Group Standard conditions and other regulations:

Condition	Requirement
SDS	Safety data sheet must be available to a person handling the substance within 10 minutes.
Emergency plan	Not required
Certified handler	Not required
Tracking	Not applicable
Bunding and secondary containment	Required dependent on pack size and total volume
Signage	Not required

Issued by: **CDK Stone NZ Ltd**Page 5 of 6
Phone +0800 803 932
Product: **Paste Coloranti Universal**This version issued: August 2020



Page 6 of θ

Location Compliance Certificate	Not required
Hazardous Area	Not required
Fire extinguisher	Not required

National Inventories

Australia	AICS	Ν
Canada	DSL	Ν
Canada	NDSL	Ν
China	IECSC	Ν
Europe	EINEC/ELINCS/NLP	Ν
Japan	ENCS	Ν
Korea	KECI	Ν
New Zealand	NZIOC	Ν
Philippines	PICCS	Ν
USA	TSCA	Ν
Taiwan	TCSI	Ν
Mexico	INSQ	Ν
Vietnam	NCI	Ν
Russia	ARIPS	Ν

Section 16 - Other Information

Revision History

August 2020 Reclassification and reformat

November 2015 Initial Preparation

Acronyms:

CAS number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency services especially

fire-fighters

HSNO Hazardous Substances & New Organisms Act
IARC International Agency for Research on Cancer

ICAO Technical Instruction International Civil Aviation Organization Technical Instructions

IMDG Code International Maritime Dangerous Goods Code controlled by the International Maritime Organisation (IMO)

LC50 Lethal concentration 50% - concentration fatal to 50% of a population LD50 Lethal dose 50% - concentration fatal to 50% of a population

NZS 5433 New Zealand Standard 5433 (Standard for the Transport of Dangerous Goods on Land)

SDS Safety Datasheet

STEL Short Term Exposure Limit

TWA Time Weighted Average (typically measured as 8-hours)

UN Number United Nations Number
WES United Nations Number
Workplace Exposure standard

References

Chemical properties and HSNO classifications derived from the New Zealand chemical classification information database (CCID). www.epa.govt.nz

Workplace exposure limits derived from Workplace Exposure Standards and Biological Exposure Indices 11th Edition (November 2019).

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other material or in any process, unless specified in the text.

This SDS was prepared by Collievale Enterprises Ltd in accord with the Hazardous Substances (Safety Data Sheets) Notice 2017 http://www.collievale.com Phone +64 7 5432428

End of SDS

Issued by: **CDK Stone NZ Ltd**Page 6 of 6
Phone +0800 803 932
Product: **Paste Coloranti Universal**This version issued: August 2020