

EZ-FLEX40

ANTI-FRACTURE MEMBRANE | LA MEMBRANA ANTIFRACTURAS



EASY TO INSTALL!
NO SPECIAL TOOLS NEEDED

ZEFEZFLEX40

EZ-FLEX40 Crack Isolation
Peel & Stick Membrane
225SF Roll

ZEFEZFLEX4OKIT

EZ-FLEX40 Crack Isolation
Peel & Stick Membrane Kit
25SF Kit with 8oz Primer

ZEFEZFLEXPRIMER

Water Based Primer
Concentrate
1 Gallon

TECHNICAL PROPERTIES

Thickness 40 Mils

Elongation 500% Min. (Rubberized Asphalt Only)

Application Temp 45°F (7°C) Min.

In Service Temp -20°F To 180°F (-28°C To 82°C)

Bond Strength of Ceramic Tile to Portland Cement,
ASTM C482: Passed

Ceramic Floor Installation Systems, ASTM C627:
Exceeded test requirements for "Extra Heavy
Applications"



THE ULTIMATE ANTI-FRACTURE MEMBRANE

- Helps eliminate stress cracking in marble, terrazzo and ceramic tile caused by stress, shrinkage and control cracks in concrete floors.
- Elastomeric properties of membrane can withstand horizontal expansion and contraction up to 3/8" when the membrane is a minimum of 1 1/2 times larger than the width of the individual tile, or when utilized in full floor applications. Existing cracks larger than 3/16" should be prepared with proper backing material prior to installation of membrane. EZ-Flex40 also protects tile floors from reflective cracking and delamination.
- EZ-Flex40 is cold applied and is self bonding to most substrates.
- No down or curing time is required. Membrane can be covered immediately after application.
- Not recommended for use on concrete floors where hydrostatic pressure exists or where moisture vapor transmission exceeds 4 lb. (1.8 kg), as tested by the calcium chloride test method ASTM F1869
- Tile floors stay quieter, drier and warmer.
- EZ-Flex40 is only 40 mils thick and can be used in new and remodel construction without causing height restrictions found in other subfloor systems and materials.

EZFlex40 contains no V.O.C.'s and is environmentally safe, which allows it to be used in confined areas. The SBS rubberized asphalt retains its flexibility throughout the floor's life span and will not dry out or decay with time. The ease of application makes EZ-Flex40 a cost-effective cleavage membrane that even unskilled labor can install.

Note: intended for indoor use only. Contact Emser Tile For information on outdoor applications.