

		AJ-1600A(W)	AJ-1600A(S)
Printing Method		Piezo Ink-jet Method (CX5 Print Head)	
Printing Width		210-1610mm	
Acceptable Media Width		210-1610mm	
Conditions for Usable Media	Type	Roll or Sheet, width is not less than A4 or 210mm	
	Max Thickness	1.5mm	
	Roll Weight	25kg	40kg
Ink Cartridge	Type	Water Based Dye Ink	ECO Solvent Ink
		Water Based Pigment Ink	
		Sublimation Ink	
	Capacity	440ml	
Color	Double 4-color (C M Y K) or 8-color (C M Y K + LC LM OR OG)		
Capacity		Continuous Ink Supply	
Color Gamut Performance		1670 Million Color	
Printing Resolution		1440 dpi x 1440 dpi / 720 dpi x 1440 dpi / 720 dpi x 1080 dpi / 540 dpi x 720 dpi / 540 dpi x 1080 dpi / 720 dpi x 720 dpi / 540 dpi x 720 dpi	
Media Control		Automatic Feeding System and Sheet Cutter	
Media Sensors		Two Sides: front and back	
Height of Printing Heads		Two types optional : 1.2mm/2.8mm	
Printing Heads Cleaning		Automatic cleaning and manual cleaning	
Interface		USB2.0/ HI USB	
Power Consumption	During Operation	1.7A / 100V to 240V 10%, 50/60 Hz	
	Sleep Mode	0.5A / 100V to 240V 10%, 50/60 Hz	
Power Saving Function		Automatic Sleep Function	
Acoustic Noise Level	Printing Mode	< 65 dB (according to ISO 7779)	
	Standby Mode	< 40 dB (according to ISO 7779)	
Packing Dimensions (with stand)		2680mm(W) x 870mm(D) x 940mm(H)	
Printer Dimensions (with stand)		2500mm(W) x 740mm(D) x 1240mm(H)	
Weight (with stand)		148kg	
Power Consumption		Under 1500VA	
Environmental	Power On	Temperature: 20 to 30°C Humidity: 35 to 80%RH (non-condensing)	
	Power Off	Temperature: 20 to 30°C Humidity: 35 to 80%RH (non-condensing)	
Accessories		Power Cord. Drain Bottle, Manual	