# CARBOWAX™ SENTRY™ Polyethylene Glycol (PEG) 1450

Product CAS # 25322-68-3

Description CHEMICAL FAMILY - Oxyalkylene Polymer

CFTA NOMENCLATURE - PEG-32

Typical Physical Properties - CARBOWAX™ SENTRY™ Polyethylene Glycol 1450 NF, FCC(1)

Range of Avg. Molecular Weight	1305 - 1595
Range of Average Hydroxyl Number, mg KOH/g	70-86
Density, g/cm3 @ 20°C	1.0919
Melting or Freezing Range, C	42 + 46
Solubility in Water at 20°C, % by wt	72
Viscosity at 100°C, cSt	26.5
Average Number of Repeating Oxyethylene Units	32.5
Avg. Liquid Specific Heat, cal/g/°C	0.51
Heat of Fusion, Cal/g	37
pH at 25°C, 5% Aqueous Solution	4.5 - 7.5
Flash Point, Pensky Martens Closed Cup, C	246
Flash Point, Cleveland Open Cup, °C	285
Physical Form	Molten, Flake <sup>2</sup>
Weight per gallon, lbs/gal @ 55°C , The state of the stat	9.15

<sup>1.</sup> Typical properties, not to be construed as specifications

Typical Known Applications fo Polyethylene Glycols\*

- Cosmetics & Personal Care
- Chemical Intermediates
- Food Processing & Packaging
- Pharmaceuticals

FDA Status

CARBOWAX™ SENTRY™ Polyethylene Glycols are produced to meet the requirements of the National Formulary (NF) monograph and the Food Chemicals Codex (FCC) monograph.

**Product Stewardship** 

Dow encourages its customers and potential users to review their applications from the standpoint of human health and environmental aspects. To help ensure that Dow products are not used in ways for which they are not intended or tested, Dow personnel will assist customers in dealing with environmental and product safety considerations. Dow literature, including material Safety Data Sheets, should be consulted prior to the use.




Form No. 118-01814-1211

<sup>2.</sup> Contains BHT, 100 ppm nominal

<sup>\*</sup>Refer to the CARBOWAN\*\* SENTRY\*\* Polyethylene Glycols and Methoxypolyethylene Glycols brochure (Form No. 118-01790-1011) for more specific

#### Technical Data Sheet

## Kinematic Viscosity of Aqueous Solutions of CARBOWAX™ SENTRY™ Polyethylene Glycol 1450



### For further information, call...

In the United States and Canada: 1-800-447-4369 • FAX: 1-989-832-1465

In Europe: +800 3 694 6367 • FAX: +31 11567 4704 In the Asia Pacific: +800 7776 7776 • FAX: +800 7779 7779 In Latin America: +55 11 5188 9000 • FAX: +55 11 5184 8790

#### www.carbowax.com

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPUED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Published December 2011



Form No. 118-01814-1211