

**Benz Microscope Optics Center, Inc.** 

3980 Varsity Drive Ann Arbor, MI 48108 Tel: 734-994-3880 Fax: 734-994-9090

email: benzmicroscope@aol.com

# Hematoxylin Eosin Stain Kit

Safety Data Sheets

Part # SS0921-KIT

# **Kit Contains:**

1 x 30 ml Hematoxylin (Ehrlichs) Solution

1 x 30 ml Eosin Y Alcoholic 1%

1 x 30 ml Acid Alcohol 1%

# FLAMMABLE STORAGE CODE RED

Section 1 Identification Page E1 of E2



Benz Microscope Optics Center, Inc. 3980 Varsity Drive

Ann Arbor, MI 48108 Tel: 734-994-3880 Fax: 734-994-9090 email: benzmicroscope@aol.com **CHEMTREC 24 Hour Emergency** Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

**HEMATOXYLIN (EHRLICHS) SOLUTION Product** 

Synonyms

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS06 / GHS08

Target organs: Central nervous system, Liver, Kidneys, Heart



GHS Classification:

Flammable liquid (Category 2) Eye irritation (Category 2B) Acute toxicity, oral (Category 3) Acute toxicity, dermal (Category 3) Acute toxicity, inhalation (Category 3) STOT-SE (Category 1)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed H311: Toxic in contact with skin. H320: Causes eye irritation.

H331: Toxic if inhaled

H370: Causes damage to organs.

# Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233: Keep container tightly closed.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge

P260: Do not breathe mist/vapours/spray P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P330: Rinse mouth.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical attention.

P312: Call a POISON CENTER or doctor if you feel unwell.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

P311: Call a POISON CENTER or doctor.

P370+P378: In case of fire: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant

foam to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

### Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3	Composition / informatio	n on ingredients			
Chemical Name		CAS#	%	EINECS	
Methanol		67-56-1	32.0%	200-659-6	
Glycerin		56-81-5	32.0%	200-289-5	
Water		7732-18-5	27.3%	231-791-2	
Aluminum ammor	nium sulfate	7784-26-1	5.0%	232-055-3	
Acetic acid		64-19-7	3%	200-580-7	
Hematoxylin		517-28-2	0.7%	208-237-3	

### Section 4 First aid measures

INGESTION: MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: VAPOR HARMFUL. HARMFUL IF INHALED. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical

EYE CONTACT: CAUSES EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: HARMFUL IN CONTACT WITH SKIN. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention

### Section 5 Fire fighting measures

Suitable Extinguishing Media: Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Fires involving a small amount of combustibles may be smothered by dry chemical. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instanty. Closed containers exposed to heat may explode. Burns with a clear, almost invisible flame. Contact with strong oxidizers may cause fire.

# Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Page E2 of E2 Section 7 Handling and storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits:	Methanol	TWA: 262 mg/m <sup>3</sup> / STEL: 328 mg/m <sup>3</sup>	TWA: 260 mg/m <sup>3</sup>	TWA: 260 mg/m <sup>3</sup> / STEL: 325 mg/m <sup>3</sup>			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

### Section 9 Physical and chemical properties

Appearance: Liquid. Dark red-purple. Odor: Pungent odor. Odor threshold: Data not available.

pH: Data not available

Melting / Freezing point: Data not available Boiling point: Data not available

Flash point: Data not available

Evaporation rate ( Butyl acetate = 1): >1 Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: Data not available Vapor pressure (mm Hg): Data not available

Vapor density (Air = 1): Data not available Relative density (Specific gravity): Data not available

Solubility(ies): Complete in water.

Partition coefficient: Data not available Auto-ignition temperature: Data not available Decomposition temperature: Data not available.

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

### Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizing agents, strong acids, zinc, aluminum and magnesium, reducers, alkalies, chromic acid, nitric acid, sodium peroxide, carbonates, hydroxides, and phosphates. Corrosive to some metals. Potentially violent reaction with acetaldehyde and acetic anhydride. Ignites on contact with potassium-tert-botoxide. Hazardous decomposition products: Carbon oxides, formaldehyde, poisonous Acrolein fumes, nitrogen oxides, ammonia fumes, hydrogen sulfide and other harmful gases or vapors including oxides and/or other compounds of sulfur and sodium.

### Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 5,628 mg/kg; Inhalation-rat LC50: 64,000 mg/kg/4hours; Skin-rabbit LD50: 15,800 mg/kg [Methanol], Oral-rat LD50: 3,310 mg/kg; Inhalation-rat

LC50: 11.4 mg/L/4 hours ; Dermal-rabbit LD50: 1,060 mg/kg [Acetic acid, glacial]

Skin corrosion/irritation: Data not available Serious eye damage/irritation: Data not available Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA

CA Prop 65: MWARNING! : This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1 with narcotic effects.

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation of this material may cause irritation of the respiratory tract, nausea, shortness of breath and headache.

Ingestion: Ingestion may cause headache, dizziness, weakness, euphoria, drowsiness, shortness of breath, vomiting and incoordination. Can also cause blindness and death, Cannot be made nonpoisonous.

Skin: Contact with skin can cause moderate irritation, defatting, cracking and dermatitis. Skin absorption may contribute to overall exposure.

Eves: Contact with eves can cause severe irritation, even corneal burns. High concentrations of vapors may cause irritation.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: PC1400000 [Methanol], AF1225000 [Acetic acid, glacial]

### Section 12 **Ecological information**

Toxicity to fish: Lepomis macrochirus (fish, fresh water), LC50 = 15,400 mg/l/96 hours [Methanol], Gambusia affinis (fish, fresh water), LC50 = 251 mg/L/24 hours [Acetic acid, glacial]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna, EC50 = >10,000 mg/l/48 hours [Methanol], Daphnia magna (Crustacea), EC50 = 95 mg/L/24 hours [Acetic acid, glacial]

Toxicity to algae: Euglena gracilis (Algae), EC100 = 720 mg/L [Acetic acid, glacial]

Persistence and degradability: Readily biodegradable Bioaccumulative potential: Not expected to bioaccumulate Mobility in soil: No data available PBT and vPvB assessment: No data available Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal

# **Disposal considerations**

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

### Section 14 Transport information

UN/NA number: UN1993 Shipping name: Flammable liquid, n.o.s., (Methyl alcohol)

Hazard class: 3 Packing group: III Reportable Quantity: Yes Marine pollutant: No

Exceptions: Limited quantity equal to or less than 5 L 2020 ERG Guide # 128

### Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Methanol	Listed	5,000 lbs. (2270 kg)	U154	Listed	Not listed	MARNING - Reproductive Harm - www.P65Warnings.ca.gg
Acetic acid, glacial	Listed	5,000 lbs (2270 kg)	D001, D002	Listed	Not listed	

### Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: October 1, 2020 Supercedes: May 16, 2018 Form 06/2015

# Section 1 Identification Page E1 of E2

MICROSCOPE

OPTICS

CENTER

INC.

Voruberaria cocepe con

Benz Microscope Optics Center, Inc. 3980 Varsity Drive Ann Arbor, MI 48108 Tel: 734-994-3880

Fax: 734-994-9090 email: benzmicroscope@aol.com

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

Product	EOSIN Y ALCHOHOLIC	1%
---------	--------------------	----

Synonyms None

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS06 / GHS08

Target organs: Eyes, Central nervous system, Liver, Kidneys.







### GHS Classification:

Flammable liquid (Category 2)
Acute toxicity, oral (Category 3)
Acute toxicity, dermal (Category 3)
Acute toxicity, inhalation (Category 3)
Eye irritation (Category 2B)

STOT-SE (Category 2) STOT-SE (Category 3)

# GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness. H371: May cause damage to organs.

# Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233+P235: Keep container tightly closed. Keep cool. P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P311: IF exposed or concerned: Call a POISON CENTER or doctor.

P337+P313: If eye irritation persists: Get medical attention.

P361+P364: Take off immediately all contaminated clothing and wash it before reuse. P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P405: Store in a well-ventilated place. Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

# Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / information on ingredients						
Chemical Name	CAS#	%	EINECS			
Ethyl alcohol denatured* Water Eosin Y (C.I. No. 45380)	64-17-5 7732-18-5 17372-87-1	80% 19% 1%	200-578-6 231-791-2 241-409-6			
*Denaturants Isopropyl alcohol Methanol Methyl isobutyl ketone	67-63-0 67-56-1 108-10-1		200-661-7 200-659-6 203-550-1			

# Section 4 First aid measures

**INGESTION:** TOXIC IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

**INHALATION:** TOXIC IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

**SKIN ABSORPTION:** TOXIC IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

# Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

**Specific Hazards:** During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

# Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Page E2 of E2 Section 7 Handling and storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits:	Ethanol	STEL: 1000 ppm / 1880 mg/m <sup>3</sup> (A3)	TWA: 1000 ppm / 1900 mg/m <sup>3</sup>	TWA: 1000 ppm / 1900 mg/m <sup>3</sup>			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Section 9 Physical and chemical properties

Appearance: Redish orange liquid Odor: Mild characteristic odor. Odor threshold: Data not available

pH: Data not available

Melting / Freezing point: -114°C (-173°F)\* Boiling point: 74-80°C (165.2-176°F)\*

Flash point: 5°C (41°F)\*

Vapor pressure (mm Hg): Ca 50 @ 20°C' Vapor density (Air = 1): Ca 1.5\*

Relative density (Specific gravity): 0.7919-0.7955°C @ 60/60°F\*

Solubility(ies): Soluble in water.

Evaporation rate ( Butyl acetate = 1): Ca 2\*

Flammability (solid/gas): Data not available.

Explosion limits: Lower / Upper: 4.0%(V) / 20.0%(V)\*

Partition coefficient: (n-octanol / water): Low Pow: -.32\*

Auto-ignition temperature: 400°C (752°F)\* Decomposition temperature: Data not available

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

\*Ethanol

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizers, inorganic acids, halogens, metals and alkalines. Hazardous decomposition products: Oxides of carbon. May produce hydrogen chloride gas.

### Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours [Ethanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Severe irritant. Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: A WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma.

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eves: Contact with eves may cause blindness.

Signs and symptoms of exposure: See Potential health effects above. Additional information: RTECS #: KQ6300000 [Ethanol], LM5850000 [Eosin Y]

# **Ecological information**

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

# Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

### Section 14 Transport information

UN/NA number: UN1170 Shipping name: Ethanol solution

Reportable Quantity: 5,000 lbs (2270 kg) Hazard class: 3 Packing group: || Marine pollutant: No

2020 ERG Guide # 127 **Exceptions:** Limited quantity equal to or less than 1 L

### Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol	Listed	Not listed	D001	Listed	Not listed	▲ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
Methanol	Listed	5,000 lbs.	U154	Listed	Not listed	
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed	
Eosin Y	Listed	Not listed	Not listed	Listed	Not listed	

### Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: September 28, 2020 Supercedes: May 15, 2018 Form 06/2015

# Section 1 Identification Page E1 of E2

BENZ MICROSCOPE OPTICS CENTER INC.

Benz Microscope Optics Center, Inc. 3980 Varsity Drive Ann Arbor, MI 48108 Tel: 734-994-3880

Fax: 734-994-9090 email: benzmicroscope@aol.com

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

Product	ACID ALCOHOL 1%

Synonyms None

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS06 / GHS08

Target organs: Eyes, Central nervous system, Liver, Kidneys.







# GHS Classification:

Flammable liquid (Category 2)
Acute toxicity, oral (Category 3)
Acute toxicity, dermal (Category 3)
Acute toxicity, inhalation (Category 3)
Eye irritation (Category 2B)
STOT-SE (Category 2)
STOT-SE (Category 3)

# GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness. H371: May cause damage to organs.

# Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233+P235: Keep container tightly closed. Keep cool. P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray. P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P311: IF exposed or concerned: Call a POISON CENTER or doctor.

P337+P313: If eye irritation persists: Get medical attention.

P361+P364: Take off immediately all contaminated clothing and wash it before reuse. P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P405: Store in a well-ventilated place. Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

# Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / information or	Section 3 Composition / information on ingredients							
Chemical Name	CAS#	%	EINECS					
Ethyl alcohol denatured* Water Hydrochloric acid	64-17-5 7732-18-5 7647-01-0	70% 29% 1%	200-578-6 231-791-2 231-595-7					
*Denaturants Isopropyl alcohol Methanol Methyl isobutyl ketone	67-63-0 67-56-1 108-10-1		200-661-7 200-659-6 203-550-1					

# Section 4 First aid measures

**INGESTION:** TOXIC IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

**INHALATION:** TOXIC IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

**SKIN ABSORPTION:** TOXIC IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

# Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

# Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Page E2 of E2 Section 7 Handling and storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits.	Ethanol	STEL: 1000 ppm / 1880 mg/m <sup>3</sup> (A3)	TWA: 1000 ppm / 1900 mg/m <sup>3</sup>	TWA: 1000 ppm / 1900 mg/m <sup>3</sup>			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

### Section 9 Physical and chemical properties

Appearance: Clear, colorless liquid. Odor: Mild characteristic odor. Odor threshold: Data not available

pH: Data not available Melting / Freezing point: -114°C (-173°F)\*

Boiling point: 74-80°C (165.2-176°F)\*

Flash point: 5°C (41°F)\*

Evaporation rate ( Butyl acetate = 1): Ca 2\* Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: 4.0%(V) / 20.0%(V)\*

Vapor pressure (mm Hg): Ca 50 @ 20°C' Vapor density (Air = 1): Ca 1.5\*

Relative density (Specific gravity): 0.7919-0.7955°C @ 60/60°F\*

Solubility(ies): Soluble in water.

Partition coefficient: (n-octanol / water): Low Pow: -.32\*

Auto-ignition temperature: 400°C (752°F)\* Decomposition temperature: Data not available.

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

\*Ethanol

### Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizers, inorganic acids, halogens, metals and alkalines. Hazardous decomposition products: Oxides of carbon. May produce hydrogen chloride gas.

### Section 11 Toxicological information

Acute toxicity: Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours [Ethanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Severe irritant. Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

CA Prop 65: \Lambda WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause

cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma.

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eyes: Contact with eyes may cause blindness.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: KQ6300000 [Ethanol], MW4025000 [Hydrochloric acid]

### Section 12 **Ecological information**

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

# Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

### Section 14 Transport information

UN/NA number: UN2924 **Shipping name:** Flammable liquids, corrosive, n.o.s., (Ethanol, Hydrochloric acid)

Hazard class: 3, (8) Packing group: || Reportable Quantity: 5,000 lbs (2270 kg) Marine pollutant: No

2020 ERG Guide # 132 **Exceptions:** Limited quantity equal to or less than 1 L

### Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol	Listed	Not listed	D001	Listed	Not listed	▲ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
Methanol	Listed	5,000 lbs.	U154	Listed	Not listed	
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed	
Hydrochloric acid	Listed	Not listed	D002	Listed	Not listed	

### Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: September 9, 2020 Supercedes: January 30, 2019 Form 06/2015

