

# ULTRA-CAM ARMORED HD CAMERA™

## 1080P + 960H SONY SUPER HD Nightvision

### PROBLEM SOLVED TVI - CVI - AHD - Composite

**24 IR LED**  
**60Ft Nightvision**  
**3.6mm wide angle**



CDX-4W2024-WDRW

**36 IR LED**  
**90Ft Nightvision**  
**Vari-Focal 2.8mm~12mm**



CDX-4W2036-WDR-VFW

**WDR - Wide Dynamic Range**

**OSD - On Screen Display**


**Wide-Angle View**

**SONY 2.4 Megapixel**



**SONY CAMERAS**

2.4 MEGA-PIXEL



**Looks Great - Sees Great - Does it All!**



ENC-JBOX375-XLW



ENC-JBOX475-XLW

**Extra Deep Base Option**  
**Lowers View, Hides Connections**  
**(optional not included)**

- ★ Gloss white powder coated finish repels dirt.
- ★ Turret Dome eyeball design allows to mount on any surface, wall, ceiling, etc.
- ★ Rugged Ip66 weatherproof housing great for tough environments. Can be used indoors or out.
- ★ 3 mega-pixel precision ground lens for true high definition mega-pixel clarity.
- ★ Joystick on cable for control of OSD or use UTC control, or TVI Co-Axित्रon control.
- ★ Works with all Standard Definition DVRs as well as HD TVI, CVI, and AHD recorders.

Image	Image Sensor Effective Pixels Horizontal Resolution Focal Length Focus Zoom	SONY IMX322 1/2.9" chipset 2.4 megapixel NTSC:1920(H)X1080(V) 1080P TVI, CVI, AHD, or 960H, 1,000 TVL 2.8~12mm Zoom manual Varifocal or 3.6mm Manual
Lens	Video System Video Scanning Type Sync. System S/N Ratio	TVI or CVI or AHD or NTSC / CVBS Interlace Internal > 60dB(AGC off)
Electrical	Min. Illumination Video Output Electronic Shutter Wide Dynamic Range ATR OSD Mirror White Balance Back Light Compensation	0 Lux(when IR LED turn on) .001LUX native 1 BNC, 1.0 Vp-p, 75 Ohm composite 1/60 ~ 1/100,000 Yes Digital WDR Yes Yes No (Horizontal/Vertical Flip, ON/OFF) Yes (include ATW / Manual / AWC/PUSH) OFF/ON (48 zones compensation)
Function	DNR	YES
Infrared LED	Effective IR Distance Infrared Red Lamps Supply Voltage	60FT 24LED or 90FT 36LED 24 or 36 pcs 5mm IR LED @850nm DC 12V +/- 10%
Power	Power Consumption	Max. 450mA or Max. 550mA
Environment	Operating Temperature	-10 ~ 50
Accessories	Bracket Chassis Material & Color Weather-resistant Vandal-resistant Net Weight	Yes Alloy Aluminum & White Yes Yes 400g on 24LED model 800g on 36LED model
Mechanical	Dimension	94mmx69mm or 131mmx93mm

Manufactured By:

Your Local authorized dealer:



**WebWarrior®**  
 SURVEILLANCE TECHNOLOGIES

